AD 2. AERODROMES

VIDD AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VIDD - SAFDARJUNG AIRPORT

VIDD AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	283505N 0771224E MAG. BRG. 315.41 DEG/ 487 M from physical beginning of RWY 30.	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	4.75 NM South of Delhi Jn. Railway Station	
3	Aerodrome elevation and reference temperature	705 FT / 39.9 DEG C	
4	Magnetic variation, date of information and annual change	0.75 DEG E (2010) /0.033 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airport Director Airports Authority of India, Safdarjung Airport, New Delhi - 110003	
		Telephone:	(91) 11 24640859 (91) 11 24618680
		Fax:	(91) 11 24693926
		AFS:	VIDDYDYX
		Email:	apdsap@aai.aero
6	Types of traffic permitted (IFR/VFR)	VFR	
7	Remarks	1. No Night Operations 2. Non-Schedules operations only with prior approval from Ministry of Home Affairs (MHA) 3. Gravity Model: EGM 08	

VIDD AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON-FRI 0400-1230 UTC (0930-1800 IST) SAT, SUN & HOLIDAY: NIL	
2	Custom and immigration	NIL	
3	Health and sanitation	NIL	
4	AIS briefing office	As ATS	
5	ATS reporting office (ARO)	As ATS	
6	MET Briefing office	As ATS	
7	Air Traffic Service	0130 – 1330 UTC	
8	Fuelling	NIL	
9	Handling	NIL	
10	Security	H24	
11	De-icing	NIL	
12	Remarks	See details in AD 2.20 Outside of ATS hour's services are available O/R with 24 HR PN to AD.	
		ATS approved hourly runway traffic handling capacity	Maximum number of arrival and departure: 12 (The Minimum Spacing between two successive arrivals shall be more than 5 Minutes) Maximum number of arrival only: 06 Maximum number of departure only: 12

VIDD AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	NIL
2	Fuel and Oil types	NIL
3	Fuelling facilities and capacity	NIL
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

VIDD AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	NIL
2	Restaurant(s) at or in the vicinity of aerodrome	NIL
3	Transportation possibilities	NIL
4	Medical Facilities	First aid available. Hospitals available at 2 KM in city.
5	Bank and post office at or in the vicinity of aerodrome	Banks: Available Post office: Available
6	Tourist office	NIL
7	Remarks	NIL

VIDD AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-4
2	Rescue equipment	Power saw and RR generator
3	Capability for removal of disabled aircraft	1. The critical aircraft for the airport is -Beechcraft350. 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3.The airlines may contact ‘Aerodrome Coordinator for Disabled Aircraft Removal Operations’ for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: AIRPORT COORDINATOR: Airport Director CONTACT:011-24640859 EMAIL: apdsap@aai.aero
4	Remarks	NIL

VIDD AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VIDD AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Designator: FIU Surface: Asphalt Strength: Designator: MAIN Surface: Asphalt Strength:

2	Designation, width, surface and strength of taxiways	Designator: TWY A Width: 15 M Surface: Asphalt Strength: Designator: TWY B VIP APRON Width: 45 M Surface: Asphalt Strength: Designator: TWY C1 Width: 15 M Surface: Asphalt Strength: Designator: TWY C2 Width: 15 M Surface: Asphalt Strength: Designator: TWY D Width: 15 M Surface: Asphalt Strength: Designator: TWY E Width: 11 M Surface: Asphalt Strength:
3	Location and elevation of altimeter checkpoints	Holding Position on TWY C. Elevation 697 FT
4	Location of VOR checkpoints	NIL
5	Position of INS checkpoints	NIL
6	Remarks	1. Coordinates of Runway Holding Position: i) TWY A: 283459.842N 0771223.426E/ 700FT ii) TWY B: 283501.604N 0771226.107E/ 699FT iii) TWY C1: 283457.390N 0771232.650E/ 699FT iv) TWY C2: 283456.183N 0771234.440E/ 698FT v) TWY D: 283452.855N 0771239.911E/ 697FT vi) TWY E: 283510.371N 0771206.478E/ 699FT 2. Coordinates of RWY & Taxi Intersection: i) TWY A/B: 283500.661N 0771224.689E/ 700FT ii) TWY C1: 283456.692N 0771231.030E/ 699FT iii) TWY C2: 283455.514N 0771232.912E/ 699FT iv) TWY E: 283511.493N 0771207.374E/ 699FT 3. Vertical Datum : EGM 08 4..Main Apron Strength - PCR /228/F/C/Y/T 5, FIU Apron Strength - PCR/190/F/C/X/T 6. TWY A- PCR/230/F/C/X/T 7. TWY B VIP APRON - PCR/173/F/C/X/T 8. TWY C1- PCR/173/F/C/X/T 9. TWY C2- PCR/173/F/C/X/T 10.TWY D - PCR/173/F/C/X/T 11. TWY E- PCR/150/F/C/X/T

VIDD AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Parking Stands No. 1, 2, 3 And 4 are designated as aircraft stands signs in apron. Taxiway guidelines available. Visual Docking/Parking Guidance System of Aircraft Stands: NA

2	Runway and taxiway markings and lights	RWY Markings Displaced Threshold Markings, RWY Designation Marking, Centre Line Marking, RWY Edge Line Marking, Turn Pad Marking at Beginning of RWY 12, RWY End Marking Lights NIL ----- TWY Marking Centreline Marking, TWY Edge Marking, TWY Holding Position Marking Lights NIL -----
3	Stop bars (if any)	NIL
4	Remarks	NIL

VIDD AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
30/TKOF 12/APCH	OTHER	283515.6N 0771158.1E	726 FT	NIL	Mobile Road Traffic (Road Elev. 216.3M + Traffic Ht: 5.0M)
30/TKOF 12/APCH	TREE	283519.4N 0771157.7E	764 FT	NIL	Tree
30/TKOF 12/APCH	TREE	283518.3N 0771157.5E	766 FT	NIL	Tree
30/TKOF 12/APCH	FENCE	283516.0N 0771157.4E	720 FT	NIL	Airport Boundary Wall
30/TKOF 12/APCH	TREE	283516.9N 0771157.3E	765 FT	NIL	Tree
30/TKOF 12/APCH	POLE	283518.1N 0771153.8E	734 FT	NIL	LIGHT POLE
30/TKOF 12/APCH	OTHER	283537.4N 0771134.3E	830 FT	NIL	MAST
30/TKOF 12/APCH	TREE	283531.4N 0771132.5E	843 FT	NIL	Tree
30/TKOF 12/APCH	TREE	283520.2N 0771156.8E	774 FT	NIL	Group of Tree
30/TKOF 12/APCH	TREE	283519.9N 0771152.1E	780 FT	NIL	GROUP OF TREE
30/APCH 12/TKOF	FENCE	283450.2N 0771238.7E	710 FT	NIL	Airport Boundary Wall
30/APCH 12/TKOF	OTHER	283449.8N 0771239.1E	716 FT	NIL	Mobile Road Traffic (Road Elev. 213.2M + Traffic Ht: 5.0M)
30/APCH 12/TKOF	OTHER	283450.2N 0771241.4E	715 FT	NIL	Mobile Road Traffic (Road Elev. 212.9M + Traffic Ht: 5.0 M)
30/APCH 12/TKOF	OTHER	283450.1N 0771241.6E	733 FT	NIL	Bridge Grill
30/APCH 12/TKOF	POLE	283448.4N 0771241.9E	745 FT	NIL	LIGHT POLE
30/APCH 12/TKOF	POLE	283449.3N 0771242.1E	743 FT	NIL	LIGHT POLE

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
30/APCH 12/TKOF	OTHER	283449.7N 0771242.2E	728 FT	NIL	Road (Bridge)
30/APCH 12/TKOF	SIGN	283447.6N 0771242.3E	744 FT	NIL	Sign Board
30/APCH 12/TKOF	POLE	283450.3N 0771242.4E	740 FT	NIL	LIGHT POLE
30/APCH 12/TKOF	POLE	283450.8N 0771242.5E	738 FT	NIL	LIGHT POLE
30/APCH 12/TKOF	TREE	283447.4N 0771242.6E	764 FT	NIL	Group of Tree
30/APCH 12/TKOF	TREE	283448.8N 0771242.9E	760 FT	NIL	Group of Tree
30/APCH 12/TKOF	TREE	283450.0N 0771244.2E	756 FT	NIL	Group of Tree
30/APCH 12/TKOF	OTHER	283447.4N 0771244.2E	743 FT	NIL	Flood Light Mast
30/APCH 12/TKOF	TREE	283447.5N 0771244.5E	778 FT	NIL	Group of Tree
30/APCH 12/TKOF	TREE	283449.4N 0771245.0E	752 FT	NIL	Group of Tree
30/APCH 12/TKOF	TREE	283446.1N 0771245.5E	759 FT	NIL	Group of Tree
30/APCH 12/TKOF	TREE	283445.6N 0771247.1E	766 FT	NIL	Group of Tree
30/APCH 12/TKOF	TREE	283445.0N 0771248.4E	757 FT	NIL	Group of Tree
30/APCH 12/TKOF	TREE	283441.9N 0771250.1E	779 FT	NIL	Group of Tree
30/APCH 12/TKOF	TREE	283444.4N 0771253.2E	790 FT	NIL	Group of Tree
30/APCH 12/TKOF	TREE	283447.2N 0771247.7E	763 FT	NIL	Group of Tree
30/APCH 12/TKOF	OTHER	283439.3N 0771305.1E	819 FT	NIL	Rostrum
30/APCH 12/TKOF	TREE	283450.1N 0771239.2E	767 FT	NIL	Group of Tree
30/APCH 12/TKOF	POLE	283449.6N 0771239.5E	728 FT	NIL	LIGHT POLE
30/APCH 12/TKOF	TREE	283450.0N 0771240.4E	740 FT	NIL	Group of Tree
30/APCH 12/TKOF	POLE	283450.0N 0771240.4E	727 FT	NIL	LIGHT POLE
30/APCH 12/TKOF	TREE	283449.5N 0771240.5E	749 FT	NIL	Group of Tree
30/APCH 12/TKOF	POLE	283449.4N 0771241.0E	727 FT	NIL	LIGHT POLE
30/APCH 12/TKOF	TREE	283449.2N 0771241.1E	740 FT	NIL	Group of Tree
30/APCH 12/TKOF	BUILDING	283451.9N 0771241.5E	715 FT	NIL	Security Hut
30/APCH 12/TKOF	TREE	283450.3N 0771241.5E	743 FT	NIL	Group of Tree
30/APCH 12/TKOF	POLE	283450.3N 0771241.6E	727 FT	NIL	Light Pole

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
30/APCH 12/TKOF	TREE	283450.8N 0771241.6E	753 FT	NIL	Group of Tree
30/APCH 12/TKOF	POLE	283450.3N 0771241.2E	719 FT	NIL	Light Pole
30/APCH 12/TKOF	POLE	283450.7N 0771241.3E	720 FT	NIL	Light Pole
30/APCH 12/TKOF	OTHER	283439.2N 0771305.0E	818 FT	NIL	Rostrum
In circling area and at AD	TREE	283520.4N 0771201.5E	779 FT	NIL	Tree
In circling area and at AD	TREE	283520.8N 0771200.8E	776 FT	NIL	Tree
In circling area and at AD	TREE	283512.4N 0771157.9E	773 FT	NIL	Tree
In circling area and at AD	TREE	283514.1N 0771157.6E	775 FT	NIL	Tree
In circling area and at AD	OTHER	283528.2N 0771155.2E	861 FT	NIL	MAST
In circling area and at AD	TREE	283516.8N 0771154.5E	763 FT	NIL	Tree
In circling area and at AD	TREE	283517.1N 0771154.2E	765 FT	NIL	Tree
In circling area and at AD	TREE	283516.8N 0771153.4E	767 FT	NIL	Tree
In circling area and at AD	POLE	283519.5N 0771157.8E	732 FT	NIL	Light Pole
In circling area and at AD	ANTENNA	283501.9N 0771129.8E	871 FT	NIL	Antenna on Chanakya (Chanakya Building Top 263.4M)
In circling area and at AD	ANTENNA	283506.7N 0771125.9E	974 FT	NIL	Antenna on Akbar Bhawan (Building Top 286.9M)
In circling area and at AD	OTHER	283448.3N 0771240.5E	731 FT	NIL	Mobile Rail Traffic (Rail Track Elev. 215.3M+ Traffic Ht: 7.6 M)
In circling area and at AD	TREE	283447.5N 0771240.5E	785 FT	NIL	Group of Tree
In circling area and at AD	SIGN	283447.7N 0771241.0E	743 FT	NIL	Sign Board
In circling area and at AD	POLE	283447.4N 0771241.6E	745 FT	NIL	Light Pole
In circling area and at AD	TREE	283444.8N 0771243.0E	766 FT	NIL	Group of Tree
In circling area and at AD	TREE	283451.5N 0771243.5E	755 FT	NIL	Group of Tree
In circling area and at AD	TREE	283443.2N 0771246.4E	773 FT	NIL	Group of Tree
In circling area and at AD	TREE	283446.3N 0771256.7E	810 FT	NIL	Group of Tree
In circling area and at AD	POLE	283446.5N 0771243.3E	736 FT	NIL	Light Pole

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
In circling area and at AD	BUILDING	283444.5N 0771245.5E	747 FT	NIL	Building
In circling area and at AD	TREE	283445.5N 0771254.8E	776 FT	NIL	Group of Tree
In circling area and at AD	OTHER	283437.7N 0771310.8E	871 FT	NIL	Rostrum
In circling area and at AD	ANTENNA	283422.0N 0771241.2E	867 FT	NIL	Antenna On Building (Building Top: 260.4M)
In circling area and at AD	TREE	283450.8N 0771233.7E	768 FT	NIL	Group of Tree
In circling area and at AD	TREE	283450.5N 0771235.1E	766 FT	NIL	Group of Tree
In circling area and at AD	TREE	283448.1N 0771235.9E	783 FT	NIL	Group of Tree
In circling area and at AD	TREE	283450.2N 0771237.3E	772 FT	NIL	Group of Tree
In circling area and at AD	TREE	283449.6N 0771239.0E	741 FT	NIL	Group of Tree
In circling area and at AD	TREE	283452.9N 0771241.9E	754 FT	NIL	Group of Tree
In circling area and at AD	TREE	283453.8N 0771242.0E	757 FT	NIL	Group of Tree
In circling area and at AD	TREE	283452.1N 0771242.1E	756 FT	NIL	Group of Tree
In circling area and at AD	TREE	283451.7N 0771234.4E	755 FT	NIL	Group of Tree
In circling area and at AD	OTHER	283528.2N 0771155.2E	861 FT	NIL	Mast
In circling area and at AD	OTHER	283437.7N 0771310.8E	870 FT	NIL	Rostrum
In circling area and at AD	BUILDING	283447.7N 0771122.4E	928 FT	NIL	Leela Hotel Building Top
In circling area and at AD	BUILDING	283506.9N 0771130.1E	866 FT	NIL	Yashwant Palace Building
In circling area and at AD	ANTENNA	283549.7N 0771143.0E	872 FT	NIL	Ashoka Hotel Antenna Top
In circling area and at AD	BUILDING	283435.1N 0771043.3E	905 FT	NIL	OHWT
In circling area and at AD	OTHER	283501.3N 0771122.5E	868 FT	NIL	Mast
In circling area and at AD	BUILDING	283449.0N 0771132.0E	863 FT	NIL	Building
In circling area and at AD	BUILDING	283500.4N 0771135.6E	861 FT	NIL	Building U/C
In circling area and at AD	BUILDING	283449.9N 0771139.9E	867 FT	NIL	Building
In circling area and at AD	OTHER	283451.2N 0771146.7E	887 FT	NIL	Mast
In circling area and at AD	OTHER	283444.5N 0771147.9E	855 FT	NIL	Crane on Building U/C (Building U/C Top: 260.7M)

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
In circling area and at AD	OTHER	283445.4N 0771150.4E	905 FT	NIL	Crane on Building U/C (Building U/C Top:260.4M)
In circling area and at AD	OTHER	283617.2N 0771324.4E	920 FT	NIL	LC Rod On Taj Maan Singh Hotel (Hotel Bldg. Top 277.3M
In circling area and at AD	OTHER	283542.6N 0771015.6E	959 FT	NIL	LC Rod on Taj Hotel (Hotel Bldg. Top 285.6M
In circling area and at AD	BUILDING	283549.1N 0771025.3E	920 FT	NIL	Hotel Maurya Sheraton
In circling area and at AD	OTHER	283611.2N 0771045.3E	999 FT	NIL	Mast
In circling area and at AD	BUILDING	283934.3N 0771143.4E	1460 FT	NIL	Building U/C
In circling area and at AD	STACK	283809.3N 0771515.3E	1206 FT	NIL	Chimney

See AD 2.23

VIDD AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Safdarjung Airport
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	0600-1700 UTC Monitoring H24
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Safdarjung Airport issues nine hourly TAF every three hours from 0000-1500 UTC.
4	Availability of the trend forecast for the aerodrome and interval of issuance	Issues Met Report half hourly from 0000 - 0500 UTC and hourly upto1300 UTC and Special Reports
5	Information on how briefing and/or consultation is provided	Yes
6	Types of flight documentation supplied and language(s) used in flight documentation	English
7	Charts and other information displayed or available for briefing or consultation	Surface and upper air weather charts, satellite imageries & NWP products.
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Distant Indicator Wind Equipment installed with ATC
9	The air traffic services unit(s) provided with meteorological information	VIDD Air Traffic Control Tower
10	Additional information, e.g. concerning any limitation of service.	At least two hours' time is required for preparation of Flight Forecast Documentation.

VIDD AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCR) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
12	125.50 DEG	1180 x 30 M	140/F/C/X/T Asphalt	THR: 283515.25N 0771201.36E RWY END: 283453.09N 0771236.79E
30	305.50 DEG	1180 x 30 M	140/F/C/X/T Asphalt	THR: 283459.65N 0771226.31E RWY END: 283515.25N 0771201.36E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 705.0FT TDZ: 705.0FT		NIL	NIL	1356 x 80 M
THR: 699.0FT TDZ: 700.0FT		NIL	NIL	1356 x 80 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
		NIL	1. THR RWY 30 displaced by 350M (1149FT) due mobile traffic on over-bridge in approach area of RWY 30. 2. First 79M (260FT) of RWY 12 and 97 M (319FT) of RWY 30 are not available as the requisite strip width of 80M (263FT) is not available at both ends. 3. The runway length available for operational purpose is 1180M (3872FT).
		NIL	1. THR RWY 30 displaced by 350M (1149FT) due mobile traffic on over-bridge in approach area of RWY 30. 2. First 79M (260FT) of RWY 12 and 97 M (319FT) of RWY 30 are not available as the requisite strip width of 80M (263FT) is not available at both ends. 3. The runway length available for operational purpose is 1180M (3872FT).

VIDD AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	**2**	**3**	**4**	**5**	**6**
12	1180	1180	1180	1180	
30	1180	1180	1180	830	

VIDD AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	**2**	**3**	**4**	**5**
12	NIL	NIL	NIL	NIL
30	NIL	NIL	NIL	NIL

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	**7**	**8**	**9**	**10**
		NIL	NIL	NIL
		NIL	NIL	NIL

VIDD AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	White & green flashes, 15 rpm. available at roof of control tower building as per ATS watch hrs
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	NIL
		Anemometer	NIL
3	Taxiway edge and taxiway centre line lights;	Edge	NIL
		Centre Line	NIL
4	Secondary power supply including switch-over time;	Secondary Power supply to VHF. Switch-over time :12 SEC.	
5	Remarks	NIL	

VIDD AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	
2	TLOF and/or FATO area elevation:	
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	
4	True bearings of FATO;	
5	Declared distances available	
6	Approach and FATO lighting;	
7	Remarks	

VIDD AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	ATZ: Area bounded by lines joining points 283430N 0771313E; 283406N 0771255E; 283406N 0771155E; 283448N 0771055E; 283536N 0771119E to point of origin.
2	Vertical limits	1400 FT AMSL
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Safdarjung Tower, English
5	Transition altitude	5000 FT
6	Hours of applicability	HO
7	Remarks	No flying activities permitted at Safdarjung Airport except for VIP flights and for flights undertaking repair/ maintenance of VIP aircrafts as per their annual maintenance schedule, subject to prior intimation to ATC.

VIDD AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	**2**	**3**	**4**
TWR	Safdarjung Tower	118.875 MHZ	
TWR	Safdarjung Tower	122.300 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	**6**	**7**
	BTN 0130-1330 DLY	BACKUP
	BTN 0130-1330 DAILY	NIL

VIDD AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8

VIDD AD 2.20 LOCAL AERODROME REGULATIONS

1.A visual circuit of 700 FT AGL (1400 FT) AMSL around Safdarjung Aerodrome is available for light aircraft operating at or from Safdarjung Airport.

2.Operations at Safdarjung Airport are permitted only during the hours of day-light and in meteorological conditions specified below:

a)Ceiling not below 2000 ft.
b)Ground visibility not less than 5 KM at both Safdarjung Airport and IGI Airport.
3.a)Left-hand circuit for RWY 30 and right-hand circuit for RWY 12 shall be in use at Safdarjung Aerodrome and the aircraft shall at no time proceed South of the drain.
b) All aircraft operating to/from Safdarjung aerodrome shall avoid overflying the prohibited airspace in the North and no aircraft shall operate North of the RWY 12/30 to ensure compliance with this procedure.
c) After take-off from RWY 30, the aircraft approaching Nehru Park shall commence gradual climbing left turn and shall complete the turn not later than Niti Marg, exercising caution to avoid Akbar Hotel and NDMC Building during the turn.

4.All aircraft operating within Safdarjung Aerodrome Traffic Zone shall maintain two-way communication with Aerodrome Control Tower on Appropriate VHF Channel.

5.Pilots are warned to be extremely careful while operating from/to IGI Airport in View of small aircraft/helicopter operations from Safdarjung Airport.

6.Except official flights which may include The President of India, The Vice President of India, The Prime Minister and Union Ministers, Governors of States, Chief Ministers of States, CPMFS and Pawan Hans, no flying activity is permitted. Flights other than these are required to obtain the clearance from The Ministry of Home Affairs, Govt. Of India.

VIDD AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VIDD AD 2.22 FLIGHT PROCEDURES

NIL

VIDD AD 2.23 ADDITIONAL INFORMATION

VIDD AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart (09 July 2026)
2. Aerodrome Obstacle Chart - Type A (Operating Limitations) RWY 12(09 July 2026)
3. Aerodrome Obstacle Chart - Type A (Operating Limitations) RWY 30(09 July 2026)
4.Aerodrome Obstacle Chart - Type B (09 July 2026)

VIDD AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3