INSTRUMENT APPROACH CHART

AERODROME ELEV 1010FT
HEIGHTS RELATED TO
THR RWY 04 ELEV 987FT

TWR 122.400/118.850

SALEM (VOSM)
INDIA
RNP Y RWY 04
(CAT A/B)

078°0'E 078°10'E

ELEV, ALT IN FEET
DIST IN NAUTICAL MILE
BRG ARE MAGNETIC
VAR 2.0°W(2010)

RNP APCH

Baro-VNAV not authorized
below 10°C & above 45°C

Caution-High terrain in missed approach area

180° 6100 6600 360°
MSA 25NM
SALEM ARP

11°50'N

11°40'N

SM705

1326

10NM

1837

1900

028°

FL090
5800

SM706

1054
1047

1112

RW04
(MAPt)

VOR181A
UNL
GND

1187

171°

SM704
1890 (IAF)
6100

6.9

5.9

SM701
(FAF)
3300

890

036°

972

SM707
5800

126°

8.0

036°

3.3

216°

6.4

SM702
(IF)
3700

4.0

306°

903

3238

SM703
4700

Caution:PAPI ANGLE 3°

SM706
HOLD

171°

FL090
5800
1 MIN

351°

SM706

RW04
(MAPt)

SCALE 1:250,000

0 1 2 3 4 5 NM

5355

SM702
IF
3700

SM701
FAF
3300
(LNAV)

RW04
MAPt
(LNAV)

036°

3300

3.1°(5.42%)

036°

028°

OCA

12 11 10 9 8 7 6 5 4 3 2 1 0

NAUTICAL MILES FROM THR 04

THR Elev 987

TCH 50

Transition Alt 7000

MISSED APPROACH

Speed restricted to 130 KIAS MAX
Climb on track 028°(M) at 1900 ft climbing turn LEFT proceed direct to SM705 then climbing turn LEFT proceed direct to SM706 to join hold at 5800 ft or as instructed by ATC.

OCA(H)	A	B
LNAV/VNAV	1290(303)	
LNAV	1440(453)	

Distance/Altitude Information							
Distance to RW04	NM	6.9(FAF)	6	5	4	3	2
Altitude	Ft	3300	3020	2690	2360	2030	1700

Rate of Descent/Ground Speed Information					
Ground Speed	Kt	80	100	120	140
Rate of Descent (5.42%)	Ft/Min	440	550	660	770

DRG.NO. AAI/115-IALC/260624/02/09/2025