AD 2. AERODROMES

VISM AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VISM - SHIMLA AIRPORT, SHIMLA

VISM AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	310454N 0770404E 320.5 DEG/510M from physical extremity of RWY32	
2	Direction and distance of aerodrome reference point from the centre of the city or town which the aerodrome serves	256 DEGREE/22 KM from RITZ,MALL ROAD,SHIMLA.	
3	Aerodrome elevation and reference temperature	5073 FT / 25.0 DEG C	
4	Magnetic variation, date of information and annual change	1.25 DEG E (2010) /0.0167 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airport Director Airports Authority of India, Shimla Airport, Jubberhatti Shimla - 171011 (Himachal Pradesh)	
		Telephone:	(91) 177 2736835 (91) 177 2736675
		Fax:	(91) 177 2736681 (91) 177 2736676
		AFS:	
		Email:	apc_vism@aai.aero; atc_vism@aai.aero
6	Types of traffic permitted (IFR/VFR)	VFR	
7	Remarks	1. AERODROME REFERENCE CODE: 2C 2. VERTICAL DATUM : EGM-08	

VISM AD 2.3 OPERATIONAL HOURS

1.	Aerodrome Operator	MON-FRI 0400-1230 UTC (0930-1800 IST) (Except SAT, SUN and Closed Holidays)
2.	Custom and immigration	NIL
3.	Health and sanitation	Available within AD hours.
4.	AIS briefing office	As ATS
5.	ATS reporting office (ARO)	As ATS
6.	MET Briefing office	As ATS
7.	Air Traffic Service	Consult NOTAM for current ATS HRS
8.	Fuelling	As ATS
9.	Handling	NIL
10.	Security	H24
11.	De-icing	NIL

12.	Remarks	1. Outside ATS Hours the services are available O/R with 24 HR PN to AD	
		2. ATS approved hourly runway traffic handling capacity	Maximum number of arrival and departure- 04 (due only one parking bay available) Maximum number of arrival only – 02 Maximum number of departure only -02
		3. Defence and non-sked OPR to take positive clearance from ATC Shimla on telephone 01772736675,9418092294 and 9418712794. due to only one parking stand available.	

VISM AD 2.4 HANDLING SERVICES AND FACILITIES

1.	Cargo-handling facilities	NIL
2.	Fuel/Oil types	JET A1
3.	Fuelling facilities/capacity	IOCL/32KL
4.	De-icing facilities	NIL
5.	Hangar space for visiting aircraft	NIL
6.	Repair facilities for visiting aircraft	NIL
7.	Remarks	NIL

VISM AD 2.5 PASSENGER FACILITIES

1.	Hotel(s) at or in the vicinity of aerodromes	In the city
2.	Restaurant(s) at or in the vicinity of aerodromes	In the city
3.	Transportation possibilities	Taxis from AD to city
4.	Medical Facilities	First Aid at AD. Hospitals in city.
5.	Bank and post office at or in the vicinity of aerodromes	Banks: Near AD and in the city Post office: Near AD and in the city.
6.	Tourist office	Office in the city: Tourist Information Centre Shimla +91-177-2652561, 2658302
7.	Remarks	NIL

VISM AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1.	Aerodrome category for fire fighting	Within ATS HR: CAT-4
2.	Rescue equipment	Available as per category
3.	Capability for removal of disabled aircraft	1. The critical aircraft for the airport is ATR-42 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Airport Director, Shimla Airport Office: 0177-02736835 Mob: 9418037925 Email: apdshimla@aai.aero
4.	Remarks	NIL

VISM AD 2.7 SEASONAL AVAILABILITY CLEARING

1.	Types of clearing equipment	NIL
2.	Clearance priorities	NIL
3.	Remarks	NIL

VISM AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking/Docking Chart
2	Designation, width, surface and strength of taxiways	Refer Aircraft Parking/Docking Chart
3	Location and elevation of altimeter checkpoints	New PB / 5071FT
4	Location of VOR checkpoints	NIL
5	Position of INS checkpoints	NIL
6	Remarks	Refer Parking & Docking Chart Apron Dimension: 60 X 30m

VISM AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1.	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Taxiing guidance signs at all intersections with taxiway and runway and at all holding postions.
2.	RWY and TWY markings and LGT	RWY Markings: Designation, THR, Centerline, Edge,Turn pad, Aiming Point, TDZ. RWY Lighting: RWY Edge Lights, Turn Pad. TWY Markings: Edge, Centerline TWY Lighting: Edge
3.	Stop bars	NIL
4.	Remarks	NIL

VISM AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	ANTENNA	310508.5N 0770358.5E	5122 FT	NIL	ANTENNA ON TERMINAL BUILDING
In circling area and at AD	OTHER	310507.0N 0770359.2E	5107 FT	NIL	MET ANTENNA
In circling area and at AD	ANTENNA	310507.7N 0770358.7E	5129 FT	NIL	ANTENNA ON ATC TOWER
In circling area and at AD	OTHER	310507.8N 0770358.6E	5118 FT	NIL	ATC BEACON
In circling area and at AD	BUILDING	310507.8N 0770358.6E	5115 FT	NIL	ATC BUILDING
In circling area and at AD	NAVAID	310507.9N 0770351.0E	5099 FT	LGTD	DVOR MONITOR ANTEENA
In circling area and at AD	BUILDING	310508.8N 0770357.8E	5112 FT	NIL	LIGHTENING ARRESTER ON TERMINAL BUILDING (BUILDING TOP-1553.8M)
In circling area and at AD	TREE	310616.6N 0770650.4E	6791 FT	NIL	TREE

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	TANK	310617.3N 0770649.4E	6774 FT	NIL	OVERHEAD WATER TANK
In circling area and at AD	OTHER	310618.1N 0770650.2E	6823 FT	NIL	CELLPHONE MAST ON HILL
In circling area and at AD	TRANSMISSION LINE	310617.5N 0770735.4E	6481 FT	NIL	H.T.PYLON MAST
In circling area and at AD	TRANSMISSION LINE	310603.9N 0770749.4E	6708 FT	NIL	H.T.PYLON MAST
In circling area and at AD	TRANSMISSION LINE	310558.4N 0770744.3E	6704 FT	NIL	H.T.PYLON MAST
In circling area and at AD	TOWER	310613.0N 0770904.4E	7425 FT	NIL	DOORDARSHAN TOWER
In circling area and at AD	NATURAL HIGHPOINT	310623.3N 0770622.5E	6660 FT	NIL	TREE ON HILL
In circling area and at AD	OTHER	310331.4N 0770810.0E	7023 FT	NIL	CELLPHONE MAST ON HILL
In circling area and at AD	NATURAL HIGHPOINT	311146.7N 0770347.1E	6086 FT	NIL	HILL TOP
In circling area and at AD	BUILDING	310622.9N 0770622.8E	6653 FT	NIL	KALIMATA TEMPLE ON HILL
In circling area and at AD	NATURAL HIGHPOINT	310746.6N 0770600.8E	6451 FT	NIL	HILL TOP
In circling area and at AD	NATURAL HIGHPOINT	310921.4N 0770455.8E	6275 FT	NIL	HILL TOP
In circling area and at AD	NATURAL HIGHPOINT	310943.6N 0770226.8E	5824 FT	NIL	HILL TOP
In circling area and at AD	NATURAL HIGHPOINT	305947.1N 0770600.3E	6457 FT	NIL	HILL TOP
In circling area and at AD	NATURAL HIGHPOINT	310152.8N 0770632.2E	6308 FT	NIL	HILL TOP
In circling area and at AD	NATURAL HIGHPOINT	310124.8N 0770716.5E	6467 FT	NIL	HILL TOP
In circling area and at AD	NATURAL HIGHPOINT	310114.7N 0770812.2E	6808 FT	NIL	HILL TOP
In circling area and at AD	BUILDING	310314.4N 0770831.0E	7178 FT	NIL	TEMPLE ON HILL
In circling area and at AD	OTHER	310545.0N 0770803.0E	7219 FT	NIL	CELLPHONE MAST ON HILL
In circling area and at AD	NATURAL HIGHPOINT	310938.0N 0770411.9E	6084 FT	NIL	HILL TOP
In circling area and at AD	TOWER	310613.0N 0770629.1E	6584 FT	NIL	JUTOG TOWER
In circling area and at AD	OTHER	310518.8N 0770810.7E	6887 FT	NIL	CELLPHONE MAST ON HILL
In circling area and at AD	NATURAL HIGHPOINT	310452.5N 0770701.6E	5700 FT	NIL	HILL TOP
In circling area and at AD	NATURAL HIGHPOINT	310144.8N 0770606.4E	6080 FT	NIL	HILL TOP
In circling area and at AD	OTHER	310039.3N 0770512.0E	5721 FT	NIL	CELLPHONE MAST ON HILL
In circling area and at AD	NATURAL HIGHPOINT	311000.7N 0770154.9E	5799 FT	NIL	HILL TOP

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	OTHER	310817.5N 0770516.0E	5902 FT	NIL	CELLPHONE MAST ON HILL
In circling area and at AD	OTHER	310721.2N 0770609.6E	6137 FT	NIL	CELLPHONE MAST ON HILL
In circling area and at AD	OTHER	310214.8N 0770721.4E	6207 FT	NIL	CELLPHONE MAST ON HILL
In circling area and at AD	OTHER	310208.4N 0770632.3E	5888 FT	NIL	CELLPHONE MAST ON HILL
In circling area and at AD	TANK	310218.1N 0770720.1E	6074 FT	NIL	OVERHEAD WATER TANK ON HILL
In circling area and at AD	BUILDING	310214.3N 0770633.4E	5682 FT	NIL	BUILDING ON HILL

VISM AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1.	Name of the associated meteorological office	Shimla
2.	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	0800 – 1500 IST/As ATS
3.	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Delhi As Requested
4.	Availability of the trend forecast for the aerodrome and interval of issuance	NIL
5.	Information on how briefing and/or consultation is provided	NIL
6.	Types of flight documentation supplied and language(s) used in flight documentation	Tabular Form, English
7.	Charts and other information displayed or available for briefing or consultation	NIL
8.	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	DPI, DIWE, Thermograph, Hydrograph, S. R. R. G.
9.	The air traffic services unit(s) provided with meteorological information	Shimla ATC
10.	Additional information, e.g. concerning any limitation of service.	MET Data available on request

VISM AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
14	146.02 DEG	1189 x 30 M	14/F/B/W/T Asphalt	THR: 310512.02N 0770351.06E RWY END: 310440.02N 0770416.14E
32	326.02 DEG	1189 x 30 M	14/F/B/W/T Asphalt	THR: 310440.02N 0770416.14E RWY END: 310512.02N 0770351.06E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 5073.0FT TDZ: 5073.0FT		NIL	NIL	1309 x 80 M
THR: 5045.0FT TDZ: 5050.0FT		NIL	NIL	1309 x 80 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
30M x 60M			Vertical Datum: EGM-08
30M x 60M			Vertical Datum: EGM-08

VISM AD 2.13 DECLARED DISTANCES

RWY Designation	TORA (M)	TODA (M)	ASDA (M)	LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared) Remarks
1	2	3	4	5	6
14	1189	1189	1189	1189	
32	1189	1189	1189	1189	

VISM AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
14		Green	PAPI LEFT/3.00 DEG MEHT (40.75FT)	
32		Green	PAPI LEFT/3.00 DEG MEHT (41.50FT)	

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	1189 M 60 M White LIH	Red		NIL
	1189 M 60 M White LIH	Red		NIL

VISM AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	On Tower building. White and Green flashes, 22 rpm. As ATS
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	---
		Anemometer	---
3	Taxiway edge and taxiway centre line lights;	Edge	Lighted
		Centre Line	NIL
4	Secondary power supply including switch-over time;	Secondary power supply to all lighting at AD. Switch-over time10 sec.	
5	Remarks	NIL	

VISM AD 2.16 HELICOPTER LANDING AREA

1.	Geographical coordinates of the geometric centre of touchdown and liftoff (TLOF) or of each threshold of final approach and take-off (FATO) area	--
2.	TLOF and/or FATO area elevation:	--
3.	TLOF and FATO area dimensions to the nearest meter or foot, surface type, bearing strength and marking;	--
4.	True bearings of FATO;	--
5.	Declared distances available	--
6.	Approach and FATO lighting;	--
7.	Remarks	Not established

VISM AD 2.17 ATS AIRSPACE

1.	Airspace designation, geographical coordinates and lateral limits	CTR: Area bounded by lines joining points 305911N 0765341E; 310735N 0765906E then along the clockwise arc of a circle of 5NM radius centred on 310454N 0770404E to 310200N 0770855E; 305344N 0770349E then along the counter clockwise arc of a circle of 20NM radius centred on 303959N 0764655E to point of origin.
2.	Vertical limits	8000 FT AMSL
3.	Airspace classification	D
4.	Call sign and language(s) of the air traffic services unit providing service;	SHIMLA Tower, English
5.	Transition altitude	13000 FT
6.	Hours of applicability	HO
7.	Remarks	NIL

VISM AD 2.18 ATS COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
TWR	SHIMLA Tower	118.350 MHZ	
TWR	SHIMLA Tower	118.650 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	As ATS	NIL
	AS ATS	BACKUP FREQ.

VISM AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic and type of supported operation for ILS/MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
DVOR/DME	SLA	114.100 MHz CH88X	As ATS

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
310510.1N 0770347.9E	5102 FT		Vertical Datum: EGM-08

VISM AD 2.20 LOCAL AERODROME REGULATIONS

• No Aircraft shall take lock turn/ pivotal turn on the Runway to avoid pavement damage.

VISM AD 2.21 NOISE ABATEMENT PROCEDURES

VISM AD 2.22 FLIGHT PROCEDURES

1. Preferred departure on Runway 14 and landing on Runway 32.
2. Minimum flight altitude Chandigarh/Shimla Sector: 8600 FT.
3. Minimum flight altitude Shimla/Kullu Sector: 12600 FT.
4. Aircraft operating below the specified minimum altitude are required to avoid terrain immediately north of airfield.

VISM AD 2.23 ADDITIONAL INFORMATION

1. Objects of Vertical Significance around Shimla Aerodrome

S No.	Object	Top Elevation (M)	Horizontal Distance from ARP (M)	MAG. Bearing From ARP
1	Tree on Hill Top	2076	5150	60.00 DEG
2	Pylon Mast on Hill	2043	6175	70.75 DEG
3	Hill Top	2119	6625	76.25 DEG
4	House on Hill Top	2188	8425	113.50 DEG
5	Hill Top	2075	9450	135.50 DEG
6	Hill Top	1971	8250	141.25 DEG
7	Hill Top	1919	6900	143.50 DEG
8	Hill Top	1973	10050	162.00 DEG
9	Hill Top	2216	15250	169.75 DEG
10	Hill Top	1976	19075	179.75 DEG
11	TV Tower	1962	22975	204.75 DEG
12	Hill Top	1602	3825	231.50 DEG
13	Hill Top	2069	21400	304.75 DEG
14	Hill Top	1828	18425	324.00 DEG
15	Hill Top	1782	9325	343.75 DEG
16	Hill Top	1917	8375	008.50 DEG
17	Hill Top	1972	6150	030.25 DEG
18	Temple on Hill Top	2026	4625	053.00 DEG
19	Hill Top	1525	2125	255.75 DEG
20	Hill Top	1474	3300	133.00 DEG
21	Hill Top	1522	3250	332.00 DEG
22	Hill Top	1855	12700	357.75 DEG
23	ATC Tower	1562.2	450	342.00 DEG

VISM AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart(02 October 2025)
2. Aircraft Parking/Docking Chart(27 November 2025)
3. Aerodrome Obstacle Chart Type - A, (Operating Limitations) RWY 14/32
4. Aerodrome Obstacle Chart Type - B

VISM AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3