AD 2. AERODROMES

VASD AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VASD - SHIRDI AIRPORT, SHIRDI

VASD AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	194127N 0742218E	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	Approximately 16KM South-West of Shirdi Railway Station near village Kakadi.	
3	Aerodrome elevation and reference temperature	1938 FT / 38.5 DEG C	
4	Magnetic variation, date of information and annual change	1.00 DEG W (2010) /0.033 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airport Director, Shirdi Airport, Near Village Kakadi, Taluka Kopargaon, District Ahmednagar, Pin Code 423107, Kelwad Post Office.,	
		Telephone:	(91) 02423246201
		Fax:	91 02423246202
		AFS:	
		Email:	apd.sag@madcindia.org
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	Aerodrome Reference Code: 4C	

VASD AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON-SUN: 0320 UTC to 1230 UTC
2	Custom and immigration	NIL
3	Health and sanitation	NIL
4	AIS briefing office	As ATS
5	ATS reporting office (ARO)	As ATS
6	MET Briefing office	As ATS
7	Air Traffic Service	Consult NOTAM for current ATS HR.
8	Fuelling	As ATS
9	Handling	As ATS
10	Security	As ATS
11	De-icing	NIL
12	Remarks	Security by CISF H24.

VASD AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Limited cargo operations carried out through terminal building
2	Fuel and Oil types	JET A1

3	Fuelling facilities and capacity	IOCL: Static Storage 800KL & Bowsers - 16KL (3nos.) Total cacpacity: 848 KL HPCL: Static Storage 30KL & Bowsers - 15KL (3nos.) Total cacpacity: 75 KL
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

VASD AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	In the city
2	Restaurant(s) at or in the vicinity of aerodrome	Snacks counter available at AD and restaurants available in the city
3	Transportation possibilities	Taxis and buses from AD
4	Medical Facilities	First Aid at AD. Hospitals in city.
5	Bank and post office at or in the vicinity of aerodrome	Banks: In the city Post office: In the city
6	Tourist office	In the city
7	Remarks	Shirdi Sansthan Information counter available at AD

VASD AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-7
2	Rescue equipment	Available as per category.
3	Capability for removal of disabled aircraft	1. The critical aircraft for the airport is B737-800 2. Primary responsibility for removing disabled aircraft rests with the concerned airline. 3. The airlines may contact Airport Director for coordinating with the agencies (Air India) for Disabled Aircraft Recovery Kit. 4. Contact Details of Airport Director: M-9900521853 apd.sag@madcindia.org
4	Remarks	MADC has tied up with Air India for providing the recovery kit

VASD AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VASD AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking / Docking Chart
2	Designation, width, surface and strength of taxiways	Refer Aircraft Parking / Docking Chart
3	Location and elevation of altimeter checkpoints	Aircraft Stand No. 1: 1878.84 FT Aircraft Stand No. 2: 1879.59 FT Aircraft Stand No. 3 : 1880.09 FT Aircraft Stand No. 4 : 1880.91 FT
4	Location of VOR checkpoints	NIL

5	Position of INS checkpoints	NIL
6	Remarks	1. Apron 225 M x 105 M to accommodate three ATR72 and one A320 aircraft. 2. All the bays are power in/ power out. 3. All are remote stands. Clearance between stands 4.5M.

VASD AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Aircraft stand ID markings available. Taxiing guidance provided on R/T Guidelines at Apron. VDGS not available
2	Runway and taxiway markings and lights	RWY Markings: Designation, Center Line, Transverse Strip, THR, TDZ, Edge, Aiming Point, Turn pad. RWY Lights: Nil TWY Marking: Center Line, Holding Positions on TWY A & TWY B, Mandatory Instruction Marking TWY Lights: Nil
3	Stop bars (if any)	NIL
4	Remarks	NIL

VASD AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
27/TKOF 09/APCH	OTHER	194121.4N 0742141.3E	1968 FT	NIL	Shed Top
27/TKOF 09/APCH	POLE	194121.6N 0742143.0E	1983 FT	NIL	Electric Pole
27/TKOF 09/APCH	POLE	194119.6N 0742143.0E	1979 FT	NIL	Electric Pole
27/TKOF 09/APCH	POLE	194118.7N 0742139.5E	1979 FT	NIL	Electric Pole
27/TKOF 09/APCH	POLE	194118.2N 0742137.7E	1982 FT	NIL	Electric Pole
27/TKOF 09/APCH	POLE	194117.8N 0742136.1E	1983 FT	NIL	Electric Pole
In circling area and at AD	NATURAL HIGHPOINT	193732.8N 0741941.5E	2582 FT	NIL	Hill Top
In circling area and at AD	NATURAL HIGHPOINT	193647.0N 0741950.4E	2575 FT	NIL	Hill Top
In circling area and at AD	NATURAL HIGHPOINT	193554.4N 0742126.6E	2733 FT	NIL	Hill Top
In circling area and at AD	NATURAL HIGHPOINT	193508.8N 0742126.1E	2484 FT	NIL	Hill Top

VASD AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Mumbai
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	As ATS

3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Mumbai
4	Availability of the trend forecast for the aerodrome and interval of issuance	METAR on half an hour frequency
5	Information on how briefing and/or consultation is provided	Report is sent manually to ATC
6	Types of flight documentation supplied and language(s) used in flight documentation	Tabular Form (English)
7	Charts and other information displayed or available for briefing or consultation	NIL
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	NIL
9	The air traffic services unit(s) provided with meteorological information	Shirdi Airport ATC
10	Additional information, e.g. concerning any limitation of service.	Actual visibility based on visual landmarks.

VASD AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
09	88.41 DEG	2500 x 45 M	54/F/C/W/T Asphalt	THR: 194118.64N 0742154.52E RWY END: 194120.88N 0742320.32E
27	268.41 DEG	2500 x 45 M	54/F/C/W/T Asphalt	THR: 194120.88N 0742320.32E RWY END: 194118.64N 0742154.52E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 1938.3FT TDZ:		NIL	NIL	2620 x 150 M
THR: 1909.5FT TDZ:		NIL	NIL	2620 x 150 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
240M x 150M		NIL	Slope of RWY: LONG: 1% TRANS: 1.5%
240M x 150M		NIL	Slope of RWY: LONG: 1% TRANS: 1.5%

VASD AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
09	2500	2500	2500	2500	
27	2500	2500	2500	2500	

VASD AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
09	SALS 420 M LIH	Green	PAPI LEFT/3.00 DEG MEHT (16.19M)	NIL
27	CAT I 900 M LIH	Green	PAPI LEFT/3.00 DEG MEHT (16.12M)	NIL

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	2500 M 60 M White LIH	Red	NIL	NIL
	2500 M 60 M White LIH	Red	NIL	NIL

VASD AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	At ATC Tower Building, FLG W & G with a frequency of 24 flashes per minute.
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	South of THR RWY 27 (194115.788N 0742319.525E) ELEV: 580.222 M
		Anemometer	North of RWY abeam TWY A
3	Taxiway edge and taxiway centre line lights;	Edge	NIL
		Centre Line	NIL
4	Secondary power supply including switch-over time;	DG Set available for all light at aerodrome (PAPI AND ABN). DG set will be switched on 20 minutes before arrival of EV FLT.	
5	Remarks	ABN operational during ATS hours	

VASD AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not Established
2	TLOF and/or FATO area elevation:	Not Established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not Established
4	True bearings of FATO;	Not Established
5	Declared distances available	Not Established
6	Approach and FATO lighting;	Not Established
7	Remarks	Not Established

VASD AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Circular area centered on 194127N 0742218E within a 11NM radius.
2	Vertical limits	FL 95
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	SHIRDI TOWER, English
5	Transition altitude	7000 FT
6	Hours of applicability	HO
7	Remarks	1. 24 HR prior information for Non Schedule operations and watch extension. 2. Shirdi Approach Control Unit is combined with Shirdi Aerodrome Control Tower.

VASD AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
APP	SHIRDI TOWER	118.875 MHZ	
APP	SHIRDI TOWER	121.225 MHZ	
TWR	SHIRDI TOWER	118.875 MHZ	
TWR	SHIRDI TOWER	121.225 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	HO	1. Functions of Approach Control Service provided by Aerodrome Control Tower. 2. Main FREQ
	HO	1.Functions of Approach Control Service provided by Aerodrome Control Tower. 2. Backup FREQ
	HO	1. Main frequency
	HO	1. Backup

VASD AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
DVOR/DME	SRD	112.000 MHz CH57X	HO

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
194117.8N 0742347.3E	1904 FT		Vertical datum: EGM08

VASD AD 2.20 LOCAL AERODROME REGULATIONS

1. Taxiing procedure: All the aircraft stands are power in/ power out, more precaution required during taxiing.

2. Wing Tip Marsheller mandatory to be available during movement of aircraft at apron & abeam apron.

VASD AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VASD AD 2.22 FLIGHT PROCEDURES

NIL

VASD AD 2.23 ADDITIONAL INFORMATION

1. Aerodrome Reference Code 4C.
2. Apron Suitable up to Aircraft type A320
3. Apron Slope 1%
4. Temporary Isolation temporary location Dumbbell RWY 09

VASD AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart (23 January 2025)
2. Aircraft Parking / Docking Chart (23 January 2025)
3. Aerodrome Obstacle Chart – (Operating Limitations) Type A RWY 09/27
4. Objects of Vertical Significance Around Shirdi Airport
5. Instrument Approach Chart - VOR Procedure RWY 09 (17 APR 2025)
6. Instrument Approach Chart - VOR Procedure RWY 27 (17 APR 2025)
7. Instrument Approach Chart - RNP Y Procedure RWY 09 (17 APR 2025)
8. Coding Table - RNP Y Procedure RWY 09
9. Instrument Approach Chart - RNP Y Procedure RWY 27 (17 APR 2025)
10. Coding Table - RNP Y Procedure RWY 27

VASD AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	**2**	**3**