AD 2. AERODROMES

VOSH AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VOSH - SHIVAMOGGA AIRPORT, SHIVAMOGGA

VOSH AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	135135N 0753704E	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	5.4 NM South East of Shivamogga City	
3	Aerodrome elevation and reference temperature	2069 FT / 36.4 DEG C	
4	Magnetic variation, date of information and annual change	1.75 DEG W (2010) /0.0333 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Karnataka State Industrial Infrastructure Development Corporation (KSIIDC) Aerodrome Reporting Officer: MD : Dr. MR Ravi,	
		Telephone:	(91) 080 22255740
		Fax:	
		AFS:	
		Email:	bic3@ksiidc.com
6	Types of traffic permitted (IFR/VFR)	VFR	
7	Remarks	1. Vertical Datum : EGM 08	

VOSH AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	0930 to 1800 IST (0400-1230 UTC) Daily except SAT, SUN and HOL
2	Custom and immigration	NIL
3	Health and sanitation	NIL
4	AIS briefing office	As per ATS
5	ATS reporting office (ARO)	As per ATS
6	MET Briefing office	As per ATS
7	Air Traffic Service	Consult NOTAMs for current ATS Hrs.
8	Fuelling	IOCL and Sky Tanking Available
9	Handling	NIL
10	Security	H24. Karnataka State Industrial Security Force
11	De-icing	NIL
12	Remarks	Nil

VOSH AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	No exclusive facilities. Cargo is handled by the operator concerned.
2	Fuel and Oil types	Not Available
3	Fuelling facilities and capacity	Not Available
4	De-icing facilities	Not Available
5	Hangar space for visiting aircraft	Not Available

6	Repair facilities for visiting aircraft	On apron (On Request)
7	Remarks	Equipment must be carried by the operator

VOSH AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	In nearby townships within 15Kms.
2	Restaurant(s) at or in the vicinity of aerodrome	In nearby townships within 15Kms.
3	Transportation possibilities	Buses, Auto Rickshaws and Hired Cars.
4	Medical Facilities	First Aid and basic facilities at ESIC Hospital located within 15 Kilometer. For serious & critical cases District Hospital located in Shivamogga City about 12 kms.
5	Bank and post office at or in the vicinity of aerodrome	Banks: Within Shivamogga Township, 15 kms
6	Tourist office	Not Available
7	Remarks	Nil

VOSH AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-7 Within AD Hours
2	Rescue equipment	Two CFTs along with rescue tools.
3	Capability for removal of disabled aircraft	1. The critical aircraft for the airport is A320. 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Aerodrome coordinator - Safety Manager Email: trmmgrsmgairport.ksiidc@gmail.com Contact No: 08182-288306
4	Remarks	Nil

VOSH AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	Nil
2	Clearance priorities	Nil
3	Remarks	Aerodrome is operational during all seasons.

VOSH AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking/docking Chart
2	Designation, width, surface and strength of taxiways	Refer Aircraft Parking/docking Chart
3	Location and elevation of altimeter checkpoints	Location: Entire Apron Elevation: 2008 FT
4	Location of VOR checkpoints	NIL
5	Position of INS checkpoints	NIL
6	Remarks	1. Coordinates of Runway Holding Positions: i. TWY A: 135121.757N 0753624.532E, ELEV: 2010 FT ii. TWY B: 135116.865N 0753625.667E, ELEV: 2010 FT 2. Coordinates of Runway/Taxiway Intersection: i. TWY A & B : 135119.308N 0753625.094E, ELEV: 2012 FT

VOSH AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Aircraft ID marking provided on ground, Taxiing guidance provided on R/T. Standard marking at Apron, Mandatory Information and Location signs provided.
2	Runway and taxiway markings and lights	RWY Markings: RWY Designator,Threshold Markings,Aiming point, Centerline Marking, Touchdown Zone Markings, RWY Side Stripe Marking. Turn Pad Marking. RWY Lights: Not Available. TWY Markings: Side Stripe Marking, Centerline Marking, RWY Holding Position Marking. TWY Lights: Not Available
3	Stop bars (if any)	Provided at Each Taxiway
4	Remarks	Nil

VOSH AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	OTHER	135206.4N 0753839.5E	2244 FT	LGTD	Chimney
In circling area and at AD	OTHER	135222.9N 0753859.4E	2275 FT	LGTD	Chimney Top
In circling area and at AD	OTHER	135223.1N 0753859.3E	2275 FT	LGTD	Chimney Top
In circling area and at AD	BUILDING	135225.1N 0753859.8E	2227 FT	LGTD	Building, Grill Top - 2227.23 FT, Staircase Room Top –2224.67 FT, Building Top - 2208.20FT.
In circling area and at AD	TOWER	135227.7N 0753907.2E	2219 FT	LGTD	H. T. Tower
In circling area and at AD	OTHER	135231.7N 0753913.3E	2237 FT	LGTD	Cellphone Mast Top
In circling area and at AD	OTHER	135229.9N 0753911.2E	2251 FT	LGTD	Cellphone Mast Top
In circling area and at AD	OTHER	135228.2N 0753913.1E	2270 FT	LGTD	Cellphone Mast Top
In circling area and at AD	OTHER	135201.5N 0753924.8E	2220 FT	LGTD	Cellphone Mast Top

VOSH AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	AMO Bengaluru
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	AMO Bengaluru
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Head AMO Bengaluru Every 3 hours validity 9 hrs

4	Availability of the trend forecast for the aerodrome and interval of issuance	Every half hour trend forecast will issued Valid 2 hrs If Special or additional report issue then trend is also part of it.
5	Information on how briefing and/or consultation is provided	Through online OLBS Chennai or OLBS Delhi website, Chart documents
6	Types of flight documentation supplied and language(s) used in flight documentation	English and Hindi
7	Charts and other information displayed or available for briefing or consultation	Yes as per the requirement
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Yes
9	The air traffic services unit(s) provided with meteorological information	AMO Bengaluru
10	Additional information, e.g. concerning any limitation of service.	Warning for Aerodrome, e.g. light aircraft warning and Thunder storm warning

VOSH AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
RWY 08	77.11 DEG	3050 x 45 M	66/F/C/W/T Asphalt	THR: 135118.58N 0753621.85E RWY END: 135140.74N 0753800.89E
RWY 26	257.11 DEG	3050 x 45 M	66/F/C/W/T Asphalt	THR: 135140.74N 0753800.89E RWY END: 135118.58N 0753621.85E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 2009.0FT TDZ: 2069.0FT	0.59%	NIL	NIL	3170 x 280 M
THR: 2069.0FT TDZ: 2069.0FT	0.59%	NIL	NIL	3170 x 280 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
240M x 90M	NIL	AVBL	Vertical Datum: EGM-08
240M x 90M	NIL	AVBL	Vertical Datum: EGM-08

VOSH AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
RWY 08	3050	3050	3050	3050	
RWY 26	3050	3050	3050	3050	

VOSH AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
RWY 08	NIL	NIL	NIL	NIL
RWY 26	NIL	NIL	NIL	NIL

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
NIL	NIL	NIL	NIL	NIL
NIL	NIL	NIL	NIL	NIL

VOSH AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	Provided on top of ATC
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	Available
		Anemometer	Available
3	Taxiway edge and taxiway centre line lights;	Edge	Not Available
		Centre Line	Not Available
4	Secondary power supply including switch-over time;	Secondary Power Supply is available through two Diesel Generators, Three Phase 500 KVA /400V, Auto Start (Within fifteen seconds)	
5	Remarks	Nil	

VOSH AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not Established
2	TLOF and/or FATO area elevation:	Not Established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not Established
4	True bearings of FATO;	Not Established
5	Declared distances available	Not Established
6	Approach and FATO lighting;	Not Established
7	Remarks	Not Established

VOSH AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Circular area centered on 135135N 0753704E within a 18NM radius.
2	Vertical limits	FL 105
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	SHIVAMOGGA TOWER, English
5	Transition altitude	9000 FT
6	Hours of applicability	HO
7	Remarks	1.CTR available only during published hours of operations 2.Shivamogga Approach Control Unit is combined with Shivamogga Aerodrome Control Tower.

VOSH AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
APP	SHIVAMOGGA TOWER	120.825 MHZ	
APP	SHIVAMOGGA TOWER	124.075 MHZ	
TWR	SHIVAMOGGA TOWER	120.825 MHZ	
TWR	SHIVAMOGGA TOWER	124.075 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	HO	1. Main 2.Functions of Approach Control Service provided by Aerodrome Control Tower
	HO	1.Back up 2.Functions of Approach Control Service provided by Aerodrome Control Tower
	AS ATS	1. Main Frequency
	As ATS	1. Backup Frequency

VOSH AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8

VOSH AD 2.20 LOCAL AERODROME REGULATIONS

NIL

VOSH AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VOSH AD 2.22 FLIGHT PROCEDURES

NIL

VOSH AD 2.23 ADDITIONAL INFORMATION

NIL

VOSH AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart
2. Aircraft Parking/Docking Chart
3. Aerodrome Obstacle Chart Type A (Operating Limitations) RWY 08
4. Aerodrome Obstacle Chart Type A (Operating Limitations) RWY 26
5. Aerodrome Obstacle Chart Type B

VOSH AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3