AD 2. AERODROMES

VASL AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VASL - SOLAPUR AIRPORT, SOLAPUR

VASL AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	173740N 0755603E	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	7 KM Southeast of Solapur Railway Station.	
3	Aerodrome elevation and reference temperature	1588 FT / 40.7 DEG C	
4	Magnetic variation, date of information and annual change	1.00 DEG W (2010) /0.033 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airport Director, Airports Authority of India, Solapur Airport, Solapur 413224,	
		Telephone:	0217-2607071
		Fax:	
		AFS:	
		Email:	apdvasl@aai.aero
6	Types of traffic permitted (IFR/VFR)	VFR	
7	Remarks	Gravity Model: EGM-08	

VASL AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON-FRI 0400 –1230 UTC (0930-1800 IST) SAT, SUN: NIL
2	Custom and immigration	Not Applicable
3	Health and sanitation	As ATS
4	AIS briefing office	As ATS
5	ATS reporting office (ARO)	As ATS
6	MET Briefing office	As ATS
7	Air Traffic Service	Refer NOTAM
8	Fuelling	As ATS
9	Handling	Not Available
10	Security	Maharashtra State Police
11	De-icing	NIL
12	Remarks	Non-Schedule flight to obtain positive clearance at least 48 hrs. prior to departure for Solapur Airport.

VASL AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Not Available
2	Fuel and Oil types	JET A1
3	Fuelling facilities and capacity	HPCL Bowsers
4	De-icing facilities	Not Available
5	Hangar space for visiting aircraft	Not Available
6	Repair facilities for visiting aircraft	Not Available

7	Remarks	Nil

VASL AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Available in City
2	Restaurant(s) at or in the vicinity of aerodrome	Available
3	Transportation possibilities	Auto/Cab from AD
4	Medical Facilities	Available (First aid in Terminal building PHC facility hospital 2 km. Serious & critical case 9 km hospital)
5	Bank and post office at or in the vicinity of aerodrome	Banks: Available in City Post office: Available in City
6	Tourist office	Available in City
7	Remarks	NIL

VASL AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-5
2	Rescue equipment	CFT: 1 (One) Ambulance: 1 (One)
3	Capability for removal of disabled aircraft	1. The critical aircraft for Solapur Airports is ATR42. 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Airport Director Contact Details: +91 217 2607071 apdvasl@aai.aero
4	Remarks	NIL

VASL AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VASL AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking/Docking Chart
2	Designation, width, surface and strength of taxiways	Designator: TWY A Width: 23 M Surface: Asphalt Strength: PCN 19/F/B/W/T
3	Location and elevation of altimeter checkpoints	Location: Centre of the apron on power out taxiway marking Elevation: 482.434 M
4	Location of VOR checkpoints	NIL
5	Position of INS checkpoints	NIL

6	Remarks	1. Coordinates of Runway Holding Position: TWY A: 173735.76N 0755605.00E/ELEV: 1584FT 2. Coordinates of RWY & Taxi Intersection: TWY A: 173737.43N 0755607.51E/ELEV: 1584FT 3. Vertical Datum: EGM 08

VASL AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Taxiing guidance provided on R/T. Taxi Guidance lines, Apron Stand Markings, Nose wheel markings, Apron safety lines.
2	Runway and taxiway markings and lights	RWY Markings: TDZ and APM markings available. Runway designator, threshold marking, Runway centre line & edge line marking, turn pad marking Lights: Not Available TWY Markings: Holding point marking, Taxiway Edge marking, Taxiway centre line, shoulder strip markings available Lights: Not Available
3	Stop bars (if any)	Not Available
4	Remarks	NIL

VASL AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
33/TKOF 15/APCH	BUILDING	173816.0N 0755538.3E	1620 FT	NIL	Building
33/APCH 15/TKOF	STACK	173648.6N 0755641.2E	1705 FT	NIL	Chimney
33/APCH 15/TKOF	STACK	173646.8N 0755642.6E	1704 FT	NIL	Chimney
In circling area and at AD	BUILDING	173758.3N 0755440.2E	1744 FT	NIL	Building
In circling area and at AD	OTHER	173912.5N 0755559.7E	1943 FT	NIL	TV Tower
In circling area and at AD	OTHER	173903.0N 0755516.7E	1751 FT	NIL	Mast
In circling area and at AD	OTHER	173301.2N 0755900.9E	2429 FT	NIL	Lightning Arrester on NTPC Chimney (Chimney Top737m)
In circling area and at AD	TREE	173815.7N 0755536.5E	1628 FT	NIL	Group of Trees
In circling area and at AD	BUILDING	173754.4N 0755441.5E	1746 FT	NIL	Building

VASL AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	IMD

2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	During ATC watch hours (TBN)
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	IMD personnel deputed/stationed in tower (Every half hour)
4	Availability of the trend forecast for the aerodrome and interval of issuance	Not available
5	Information on how briefing and/or consultation is provided	No digital means available (During the flight by ATC via VHF).
6	Types of flight documentation supplied and language(s) used in flight documentation	English as per ICAO code
7	Charts and other information displayed or available for briefing or consultation	Not available
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Not available
9	The air traffic services unit(s) provided with meteorological information	ATC
10	Additional information, e.g. concerning any limitation of service.	NIL

VASL AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
15	144.98 DEG	2009 x 45 M	28/F/B/W/T Asphalt	THR: 173808.46N 0755544.84E RWY END: 173714.93N 0755623.95E
33	324.98 DEG	2009 x 45 M	28/F/B/W/T Asphalt	THR: 173717.14N 0755622.33E RWY END: 173808.46N 0755544.84E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 1586.0FT TDZ: 1588.0FT	-0.20%	NIL	NIL	2129 x 80 M
THR: 1575.0FT TDZ: 1585.0FT	0.20%	NIL	NIL	2129 x 80 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	**12**	**13**	**14**
90M x 90M	NIL	NIL	NIL
90M x 90M	NIL	NIL	NIL

VASL AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	**2**	**3**	**4**	**5**	**6**
15	1926	1926	1926	2009	--
33	2009	2009	2009	1926	THR displaced by 83M

VASL AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	**2**	**3**	**4**	**5**
15	NIL	NIL	PAPI LEFT/3.20 DEG	NIL
33	NIL	NIL	PAPI LEFT/3.22 DEG	NIL

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	**7**	**8**	**9**	**10**
NIL	NIL	NIL	NIL	NIL
NIL	NIL	NIL	NIL	NIL

VASL AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	Available Installed on top of ATC Tower. Green and White flashes
		IBN	Not AVBL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	Available adjacent to ARP
		Anemometer	Not Available Windsock available near ARP

3	Taxiway edge and taxiway centre line lights;	Edge	Not Available
		Centre Line	Not Available
4	Secondary power supply including switch-over time;	Substation: 2 Nos. DG Set 320 KVA each (01 main and 01 standby) Switch-over time: less than 15 SEC	
5	Remarks	NIL	

VASL AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not Established
2	TLOF and/or FATO area elevation:	Not Established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not Established
4	True bearings of FATO;	Not Established
5	Declared distances available	Not Established
6	Approach and FATO lighting;	Not Established
7	Remarks	NIL

VASL AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Circular area centered on 173740N 0755603E within a 10NM radius.
2	Vertical limits	FL 55
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Solapur TWR, English
5	Transition altitude	5000 FT
6	Hours of applicability	HO
7	Remarks	Beyond operational hours airspace classification is Class G

VASL AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	**2**	**3**	**4**
TWR	Solapur TWR	118.600 MHZ	
TWR	Solapur TWR	124.300 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	**6**	**7**
	HO	Main Frequency
	HO	Backup Frequency

VASL AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
NDB	SO	345 kHz	As ATS

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
173732.9N 0755555.4E			Geoid Model: EGM08

VASL AD 2.20 LOCAL AERODROME REGULATIONS

NIL

VASL AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VASL AD 2.22 FLIGHT PROCEDURES

NIL

VASL AD 2.23 ADDITIONAL INFORMATION

NIL

VASL AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart(27 November 2025)
2. Aircraft Parking/Docking Chart(27 November 2025)
3. Aerodrome Obstacle Chart Type A (Operating Limitations) RWY 15(27 November 2025)
4. Aerodrome Obstacle Chart Type A (Operating Limitations) RWY 33(27 November 2025)
5. Aerodrome Obstacle Chart Type B(27 November 2025)

VASL AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3
