AD 2. AERODROMES

VASU AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VASU - SURAT AIRPORT, SURAT

VASU AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	210658N 0724431E M. Brg. 37.50 DEG /1364 M from Physical Beginning of RWY 04	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	14 Km South-West of Surat Railway Station	
3	Aerodrome elevation and reference temperature	25 FT / 42.0 DEG C	
4	Magnetic variation, date of information and annual change	0.50 DEG W (2010) /0.0333 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airport Director Airports Authority of India Surat Airport,Dumas Road,, Surat - 394550	
		Telephone:	(91) 2612720109 (91) 9429892020
		Fax:	(91) 261 2720195
		AFS:	VASUYHYX
		Email:	apdsurat@aai.aero
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	1. Gravity Model: EGM-08	

VASU AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON-FRI 0400-1230 UTC (0930-1800 IST) SAT, SUN + HOL: NIL
2	Custom and immigration	As ATS. See Serial No.12 Remark No. 1
3	Health and sanitation	NIL
4	AIS briefing office	NIL
5	ATS reporting office (ARO)	NIL
6	MET Briefing office	As ATS
7	Air Traffic Service	H24
8	Fuelling	As ATS
9	Handling	As ATS
10	Security	H24
11	De-icing	Not Available

12	Remarks	**1.** Customs and Immigration facilities are provided on limited basis to cover operations of scheduled INTL flights. The facilities can be arranged to cover any authorized non-sked operations O/R with 24 HRS PN to Airport Director. **2.** 4 HRS PN required for extension of ATC watch for non-scheduled flights. **3.** The ATS approved hourly RWY TFC handling capacity is as follows: Max number of ARR and DEP -12 (the minimum spacing between two successive arrivals shall be more than five min) Max number of arrivals only - 06 Max number of departures only - 10

VASU AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Domestic Cargo Available
2	Fuel and Oil types	JET A1 ATF
3	Fuelling facilities and capacity	Fuelling Equipment: Refueller Services: Single product of Jet A1 IOCL: ATF (JET A-1) Storage capacity: 91 KL Reliance: ATF (JET A-1) Storage capacity: 140 KL
4	De-icing facilities	Not Available
5	Hangar space for visiting aircraft	Not Available
6	Repair facilities for visiting aircraft	Not Available
7	Remarks	Mooring Facility: NIL

VASU AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Available in City
2	Restaurant(s) at or in the vicinity of aerodrome	Available at Airport and in City
3	Transportation possibilities	City Bus and Taxi Available at Airport
4	Medical Facilities	Medical Inspection room is available in Terminal Building. Hospital in City.
5	Bank and post office at or in the vicinity of aerodrome	Banks: Available in City Post office: Available in the city.
6	Tourist office	Available in City
7	Remarks	NIL

VASU AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-7
2	Rescue equipment	03 CFT, 02 Ambulance, Extinguishing Agent - Aqueous Film Forming Foam, 16 Proximity Suite, 18 BA Sets, Static water tank of 1,00,000 litres and Overhead tank capacity 50,000 litres

3	Capability for removal of disabled aircraft	1. The Critical Aircraft for the Airport is A321. 2. Primary responsibility for the removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Airport Director, Surat Airport Phone: 9429892020/0261-2700200 Email: apdsurat@aai.aero
4	Remarks	NIL

VASU AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	
2	Clearance priorities	
3	Remarks	All Season

VASU AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking/Docking Chart
2	Designation, width, surface and strength of taxiways	Refer Aircraft Parking/Docking Chart
3	Location and elevation of altimeter checkpoints	Location: All aircraft Stands Elevation: Refer Aircraft Parking/Docking Chart
4	Location of VOR checkpoints	TWY E1: 210733.509N 0724507.889E / ELEV: 22 FT TWY E2: 210713.092N 0724446.969E / ELEV: 17 FT TWY E3: 210707.404N 0724441.579E / ELEV: 17 FT TWY E4: 210648.639N 0724422.943E / ELEV: 17 FT TWY E6: 210624.925N 0724359.782E / ELEV: 18 FT
5	Position of INS checkpoints	

6	Remarks	i. Isolated Aircraft parking Position details: a) Location: NE of THR RWY 04 b) Dimensions: 75MX65M c) Link TWY: TWY D, 70.35M X 23M d) Surface: Concrete e) Strength (PCN): 66/R/A/W/T ii. Coordinates of RWY Holding Positions: a) TWY E1: 210733.374N 0724508.0466E / ELEV: 22 FT b) TWY E2: 210712.841N 0724447.257E / ELEV: 17FT c) TWY E3: 210707.273N 0724441.729E / ELEV: 17FT d) TWY E4: 210648.516N 0724423.105E / ELEV: 17 FT e) TWY E5: 210642.897N 0724417.518E / ELEV: 17 FT f) TWY E6: 210624.765N 0724359.964E / ELEV: 18 FT iii.Coordinates of RWY & TAXI intersection: a) TWY E1: 210731.353N 0724510.350E / ELEV: 25 FT b) TWY E2: 210710.643N 0724449.782E / ELEV: 18 FT c) TWY E3: 210705.073N 0724444.248E / ELEV: 19 FT d) TWY E4: 210646.472N 0724425.770E / ELEV: 18 FT e) TWY E5: 210640.690N 0724420.034E / ELEV: 18 FT f) TWY E6: 210622.743N 0724402.217E / ELEV: 20 FT iv. Gravity Model: EGM-08

VASU AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Taxiing guidance sign at all the intersections with TWY and RWY and all holding position guidance at apron. Standard Markings at Apron.
2	Runway and taxiway markings and lights	RWY Markings: Edge, Designation, THR, TDZ, Aiming Point, Centreline RWY Lighting: THR, RWY Edge, RWY END. RWY Guard LGT: AVBL at TWY E1, A,B,C,D and E6. TWY Markings: Edge, Centreline, TWY RWY Holding Position, VOR Check location TWY Lighting: Edge
3	Stop bars (if any)	NIL
4	Remarks	NIL

VASU AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
22/TKOF 04/APCH	OTHER	210618.9N 0724349.9E	40 FT	NO	Mobile Road Traffic (Road Elev. 7.1M + 5M Mobile Traffic)
22/TKOF 04/APCH	OTHER	210621.9N 0724353.9E	41 FT	NO	Mobile Road Traffic (Road Elev. 7.5M + 5M Mobile Traffic)

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
22/TKOF 04/APCH	FENCE	210621.4N 0724353.3E	36 FT	NO	Airport Boundary Wall with Fencing on Top
22/TKOF 04/APCH	OTHER	210621.2N 0724353.5E	40 FT	NO	Mobile Road Traffic (Road Elev. 7.3M + 5M Mobile Traffic)
22/TKOF 04/APCH	OTHER	210620.2N 0724351.6E	40 FT	NO	Mobile Road Traffic (Road Elev. 7.2M + 5M Mobile Traffic)
22/TKOF 04/APCH	POLE	210618.3N 0724349.6E	39 FT	NO	Light Pole
22/TKOF 04/APCH	OTHER	210617.4N 0724356.9E	32 FT	NO	Lightning Arrestor
22/TKOF 04/APCH	OTHER	210616.7N 0724352.0E	39 FT	NO	Mobile Road Traffic (Road Elev. 6.8M + 5M Mobile Traffic)
22/TKOF 04/APCH	TREE	210615.7N 0724348.8E	55 FT	NO	Group of Trees
22/TKOF 04/APCH	TREE	210616.0N 0724348.0E	61 FT	NO	Group of Trees
22/APCH 04/TKOF	OTHER	210739.2N 0724510.8E	40 FT	NO	Mobile Road Traffic (Road Elev. 7.2M + 5M Mobile Traffic)
22/APCH 04/TKOF	POLE	210739.5N 0724511.9E	34 FT	NO	Light Pole
22/APCH 04/TKOF	BUILDING	210803.2N 0724554.3E	135 FT	NO	Star Galaxy Building Top - Block G
22/APCH 04/TKOF	BUILDING	210806.0N 0724602.2E	155 FT	LGTD	Lighted Top on Shrungar Residency (Building Top - 46.6M) - Block J
22/APCH 04/TKOF	BUILDING	210806.7N 0724553.4E	139 FT	NO	Dish on Star Galaxy Building (Building Top - 41.5M) - Block D
22/APCH 04/TKOF	BUILDING	210808.2N 0724559.5E	168 FT	NO	Dish on Aagam Crossroad (Building Top - 50.2M) - Block A
22/APCH 04/TKOF	BUILDING	210809.2N 0724554.7E	147 FT	LGTD	Lighted Top on Horizon Building (Dish Top - 43.6M, Building Top - 42.7M) - Block B
22/APCH 04/TKOF	BUILDING	210809.9N 0724539.0E	161 FT	LGTD	Lighted Top on 7 Heavan Building (Building Top - 47.3M) - Block F
22/APCH 04/TKOF	BUILDING	210810.4N 0724554.5E	146 FT	NO	Pipe on Empire Regency (Dish Top - 44.0M, Building Top - 43.2M) - Block C

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
22/APCH 04/TKOF	BUILDING	210810.4N 0724547.6E	169 FT	LGTD	Lighted Top on The Evolution Building (Building Top - 50.2M) - Block A
22/APCH 04/TKOF	BUILDING	210810.8N 0724538.4E	159 FT	LGTD	Lighted Top on 7 Heavan Building (Building Top - 47.2M) - Block G
22/APCH 04/TKOF	BUILDING	210811.4N 0724557.0E	145 FT	NO	Empire Regency Board Top (Building Top - 43.4M) – Block A
22/APCH 04/TKOF	BUILDING	210811.6N 0724605.2E	164 FT	LGTD	Lighted Top on Shyam Palace (Building Top - 49.6M) - Block C
22/APCH 04/TKOF	BUILDING	210812.6N 0724542.0E	163 FT	LGTD	Board on 7 Heavan Building (Lighted Top - 48.8M, Building Top - 47.2M) - Block C
22/APCH 04/TKOF	BUILDING	210816.0N 0724539.3E	159 FT	LGTD	Lighted Top on Samarth Building (Building Top - 47.5M, Board Top - 46.9M) - Block A
22/APCH 04/TKOF	BUILDING	210817.8N 0724617.7E	179 FT	LGTD	Lighted Top on Florence Building (Building Top - 53.7M) - Block E
22/APCH 04/TKOF	BUILDING	210821.5N 0724548.9E	173 FT	NO	Happy Glorious Building Top - Block G4
22/APCH 04/TKOF	BUILDING	210821.8N 0724604.3E	167 FT	NO	Sarjan Building, Dish Antenna Top - 50.3M
22/APCH 04/TKOF	BUILDING	210821.8N 0724550.1E	174 FT	NO	Happy Glorious Building Top - Block G3
22/APCH 04/TKOF	BUILDING	210822.7N 0724552.8E	170 FT	NO	Dish Antenna on Green Fortune Building (Hoarding Top - 50.9M, Building Top - 50.8M) - Block C
22/APCH 04/TKOF	BUILDING	210822.8N 0724553.9E	154 FT	NO	Vastugram Building Top - Block D
22/APCH 04/TKOF	BUILDING	210824.6N 0724550.8E	153 FT	NO	Salasar Building Top - Block A
22/APCH 04/TKOF	BUILDING	210824.6N 0724557.5E	166 FT	LGTD	Lighted Top on Rashik Villa Building (Building Top - 50.2M)

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
22/APCH 04/TKOF	BUILDING	210824.9N 0724549.6E	174 FT	NO	Board On Happy Glorious Building (Building Top - 52.8M) - Block G1
22/APCH 04/TKOF	BUILDING	210825.4N 0724554.2E	157 FT	NO	Vastugram Building - Block A
22/APCH 04/TKOF	BUILDING	210826.6N 0724608.6E	173 FT	NO	Board On Shubh Residency (Building Top - 51.1M) - Block A
22/APCH 04/TKOF	BUILDING	210826.8N 0724604.4E	178 FT	NO	Dish On Shilp Residency Building (Building Top - 52.0M) - Block B
22/APCH 04/TKOF	BUILDING	210828.5N 0724552.8E	177 FT	NO	Dish On Gokul Platinum Building (Building Top - 53.2M) - Block B
22/APCH 04/TKOF	BUILDING	210830.3N 0724605.1E	174 FT	NO	Dish On Hi-Tech Building (Building Top - 52.2M) - Block C
22/APCH 04/TKOF	BUILDING	210831.1N 0724607.2E	175 FT	NO	Hi-Tech Board Top - Block A
22/APCH 04/TKOF	BUILDING	210831.8N 0724556.1E	170 FT	NO	The Legend Top - Block A
22/APCH 04/TKOF	BUILDING	210839.2N 0724619.8E	182 FT	LGTD	Lighted Top on Fionna Apartment (Building Top - 54.4 M) - Block B
22/APCH 04/TKOF	BUILDING	210839.6N 0724607.9E	173 FT	NO	Surya Heritage (Under Construction)
22/APCH 04/TKOF	BUILDING	210841.6N 0724621.9E	174 FT	LGTD	Lighted Top on Hampton Park Building (Shed Top - 54.1M, Building Top - 52.7M) - Block A
22/APCH 04/TKOF	BUILDING	210844.5N 0724642.4E	180 FT	NO	Swastik Vihar Appt. Top
22/APCH 04/TKOF	BUILDING	210844.8N 0724614.4E	176 FT	LGTD	Solar Panel on Building, Lighted Top -53.4M, Building Top - 53.1M - Block A
22/APCH 04/TKOF	BUILDING	210845.2N 0724615.9E	177 FT	NO	Dish on Jolly Residency (Building Top - 52.9M) - Block G

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
22/APCH 04/TKOF	BUILDING	210846.6N 0724609.5E	178 FT	LGTD	Lighted Top on Happy Excelencia Building (Building Top - 54.1M) - Block U2
22/APCH 04/TKOF	BUILDING	210848.3N 0724613.1E	184 FT	LGTD	Lighted Top on Happy Excelencia Building (Building Top - 54.1M) - Block S2
22/APCH 04/TKOF	BUILDING	210849.0N 0724619.4E	181 FT	LGTD	Shed On Jolly Residency (Lighted Top - 54.4M, Building Top - 52.8M) - Block B
22/APCH 04/TKOF	BUILDING	210856.4N 0724655.6E	177 FT	NO	Shreeji Residency Building Top
22/APCH 04/TKOF	BUILDING	210858.4N 0724634.3E	175 FT	NO	Pipe on Shrenik Residency (Building Top - 52.0M) - Block A
22/APCH 04/TKOF	BUILDING	210900.6N 0724637.2E	174 FT	LGTD	Lighted Top on Ravi Ratnam Building, Building Top - 52.6M
22/APCH 04/TKOF	BUILDING	210902.3N 0724622.5E	187 FT	LGTD	Cell Phone Mast on Western Business Park (Building Top - 45.8M)
22/APCH 04/TKOF	BUILDING	210913.1N 0724620.7E	188 FT	NO	Board on Ratna Aashtha Building (Building Top - 52.9M)
22/APCH 04/TKOF	OTHER	210902.3N 0724614.4E	185 FT	LGTD	Mast
22/APCH 04/TKOF	BUILDING	210844.5N 0724631.3E	178 FT	LGTD	Lighted Top on Samprati Palace (Building Top - 53.7M)
In circling area and at AD	BUILDING	210638.4N 0724425.3E	40 FT	NO	DVOR Antenna (Building Top - 9.4 M)
In circling area and at AD	OTHER	210638.2N 0724425.6E	48 FT	LGTD	DVOR DME
In circling area and at AD	OTHER	210640.6N 0724427.5E	48 FT	LGTD	DVOR Monitor Antenna
In circling area and at AD	POLE	210620.9N 0724350.4E	60 FT	NO	Light Pole
In circling area and at AD	POLE	210622.1N 0724353.5E	43 FT	NO	Light Pole
In circling area and at AD	POLE	210621.4N 0724352.6E	42 FT	NO	Electric Pole
In circling area and at AD	TREE	210621.9N 0724352.4E	56 FT	NO	Group of Trees

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	TREE	210621.2N 0724351.2E	55 FT	NO	Group of Trees
In circling area and at AD	TREE	210623.4N 0724352.1E	61 FT	NO	Group of Trees
In circling area and at AD	FENCE	210622.2N 0724353.6E	36 FT	NO	Airport Boundary Wall with Fencing on Top
In circling area and at AD	POLE	210622.0N 0724353.6E	42 FT	NO	Light Pole
In circling area and at AD	POLE	210620.8N 0724351.4E	50 FT	NO	Electric Pole
In circling area and at AD	TREE	210620.2N 0724349.7E	54 FT	NO	Group of Trees
In circling area and at AD	POLE	210617.6N 0724347.9E	46 FT	NO	Electric Pole
In circling area and at AD	BUILDING	210456.6N 0724313.9E	175 FT	NO	Antenna on Aquatica Building (Building Top - 50.6M)
In circling area and at AD	POLE	210621.3N 0724352.0E	43 FT	NO	Light Pole
In circling area and at AD	TREE	210620.1N 0724350.6E	54 FT	NO	Group of Trees
In circling area and at AD	POLE	210739.1N 0724510.6E	34 FT	NO	Light Pole
In circling area and at AD	BUILDING	210806.6N 0724605.4E	155 FT	LGTD	Lighted Top on Shrungar Residency (Building Top - 46.4M) - Block G
In circling area and at AD	BUILDING	210813.5N 0724631.7E	187 FT	NO	Antila Dream Building Corner (Under Construction)
In circling area and at AD	BUILDING	210814.3N 0724615.1E	178 FT	LGTD	Lighted Top on Crystal Palace (Building Top - 53.3M) - Block A
In circling area and at AD	BUILDING	210814.5N 0724616.8E	178 FT	LGTD	Lighted Top on Crystal Palace (Building Top - 53.4M) - Block B
In circling area and at AD	BUILDING	210814.1N 0724514.1E	177 FT	LGTD	Lighted Top On L&T Building, Building Top - 53.8M
In circling area and at AD	BUILDING	210815.7N 0724618.1E	179 FT	LGTD	Lighted Top on Florence Building (Dish Top - 54.8M, Building Top - 53.7M) - Block D

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	BUILDING	210816.6N 0724623.7E	185 FT	LGTD	Lighted Top on Florence Building (Board Top - 55.5M, Building Top - 53.7M) - Block A
In circling area and at AD	BUILDING	210819.2N 0724538.3E	177 FT	LGTD	Building Top of OM Icon Building - Block D
In circling area and at AD	BUILDING	210819.3N 0724538.2E	171 FT	LGTD	OM Icon Building Top - Block D
In circling area and at AD	BUILDING	210819.5N 0724539.9E	177 FT	LGTD	Lighted Top on OM Icon Building (Building Top - 52.1M) - Block C
In circling area and at AD	BUILDING	210842.5N 0724556.3E	173 FT	NO	Happy Residency Building - Block A
In circling area and at AD	BUILDING	210845.5N 0724713.5E	261 FT	LGTD	Lighted Top on Cellestial Dream Block-A Building, (Building Top - 79.5M)
In circling area and at AD	BUILDING	210849.2N 0724718.3E	261 FT	NO	Cellestial Dream Block-C Building
In circling area and at AD	BUILDING	210819.3N 0724519.4E	182 FT	LGTD	Antenna on Mufaddal Heights, Hoarding Top - 51.0M, Building Top - 47.0M
In circling area and at AD	BUILDING	210823.9N 0724524.8E	183 FT	LGTD	Lighted Top on Shell Building, Building Top - 54.8M
In circling area and at AD	BUILDING	210913.3N 0724610.4E	185 FT	NO	KPM Terre Prime Building Top
In circling area and at AD	BUILDING	210801.4N 0724611.3E	181 FT	LGTD	Lighted Top on Sumeru Residency - Milestone (Building Top -53.7M)
In circling area and at AD	BUILDING	210809.4N 0724615.6E	176 FT	NO	Dish Antenna on Building (Building Top - 52.1M)
In circling area and at AD	BUILDING	210820.5N 0724636.3E	180 FT	LGTD	Lighted Top on Swapna Sangini Building (Dish Antenna Top - 53.5M, Building Top -53.5M)
In circling area and at AD	BUILDING	210830.9N 0724652.5E	177 FT	NO	Hoarding Top on Building (Building (Under Constriction) - 51.6M)

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	BUILDING	210837.1N 0724708.0E	178 FT	NO	Sangini Terraza Building Top
In circling area and at AD	OTHER	210705.8N 0724450.8E	75 FT	LGTD	GP Antenna (Hut Top - 8.6M)
In circling area and at AD	OTHER	210705.7N 0724450.8E	35 FT	LGTD	GP DME
In circling area and at AD	OTHER	210707.8N 0724452.8E	35 FT	LGTD	GP Monitor Antenna
In circling area and at AD	OTHER	210658.6N 0724429.8E	44 FT	LGTD	W.D.I.
In circling area and at AD	OTHER	210638.3N 0724425.3E	56 FT	NO	Lightning Arrestor on DVOR
In circling area and at AD	TREE	210705.7N 0724437.6E	34 FT	NO	Tree
In circling area and at AD	OTHER	210704.7N 0724449.7E	50 FT	LGTD	CWIS Antenna
In circling area and at AD	OTHER	210714.2N 0724436.2E	125 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	210715.2N 0724437.2E	126 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	210716.2N 0724438.2E	126 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	210717.4N 0724439.4E	126 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	210718.6N 0724440.5E	125 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	210720.3N 0724442.2E	125 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	210721.9N 0724443.8E	125 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	210713.2N 0724435.2E	125 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	210712.2N 0724434.2E	126 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	210711.2N 0724433.2E	125 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	210709.6N 0724431.6E	126 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	210707.9N 0724429.9E	127 FT	LGTD	Flood Light Mast
In circling area and at AD	BUILDING	210814.5N 0724401.1E	193 FT	NO	Narmada Cement Factory
In circling area and at AD	BUILDING	210821.2N 0724421.4E	179 FT	NO	Factory
In circling area and at AD	OTHER	210918.6N 0724537.6E	305 FT	NO	H.T. Tower
In circling area and at AD	OTHER	210935.5N 0724522.1E	303 FT	NO	H.T. Tower
In circling area and at AD	STACK	210906.8N 0724417.7E	250 FT	LGTD	Chimney

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	STACK	210913.4N 0724416.1E	363 FT	LGTD	Chimney
In circling area and at AD	OTHER	210937.2N 0724424.2E	356 FT	LGTD	Mast Rod Top (GAIL)
In circling area and at AD	STACK	210931.6N 0724358.9E	241 FT	LGTD	Chimney White ONGC
In circling area and at AD	OTHER	210938.0N 0724359.4E	354 FT	LGTD	Mast (Disc. Top) ONGC
In circling area and at AD	OTHER	210612.2N 0724141.9E	336 FT	NO	H.T. Tower
In circling area and at AD	OTHER	210604.7N 0724201.0E	211 FT	NO	H.T. Tower
In circling area and at AD	STACK	210936.2N 0724120.2E	740 FT	LGTD	Chimney
In circling area and at AD	STACK	210931.4N 0724120.4E	739 FT	LGTD	Chimney
In circling area and at AD	BUILDING	210708.5N 0724309.0E	177 FT	LGTD	Mast on Utopia Building (Building Top - 50.3M)
In circling area and at AD	BUILDING	210833.1N 0724507.3E	181 FT	LGTD	Lighted Top on Building, Building Top -53.2M
In circling area and at AD	BUILDING	210729.0N 0724628.8E	180 FT	NO	Lift Top of Building (Under Construction), Building Top - 52.1M
In circling area and at AD	BUILDING	210727.5N 0724628.8E	176 FT	NO	Lift Top of Building (Under Construction), Building Top - 52.0M
In circling area and at AD	BUILDING	210745.9N 0724629.7E	181 FT	NO	Building Top
In circling area and at AD	BUILDING	210741.3N 0724630.6E	177 FT	NO	Building (Under Construction)
In circling area and at AD	BUILDING	210730.5N 0724635.0E	174 FT	NO	Building Top

VASU AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Available in City
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	AS ATS
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	NOT AVBL
4	Availability of the trend forecast for the aerodrome and interval of issuance	NOT AVBL
5	Information on how briefing and/or consultation is provided	NOT AVBL
6	Types of flight documentation supplied and language(s) used in flight documentation	ENGLISH

7	Charts and other information displayed or available for briefing or consultation	NOT AVBL
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	NOT AVBL
9	The air traffic services unit(s) provided with meteorological information	METAR
10	Additional information, e.g. concerning any limitation of service.	Wind Direction Indicator Available, Lighted.

VASU AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
04	42.98 DEG	2906 x 45 M	71/F/C/W/T Asphalt	THR: 210622.49N 0724401.97E RWY END: 210731.63N 0724510.62E
22	222.98 DEG	2906 x 45 M	71/F/C/W/T Asphalt	THR: 210716.97N 0724456.07E RWY END: 210622.49N 0724401.97E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 20.0FT TDZ: 20.0FT	0.10%			3026 x 280 M
THR: 19.0FT TDZ: 19.0FT	-0.10%			3026 x 280 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
240M x 90M			i. PCN RWY 04: 0 to 655 M: 73/R/B/W/T 655 M to 2755 M: 71/F/C/W/T 2755 M to 2906 M: 73/R/B/W/T ii. Gravity Model: EGM-08
240M x 90M			i. PCN RWY 22 0 to 151 M: 73/R/B/W/T 151 M to 2251 M: 71/F/C/W/T 2251 M to 2906 M: 73/R/B/W/T ii. Gravity Model: EGM-08

VASU AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
04	2290	2290	2290	2906	
22	2906	2906	2906	2290	Threshold displaced by 616 M

VASU AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
04	SALS 420 M LIH	Green	PAPI /3.00 DEG MEHT (15.88M)	
22	SALS 420 M LIH	Green	PAPI /3.00 DEG MEHT (17.41M)	

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	2906 M 60 M White LIH	Red		NIL
	2906 M 60 M White LIH	Red		NIL

VASU AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	Available at ATC Tower with alternate White & Green flashes: 30 flashes per minute. As ATS
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	In front of ATC Control Tower near approach road to fire station
		Anemometer	Not Available
3	Taxiway edge and taxiway centre line lights;	Edge	Available
		Centre Line	Not Available
4	Secondary power supply including switch-over time;	Available Switch over Time 10 sec	

5	Remarks	NIL

VASU AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not Established
2	TLOF and/or FATO area elevation:	Not Established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not Established
4	True bearings of FATO;	Not Established
5	Declared distances available	Not Established
6	Approach and FATO lighting;	Not Established
7	Remarks	Not Established

VASU AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Circular area centered on 210658N 0724431E within a 15NM radius.
2	Vertical limits	FL 65
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Surat Tower, English
5	Transition altitude	4000 FT
6	Hours of applicability	HO
7	Remarks	Surat Approach Control Unit is combined with Surat Aerodrome Control Tower.

VASU AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	**2**	**3**	**4**
APP	Surat Tower	118.050 MHZ	
APP	Surat Tower	118.550 MHZ	
TWR	Surat Tower	118.050 MHZ	
TWR	Surat Tower	118.550 MHZ	
ATIS	Surat Information	127.075 MHZ	
ALRS	Surat Emergency	121.500 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	**6**	**7**
	HO	1.Backup FREQ 2.Functions of Approach Control Service provided by Aerodrome Control Tower
	HO	1.Main FREQ 2.Functions of Approach Control Service provided by Aerodrome Control Tower
	HO	Backup FREQ

Logon address, as appropriate	Hours of operation	Remarks
	HO	NIL
	HO	NIL
	HO	NIL

VASU AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 22 CAT I	ISUT	109.100 MHz	AS ATS
GP 22		331.400 MHz	AS ATS
DME ILS 22	ISUT	CH28X	AS ATS
DVOR/DME	SUR	112.200 MHz CH59X	As ATS

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
210615.3N 0724354.8E			
210705.8N 0724450.8E			Glide angle 3 DEG.
210705.7N 0724450.8E	35 FT		i. Collocated with GP ii. Gravity Model: EGM-08
210642.1N 0724409.6E	61 FT		Gravity Model: EGM-08

VASU AD 2.20 LOCAL AERODROME REGULATIONS

1. **Pushback Procedures on Main Apron:**

i) All stands are power -in and push back stands in the Main Apron. For Runway 04

I. Push back from stand 1,2,3,14 and 15 shall be facing the south-west direction only.

II. Aircraft from stand 2,3 and 15 shall be deep push abeam stand 1 to keep taxiway A clear (if required)

III. Push back from stand 4,5,6,7,8,16,17,18, and 19 should facing south-west direction only.

IV. Aircraft from stands 4 and 16 shall pull abeam stand 5 to keep taxiway A clear (if required)

V. Aircraft from stand 8 shall push abeam 6 to keep taxiway B clear (if required).

VI. Push back from stand 9,10,20 and 21 shall be facing the north -east direction only.

For Runway 22

I. Push back from stand 1,2,3,14 and 15 shall be facing the south-west direction only.

II. Aircraft from stands 2,3 and 15 shall be deep push abeam stand 1 to keep taxiway A clear (if required).

III. Push back from stand 4 to 10 and 16 to 21 shall be facing the north-east direction only. Aircraft from stands 7,8, and 19 shall deep push abeam stand 10 to keep taxiway B clear (if required).

2. No Aircraft shall take lock turn/ pivotal turn on the Runway to avoid pavement damage.

2. RADIO COMMUNICATION FAILURE PROCEDURE:

1. INTRODUCTION:

Radio communication failure procedures are described in ICAO PANS ATM DOC 4444. Based on these provisions , following radio communication failure procedures are established, to standardize the actions to be taken by the pilot of arriving and departing aircraft at Surat Airport.

The purpose of this document is to establish the standard procedure to handle the event of a radio communication failure situation at Surat airport to ensure safe and efficient aircraft operation**.**

2. GENERAL

2.1 As soon as it is known to ATC that two-way communication has failed, the action shall be taken to ascertain whether the aircraft is able to receive transmissions from the air traffic control unit by requesting it to execute a specified manoeuvre (if the aircraftvisual with ATC Tower) or to transmit, if possible, a specified signal in order to indicate acknowledgment.

2.2 SURAT ATC shall immediately forward information concerning the radio communication failure to all air traffic units concerned along the route of the flight

2.3 All Transponder-equipped aircraft experiencing Radio Communication failure shall set transponder to Mode A/C code 7600 as soon as practicable

2.4 Immediately after detection of RCF, the aircraft shall attempt to establish communications with the appropriate air traffic control unit using all other available means. In addition, the aircraft shall keep a watch for any instructions that may be issued by visual signals.

2.5 The pilot shall make blind transmission to ATC of all necessary reports and actions taken by the aircraft, e.g. descent, turn, proceeding to waypoint, etc., irrespective of whether partial/ complete RCF has been established or not.

2.6 Aircraft experiencing radio communication failure shall be provided all required information necessary for the safe and efficient conduct of flight and landing clearance without expecting acknowledgment.

3. ASSIGNED RUNWAY AND ITS AVAILABILITY FOR RCF AIRCRAFT:

3.1 In case of an arriving aircraft experiencing RCF, when the Runway for landing has already been advised to the aircraft by SURAT ATC via VHF, such runway shall be considered as the assigned runway. If an arriving aircraft has not been advised of any runway, Runway 22 shall be considered as an assigned runway for such arrival.

NOTE: In the case of RCF, pilots shall not assume runway on the basis of ATIS (127.075MHZ) Broadcast.

3.2 In case of departures from Surat airport is returning due to RCF, Runway 22 shall be considered as the assigned runway for landing, irrespective of the runway used for departure.

3.3 Runway lights and Approach lights shall be in the 'SWITCHED ON' position to indicate the availability of such Runway for aircraft experiencing RCF irrespective of visibility and Day or Night.

3.4 Runway and Approach lights in the 'SWITCHED OFF' position shall indicate the non-availability of such Runway for aircraft experiencing RCF.

3.5 In case strong tailwind conditions are encountered during approach for

3.6 the Runway as mentioned in para 3.1, the aircraft experiencing RCF will carry out a missed approach on the runway as mentioned in para 3.1 and after following the complete missed approach procedure for such approach, aircraft will carry out the published approach procedure for the opposite runway.

4. PROCEDURE FOR ARRIVALS:

4.1 In case radio communication failure takes place after establishing the ILS/final approach track, aircraft may continue the approach and land if visual or go around andcarry out the missed approach procedure and join the VOR (112.2) SUR holdingprocedure climbing to and maintaining 3100ft.

.4.2 Except when descent clearance has already been received from ATC SURAT and acknowledged, the pilot shall continue on the ATS route maintaining filed flight plan level or level cleared by adjacent area control unit i.e. VABB AREA or VAAH AREA and do not commence descent before 20-mile VOR (112.2) SUR.

4.3 After crossing 20-mile, the pilot shall descend to FL080 to join the published hold over VOR (112.2) SUR for the runway as mentioned in para 3.1.

4.4 Commence descent to 3100 feet in published hold over VOR (112.2) SUR at, or as close as possible to, the expected approach time (EAT) last received and acknowledged; or, if no expected approach time (EAT) has been received and acknowledged, at, or as close as possible to, the estimated time of arrival (ETA) over SUR VOR.

4.5 Leave VOR (112.2) SUR and carry out the published ILS/VOR Procedure for the runway as mentioned in para 3.1.

4.6 Land, if possible, within 30 minutes after the estimated time of arrival (ETA) or the last acknowledged expected approach time (EAT), whichever is later.

5. PROCEDURE FOR DEPARTURES:

5.1 Departing aircraft experiencing radio communication failure and intending to continue to its filed flight plan destination shall:

5.1.1 Continue ATS route as per filed flight plan, climbing to/maintaining cleared and acknowledged flight level, or minimum flight altitude if higher, for a period of 20 minutes following the aircraft's failure to report its position over compulsory reporting point and thereafter adjust level and speed in accordance with the filed flight plan to destination.

5.1.2 When the aircraft is given clearance for offset from flight plan route in without a specified limit, re-join the current flight plan route after passing 20Mile from SUR VOR but no later than the next significant point, taking into consideration the applicable minimum flight altitude.

5.2 A departing aircraft, experiencing radio communication failure and intending to land back at Surat Airport, shall:

5.2.1 Maintain the last assigned level, or minimum flight altitude if higher, for a period of 10 minutes on the flight plan route or on offset radial as cleared in ATC clearance.

5.2.2 After 10 minutes turn towards VOR (112.2) SUR via the same flight plan route or radial as per departure clearance. On Reaching VOR (112.2) SUR joins hold as published.

5.2.3 If required jettison fuel, then remain in hold over VOR (112.2) SUR after taking all precautions.

5.2.4 Commence descent in the hold to 3100 feet. Leave VOR (112.2) SUR and carry out the published ILS/VOR Procedure for the runway as mentioned in para 3.2

.

5.3 Procedures for VFR Traffic:

5.3.1 In case of a VFR flight experiencing RCF and does not intend to land at Surat:

It shall continue to fly in VMC, land at the nearest suitable aerodrome/helipad, and report its arrival by the most expeditious means to the ATC, Surat.

5.3.2 In case of a VFR flight experiencing RCF and intending to land at Surat:

a) Proceed according to the current flight plan route in VMC and maintain the altitude/level last assigned and acknowledged.

b) Proceed towards 15 miles NW/SE of the field subject to arrival route and descent 1500 ft AGL.

c) Maintaining 1500 ft AGL proceed to Surat to join the traffic circuit for the last acknowledged Runway or the Runway as per para 3.1.

d) Carry out a complete aerodrome traffic circuit and land on the last acknowledged Runway or the Runway as per para 3.1

• *When Surat ATC becomes aware of the RCF of the aircraft, the controller concerned shall accord priority for the RCF aircraft to land.*

• *If the aircraft re-establishes communication or has landed, the ATC unit shall inform all con**cerned units/aerodromes** along the route as per the flight plan including the alternate aerodrome**.***

5.4 Various Signals used by ATCO during communication failure

Air traffic controllers have ALDIS lamps as backup systems for communication if the radio fails**.**

The various signals used by the ATCO during communication failure are as follows	**Aircraft in Flight**	**Aircraft on the ground**
Steady green	**Cleared to land**	**Cleared for take-off**
Steady red	**Give way to other aircraft, continue circling**	**Stop**
A series of green flashes	**Return for landing* (*Clearances to land and to taxi will be given in due course.)**	**Cleared to taxi**
Series of red flashes	**The aerodrome is unsafe, do not land**	**Taxi clear of landing area in use**
Series of white flashes	**Land at this aerodrome and proceed to the apron***	**Return to starting point on the aerodrome**
Alternate Red and Green	**Exercise extreme caution**	**Exercise extreme caution**
Blinking runway lights	**Vehicles, Plans, and pedestrians immediately clear the landing area in use**	

VASU AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VASU AD 2.22 FLIGHT PROCEDURES

NIL

VASU AD 2.23 ADDITIONAL INFORMATION

1. All bays on Main APN are Power-in Pushback only, ACFT operator to arrange pushback facility while operating at the Airport.
2. Runway Turn Pad capable of handling B777-300 ER type of aircraft, provided at the beginning of RWY 22 for special ops with prior permission. PCN for extended portion of turn pad RWY 22: 74/R/A/W/T.
3. No aircraft shall take a Lock Turn / Pivotal Turn on the RWY to avoid pavement damage
4. Following intersection Take Off Run Available (TORA):

RWY	From TWY Intersection	TORA (M)
RWY 22	TWY E3	1790
RWY 22	TWY E2	2025

VASU AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart(11 JUNE 2026)
2. Aircraft Parking/Docking Chart(11 JUNE 2026)
3. Aerodrome Obstacle Chart Type-A, (Operating Limitations) RWY 04
4. Aerodrome Obstacle Chart Type-A, (Operating Limitations) RWY 22
5. ILS or LOC Procedure RWY 22
6. VOR Procedure RWY 04 (CAT A/B/C)(9 JULY 2026)
7. VOR Procedure RWY 22 (CAT A/B/C)(9 JULY 2026)
8. RNP Procedure RWY 22
9. Coding Table - RNP Procedure RWY 22
10. RNP Procedure RWY 04 (17 April 2025)
11. Coding Table - RNP Procedure RWY 04 (17 April 2025)
12. FAS DATA - RNP Procedure RWY 04 (17 April 2025)

VASU AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	**2**	**3**