AD 2. AERODROMES

VOTK AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VOTK - TUTICORIN AIRPORT, TUTICORIN

VOTK AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	084320N 0780134E MAG BRG. 279.81 DEG / 1533 M from physical extremity of RWY 28	
2	Direction and distance of aerodrome reference point from the centre of the city or town which the aerodrome serves	20KM SW of Tuticorin Railway Station	
3	Aerodrome elevation and reference temperature	98 FT / 37.0 DEG C	
4	Magnetic variation, date of information and annual change	2.45 DEG W (2010) /0.033 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airport In-Charge Airports Authority of India, Tuticorin Airport, Mangalagiri (Post), Tuticorin District - 628103 Tamil Nadu	
		Telephone:	0461 2271863
		Fax:	0461 2271863 2271110
		AFS:	
		Email:	apd-tuticorin@aai.aero
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	Elevation in EGM08	

VOTK AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON-FRI 0400-1230 UTC (0930-1800 IST) SAT, SUN + HOL: NIL
2	Custom and immigration	NIL
3	Health and sanitation	NIL
4	AIS briefing office	As ATS
5	ATS reporting office (ARO)	As ATS
6	MET Briefing office	As ATS
7	Air Traffic Service	Consult NOTAM for current ATS HR
8	Fuelling	AS ATS
9	Handling	As ATS
10	Security	As ATS
11	De-icing	NIL
12	Remarks	(i) 24HR Prior notice for Non-scheduled ops and for extension of watch hours (ii) The ATS approved hourly RWY traffic handling capacity is as follows: Maximum number of arrivals and departures -12 Maximum number of arrivals only -06 Maximum number of departures only -10

VOTK AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	NIL
2	Fuel and Oil types	JET A1 NIL
3	Fuelling facilities and capacity	IOCL: 2 Bowsers (2X16 KL and 2X35KL Storage tank available during operational hours. For outside operational hours 24 hour prior notice required.
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

VOTK AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	In the city
2	Restaurant(s) at or in the vicinity of aerodrome	In the city
3	Transportation possibilities	Taxis and car hire from the city & outside AD (4 KM from AD)
4	Medical Facilities	First Aid at AD. Hospitals in the city
5	Bank and post office at or in the vicinity of aerodrome	Banks: Outside AD (4KM from AD) and in city Post office: Outside AD (4KM from AD) and in city
6	Tourist office	At AD and in the city
7	Remarks	NIL

VOTK AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-7
2	Rescue equipment	AVBL as per Category
3	Capability for removal of disabled aircraft	1. The critical aircraft for the airport is A-321. 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3.The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4.Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: AIRPORT DIRECTOR,TUTICORIN AIRPORT Tel. 0461 2271863/Fax. 0461 2271110 Mobile: 9761722089 EMAIL: apd-tuticorin@aai.aero
4	Remarks	Outside ATS HO, fire fighting service to be requested at least 24HR prior

VOTK AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VOTK AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Designator: APRON 1 (Old Apron) Surface: Concrete Strength: PCN 22/R/C/W/T Dimension: 76X46 M Designator: APRON 2 (New Apron) Surface: Concrete Strength: PCN 64/R/B/W/T Dimension:191X89 M Designator: Isolated Aircraft Parking Position: Surface: Concrete Strength: PCN 64/R/B/W/T Dimension:91X 76 M Blue edge Lights. COORD / ELEV: 084317.63484N 0780106.45192E / 96 FT Access to Isolated Aircraft Parking Position is via TWY C.
2	Designation, width, surface and strength of taxiways	Aircraft Parking/ Docking Chart
3	Location and elevation of altimeter checkpoints	Location: Entire Apron 1, Elevation: 77 FT Location: Entire Apron 2, Elevation: 74 FT
4	Location of VOR checkpoints	TWY B1: 084335.77151N0780044.81068E/96FT TWY B2: 084329.72195N0780116.35761E/83 FT TWY B3: 084326.07618N0780135.36220E/81FT
5	Position of INS checkpoints	NIL
6	Remarks	1. Coordinates of RWY Holding Position/Elevation TWY B1: 084335.53647N 0780044.76532E/96 FT TWY B2: 084329.48692N 0780116.31212E/83 FT TWY B3: 084325.84131N 0780135.31632E/81 FT TWY C: 084325.13174N 0780107.90565E/89 FT 2. Coordinates of RWY & Taxi Intersection/Elevation TWY B1: 084332.65873N 0780044.20775E/98 FT TWY B2: 084326.60899N 0780115.75548E/86 FT TWY B3: 084322.967N 0780134.756E/83FT TWY C: 084328.00854N 0780108.46297E/88 FT 3. Coordinates of Intermediate Holding Position TWY B facing East: 084331.91484N 0780115.39410E/82 FT TWY B facing West: 084331.40139N 0780118.07187E/81 FT TWY B2 facing South: 084332.98983E 0780116.99059E/80FT TWY A1 facing North: 084330.33958N 0780116.47710E/83 FT 4. Intermediate turn pads available at: 1000 M from the beginning of Runway 10 765 M from the beginning of Runway 28. 5. Vertical Datum: EGM 08

VOTK AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Aircraft ID marking provided on ground. Taxi guidance provided on R/T. Standard marking at Apron, Mandatory Information and Location signs provided. Guidelines at Apron. Nose-in Guidance at aircraft stands, AVDGS provided on Aircraft Stands 4, 5 and 6 with aerobridge facility.

2	Runway and taxiway markings and lights	RWY Markings: Designation, THR, TDZ, Centreline, Edge, RWY END as appropriate. RWY Lighting: THR, EDGE, END. TWY Markings: Centreline, edge, Holding PSN at TWY/RWY intersection. TWY Lighting: Edge
3	Stop bars (if any)	NIL
4	Remarks	NIL

VOTK AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
28/TKOF 10/APCH	OTHER	084333.1N 0780041.9E	100 FT	NIL	Approach Light
28/TKOF 10/APCH	BUILDING	084333.1N 0780041.9E	129 FT	NIL	Temple
28/TKOF 10/APCH	TREE	084330.7N 0780013.7E	161 FT	NIL	Group Of Tree
28/TKOF 10/APCH	TREE	084337.9N 0780008.5E	174 FT	NIL	Group Of Tree
28/TKOF 10/APCH	TREE	084340.1N 0780030.9E	124 FT	NIL	Group Of Tree
28/TKOF 10/APCH	TREE	084341.6N 0780012.0E	168 FT	NIL	Group Of Tree
28/TKOF 10/APCH	TREE	084343.1N 0780011.7E	177 FT	NIL	Group Of Tree
28/TKOF 10/APCH	TREE	084332.8N 0780014.4E	161 FT	NIL	Group Of Tree
28/TKOF 10/APCH	TREE	084329.8N 0780017.3E	164 FT	NIL	Group Of Tree
28/TKOF 10/APCH	TREE	084329.6N 0780019.1E	158 FT	NIL	Group Of Tree
28/TKOF 10/APCH	TREE	084331.3N 0780025.3E	131 FT	NIL	Group Of Tree
28/TKOF 10/APCH	TREE	084331.7N 0780028.1E	147 FT	NIL	Group Of Tree
28/TKOF 10/APCH	POLE	084331.3N 0780027.4E	136 FT	NIL	Electric Pole
28/TKOF 10/APCH	TREE	084334.5N 0780027.8E	127 FT	NIL	Group Of Tree
28/TKOF 10/APCH	TREE	084334.6N 0780026.8E	129 FT	NIL	Group Of Tree
28/TKOF 10/APCH	OTHER	084519.4N 0775451.4E	701 FT	NIL	Windmill
28/TKOF 10/APCH	OTHER	084534.5N 0775251.0E	745 FT	NIL	Windmill
28/TKOF 10/APCH	OTHER	084328.9N 0780122.1E	109 FT	NIL	Wind Sock
28/TKOF 10/APCH	OTHER	084333.5N 0780056.2E	116 FT	NIL	WDI (Rwy-10)
28/TKOF 10/APCH	TREE	084329.0N 0780016.1E	162 FT	NIL	Group Of Tree

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
28/TKOF 10/APCH	TREE	084345.0N 0780022.0E	153 FT	NIL	Group Of Tree
28/TKOF 10/APCH	TREE	084328.7N 0780019.4E	166 FT	NIL	Group Of Tree
28/TKOF 10/APCH	TREE	084327.0N 0780023.2E	187 FT	NIL	Group Of Tree
28/TKOF 10/APCH	TREE	084326.8N 0780024.8E	174 FT	NIL	Group Of Tree
28/TKOF 10/APCH	OTHER	084328.6N 0780035.4E	113 FT	NIL	Raling Structure U/C
28/APCH 10/TKOF	TREE	084301.2N 0780249.3E	138 FT	NIL	Group Of Tree
28/APCH 10/TKOF	OTHER	084315.9N 0780153.2E	104 FT	NIL	Wind Sock
28/APCH 10/TKOF	OTHER	084314.4N 0780213.2E	83 FT	NIL	PAPI Light
28/APCH 10/TKOF	OTHER	084312.6N 0780212.4E	105 FT	NIL	WDI (RWY-28)
In circling area and at AD	OTHER	084604.6N 0775354.0E	652 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084331.8N 0780055.4E	94 FT	NIL	PAPI
In circling area and at AD	OTHER	084633.6N 0775508.8E	689 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084729.5N 0780022.5E	619 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084717.7N 0780101.4E	629 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084738.8N 0775901.5E	658 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084539.2N 0775527.5E	697 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084619.8N 0775752.2E	637 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084749.5N 0780310.5E	645 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084805.8N 0780300.3E	652 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084824.2N 0780230.4E	657 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084841.3N 0780203.3E	658 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084819.4N 0780156.9E	632 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084734.5N 0780110.9E	632 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084545.7N 0775609.9E	682 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084743.3N 0775952.9E	645 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084715.5N 0775957.4E	645 FT	NIL	Wind Mill

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	OTHER	084912.0N 0780044.0E	611 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084942.6N 0780018.9E	716 FT	NIL	Wind Mill
In circling area and at AD	OTHER	085016.0N 0780041.3E	633 FT	NIL	Wind Mill
In circling area and at AD	OTHER	085037.8N 0780118.9E	641 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084830.6N 0780049.2E	613 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084723.6N 0775932.1E	596 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084824.5N 0780017.2E	617 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084826.8N 0775930.2E	593 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084759.5N 0775906.8E	597 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084656.4N 0775430.4E	761 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084633.5N 0775435.6E	700 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084622.6N 0775417.9E	764 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084701.9N 0775448.8E	759 FT	NIL	Wind Mill
In circling area and at AD	OTHER	084703.0N 0775528.8E	680 FT	NIL	Wind Mill

VOTK AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Tuticorin Airport
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	As ATS
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Chennai 9 HR (Domestic) 30 HR (International)
4	Availability of the trend forecast for the aerodrome and interval of issuance	Every 30 min during operational hours (METAR)
5	Information on how briefing and/or consultation is provided	Personal consultation
6	Types of flight documentation supplied and language(s) used in flight documentation	Tabular and Charts, English
7	Charts and other information displayed or available for briefing or consultation	NIL
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Available
9	The air traffic services unit(s) provided with meteorological information	Tuticorin TWR
10	Additional information, e.g. concerning any limitation of service.	As per requirement basis

VOTK AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
10	100.90 DEG	3115 x 45 M	61/F/C/W/T Asphalt	THR: 084332.73N 0780043.84E RWY END: 084313.55N 0780223.91E
28	280.90 DEG	3115 x 45 M	61/F/C/W/T Asphalt	THR: 084313.55N 0780223.91E RWY END: 084332.73N 0780043.84E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 97.8FT TDZ: 97.8FT	-0.15%	NIL	NIL	3235 x 280 M
THR: 82.0FT TDZ: 82.4FT	0.15%	NIL	NIL	3235 x 280 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
240M x 90M			Geoid Model: EGM 08
240M x 90M			Geoid Model: EGM 08

VOTK AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
10	3115	3115	3115	3115	
28	3115	3115	3115	3115	

VOTK AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
10	SALS 420 M LIH	Green	PAPI LEFT/3.00 DEG MEHT (8.53M)	NIL
28	CAT I 900 M LIH	Green	PAPI LEFT/3.00 DEG MEHT (8.53M)	NIL

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	3115 M 60 M White LIH	Red	NIL	The colour of last 600 M of runway edge lights is Yellow.
	3115 M 60 M White LIH	Red	NIL	The colour of last 600 M of runway edge lights is Yellow.

VOTK AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	At Tower Building, 23RPM, HO
		IBN	NIL

2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	347 M N of ARP, Lighted
		Anemometer	1500 M from THR RWY28, lighted
3	Taxiway edge and taxiway centre line lights;	Edge	TWY A1, B, B1, B2, B3, C
		Centre Line	NIL
4	Secondary power supply including switch-over time;	Secondary power supply to all lighting at AD, Switch-over time: 15 sec Critical circuits provided with UPS for 1 sec switchover time.	
5	Remarks	Turn pad light for runway 28 available. Intermediate Turn pad lights available at: 1000 M from the beginning of Runway 10 765 M from the beginning of Runway 28.	

VOTK AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	--
2	TLOF and/or FATO area elevation:	--
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	--
4	True bearings of FATO;	--
5	Declared distances available	--
6	Approach and FATO lighting;	--
7	Remarks	--

VOTK AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Circular area centered on 084336N 0780135E within a 25NM radius.
2	Vertical limits	FL 85
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Tuticorin Tower, English
5	Transition altitude	4000 FT
6	Hours of applicability	HO
7	Remarks	Tuticorin Approach Control Unit is combined with Tuticorin Aerodrome Control Tower.

VOTK AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
APP	Tuticorin Tower	118.350 MHZ	
APP	Tuticorin Tower	120.375 MHZ	
TWR	Tuticorin Tower	118.350 MHZ	
TWR	Tuticorin Tower	120.375 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	HO	1.Back up 2.Functions of Approach Control Service provided by Aerodrome Control Tower
	HO	1.Main 2.Functions of Approach Control Service provided by Aerodrome Control Tower
	AS ATS	SDBY Frequency
	As ATS	NIL

VOTK AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
DVOR/DME	TCN	114.300 MHz CH90X	As ATS
NDB	TU	376 kHz	As ATS

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
084313.7N 0780245.8E	107 FT		
084336.1N 0780135.4E			

VOTK AD 2.20 LOCAL AERODROME REGULATIONS

1. No Aircraft shall take lock turn/ pivotal turn on the Runway to avoid pavement damage.
2. Apron-1
   i. 1.Stand Number 1 to the east and stand Number 2 to the west of apron.
   ii. 2.Stand Number 1 for ATR 72-500 or lesser type of ACFT and stand Number 2 for Q400 or lesser type of aircraft.
3. Apron-2
   i. Bays 3,4,5,6 and 7 in Apron-2 are power in pushback bays.
   ii. Bays 4,5 and 6 have aerobridge facility.
   iii. Pushback from all bays should face west
   iv. 02 stands separation shall be required up to code C aircraft for simultaneous push backs.

VOTK AD 2.21 NOISE ABATEMENT PROCEDURES

VOTK AD 2.22 FLIGHT PROCEDURES

VOTK AD 2.23 ADDITIONAL INFORMATION

Stand Number 1 to the east and stand Number 2 to the west of apron.
Stand Number 1 for ATR 72-500 or lesser type of ACFT and stand Number 2 for Q400 or lesser type of ACFT.

VOTK AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart (29 OCT 2026)
2. Aircraft Parking and Docking Chart (29 OCT 2026)
3. Aerodrome Obstacle Chart - Type A (Obstacle Limitations) RWY 10 (29 OCT 2026)
4. Aerodrome Obstacle Chart - Type A (Obstacle Limitations) RWY 28 (29 OCT 2026)
5. Aerodrome Obstacle Chart - Type B (29 OCT 2026)
6. Instrument Approach Chart - VOR Procedure RWY 10 (CAT A/B/C) (16 APR 2026)
7. Instrument Approach Chart - VOR Procedure RWY 28 (CAT A/B) (27 November 2025)
8 RNP Procedure RWY 26(9 JULY 2026)
9 Coding Table - RNP Procedure RWY 26(9 JULY 2026)

VOTK AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3