

Exp. No : 9

Implement clustering techniques – Hierarchical and K-Means

a) Hierarchical Clustering

```
# Load the iris dataset
data(iris)

# Use only the numeric columns for clustering (exclude the Species column)
iris_data <- iris[, -5]

# Standardize the data
iris_scaled <- scale(iris_data)

# Compute the distance matrix
distance_matrix <- dist(iris_scaled, method = "euclidean")

# Perform hierarchical clustering using the "complete" linkage method
hc_complete <- hclust(distance_matrix, method = "complete")

# Plot the dendrogram
plot(hc_complete, main = "Hierarchical Clustering Dendrogram", xlab = "", sub = "", cex = 0.6)

# Cut the tree to form 3 clusters
clusters <- cutree(hc_complete, k = 3)

# Print the cluster memberships
print(clusters)

# Add the clusters to the original dataset
iris$Cluster <- as.factor(clusters)

# Display the first few rows of the updated dataset
head(iris)
```

Output :

[illegible]

```
The downloaded binary packages are in  
  C:\Users\super\AppData\Local\Temp\Rtmp4kw9ap\downloaded_packages  
> library(ggplot2)  
> ggplot(iris, aes(x = Sepal.Length, y = Sepal.Width, color = Cluster)) +  
+   geom_point(size = 3) +  
+   labs(title = "K-Means Clustering of Iris Dataset", x = "Sepal Length", y = "Sepal Width")  
> |
```

