

C++ Operator Precedence

The following table lists the precedence and associativity of C++ operators. Operators are listed top to bottom, in descending precedence.

Precedence	Operator	Description	Associativity
1	::	Scope resolution	Left-to-right
2	a++ a--	Suffix/postfix increment and decrement	
	type() type{}	Functional cast	
	a()	Function call	
	a[]	Subscript	
	. ->	Member access	
3	++a --a	Prefix increment and decrement	Right-to-left
	+a -a	Unary plus and minus	
	! ~	Logical NOT and bitwise NOT	
	(type)	C-style cast	
	*a	Indirection (dereference)	
	&a	Address-of	
	sizeof	Size-of ^[note 1]	
	co_await	await-expression (C++20)	
	new new[]	Dynamic memory allocation	
	delete delete[]	Dynamic memory deallocation	
4	.* ->*	Pointer-to-member	Left-to-right
5	a*b a/b a%b	Multiplication, division, and remainder	
6	a+b a-b	Addition and subtraction	
7	<< >>	Bitwise left shift and right shift	
8	<=>	Three-way comparison operator (since C++20)	
9	< <=	For relational operators < and ≤ respectively	
	> >=	For relational operators > and ≥ respectively	
10	== !=	For relational operators = and ≠ respectively	
11	&	Bitwise AND	
12	^	Bitwise XOR (exclusive or)	
13		Bitwise OR (inclusive or)	
14	&&	Logical AND	
15		Logical OR	
16	a?b:c	Ternary conditional ^[note 2]	Right-to-left
	throw	throw operator	
	co_yield	yield-expression (C++20)	
	=	Direct assignment (provided by default for C++ classes)	
	+= -=	Compound assignment by sum and difference	
	*= /= %=	Compound assignment by product, quotient, and remainder	
	<<= >>=	Compound assignment by bitwise left shift and right shift	
17	&= ^= =	Compound assignment by bitwise AND, XOR, and OR	
	,	Comma	Left-to-right

- ↑ The operand of sizeof can't be a C-style type cast: the expression sizeof (int) * p is unambiguously interpreted as (sizeof(int)) * p, but not sizeof((int)*p).
- ↑ The expression in the middle of the conditional operator (between ? and :) is parsed as if parenthesized: its precedence relative to ?: is ignored.

When parsing an expression, an operator which is listed on some row of the table above with a precedence will be bound tighter (as if by parentheses) to its arguments than any operator that is listed on a row further below it with a lower precedence. For example, the expressions `std::cout << a & b` and `*p++` are parsed as `(std::cout << a) & b` and `*(p++)`, and not as `std::cout << (a & b)` or `(*p)++`.

Operators that have the same precedence are bound to their arguments in the direction of their associativity. For example, the expression `a = b = c` is parsed as `a = (b = c)`, and not as `(a = b) = c` because of right-to-left associativity of assignment, but `a + b - c` is parsed as `(a + b) - c` and not `a + (b - c)` because of left-to-right associativity of addition and subtraction.

Associativity specification is redundant for unary operators and is only shown for completeness: unary prefix operators always associate right-to-left (`delete ++*p` is `delete(++(*p))`) and unary postfix operators always associate left-to-right (`a[1][2]++` is `((a[1][2]))++`). Note that the associativity is meaningful for member access operators, even though they are grouped with unary postfix operators: `a.b++` is parsed `(a.b)++` and not `a.(b++)`.

Operator precedence is unaffected by operator overloading. For example, `std::cout << a ? b : c;` parses as `(std::cout << a) ? b : c;` because the precedence of arithmetic left shift is higher than the conditional operator.

Notes

Precedence and associativity are compile-time concepts and are independent from order of evaluation, which is a runtime concept.

The standard itself doesn't specify precedence levels. They are derived from the grammar.

`const_cast`, `static_cast`, `dynamic_cast`, `reinterpret_cast`, `typeid`, `sizeof...`, `noexcept` and `alignof` are not included since they are never ambiguous.

Some of the operators have alternate spellings (e.g., `and` for `&&`, `or` for `||`, `not` for `!`, etc.).

In C, the ternary conditional operator has higher precedence than assignment operators. Therefore, the expression `e = a < d ? a++ : a = d`, which is parsed in C++ as `e = ((a < d) ? (a++) : (a = d))`, will fail to compile in C due to grammatical or semantic constraints in C. See the corresponding C page for details.

See also

Common operators						
assignment	increment decrement	arithmetic	logical	comparison	member access	other
<div>a = b a += b a -= b a *= b a /= b a %= b a &= b a = b a ^= b a <<= b a >>= b</div>	<div>++a --a a++ a--</div>	<div>+a -a a + b a - b a * b a / b a % b ~a a & b a b a ^ b a << b a >> b</div>	<div>!a a && b a b</div>	<div>a == b a != b a < b a > b a <= b a >= b a <=> b</div>	<div>a[b] *a &a a->b a.b a->*b a.*b</div>	<div>a(...) a, b ?:</div>
Special operators						
<div>static_cast converts one type to another related type dynamic_cast converts within inheritance hierarchies const_cast adds or removes cv qualifiers reinterpret_cast converts type to unrelated type C-style cast converts one type to another by a mix of static_cast, const_cast, and reinterpret_cast new creates objects with dynamic storage duration delete destructs objects previously created by the new expression and releases obtained memory area sizeof queries the size of a type sizeof... queries the size of a parameter pack (since C++11) typeid queries the type information of a type noexcept checks if an expression can throw an exception (since C++11) alignof queries alignment requirements of a type (since C++11)</div>						

C documentation for C operator precedence

Retrieved from "https://en.cppreference.com/mwiki/index.php?title=cpp/language/operator_precedence&oldid=118915"