

SHA-256 checksum db4bf774badbb20346afb4527479b0142090b58f4c7aca7796824ea47173c066  
Compiled from "House.java"

```
class examples.classes_instances.House
  minor version: 0
  major version: 61
  flags: (0x0020) ACC_SUPER
  this_class: #7                      // examples/classes_instances/House
  super_class: #2                     // java/lang/Object
  interfaces: 0, fields: 4, methods: 1, attributes: 1
```

Constant pool:

```
#1 = Methodref      #2.#3          // java/lang/Object."<init>":()V
#2 = Class          #4              // java/lang/Object
#3 = NameAndType    #5:#6          // "<init>":()V
#4 = Utf8           java/lang/Object
#5 = Utf8           <init>
#6 = Utf8           ()V
#7 = Class          #8              // examples/classes_instances/House
#8 = Utf8           examples/classes_instances/House
#9 = Utf8           height
#10 = Utf8          I
#11 = Utf8          length
#12 = Utf8          width
#13 = Utf8          tag
#14 = Utf8          Ljava/lang/String;
#15 = Utf8          Code
#16 = Utf8          LineNumberTable
#17 = Utf8          LocalVariableTable
#18 = Utf8          this
#19 = Utf8          Lexamples/classes_instances/House;
#20 = Utf8          SourceFile
#21 = Utf8          House.java
```

{

```
int height;
  descriptor: I
  flags: (0x0000)
```

```
int length;
  descriptor: I
  flags: (0x0000)
```

```
int width;
  descriptor: I
  flags: (0x0000)
```

```
java.lang.String tag;
  descriptor: Ljava/lang/String;
  flags: (0x0000)
```

```
examples.classes_instances.House();
  descriptor: ()V
```

```
flags: (0x0000)
Code:
stack=1, locals=1, args_size=1
0: aload_0
1: invokespecial #1          // Method java/lang/Object."<init>":()V
4: return
LineNumberTable:
line 3: 0
LocalVariableTable:
Start  Length  Slot  Name   Signature
    0      5     0  this   Lexamples/classes_instances/House;
}
```