Lab 11
Data Structures with AI: Implementing Fundamental Structures

2303A51759

Batch-28

Task 1 – Stack Implementation

Code:

```
class Stack:     def
__init__(self):
self.items = []
   def push(self, item):
      self.items.append(item)
def pop(self):        if not
self.is_empty():            return
self.items.pop()        return
"Stack is empty"     def
peek(self):        if not
```

```
self.is_empty():            return
self.items[-1]        return
"Stack is empty"     def
is_empty(self):
        return len(self.items) == 0
```

Task 2 – Queue Implementation

Code:

```
class Queue:
def __init__(self):
self.items = []
    def enqueue(self, item):
self.items.append(item)     def
dequeue(self):
        if self.items:
            return self.items.pop(0)
return "Queue is empty"
def peek(self):        if
self.items:
            return self.items[0]
        return "Queue is empty"
    def size(self):
        return len(self.items)
```

Task 3 – Singly Linked List

Code: class

Node:

def __init__(self, data):

self.data = data self.next

= None class LinkedList:

def __init__(self):

self.head = None def

insert(self, data):

new_node = Node(data)

if not self.head:

self.head = new_node

return

temp = self.head

while temp.next:

temp = temp.next

temp.next = new_node

def display(self):

temp = self.head

while temp:

```
print(temp.data, end=" -
> ")            temp =
temp.next
print("None")
```

Task 4 – Binary Search Tree (BST)

Code:

```
class BST:     def
__init__(self, key):
self.key = key        self.left =
None        self.right = None
def insert(self, value):        if
value < self.key:            if
self.left is None:
self.left = BST(value)
          else:
             self.left.insert(value)
else:            if self.right is
None:                self.right =
BST(value)
          else:
             self.right.insert(value)

   def inorder(self):
```

```
        if self.left:
            self.left.inorder()
print(self.key, end=" ")
        if self.right:
            self.right.inorder()
```

Task 5 – Hash Table (Chaining)

Code:

```
class HashTable:
    def __init__(self, size=10):
        self.size = size        self.table = [[]
for _ in range(size)]     def _hash(self,
key):
        return hash(key) % self.size     def
insert(self, key, value):        index =
self._hash(key)
self.table[index].append((key, value))
def search(self, key):        index =
self._hash(key)        for k, v in
self.table[index]:            if k == key:
return v
        return "Key not found"     def delete(self,
key):        index = self._hash(key)        for i, (k,
```

```
v) in enumerate(self.table[index]):            if k
== key:
            del self.table[index][i]
return "Deleted"        return
"Key not found"
```

Task 6 – Graph (Adjacency List)

Code:

```
class Graph:
def __init__(self):
self.graph = {}
   def add_vertex(self, vertex):
if vertex not in self.graph:
self.graph[vertex] = []
   def add_edge(self, v1, v2):
self.add_vertex(v1)        self.add_vertex(v2)
self.graph[v1].append(v2)
self.graph[v2].append(v1)     def
display(self):        for vertex in self.graph:
          print(vertex, "->", self.graph[vertex])
```

Task 7 – Priority Queue

Code:

```
import heapq class
PriorityQueue:
def __init__(self):
self.heap = []
   def enqueue(self, priority, item):
      heapq.heappush(self.heap, (priority, item))
def dequeue(self):
      if self.heap:
         return heapq.heappop(self.heap)
return "Queue is empty"     def
display(self):        print(self.heap)
```

Task 8 – Deque

Code: from collections import

```
deque class DequeDS:

   def __init__(self):
      self.deque = deque()     def
insert_front(self, item):
self.deque.appendleft(item)
def insert_rear(self, item):
self.deque.append(item)     def
remove_front(self):
```

```
        return self.deque.popleft()
def remove_rear(self):
return self.deque.pop()


)
```

Task 9 – Campus Resource Management System Feature → Data Structure Mapping

Feature	Justification	Data Structure
Student Attendance	Fast lookup by student ID. O(1) average complexity.	Hash Table
Event Registration	Dynamic insertion and removal of participants.	Linked List
Library Book Borrowing	Books can be organized by ID for sorted access.	BST

Feature	Justification	Data Structure
Bus Scheduling	Routes and stops form connected networks.	Graph
Cafeteria Order Queue	Orders must be served in FIFO order.	Queue

Implemented Feature: Cafeteria Order Queue

```
class CafeteriaQueue:
   """Manage student food orders using Queue."""

   def __init__(self):
self.orders = []

   def place_order(self, student_name):
self.orders.append(student_name)
print(f"{student_name} placed order.")

   def serve_order(self):
if self.orders:
         served = self.orders.pop(0)
print(f"Serving {served}")        else:
         print("No orders to serve.")

   def display_orders(self):
      print("Current Orders:", self.orders)


# Example cq =
CafeteriaQueue()
cq.place_order("Rahu
l")
cq.place_order("Anit
a") cq.serve_order()
cq.display_orders()
```

Task 10 – Smart E-Commerce Platform Feature → Data Structure Mapping

Feature	Data Structure	Justification
Shopping Cart	Linked List	Dynamic addition/removal of products.
Order Processing	Queue	Orders processed in FIFO order.
Top-Selling Products	Priority Queue	Ranked by highest sales.
Product Search	Hash Table	Fast product lookup by ID.
Delivery Route Planning	Graph	Warehouses and locations form network paths.

Implemented Feature: Product Search (Hash Table)

```
class ProductSearch:
    """Product lookup system using Hash Table."""

    def __init__(self):
self.products = {}

    def add_product(self, product_id, name):
        self.products[product_id] = name

    def search_product(self, product_id):
        return self.products.get(product_id, "Product not found")


# Example ps =
ProductSearch()
ps.add_product(101, "Laptop")
ps.add_product(102, "Mobile")
```

```
print(ps.search_product(101))
print(ps.search_product(200))
```