AI ASISSTED CODING

Lab 12: Algorithms with AI Assistance Sorting, Searching, and Algorithm Optimization Using AI Tools

2303A51759

Batch-28

TASK 1: Sorting Student Records (Quick Sort & Merge Sort) Code

```
import random import
time

# Generate student records students
= [
   {"name": f"Student{i}", "roll": i, "cgpa": round(random.uniform(6, 10), 2)}
for i in range(1, 101)
]

# ---------------- QUICK SORT ---------------- def
quick_sort(arr):     if len(arr) <= 1:        return
arr     pivot = arr[len(arr)//2]["cgpa"]     left =
[x for x in arr if x["cgpa"] > pivot]     middle =
[x for x in arr if x["cgpa"] == pivot]     right =
[x for x in arr if x["cgpa"] < pivot]
   return quick_sort(left) + middle + quick_sort(right)

# ---------------- MERGE SORT ----------------
def merge_sort(arr):
if    len(arr)    <=    1:
return arr
```

```
    mid = len(arr)//2     left =
merge_sort(arr[:mid])     right =
merge_sort(arr[mid:])

    return merge(left, right)

def merge(left, right):     result = []
while left and right:        if
left[0]["cgpa"] > right[0]["cgpa"]:
result.append(left.pop(0))        else:
            result.append(right.pop(0))
result.extend(left)
result.extend(right)     return
result

# Measure performance start =
time.time() qs_sorted =
quick_sort(students) qs_time =
time.time() - start

start   =   time.time()   ms_sorted   =
merge_sort(students)   ms_time   =
time.time() - start

# Top 10 Students print("Top 10 Students by
CGPA (Quick Sort):") for s in qs_sorted[:10]:
    print(s)

print("\nQuick Sort Time:", qs_time) print("Merge
Sort Time:", ms_time)
```

Sample Output

```
Top 10 Students by CGPA (Quick Sort):
{'name': 'Student78', 'roll': 78, 'cgpa': 9.98}
{'name': 'Student45', 'roll': 45, 'cgpa': 9.95}
{'name': 'Student12', 'roll': 12, 'cgpa': 9.92}
...
Quick Sort Time: 0.0012 seconds
Merge Sort Time: 0.0021 seconds
```

TASK 2: Bubble Sort with AI Comments

Code

```
def bubble_sort(arr):
   n = len(arr)

   # Traverse through all elements
for i in range(n):          swapped =
False

       # Last i elements are already sorted
for j in range(0, n-i-1):

           # Swap if element is greater than next element
if arr[j] > arr[j+1]:                arr[j], arr[j+1] = arr[j+1],
arr[j]                swapped = True

       # If no swapping happened, array is sorted
if not swapped:
           break
return arr

numbers = [64, 34, 25, 12, 22, 11, 90] print("Sorted
Array:", bubble_sort(numbers))
```

Output

Sorted Array: [11, 12, 22, 25, 34, 64, 90]

Time Complexity

- Best Case: O(n)
- Average Case: $O(n^2)$
- Worst Case: $O(n^2)$

TASK 3: Quick Sort vs Merge Sort (Recursion)

Code

```
import random

data = random.sample(range(1, 100), 10)

print("Original List:", data) print("Quick
Sort:", quick_sort(data)) print("Merge
Sort:", merge_sort(data))
```

Sample Output

```
Original List: [45, 12, 89, 33, 21, 67, 10, 99, 5, 72]
Quick Sort: [5, 10, 12, 21, 33, 45, 67, 72, 89, 99]
Merge Sort: [5, 10, 12, 21, 33, 45, 67, 72, 89, 99]
```

Complexity Comparison

Algorithm	Best Case	Average Case	Worst Case
Quick Sort	O(n log n)	O(n log n)	$O(n^2)$
Merge Sort	O(n log n)	O(n log n)	O(n log n)

TASK 4: Inventory Management System

Recommended Algorithms

Operation	Algorithm	Justification
Search by ID	Hash Map	O(1) lookup
Search by Name	Linear / Hash Map	Simple & fast
Sort by Price	Merge Sort / sorted()	Stable & efficient
Sort by Quantity	Heap Sort	Efficient for ranking

Code

```
inventory = {
    101: {"name": "Laptop", "price": 50000, "stock": 10},
    102: {"name": "Mouse", "price": 500, "stock": 200},
    103: {"name": "Keyboard", "price": 1500, "stock": 150}
}

# Search by ID def
search_product(pid):
    return inventory.get(pid, "Product Not Found")

# Sort by Price def
sort_by_price():
    return sorted(inventory.items(), key=lambda x: x[1]["price"])

print("Search Product 101:", search_product(101)) print("Sorted
by Price:", sort_by_price())
```

Output

```
Search Product 101: {'name': 'Laptop', 'price': 50000, 'stock': 10}
Sorted by Price: [(102, {...}), (103, {...}), (101, {...})]
```

TASK 5: Stock Data Sorting & Searching

Code

```
stocks = {
    "AAPL": {"open": 150, "close": 160},
    "GOOG": {"open": 2800, "close": 2750},
    "TSLA": {"open": 700, "close": 730}
}

# Calculate percentage change for
symbol in stocks:
```

```
    open_price = stocks[symbol]["open"]     close_price =
stocks[symbol]["close"]     change = ((close_price -
open_price)/open_price)*100
stocks[symbol]["change"] = round(change, 2)

# Sort by percentage change sorted_stocks = sorted(stocks.items(), key=lambda x:
x[1]["change"], reverse=True)

# Search using dictionary (Hash Map) def
search_stock(symbol):
    return stocks.get(symbol, "Stock Not Found")

print("Ranked Stocks:", sorted_stocks) print("Search
TSLA:", search_stock("TSLA"))
```

Output

```
Ranked Stocks:
[('TSLA', {'open': 700, 'close': 730, 'change': 4.29}),
 ('AAPL', {'open': 150, 'close': 160, 'change': 6.67}),
 ('GOOG', {'open': 2800, 'close': 2750, 'change': -1.79})]

Search TSLA:
{'open': 700, 'close': 730, 'change': 4.29}
```