

Router

```
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#interface ethernet 0/0
Router(config-if)#ip address 50.0.0.1 255.0.0.0
Router(config-if)#no shutdown
Router(config-if)#interface ethernet 0/1
Router(config-if)#ip address 60.0.0.1 255.0.0.0
Router(config-if)#no shutdown
Router(config-if)#exit
Router(config)#exit
Router#
*Aug 23 06:46:03.902: %SYS-5-CONFIG_I: Configured from console by console
Router#show ip interface brief
Interface                IP-Address      OK? Method Status      Prot
ocol
Ethernet0/0              50.0.0.1        YES manual  up          up
Ethernet0/1              60.0.0.1        YES manual  up          up
Ethernet0/2              unassigned      YES TFTP   down        down
Ethernet0/3              unassigned      YES TFTP   down        down
Router#
```

```
Router
Ethernet0/2          unassigned      YES TFTP    down        down
Ethernet0/3          unassigned      YES TFTP    down        down

Router#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

    50.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       50.0.0.0/8 is directly connected, Ethernet0/0
L       50.0.0.1/32 is directly connected, Ethernet0/0
    60.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       60.0.0.0/8 is directly connected, Ethernet0/1
L       60.0.0.1/32 is directly connected, Ethernet0/1
Router#
```

