1. Write a program to solve the 0/1 knapsack problem using greedy Algorithm.

```
import java.util.Arrays;
import java.util.Comparator;

class Item {
    int value, weight;
    public Item(int value, int weight){
        this.value = value;
        this.weight = weight;
    }
}
public class Knapsack {
    public static void main(String[] args){
        int capacity = 50;
        Item[] items = {new Item(60, 10),
                        new Item(100, 20),
                        new Item(120, 30),};
        double value = Knapsack(items, capacity);
        System.out.println("Maximum Knapsack value" + maxValue);
    }
    public static double 0/1 knapSack(Item[] items, int capacity){
        Arrays.sort(items, Comparator<Item>(){
            @Override
            public int compare(Item item1, item2){
                double ratio1 = (double) item1.value / item1.weight;
                double ratio2 = (double) item2.value / item2.weight;
```

```
        return Double.compare(ratio2, ratio1);
    }
);
int currentWeight = 0;
double totalValue = 0;
for (Item item : items) {
    if (currentWeight + item.weight <= capacity) {
        currentWeight += item.weight;
        totalValue += item.value;
    } else {
        double remainingCapacity = capacity - currentWeight;
        totalValue = (remainingCapacity / item.weight) * item.value;
        break;
    }
}
return totalValue;
}
}
```

Output :-

Maximum value in Knapsack = 240.0

2. Write a program to solve Fractional Knapsack problem using Greedy approach.

```
import java.util.Arrays;
import java.util.Comparator;
public class FractionalKnapsack {
    static class Item {
        int profit, weight;
        public Item(int profit, int weight) {
            this.profit = profit;
            this.weight = weight;
        }
    }
    public static double getMaxValue(Item[] items, int capacity) {
        Arrays.sort(items, (item1, item2) -> Double.compare((double)
        item2.profit / item2.weight, (double) item1.profit/item1.weight));
        double totalValue = 0;
        for (Item item : items) {
            int currentWeight = item.weight;
            int currentValue = item.profit;
            if (capacity - currentWeight >= 0) {
                capacity -= currentWeight;
                totalValue += currentValue;
            } else {
                double fraction = (double) capacity / currentWeight;
                totalValue += (currentValue * fraction);
                capacity = 0;
                break;
            }
        }
        return totalValue;
    }
    public static void main(String[] args) {
        Item[] items = { new Item(60, 10),
                         new Item(10, 20),
                         new Item(20, 30) };
```

```
int capacity = 50;
double maxvalue = getMaxValue(items, capacity);
System.out.println("Maximum value in Knapsack = " + maxvalue);
}
}
```

output:-

Maximum value in Knapsack = 85.0

3. Write a program to solve job sequencing deadline using greedy Algorithm.

```
import java.util.*;
class Job{
    char id;
    int deadline, profit;
Public Job(){}
Public Job(char id, int deadline, int profit){
    this.id = id;
    this.deadline = deadline;
    this.profit = profit;
}
void printJobScheduling(ArrayList<Job> arr, int t){
int n = arr.size();
Collections.sort(arr, (a,b) -> b.profit - a.profit);
boolean result[] = new boolean[t];
char job[] = new char[t];
for(int i=0; i<n; i++){
    for(int j = Math.min(t-1, arr.get(i).deadline-1);
        j>=0; j--){
```

```
        if (result[i] == false) {
            result[i] = true;
            job[i] = arr.get(i).id;
            break;
        }
    }
    for (char jb : job)
        SOP(jb + " ");
    SOP();
}
public static void main(String args[]) {
    ArrayList<Job> arr = new ArrayList<Job>();
    arr.add(new Job('a', 2, 100));
    arr.add(new Job('b', 1, 19));
    arr.add(new Job('c', 2, 27));
    arr.add(new Job('d', 1, 25));
    arr.add(new Job('e', 3, 15));
    SOP("Following is Maximum profit Seaquence of Jobs");
    Job job = new Job();
    job.PrintJobScheduling(arr, 3);
}
}
```

output :-

Following is Maximum profit Seaquence of Jobs

c a e.

4. write a program to find Minimum Spaning tree using prims Algorithm.

```
import. java.io.*;
import.java.lang.*;
import.java.util.*;

ccass MST{.
  Privare srabic final int v=5; //No-of vertices.
int minKey (int key[], Boolean msiSet[]){
int min = Integer.MAX_VALUE, min_idex = -1;
for (int v=0; v<V; v++)
  ie (mstSet[v] == faise && key[v] < min){
      min = key[v];
      min_index = v;
return min_index;
}
void print MST (int parent[], int graph[][]){
  Sop ("Edge \t weight");
For (int i=1; i<V; i++)
  sop (parent[i]+" - "+i+" \t "+ graph[i][parent[i]]);
}
void primMSt(int graph[][]){
  int parent[] = new int[v];
  int key[] = new int[v];
  Boolean mstSet[] = new Boolean[v];
for (int i=0; i<V; i++){
  Key[i] = Integer.MAX_VALUE;
  mstSet[i] = Faise)
}
  Key[0] = 0;
  parent[0] = -1;
for (int count = 0; count<V-1; count++){.
```

```
int u = minKey(key, mstSet);
mstSet[u] = true;
for(int v=0; v<V; v++)
if (graph[u][v] != 0 && mstSet[v] == false && graph[u][v]
    < key[v]) {
parent[v] = u;
key[v] = graph[u][v];
}
printMST(parent, graph);
}
public static void main(String[] args) {
MST t = new MST();
int graph[][] = new int[][] { {0, 2, 0, 6, 0},
                              {2, 0, 3, 8, 5},
                              {0, 3, 0, 0, 7},
                              {6, 8, 0, 0, 9},
                              {0, 5, 7, 9, 0}};
t.primMST(graph);
}
}
```

output :-

Edge	Weight
0 - 1	2
1 - 2	3
0 - 3	6
1 - 4	5