

РБНФ №1 (опис синтаксису мови всіма допустимими засобами РБНФ)	РБНФ №2 (опис формальна граматика мови)	Опис формальної граматики мови	Опис граматики з специфікацією lookahead для LL2-аналізатора	Код для перевірки РБНФ №2	/* Дані для LL2-аналізатора (лексми вже опрацьовані лексичним аналізатором) УВАГА: при копіюванні зважайте, щоб у кожному рядку після символу «\» не містилось жодних інших символів. */
		G = (N, T, P, S)	G = (N, T, P, S)	Код для перевірки РБНФ №1	
		S → program_rule	S → program_rule		
		N = { labeled_point, ident, goto_label, program_name, value_type, array_specify, declaration_element, array_specify_optional, other_declaration_ident, declaration, other_declaration_ident_iteration, index_action, unary_operator, unary_operation, binary_operator, binary_action, left_expression, group_expression, value, index_action_optional, expression, binary_action_iteration, expression_or_bind_left_to_right, bind_to_right, bind_to_right_optional, if_expression, body_for_true, false_cond_block_without_else, body_for_false, cond_block, false_cond_block_without_else_iteration, body_for_false_optional, cond_block_with_optional_bind, cycle_begin_expression, cycle_end_expression, cycle_counter, cycle_counter_lr_init, cycle_counter_init, cycle_counter_last_value, cycle_body, forto_direction, forto_cycle, continue_while, break_while, statement_in_while_and_if_body, statement, block_statements_in_while_and_if_body, statement_in_while_and_if_body_iteration, while_cycle_head_expression, while_cycle, repeat_until_cycle_cond, repeat_until_cycle, statements_or_block_statements, block_statements, input_rule, argument_for_input, output_rule, statement_iteration, expression_optional, program_rule, declaration_optional, unsigned_value, value, sign_optional, sign, ident, sign_plus, sign_minus }	N = { labeled_point, ident, goto_label, program_name, value_type, array_specify, declaration_element, array_specify_optional, other_declaration_ident, declaration, other_declaration_ident_iteration, index_action, unary_operator, unary_operation, binary_operator, binary_action, left_expression, group_expression, value, index_action_optional, expression, binary_action_iteration, expression_or_bind_left_to_right, bind_to_right, bind_to_right_optional, if_expression, body_for_true, false_cond_block_without_else, body_for_false, cond_block, false_cond_block_without_else_iteration, body_for_false_optional, cond_block_with_optional_bind, cycle_begin_expression, cycle_end_expression, cycle_counter, cycle_counter_lr_init, cycle_counter_init, cycle_counter_last_value, cycle_body, forto_direction, forto_cycle, continue_while, break_while, statement_in_while_and_if_body, statement, block_statements_in_while_and_if_body, statement_in_while_and_if_body_iteration, while_cycle_head_expression, while_cycle, repeat_until_cycle_cond, repeat_until_cycle, statements_or_block_statements, block_statements, input_rule, argument_for_input, output_rule, statement_iteration, expression_optional, program_rule, declaration_optional, unsigned_value, value, sign_optional, sign, ident, sign_plus, sign_minus }		
		T = { ";", "GOTO", "INTEGER16", " ", ",", "NOT", "AND", "OR", "==" , "!=" , "<=" , ">=" , "<" , ">" , "+", "-", "*", "/", "DIV", "MOD", "(", ")", ";", "ELSE", "IF", "DO", "FOR", "TO", "DOWNTO", "WHILE", }	T = { ";", "GOTO", "INTEGER16", " ", ",", "NOT", "AND", "OR", "==" , "!=" , "<=" , ">=" , "<" , ">" , "+", "-", "*", "/", "DIV", "MOD", "(", ")", ";", "ELSE", "IF", "DO", "FOR", "TO", "DOWNTO", "WHILE", }		

		"CONTINUE" , "BREAK" , "EXIT" , "REPEAT" , "UNTIL" , "GET" , "PUT" , "NAME" , "BODY" , "DATA" , "BEGIN" , "END" , { , } { , } { , } "0" "1" "2" "3" "4" "5" "6" "7" "8" "9" " " _ , "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z" "A" "B" "C" "D" "E" "F" "G" "H" "I" "J" "K" "L" "M" "N" "O" "P" "Q" "R" "S" "T" "U" "V" "W" "X" "Y" "Z" }	"CONTINUE" , "BREAK" , "EXIT" , "REPEAT" , "UNTIL" , "GET" , "PUT" , "NAME" , "BODY" , "DATA" , "BEGIN" , "END" , { , } { , } { , } "0" "1" "2" "3" "4" "5" "6" "7" "8" "9" " " _ , "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z" "A" "B" "C" "D" "E" "F" "G" "H" "I" "J" "K" "L" "M" "N" "O" "P" "Q" "R" "S" "T" "U" "V" "W" "X" "Y" "Z" }			
				tokenGROUPEXPRESSIONBEGIN = "{" >> BOUNDARIES;	tokenGROUPEXPRESSIONBEGIN = "{" >> BOUNDARIES;	#define T_BEGIN_GROUPEXPRESSION_0 "(" #define T_BEGIN_GROUPEXPRESSION_1 "" #define T_BEGIN_GROUPEXPRESSION_2 "" #define T_BEGIN_GROUPEXPRESSION_3 ""
				tokenGROUPEXPRESSIONEND = "}" >> BOUNDARIES;	tokenGROUPEXPRESSIONEND = "}" >> BOUNDARIES;	#define T_END_GROUPEXPRESSION_0 "]" #define T_END_GROUPEXPRESSION_1 "" #define T_END_GROUPEXPRESSION_2 "" #define T_END_GROUPEXPRESSION_3 ""
				tokenLEFTSQUAREBRACKETS = "[" >> BOUNDARIES;	tokenLEFTSQUAREBRACKETS = "[" >> BOUNDARIES;	#define T_LEFT_SQUAREBRACKETS_0 "[" #define T_LEFT_SQUAREBRACKETS_1 "" #define T_LEFT_SQUAREBRACKETS_2 "" #define T_LEFT_SQUAREBRACKETS_3 ""
				tokenRIGHTSQUAREBRACKETS = "]" >> BOUNDARIES;	tokenRIGHTSQUAREBRACKETS = "]" >> BOUNDARIES;	#define T_RIGHT_SQUAREBRACKETS_0 "]" #define T_RIGHT_SQUAREBRACKETS_1 "" #define T_RIGHT_SQUAREBRACKETS_2 "" #define T_RIGHT_SQUAREBRACKETS_3 ""
				tokenBEGINBLOCK = "{" >> BOUNDARIES;	tokenBEGINBLOCK = "{" >> BOUNDARIES;	#define T_BEGIN_BLOCK_0 "{" #define T_BEGIN_BLOCK_1 "" #define T_BEGIN_BLOCK_2 "" #define T_BEGIN_BLOCK_3 ""
				tokenENDBLOCK = "}" >> BOUNDARIES;	tokenENDBLOCK = "}" >> BOUNDARIES;	#define T_END_BLOCK_0 "}" #define T_END_BLOCK_1 "" #define T_END_BLOCK_2 "" #define T_END_BLOCK_3 ""

				tokenSEMICOLON = ";;" >> BOUNDARIES;	tokenSEMICOLON = ";;" >> BOUNDARIES;	#define T_SEMICOLON_0 ";" #define T_SEMICOLON_1 "" #define T_SEMICOLON_2 "" #define T_SEMICOLON_3 ""
				tokenCOLON = ":" >> BOUNDARIES;	tokenCOLON = ":" >> BOUNDARIES;	#define T_COLON_0 ":" #define T_COLON_1 "" #define T_COLON_2 "" #define T_COLON_3 ""
				tokenGOTO = "GOTO" >> STRICT_BOUNDARIES;	tokenGOTO = "GOTO" >> STRICT_BOUNDARIES;	#define T_GOTO_0 "GOTO" #define T_GOTO_1 "" #define T_GOTO_2 "" #define T_GOTO_3 ""
				tokenINTEGER16 = "INTEGER16" >> STRICT_BOUNDARIES;	tokenINTEGER16 = "INTEGER16" >> STRICT_BOUNDARIES;	#define T_DATA_TYPE_0 "INTEGER16" #define T_DATA_TYPE_1 "" #define T_DATA_TYPE_2 "" #define T_DATA_TYPE_3 ""
				tokenCOMMA = "," >> BOUNDARIES;	tokenCOMMA = "," >> BOUNDARIES;	#define T_COMA_0 "," #define T_COMA_1 "" #define T_COMA_2 "" #define T_COMA_3 ""
						#define T_BITWISE_NOT_0 "~" #define T_BITWISE_NOT_1 "" #define T_BITWISE_NOT_2 "" #define T_BITWISE_NOT_3 ""
				tokenNOT = "NOT" >> STRICT_BOUNDARIES;	tokenNOT = "NOT" >> STRICT_BOUNDARIES;	#define T_NOT_0 "NOT" #define T_NOT_1 "" #define T_NOT_2 "" #define T_NOT_3 ""
						#define T_BITWISE_AND_0 "&" #define T_BITWISE_AND_1 "" #define T_BITWISE_AND_2 "" #define T_BITWISE_AND_3 ""
				tokenAND = "AND" >> STRICT_BOUNDARIES;	tokenAND = "AND" >> STRICT_BOUNDARIES;	#define T_AND_0 "AND" #define T_AND_1 "" #define T_AND_2 "" #define T_AND_3 ""
						#define T_BITWISE_OR_0 " " #define T_BITWISE_OR_1 "" #define T_BITWISE_OR_2 "" #define T_BITWISE_OR_3 ""
				tokenOR = "OR" >> STRICT_BOUNDARIES;	tokenOR = "OR" >> STRICT_BOUNDARIES;	#define T_OR_0 "OR" #define T_OR_1 "" #define T_OR_2 "" #define T_OR_3 ""
				tokenEQUAL = "==" >> BOUNDARIES;	tokenEQUAL = "==" >> BOUNDARIES;	#define T_EQUAL_0 "==" #define T_EQUAL_1 "" #define T_EQUAL_2 "" #define T_EQUAL_3 ""
				tokenNOTEQUAL = "!=" >> BOUNDARIES;	tokenNOTEQUAL = "!=" >> BOUNDARIES;	#define T_NOT_EQUAL_0 "!=" #define T_NOT_EQUAL_1 "" #define T_NOT_EQUAL_2 "" #define T_NOT_EQUAL_3 ""
				tokenLESSOREQUAL = "<=" >> BOUNDARIES;	tokenLESSOREQUAL = "<=" >> BOUNDARIES;	#define T_LESS_OR_EQUAL_0 "<="
				tokenGREATEROREQUAL = ">=" >> BOUNDARIES;	tokenGREATEROREQUAL = ">=" >> BOUNDARIES;	#define T_GREATER_OR_EQUAL_0 ">="
				tokenLESS = "<" >> BOUNDARIES;	tokenLESS = "<" >> BOUNDARIES;	#define T_LESS_0 "<" #define T_LESS_1 "" #define T_LESS_2 "" #define T_LESS_3 ""
				tokenGREATER = ">" >> BOUNDARIES;	tokenGREATER = ">" >> BOUNDARIES;	#define T_GREATER_0 ">" #define T_GREATER_1 "" #define T_GREATER_2 "" #define T_GREATER_3 ""
				tokenPLUS = "+" >> BOUNDARIES;	tokenPLUS = "+" >> BOUNDARIES;	#define T_ADD_0 "+" #define T_ADD_1 "" #define T_ADD_2 "" #define T_ADD_3 ""
				tokenMINUS = "-" >> BOUNDARIES;	tokenMINUS = "-" >> BOUNDARIES;	#define T_SUB_0 "-" #define T_SUB_1 "" #define T_SUB_2 "" #define T_SUB_3 ""
				tokenMUL = "*" >> BOUNDARIES;	tokenMUL = "*" >> BOUNDARIES;	#define T_MUL_0 "" #define T_MUL_1 "" #define T_MUL_2 "" #define T_MUL_3 ""
				tokenDIV = "DIV" >> STRICT_BOUNDARIES;	tokenDIV = "DIV" >> STRICT_BOUNDARIES;	#define T_DIV_0 "DIV" #define T_DIV_1 "" #define T_DIV_2 "" #define T_DIV_3 ""
				tokenMOD = "MOD" >> STRICT_BOUNDARIES;	tokenMOD = "MOD" >> STRICT_BOUNDARIES;	#define T_MOD_0 "MOD" #define T_MOD_1 "" #define T_MOD_2 "" #define T_MOD_3 ""
				tokenLRBIND = "=:;" >> BOUNDARIES;	tokenLRBIND = "=:;" >> BOUNDARIES;	#define T_LRBIND_0 "=:;" #define T_LRBIND_1 "" #define T_LRBIND_2 "" #define T_LRBIND_3 ""
						#define T_THEN_BLOCK_0 "if" #define T_THEN_BLOCK_1 "" #define T_THEN_BLOCK_2 "" #define T_THEN_BLOCK_3 ""
				tokenELSE = "ELSE" >> STRICT_BOUNDARIES;	tokenELSE = "ELSE" >> STRICT_BOUNDARIES;	#define T_ELSE_BLOCK_0 "ELSE" #define T_ELSE_BLOCK_1 T_BEGIN_BLOCK_0 #define T_ELSE_BLOCK_2 "" #define T_ELSE_BLOCK_3 ""
				tokenIF = "IF" >> STRICT_BOUNDARIES;	tokenIF = "IF" >> STRICT_BOUNDARIES;	#define T_IF_0 "IF" #define T_IF_1 "" #define T_IF_2 "" #define T_IF_3 ""
						#define T_ELSE_IF_0 "ELSE" #define T_ELSE_IF_1 T_IF_0 #define T_ELSE_IF_2 ""

						#define T_ELSE_IF_3 ""
				tokenDO = "DO" >> STRICT_BOUNDARIES;	tokenDO = "DO" >> STRICT_BOUNDARIES;	#define T_DO_0 "DO" #define T_DO_1 "" #define T_DO_2 "" #define T_DO_3 ""
				tokenFOR = "FOR" >> STRICT_BOUNDARIES;	tokenFOR = "FOR" >> STRICT_BOUNDARIES;	#define T_FOR_0 "FOR" #define T_FOR_1 "" #define T_FOR_2 "" #define T_FOR_3 ""
				tokenTO = "TO" >> STRICT_BOUNDARIES;	tokenTO = "TO" >> STRICT_BOUNDARIES;	#define T_TO_0 "TO" #define T_TO_1 "" #define T_TO_2 "" #define T_TO_3 ""
				tokenDOWNT0 = "DOWNT0" >> STRICT_BOUNDARIES;	tokenDOWNT0 = "DOWNT0" >> STRICT_BOUNDARIES;	#define T_DOWNT0_0 "DOWNT0" #define T_DOWNT0_1 "" #define T_DOWNT0_2 "" #define T_DOWNT0_3 ""
				tokenWHILE = "WHILE" >> STRICT_BOUNDARIES;	tokenWHILE = "WHILE" >> STRICT_BOUNDARIES;	#define T_WHILE_0 "WHILE" #define T_WHILE_1 "" #define T_WHILE_2 "" #define T_WHILE_3 ""
				tokenCONTINUE = "CONTINUE" >> STRICT_BOUNDARIES;	tokenCONTINUE = "CONTINUE" >> STRICT_BOUNDARIES;	#define T_CONTINUE_WHILE_0 "CONTINUE" #define T_CONTINUE_WHILE_1 "" #define T_CONTINUE_WHILE_2 "" #define T_CONTINUE_WHILE_3 ""
				tokenBREAK = "BREAK" >> STRICT_BOUNDARIES;	tokenBREAK = "BREAK" >> STRICT_BOUNDARIES;	#define T_EXIT_WHILE_0 "BREAK" #define T_EXIT_WHILE_1 "" #define T_EXIT_WHILE_2 "" #define T_EXIT_WHILE_3 ""
				tokenEXIT = "EXIT" >> STRICT_BOUNDARIES;	tokenEXIT = "EXIT" >> STRICT_BOUNDARIES;	#define T_EXIT_0 "EXIT" #define T_EXIT_1 "" #define T_EXIT_2 "" #define T_EXIT_3 ""
				tokenREPEAT = "REPEAT" >> STRICT_BOUNDARIES;	tokenREPEAT = "REPEAT" >> STRICT_BOUNDARIES;	#define T_REPEAT_0 "REPEAT" #define T_REPEAT_1 "" #define T_REPEAT_2 "" #define T_REPEAT_3 ""
				tokenUNTIL = "UNTIL" >> STRICT_BOUNDARIES;	tokenUNTIL = "UNTIL" >> STRICT_BOUNDARIES;	#define T_UNTIL_0 "UNTIL" #define T_UNTIL_1 "" #define T_UNTIL_2 "" #define T_UNTIL_3 ""
				tokenGET = "GET" >> STRICT_BOUNDARIES;	tokenGET = "GET" >> STRICT_BOUNDARIES;	#define T_INPUT_0 "GET" #define T_INPUT_1 "" #define T_INPUT_2 "" #define T_INPUT_3 ""
				tokenPUT = "PUT" >> STRICT_BOUNDARIES;	tokenPUT = "PUT" >> STRICT_BOUNDARIES;	#define T_OUTPUT_0 "PUT" #define T_OUTPUT_1 "" #define T_OUTPUT_2 "" #define T_OUTPUT_3 ""
				tokenNAME = "NAME" >> STRICT_BOUNDARIES;	tokenNAME = "NAME" >> STRICT_BOUNDARIES;	#define T_NAME_0 "NAME" #define T_NAME_1 "" #define T_NAME_2 "" #define T_NAME_3 ""
				tokenBODY = "BODY" >> STRICT_BOUNDARIES;	tokenBODY = "BODY" >> STRICT_BOUNDARIES;	#define T_BODY_0 "BODY" #define T_BODY_1 "" #define T_BODY_2 "" #define T_BODY_3 ""
				tokenDATA = "DATA" >> STRICT_BOUNDARIES;	tokenDATA = "DATA" >> STRICT_BOUNDARIES;	#define T_DATA_0 "DATA" #define T_DATA_1 "" #define T_DATA_2 "" #define T_DATA_3 ""
				tokenBEGIN = "BEGIN" >> STRICT_BOUNDARIES;	tokenBEGIN = "BEGIN" >> STRICT_BOUNDARIES;	#define T_BEGIN_0 "BEGIN" #define T_BEGIN_1 "" #define T_BEGIN_2 "" #define T_BEGIN_3 ""
				tokenEND = "END" >> STRICT_BOUNDARIES;	tokenEND = "END" >> STRICT_BOUNDARIES;	#define T_END_0 "END" #define T_END_1 "" #define T_END_2 "" #define T_END_3 ""
						#define T_NULL_STATEMENT_0 "NULL" #define T_NULL_STATEMENT_1 "STATEMENT" #define T_NULL_STATEMENT_2 "" #define T_NULL_STATEMENT_3 ""
						#define GRAMMAR_LL2_2025 {\
labeled_point = ident , ":";	labeled_point = ident , ":";	labeled_point → ident ":"	labeled_point(1: "ident_terminal") → ident ":"	labeled_point = ident >> tokenCOLON;	labeled_point = ident >> tokenCOLON;	{ LA_IS, ("ident_terminal"), {"labeled_point", (\
goto_label = "GOTO" , ident;	goto_label = "GOTO" , ident;	goto_label → "GOTO" ident	goto_label(1: "GOTO") → "GOTO" ident	goto_label = tokenGOTO >> ident;	goto_label = tokenGOTO >> ident;	{ LA_IS, (T_GOTO_0), {"goto_label", (\
program_name = ident;	program_name = ident;	program_name → ident	program_name(1: "ident_terminal") → ident	program_name = SAME_RULE(ident);	program_name = SAME_RULE(ident);	{ LA_IS, ("ident_terminal"), {"program_name", (\
value_type = "INTEGER16";	value_type = "INTEGER16";	value_type → "INTEGER16"	value_type(1: "INTEGER16") → "INTEGER16"	value_type = SAME_RULE(tokenINTEGER16);	value_type = SAME_RULE(tokenINTEGER16);	{ LA_IS, (T_DATA_TYPE_0), {"value_type", (\
array_specify = "[" , unsigned_value , "]" ;	array_specify = "[" , unsigned_value , "]" ;	array_specify → "[" unsigned_value "]"	array_specify(1: "[" → "[" unsigned_value "]"	array_specify = "[" >> unsigned_value >> "]" ;	array_specify = "[" >> unsigned_value >> "]" ;	{ LA_IS, ("["), {"array_specify", (\
declaration_element = ident , ["[" , unsigned_value , "]"] ;	declaration_element = ident , array_specify__optional ;	declaration_element → ident array_specify__optional	declaration_element(1: "ident_terminal") → ident array_specify__optional	declaration_element = ident >> -(tokenLEFTSQUAREBRACKETS >> unsigned_value >> tokenRIGHTSQUAREBRACKETS);	declaration_element = ident >> array_specify__optional ;	{ LA_IS, ("ident_terminal"), {"declaration_element", (\
	array_specify__optional = array_specify ε ;	array_specify__optional → array_specify array_specify__optional → ε	array_specify__optional(1: "[" → array_specify array_specify__optional(1: !"[" → ε	array_specify__optional = array_specify "" ;	array_specify__optional = array_specify "" ;	{ LA_IS, ("["), {"array_specify__optional", (\
other_declaration_ident = " , " , declaration_element ;	other_declaration_ident = " , " , declaration_element ;	other_declaration_ident → " , " , declaration_element	other_declaration_ident(1: " , ") → " , " , declaration_element	other_declaration_ident = tokenCOMMA >> declaration_element ;	other_declaration_ident = tokenCOMMA >> declaration_element ;	{ LA_IS, (T_COMA_0), {"other_declaration_ident", (\
declaration = value_type , declaration_element , other_declaration_ident__iteration ;	declaration = value_type , declaration_element , other_declaration_ident__iteration ;	declaration → value_type declaration_element other_declaration_ident__iteration	declaration(1: "INTEGER16") → value_type declaration_element other_declaration_ident__iteration	declaration = value_type >> declaration_element >> other_declaration_ident__iteration ;	declaration = value_type >> declaration_element >> other_declaration_ident__iteration ;	{ LA_IS, (T_DATA_TYPE_0), {"declaration", (\

	other_declaration_ident__iteration = other_declaration_ident, other_declaration_ident__iteration ε;	other_declaration_ident__iteration → other_declaration_ident other_declaration_ident__iteration false_cond_block_without_else__iteration → ε	other_declaration_ident__iteration(1: ",") → other_declaration_ident other_declaration_ident__iteration false_cond_block_without_else__iteration(1: !",") → ε		other_declaration_ident__iteration = other_declaration_ident >> other_declaration_ident__iteration "";	{ LA_IS, { T_COMA_0 }, { "other_declaration_ident__iteration", {\ { LA_IS, { "" }, 2, { "other_declaration_ident", "other_declaration_ident__iteration" }}\ }};\} { LA_NOT, { T_COMA_0 }, { "other_declaration_ident__iteration", {\ { LA_IS, { "" }, 0, { "" }}\ }};\}
index_action = "[" , expression , "]" ;	index_action = "[" , expression , "]" ;	index_action → "[" expression "]"	index_action(1: "[") → "[" expression "]"	index_action = tokenLEFTSQUAREBRACKETS >> expression >> tokenRIGHTSQUAREBRACKETS;	index_action = tokenLEFTSQUAREBRACKETS >> expression >> tokenRIGHTSQUAREBRACKETS;	{ LA_IS, { "" }, { "index_action", {\ { LA_IS, { "" }, 3, { "[", "expression", "]" }}\ }};\}
unary_operator = "NOT";	unary_operator = "NOT";	unary_operator → "NOT"	unary_operator(1: "NOT") → "NOT"	unary_operator = SAME__RULE(tokenNOT);	unary_operator = SAME__RULE(tokenNOT);	{ LA_IS, { T_NOT_0 }, { "unary_operator", {\ { LA_IS, { "" }, 1, { T_NOT_0 }}\ }};\}
unary_operation = unary_operator , expression ;	unary_operation = unary_operator , expression ;	unary_operation → unary_operator expression	unary_operation(1: "NOT") → unary_operator expression	unary_operation = unary_operator >> expression ;	unary_operation = unary_operator >> expression ;	{ LA_IS, { T_NOT_0 }, { "unary_operation", {\ { LA_IS, { "" }, 2, { "unary_operator", "expression" }}\ }};\}
binary_operator = "AND" "OR" "=" "!=" "<=" ">=" "<" ">" "+" "-" "*" "DIV" "MOD";	binary_operator = "AND" "OR" "=" "!=" "<=" ">=" "<" ">" "+" "-" "*" "DIV" "MOD";	binary_operator → "AND" binary_operator → "OR" binary_operator → "=" binary_operator → "!=" binary_operator → "<=" binary_operator → ">=" binary_operator → "<" binary_operator → ">" binary_operator → "+" binary_operator → "-" binary_operator → "*" binary_operator → "DIV" binary_operator → "MOD"	binary_operator(1: "AND") → "AND" binary_operator(1: "OR") → "OR" binary_operator(1: "=") → "=" binary_operator(1: "!=") → "!=" binary_operator(1: "<=") → "<=" binary_operator(1: ">=") → ">=" binary_operator(1: "<") → "<" binary_operator(1: ">") → ">" binary_operator(1: "+") → "+" binary_operator(1: "-") → "-" binary_operator(1: "*") → "*" binary_operator(1: "DIV") → "DIV" binary_operator(1: "MOD") → "MOD"	binary_operator = tokenAND tokenOR tokenEQUAL tokenNOTEQUAL tokenLESSOREQUAL tokenGREATEROREQUAL tokenLESS tokenGREATER tokenPLUS tokenMINUS tokenMUL tokenDIV tokenMOD;	binary_operator = tokenAND tokenOR tokenEQUAL tokenNOTEQUAL tokenLESSOREQUAL tokenGREATEROREQUAL tokenLESS tokenGREATER tokenPLUS tokenMINUS tokenMUL tokenDIV tokenMOD;	{ LA_IS, { T_AND_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_AND_0 }}\ }};\} { LA_IS, { T_OR_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_OR_0 }}\ }};\} { LA_IS, { T_EQUAL_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_EQUAL_0 }}\ }};\} { LA_IS, { T_NOT_EQUAL_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_NOT_EQUAL_0 }}\ }};\} IF_NONUSE_COMPARE_WITH_EQUAL(\ { LA_IS, { T_LESS_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_LESS_0 }}\ }};\} { LA_IS, { T_GREATER_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_GREATER_0 }}\ }};\} \} IF_USE_COMPARE_WITH_EQUAL(\ { LA_IS, { T_LESS_OR_EQUAL_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_LESS_OR_EQUAL_0 }}\ }};\} { LA_IS, { T_GREATER_OR_EQUAL_0 }, {\ "binary_operator", {\ { LA_IS, { "" }, 1, { T_GREATER_OR_EQUAL_0 }}\ }};\} \} { LA_IS, { T_ADD_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_ADD_0 }}\ }};\} { LA_IS, { T_SUB_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_SUB_0 }}\ }};\} { LA_IS, { T_MUL_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_MUL_0 }}\ }};\} { LA_IS, { T_DIV_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_DIV_0 }}\ }};\} { LA_IS, { T_MOD_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_MOD_0 }}\ }};\}
binary_action = binary_operator , expression ;	binary_action = binary_operator , expression ;	binary_action → binary_operator expression	binary_action(1: "AND", "OR", "=", "!=", "<=", ">=", "<", ">", "+", "-", "*", "DIV", "MOD") → binary_operator expression	binary_action = binary_operator >> expression ;	binary_action = binary_operator >> expression ;	IF_NONUSE_COMPARE_WITH_EQUAL(\ { LA_IS, { T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_0, T_GREATER_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0 }, { "binary_action", {\ { LA_IS, { "" }, 2, { "binary_operator", "expression" }}\ }};\} \} IF_USE_COMPARE_WITH_EQUAL(\ { LA_IS, { T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_OR_EQUAL_0, T_GREATER_OR_EQUAL_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0 }, {\ "binary_action", {\ { LA_IS, { "" }, 2, { "binary_operator", "expression" }}\ }};\} \}
left_expression = group_expression unary_operation ident , [index_action__optional value cond_block ;	left_expression = group_expression unary_operation ident , index_action__optional value cond_block ;	left_expression → group_expression left_expression → unary_operation left_expression → ident , index_action__optional left_expression → value left_expression → cond_block	left_expression(1: "(") → group_expression left_expression(1: "NOT") → unary_operation left_expression(1: "ident_terminal") → ident , index_action__optional left_expression(1: "unsigned_value_terminal") → value left_expression(1: "+", "-": 2: "unsigned_value_terminal") → value left_expression(1: "IF") → cond_block	left_expression = group_expression unary_operation ident >> -index_action value cond_block ;	left_expression = group_expression unary_operation ident >> index_action__optional value cond_block ;	{ LA_IS, { "(" }, { "left_expression", {\ { LA_IS, { "" }, 1, { "group_expression" }}\ }};\} { LA_IS, { T_NOT_0 }, { "left_expression", {\ { LA_IS, { "" }, 1, { "unary_operation" }}\ }};\} { LA_IS, { "ident_terminal" }, { "left_expression", {\ { LA_IS, { "" }, 2, { "ident", "index_action__optional" }}\ }};\} { LA_IS, { "unsigned_value_terminal" }, { "left_expression", {\ { LA_IS, { "" }, 1, { "value" }}\ }};\} { LA_IS, { T_ADD_0, T_SUB_0 }, { "left_expression", {\ { LA_IS, { "unsigned_value_terminal" }, 1, { "value" }};\ /*{ LA_NOT, ("unsigned_value_terminal"), 1, {\ "unary_operation" } }*/\ }};\} { LA_IS, { T_IF_0 }, { "left_expression", {\ { LA_IS, { "" }, 1, { "cond_block" }}\ }};\}
	index_action__optional = index_action ε;	index_action__optional → index_action index_action__optional → ε	index_action__optional(1: "(") → index_action index_action__optional(1: !"(") → ε		index_action__optional = binary_action "";	{ LA_IS, { "" }, { "index_action__optional", {\ { LA_IS, { "" }, 1, { "index_action" }}\ }};\} { LA_NOT, { "(" }, { "index_action__optional", {\ { LA_IS, { "" }, 0, { "" }}\ }};\}
expression = left_expression , binary_action__iteration ;	expression = left_expression , binary_action__iteration ;	expression → left_expression binary_action__iteration	expression(1: "(", "NOT", "+", "-", "ident_terminal", "unsigned_value_terminal", "IF") → left_expression binary_action__iteration	expression = left_expression >> *binary_action ;	expression = left_expression >> binary_action__iteration ;	{ LA_IS, { "(", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\ "expression", {\ { LA_IS, { "" }, 2, { "left_expression", "binary_action__iteration" }}\ }};\}

						}}}\
	binary_action__iteration = binary_action, binary_action__iteration ε;	binary_action__iteration → binary_action binary_action__iteration binary_action__iteration → ε	binary_action__iteration(1: "AND", "OR", "==", "!=", "<=", ">=", "<", ">", "+", "-", "**", "DIV", "MOD") → binary_action binary_action__iteration binary_action__iteration(1: !"AND", !"OR", !"==", !"!=", !"<=", !">=", !"<", !">", !"+", !"-", !"*", !"DIV", !"MOD") → ε		binary_action__iteration = binary_action >> binary_action__iteration "";	IF_NONUSE_COMPARE_WITH_EQUAL(\ {LA_IS, {T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_0, T_GREATER_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0}}, {"binary_action__iteration"},{\ {LA_IS, {""}}, 2, {"binary_action", "binary_action__iteration"}}\ }}}\
						{LA_NOT, {T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_0, T_GREATER_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0}}, {" "binary_action__iteration"},{\ {LA_IS, {""}}, 0, { "" }}\ }}}\
						\ }\ IF_USE_COMPARE_WITH_EQUAL(\ {LA_IS, {T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_OR_EQUAL_0, T_GREATER_OR_EQUAL_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0}}, { "binary_action__iteration"},{\ {LA_IS, {""}}, 2, {"binary_action", "binary_action__iteration"}}\ }}}\
						{LA_NOT, {T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_OR_EQUAL_0, T_GREATER_OR_EQUAL_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0}}, {"binary_action__iteration"},{\ {LA_IS, {""}}, 0, { "" }}\ }}}\
						\ }\
group_expression = "(" , expression , ")";	group_expression = "(" , expression , ")";	group_expression → "(" expression ")"	group_expression(1: "(") → "(" expression ")"	group_expression = tokenGROUPEXPRESSIONBEGIN >> expression >> tokenGROUPEXPRESSIONEND;	group_expression = tokenGROUPEXPRESSIONBEGIN >> expression >> tokenGROUPEXPRESSIONEND;	{LA_IS, { "(" }, {"group_expression"},{\ {LA_IS, {""}}, 3, { "(" , "expression" , ")" }}\ }}}\
expression_or_bind_left_to_right = expression , bind_to_right__optional;	expression_or_bind_left_to_right = expression , bind_to_right__optional;	expression_or_bind_left_to_right → expression bind_to_right__optional	expression_or_bind_left_to_right(1: "(", "NOT", "+", "-", "ident_terminal", "unsigned_value_terminal", "IF") → expression bind_to_right__optional		expression_or_bind_left_to_right = expression >> bind_to_right__optional;	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "expression_or_bind_left_to_right"},{\ {LA_IS, {""}}, 2, {"expression", "bind_to_right__optional" }}\ }}}\
expression_or_bind_left_to_right = expression , ["=" , ident , [index_action]];	bind_to_right = "=" , ident , index_action__optional;	bind_to_right → "=" ident index_action__optional		expression_or_bind_left_to_right = expression >> -(tokenLRBIND >> ident >> -index_action);	bind_to_right = tokenLRBIND >> ident >> index_action__optional;	{LA_IS, {T_LRBIND_0 }, {"bind_to_right"},{\ {LA_IS, {""}}, 3, { T_LRBIND_0 , "ident", "index_action__optional" }}\ }}}\
	bind_to_right__optional = bind_to_right ε;	bind_to_right__optional → bind_to_right bind_to_right__optional → ε;			bind_to_right__optional = bind_to_right "";	{ LA_IS, {T_LRBIND_0 }, {"bind_to_right__optional"},{\ { LA_IS, {""}}, 1, { "bind_to_right" }}\ }}}\
						{ LA_NOT, {T_LRBIND_0 }, {"bind_to_right__optional"},{\ { LA_IS, {""}}, 0, { "" }}\ }}}\
if_expression = expression;	if_expression = expression;	if_expression → expression		if_expression = SAME_RULE(expression);	if_expression = SAME_RULE(expression);	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "if_expression"},{\ {LA_IS, {""}}, 1, { "expression" }}\ }}}\
body_for_true = block_statements_in_while_and_if_body;	body_for_true = block_statements_in_while_and_if_body;	body_for_true → block_statements_in_while_and_if_body		body_for_true = SAME_RULE(block_statements_in_while_and_if_body);	body_for_true = SAME_RULE(block_statements_in_while_and_if_body);	{LA_IS, {T_BEGIN_BLOCK_0 }, {"body_for_true"},{\ {LA_IS, {""}}, 1, { "block_statements_in_while_and_if_body" }}\ }}}\
false_cond_block_without_else = "ELSE" , "IF" , if_expression , body_for_true;	false_cond_block_without_else = "ELSE" , "IF" , if_expression , body_for_true;	false_cond_block_without_else → "ELSE" "IF" if_expression body_for_true		false_cond_block_without_else = tokenELSE >> tokenIF >> if_expression >> body_for_true;	false_cond_block_without_else = tokenELSE >> tokenIF >> if_expression >> body_for_true;	{LA_IS, {T_ELSE_IF_0 }, { "false_cond_block_without_else"},{\ {LA_IS, {""}}, 4, { T_ELSE_IF_0 , T_ELSE_IF_1, "if_expression", "body_for_true" }}\ }}}\
body_for_false = "ELSE" , block_statements_in_while_and_if_body;	body_for_false = "ELSE" , block_statements_in_while_and_if_body;	body_for_false → "ELSE" block_statements_in_while_and_if_body		body_for_false = tokenELSE >> block_statements_in_while_and_if_body;	body_for_false = tokenELSE >> block_statements_in_while_and_if_body;	{LA_IS, {T_ELSE_BLOCK_0 }, {"body_for_false"},{\ {LA_IS, {""}}, 2, { T_ELSE_BLOCK_0 , "block_statements" }}\ }}}\
cond_block = "IF" , if_expression , body_for_true , { false_cond_block_without_else } , [body_for_false];	cond_block = "IF" , if_expression , body_for_true , false_cond_block_without_else__iteration , body_for_false__optional;	cond_block → "IF" if_expression body_for_true false_cond_block_without_else__iteration body_for_false__optional		cond_block = tokenIF >> if_expression >> body_for_true >> *false_cond_block_without_else >> -body_for_false;	cond_block = tokenIF >> if_expression >> body_for_true >> false_cond_block_without_else__iteration >> body_for_false__optional;	{LA_IS, {T_IF_0 }, {"cond_block"},{\ {LA_IS, {""}}, 5, { T_IF_0 , "if_expression", "body_for_true", "false_cond_block_without_else__iteration", "body_for_false__optional" }}\ }}}\
	false_cond_block_without_else__iteration = false_cond_block_without_else , false_cond_block_without_else__iteration ε;	false_cond_block_without_else__iteration → false_cond_block_without_else false_cond_block_without_else__iteration false_cond_block_without_else__iteration → ε				{LA_IS, {T_ELSE_IF_0 }, { "false_cond_block_without_else__iteration"},{\ {LA_IS, {T_ELSE_IF_1}, 2, { "false_cond_block_without_else", "false_cond_block_without_else__iteration" }}\
						{LA_NOT, {T_ELSE_IF_1 }, 0, { "" }}\ }}}\
						{LA_NOT, {T_ELSE_IF_0 }, { "false_cond_block_without_else__iteration"},{\ {LA_IS, {""}}, 0, { "" }}\ }}}\
	body_for_false__optional = body_for_false ε;	body_for_false__optional → body_for_false body_for_false__optional → ε				{LA_IS, {T_ELSE_BLOCK_0 }, {"body_for_false__optional"},{\ {LA_IS, {""}}, 1, { "body_for_false" }}\ }}}\
cond_block__with_optional_bind = cond_block, [tokenLRBIND , ident , [index_action]];	cond_block__with_optional_bind = cond_block, bind_to_right__optional;	cond_block__with_optional_bind → cond_block bind_to_right__optional		cond_block__with_optional_bind = cond_block >> -(tokenLRBIND >> ident >> - index_action);	cond_block__with_optional_bind = cond_block >> bind_to_right__optional;	{LA_IS, {T_IF_0 }, {"cond_block__with_optional_bind"},{\ {LA_IS, {""}}, 2, { "cond_block", "bind_to_right__optional" }}\ }}}\
cycle_begin_expression = expression;	cycle_begin_expression = expression;	cycle_begin_expression → expression		cycle_begin_expression = SAME_RULE(expression);	cycle_begin_expression = SAME_RULE(expression);	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "cycle_begin_expression"},{\ {LA_IS, {""}}, 1, { "expression" }}\ }}}\
						\ }\
cycle_end_expression = expression;	cycle_end_expression = expression;	cycle_end_expression → expression		cycle_end_expression = SAME_RULE(expression);	cycle_end_expression = SAME_RULE(expression);	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "cycle_end_expression"},{\ {LA_IS, {""}}, 1, { "expression" }}\ }}}\
cycle_counter = ident;	cycle_counter = ident;	cycle_counter → ident		cycle_counter = SAME_RULE(ident);	cycle_counter = SAME_RULE(ident);	{LA_IS, { "ident_terminal" }, {"cycle_counter"},{\ {LA_IS, {""}}, 1, { "ident" }}\ }}}\

cycle_counter_lr_init = cycle_begin_expression , "=" , cycle_counter;	cycle_counter_lr_init = cycle_begin_expression , "=" , cycle_counter;	cycle_counter_lr_init → cycle_begin_expression "=" cycle_counter		cycle_counter_lr_init = cycle_begin_expression >> tokenLRBIND >> cycle_counter;	cycle_counter_lr_init = cycle_begin_expression >> tokenLRBIND >> cycle_counter;	{LA_IS, {"(", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "cycle_counter_lr_init", {\ LA_IS, (""), 3, { "cycle_begin_expression", T_LRBIND_0, "cycle_counter" }}}\ \}}
cycle_counter_init = cycle_counter_lr_init;	cycle_counter_init = cycle_counter_lr_init;	cycle_counter_init → cycle_counter_lr_init		cycle_counter_init = SAME_RULE(cycle_counter_lr_init);	cycle_counter_init = SAME_RULE(cycle_counter_lr_init);	{LA_IS, {"(", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "cycle_counter_init", {\ LA_IS, ("") , 1, { "cycle_counter_lr_init" }}}\ \}}
cycle_counter_last_value = cycle_end_expression;	cycle_counter_last_value = cycle_end_expression;	cycle_counter_last_value → cycle_end_expression		cycle_counter_last_value = SAME_RULE(cycle_end_expression);	cycle_counter_last_value = SAME_RULE(cycle_end_expression);	{LA_IS, {"(", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "cycle_counter_last_value", {\ LA_IS, ("") , 1, { "cycle_end_expression" }}}\ \}}
cycle_body = "DO" , {(statement} block_statements);	cycle_body = "DO" , statements__or__block_statements;	cycle_body → "DO" statements__or__block_statements;		cycle_body = tokenDO >> statements__or__block_statements;	cycle_body = tokenDO >> statements__or__block_statements;	{LA_IS, {T_DO_0 }, { "cycle_body", {\ LA_IS, ("") , 2, { T_DO_0, "statements__or__block_statements" }}}\ \}}
	forto_direction = "TO" "DOWNT0";	forto_direction → "TO" forto_direction → "DOWNT0"		forto_direction = tokenDO tokenDOWNT0;	forto_direction = tokenDO tokenDOWNT0;	{LA_IS, {T_TO_0 }, { "forto_direction", {\ LA_IS, ("") , 1, { T_TO_0 }}\ \}}
forto_cycle = "FOR" , cycle_counter_init , forto_direction, cycle_counter_last_value , cycle_body;	forto_cycle = "FOR" , cycle_counter_init , forto_direction, cycle_counter_last_value , cycle_body;	forto_cycle → "FOR" cycle_counter_init forto_direction, cycle_counter_last_value cycle_body		forto_cycle = tokenFOR >> cycle_counter_init >> forto_direction >> cycle_counter_last_value >> cycle_body;	forto_cycle = tokenFOR >> cycle_counter_init >> forto_direction >> cycle_counter_last_value >> cycle_body;	{LA_IS, {T_FOR_0 }, { "forto_cycle", {\ LA_IS, ("") , 5, { T_FOR_0, "cycle_counter_init", "forto_direction", "cycle_counter_last_value", "cycle_body" }}}\ \}}
	continue_while = "CONTINUE";	continue_while → "CONTINUE"		continue_while = SAME_RULE(tokenCONTINUE);	continue_while = SAME_RULE(tokenCONTINUE);	{LA_IS, {T_CONTINUE_WHILE_0 }, { "continue_while", {\ LA_IS, ("") , 1, { T_CONTINUE_WHILE_0 }}\ \}}
	break_while = "BREAK";	break_while → "BREAK"		break_while = SAME_RULE(tokenBREAK);	break_while = SAME_RULE(tokenBREAK);	{LA_IS, {T_EXIT_WHILE_0 }, { "break_while", {\ LA_IS, ("") , 1, { T_EXIT_WHILE_0 }}\ \}}
statement_in_while_and_if_body = statement "CONTINUE" "BREAK";	statement_in_while_and_if_body = statement continue_while break_while;	statement_in_while_and_if_body → statement statement_in_while_and_if_body → continue_while statement_in_while_and_if_body(1: "BREAK") → break_while	statement_in_while_and_if_body(1: "ident_terminal", "(", "NOT", "unsigned_value_terminal", "+", "-", "IF", "FOR", "WHILE", "REPEAT", "GOTO", "GET", "PUT", ";",") → statement statement_in_while_and_if_body(1: "CONTINUE") → continue_while statement_in_while_and_if_body(1: "BREAK") → break_while	statement_in_while_and_if_body = statement continue_while break_while;	statement_in_while_and_if_body = statement continue_while break_while;	{LA_IS, { "ident_terminal", "(", T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0, T_FOR_0, T_WHILE_0, T_REPEAT_0, T_GOTO_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0 }, { "statement_in_while_and_if_body", {\ LA_IS, ("") , 1, { "statement" }}}\ \}
block_statements_in_while_and_if_body = "(" , {statement_in_while_and_if_body} , ")";	block_statements_in_while_and_if_body = "(" , {statement_in_while_and_if_body__iteration , ")";	block_statements_in_while_and_if_body → "(" statement_in_while_and_if_body__iteration ")"		block_statements_in_while_and_if_body = tokenBEGINBLOCK >> *statement_in_while_and_if_body >> tokenENDBLOCK;	block_statements_in_while_and_if_body = tokenBEGINBLOCK >> statement_in_while_and_if_body__iteration >> tokenENDBLOCK;	{LA_IS, {T_BEGIN_BLOCK_0 }, { "block_statements_in_while_and_if_body", {\ LA_IS, ("") , 3, { T_BEGIN_BLOCK_0, "statement_in_while_and_if_body__iteration", T_END_BLOCK_0 }}\ \}}
	statement_in_while_and_if_body__iteration = statement_in_while_and_if_body , statement_in_while_and_if_body__iteration ε;	statement_in_while_and_if_body__iteration → statement_in_while_and_if_body statement_in_while_and_if_body__iteration → ε			statement_in_while_and_if_body__iteration = statement_in_while_and_if_body >> statement_in_while_and_if_body__iteration "";	{LA_IS, { "ident_terminal", "(", T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0, T_FOR_0, T_WHILE_0, T_REPEAT_0, T_GOTO_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0, T_CONTINUE_WHILE_0, T_EXIT_WHILE_0 }, { "statement_in_while_and_if_body__iteration", {\ LA_IS, ("") , 2, { "statement_in_while_and_if_body", "statement_in_while_and_if_body__iteration" }}}\ \}
while_cycle_head_expression = expression;	while_cycle_head_expression = expression;			while_cycle_head_expression = SAME_RULE(expression);	while_cycle_head_expression = SAME_RULE(expression);	{LA_NOT, { "ident_terminal", "(", T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0, T_FOR_0, T_WHILE_0, T_REPEAT_0, T_GOTO_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0, T_CONTINUE_WHILE_0, T_EXIT_WHILE_0 }, { "statement_in_while_and_if_body__iteration", {\ LA_IS, ("") , 0, { "" }}}\ \}}
while_cycle = "WHILE" , while_cycle_head_expression , block_statements_in_while_and_if_body;	while_cycle = "WHILE" , while_cycle_head_expression , block_statements_in_while_and_if_body;			while_cycle = tokenWHILE >> while_cycle_head_expression >> block_statements_in_while_and_if_body;	while_cycle = tokenWHILE >> while_cycle_head_expression >> block_statements_in_while_and_if_body;	{LA_IS, {T_WHILE_0 }, { "while_cycle", {\ LA_IS, ("") , 3, { T_WHILE_0, "while_cycle_head_expression", "block_statements_in_while_and_if_body" }}}\ \}}
repeat_until_cycle_cond = expression;	repeat_until_cycle_cond = expression;			repeat_until_cycle_cond = SAME_RULE(expression);	repeat_until_cycle_cond = SAME_RULE(expression);	{LA_IS, {"(", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "repeat_until_cycle_cond", {\ LA_IS, ("") , 1, { "expression" }}}\ \}}
repeat_until_cycle = "REPEAT" , {(statement} block_statements) , "UNTIL" , repeat_until_cycle_cond;	repeat_until_cycle = "REPEAT" , statements__or__block_statements, "UNTIL" , repeat_until_cycle_cond;			repeat_until_cycle = tokenREPEAT >> (*statement block_statements) >> tokenUNTIL >> repeat_until_cycle_cond;	repeat_until_cycle = tokenREPEAT >> statements__or__block_statements >> tokenUNTIL >> repeat_until_cycle_cond;	{LA_IS, {T_REPEAT_0 }, { "repeat_until_cycle", {\ LA_IS, ("") , 4, { T_REPEAT_0, "statements__or__block_statements", T_UNTIL_0, "repeat_until_cycle_cond" }}}\ \}}
	statements__or__block_statements = statement__iteration block_statements;				statements__or__block_statements = statement__iteration block_statements;	{LA_IS, { "ident_terminal", "(", T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0, T_FOR_0, T_WHILE_0, T_REPEAT_0, T_GOTO_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0 }, { "statements__or__block_statements", {\ LA_IS, ("") , 1, { "statement__iteration" }}}\ \}
input_rule = "GET" , (ident , [index_action] "(" , ident , [index_action] , ")");	input_rule = "GET" , argument_for_input;			input_rule = tokenGET >> (ident >> -index_action tokenGROUPEXPRESSIONBEGIN >> ident	input_rule = tokenGET >> argument_for_input;	{LA_IS, {T_INPUT_0 }, { "input_rule", {\

				>> -index_action >> tokenGROUPEXPRESSIONEND);		{LA_IS, ("", 2, { T_INPUT_0, "argument_for_input" })\ }}\ }
	argument_for_input = ident , index_action__optional; argument_for_input = "(" , "ident", "index_action__optional", ")";	argument_for_input → ident index_action__optional argument_for_input → "(" "ident" "index_action__optional" ")"	argument_for_input → ident index_action__optional argument_for_input → "(" "ident" "index_action__optional" ")"		argument_for_input = ident >> index_action__optional tokenGROUPEXPRESSIONBEGIN >> ident >> index_action__optional >> tokenGROUPEXPRESSIONEND;	{LA_IS, { "ident_terminal" }, { "argument_for_input", \ { LA_IS, ("", 2, { "ident", "index_action__optional" }) \ }}\ {LA_IS, { "(" }, { "argument_for_input", \ { LA_IS, ("", 4, { "(", "ident", "index_action__optional", ")" \ }}\ }}\ }
output = "PUT" , expression;	output = "PUT", expression;	output → "PUT" expression	output → "PUT" expression	output = tokenPUT >> expression;	output = tokenPUT >> expression;	{LA_IS, { T_OUTPUT_0 }, { "output_rule", \ { LA_IS, ("", 2, { T_OUTPUT_0, "expression" }) \ }}\ }
statement = expression_or_bind_left_to_right cond_block__with_optional_bind forto_cycle while_cycle repeat_until_cycle labeled_point goto_label input_rule output_rule ";";	statement = expression_or_bind_left_to_right cond_block__with_optional_bind forto_cycle while_cycle repeat_until_cycle labeled_point goto_label input_rule output_rule ";";	statement → expression_or_bind_left_to_right statement → cond_block__with_optional_bind statement → forto_cycle statement → while_cycle statement → repeat_until_cycle statement → labeled_point statement → goto_label statement → input_rule output_rule ";", statement → output_rule ";", statement → ";",	statement → expression_or_bind_left_to_right statement → cond_block__with_optional_bind statement → forto_cycle statement → while_cycle statement → repeat_until_cycle statement → labeled_point statement → goto_label statement → input_rule output_rule ";", statement → output_rule ";", statement → ";",	statement = expression_or_bind_left_to_right cond_block__with_optional_bind forto_cycle while_cycle repeat_until_cycle labeled_point goto_label input_rule output_rule tokenSEMICOLON;	statement = expression_or_bind_left_to_right cond_block__with_optional_bind forto_cycle while_cycle repeat_until_cycle labeled_point goto_label input_rule output_rule tokenSEMICOLON;	{LA_IS, { "ident_terminal" }, { "statement", \ { LA_IS, { T_COLON_0 }, 1, { "labeled_point" } } \ { LA_NOT, { T_COLON_0 }, 1, \ ("expression_or_bind_left_to_right") \ }}\ {LA_IS, { "(", T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0 }, { "statement", \ { LA_IS, ("", 1, ("expression_or_bind_left_to_right") \ }}\ {LA_IS, { T_IF_0 }, { "statement", \ { LA_IS, ("", 1, ("cond_block__with_optional_bind") \ }}\ {LA_IS, { T_FOR_0 }, { "statement", \ { LA_IS, ("", 1, ("forto_cycle") \ }}\ {LA_IS, { T_WHILE_0 }, { "statement", \ { LA_IS, ("", 1, ("while_cycle") \ }}\ {LA_IS, { T_REPEAT_0 }, { "statement", \ { LA_IS, ("", 1, ("repeat_until_cycle") \ }}\ {LA_IS, { T_GOTO_0 }, { "statement", \ { LA_IS, ("", 1, ("goto_label") \ }}\ {LA_IS, { T_INPUT_0 }, { "statement", \ { LA_IS, ("", 1, ("input_rule") \ }}\ {LA_IS, { T_OUTPUT_0 }, { "statement", \ { LA_IS, ("", 1, ("output_rule") \ }}\ {LA_IS, { T_SEMICOLON_0 }, { "statement", \ { LA_IS, ("", 1, (";") \ }}\ }
	statement__iteration = statement, statement__iteration ε;	statement__iteration → statement statement__iteration statement__iteration → ε	statement__iteration() → statement statement__iteration statement__iteration() → ε		statement__iteration = statement >> statement__iteration "";	{LA_IS, { "ident_terminal", "(" , T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0, T_FOR_0, T_WHILE_0, T_REPEAT_0, T_GOTO_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0 }, { "statement__iteration", \ { LA_IS, ("", 2, { "statement", "statement__iteration" } \ }}\ { LA_NOT, { "ident_terminal", "(" , T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0, T_FOR_0, T_WHILE_0, T_REPEAT_0, T_GOTO_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0 }, { "statement__iteration", \ { LA_IS, ("", 0, { "" } } \ }}\ }
block_statements = "{", {statement} , "}";	block_statements = "(" , statement__iteration , ")";	block_statements → "(" statement__iteration ")"	block_statements(1: "(") → "(" statement__iteration ")"	block_statements = tokenBEGINBLOCK >> *statement >> tokenENDBLOCK;	block_statements = tokenBEGINBLOCK >> statement__iteration >> tokenENDBLOCK;	{LA_IS, { T_BEGIN_BLOCK_0 }, { "block_statements", \ { LA_IS, ("", 3, { T_BEGIN_BLOCK_0, "statement__iteration", T_END_BLOCK_0 } \ }}\ }
	expression__optional = expression "";	expression__optional → expression expression__optional → ε	expression__optional(1: "(" , "NOT", "+", "-", "ident_terminal", "unsigned_value_terminal", "IF") → expression expression__optional(1: ! "(" , ! "NOT", ! "+", ! "-", ! "ident_terminal", ! "unsigned_value_terminal", ! "IF") → ε		expression__optional = expression "";	{LA_IS, { "(", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "expression__optional", \ { LA_IS, ("", 1, { "expression" } } \ }}\ {LA_NOT, { "(", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "expression__optional", \ { LA_IS, ("", 0, { "" } } \ }}\ }
program_rule = "NAME" , program_name , ";", "BODY", "DATA", declaration__optional , ";", statement__iteration , "END";	program_rule = "NAME", program_name , ";", "BODY", "DATA", declaration__optional , ";", statement__iteration , "END";	program_rule → "NAME" program_name ";", "BODY" "DATA" declaration__optional ";", statement__iteration "END"	program_rule(1: "NAME") → "NAME" program_name ";", "BODY" "DATA" declaration__optional ";", statement__iteration "END"	program_rule = BOUNDARIES >> tokenNAME >> program_name >> tokenSEMICOLON >> tokenBODY >> tokenDATA >> (-declaration) >> tokenSEMICOLON >> *statement >> tokenEND;	program_rule = BOUNDARIES >> tokenNAME >> program_name >> tokenSEMICOLON >> tokenBODY >> tokenDATA >> tokenSEMICOLON >> tokenEND;	{LA_IS, { T_NAME_0 }, { "program_rule", \ { LA_IS, ("", 9, { T_NAME_0, "program_name", T_SEMICOLON_0, T_BODY_0, T_DATA_0, "declaration__optional", T_SEMICOLON_0, "statement__iteration", T_END_0 } \ }}\ }
	declaration__optional = declaration "";	declaration__optional → declaration declaration__optional → ε	declaration__optional(1: !"INTEGER16") → declaration declaration__optional(1: !"INTEGER16") → ε		declaration__optional = declaration "";	{LA_IS, { T_DATA_TYPE_0 }, { "declaration__optional", \ { LA_IS, ("", 1, { "declaration" } } \ }}\ { LA_NOT, { T_DATA_TYPE_0 }, { "declaration__optional", \ { LA_IS, ("", 0, { "" } } \ }}\ }
digit = "0" non_zero_digit;	digit = "0" non_zero_digit;	digit → "0" digit → non_zero_digit	digit(1: "0") → "0" digit(1: "1", "2", "3", "4", "5", "6", "7", "8", "9") → non_zero_digit	digit_0 = '0'; digit = digit_0 non_zero_digit;	digit_0 = '0'; digit = digit_0 non_zero_digit;	\
non_zero_digit = "1" "2" "3" "4" "5" "6" "7" "8" "9";	non_zero_digit = "1" "2" "3" "4" "5" "6" "7" "8" "9";	non_zero_digit → "1" non_zero_digit → "2" non_zero_digit → "3" non_zero_digit → "4" non_zero_digit → "5" non_zero_digit → "6" non_zero_digit → "7" non_zero_digit → "8" non_zero_digit → "9"	non_zero_digit(1: "1") → "1" non_zero_digit(1: "2") → "2" non_zero_digit(1: "3") → "3" non_zero_digit(1: "4") → "4" non_zero_digit(1: "5") → "5" non_zero_digit(1: "6") → "6" non_zero_digit(1: "7") → "7" non_zero_digit(1: "8") → "8" non_zero_digit(1: "9") → "9"	digit_1 = '1'; digit_2 = '2'; digit_3 = '3'; digit_4 = '4'; digit_5 = '5'; digit_6 = '6'; digit_7 = '7'; digit_8 = '8'; digit_9 = '9'; non_zero_digit = digit_1 digit_2 digit_3 digit_4 digit_5 digit_6 digit_7 digit_8 digit_9;	digit_1 = '1'; digit_2 = '2'; digit_3 = '3'; digit_4 = '4'; digit_5 = '5'; digit_6 = '6'; digit_7 = '7'; digit_8 = '8'; digit_9 = '9'; non_zero_digit = digit_1 digit_2 digit_3 digit_4 digit_5 digit_6 digit_7 digit_8 digit_9;	\
						{LA_IS, { "unsigned_value_terminal" }, { "unsigned_value", \ { LA_IS, ("", 1, { "unsigned_value_terminal" } } \ }}\ }
unsigned_value = non_zero_digit , {digit} "0";	unsigned_value = non_zero_digit , digit__iteration "0";	unsigned_value → non_zero_digit digit__iteration unsigned_value → "0"	unsigned_value(1: "1", "2", "3", "4", "5", "6", "7", "8", "9") → non_zero_digit digit__iteration unsigned_value(1: "0") → "0"	unsigned_value = (non_zero_digit >> *digit digit_0) >> BOUNDARIES;	unsigned_value = (non_zero_digit >> digit__iteration digit_0) >> BOUNDARIES;	\

	digit__iteration = digit, digit__iteration ε;	digit__iteration → digit digit__iteration digit__iteration → ε	digit__iteration(1: "0", "1", "2", "3", "4", "5", "6", "7", "8", "9") → digit digit__iteration digit__iteration(1: l'0", l'1", l'2", l'3", l'4", l'5", l'6", l'7", l'8", l'9") → ε		digit__iteration = digit, digit__iteration "";	\\
value = [sign] , unsigned_value;	value = sign__optional, unsigned_value;	value → sign__optional unsigned_value	value → sign__optional unsigned_value	value = -sign >> unsigned_value >> BOUNDARIES;	value = sign__optional >> unsigned_value >> BOUNDARIES;	{LA_IS, { "unsigned_value_terminal", T_ADD_0, T_SUB_0 }, { "value", {\n {LA_IS, { "" } , 2, { "sign__optional", "unsigned_value" }}\n }}}\n
	sign__optional = sign ε;	sign__optional → sign sign__optional → ε	sign__optional(1: "+" , "-") → sign sign__optional(1: l'+" , l'-") → ε		sign__optional = sign "";	{LA_IS, { T_ADD_0, T_SUB_0 }, { "sign__optional", {\n {LA_IS, { "" } , 1, { "sign" }}\n }}}\n {LA_NOT, { T_ADD_0, T_SUB_0 }, { "sign__optional", {\n {LA_IS, { "" } , 0, { "" }}\n }}}\n
letter_in_lower_case = "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z";	letter_in_lower_case → "a" letter_in_lower_case → "b" letter_in_lower_case → "c" letter_in_lower_case → "d" letter_in_lower_case → "e" letter_in_lower_case → "f" letter_in_lower_case → "g" letter_in_lower_case → "h" letter_in_lower_case → "i" letter_in_lower_case → "j" letter_in_lower_case → "k" letter_in_lower_case → "l" letter_in_lower_case → "m" letter_in_lower_case → "n" letter_in_lower_case → "o" letter_in_lower_case → "p" letter_in_lower_case → "q" letter_in_lower_case → "r" letter_in_lower_case → "s" letter_in_lower_case → "t" letter_in_lower_case → "u" letter_in_lower_case → "v" letter_in_lower_case → "w" letter_in_lower_case → "x" letter_in_lower_case → "y" letter_in_lower_case → "z"	letter_in_lower_case(1: "a") → "a" letter_in_lower_case(1: "b") → "b" letter_in_lower_case(1: "c") → "c" letter_in_lower_case(1: "d") → "d" letter_in_lower_case(1: "e") → "e" letter_in_lower_case(1: "f") → "f" letter_in_lower_case(1: "g") → "g" letter_in_lower_case(1: "h") → "h" letter_in_lower_case(1: "i") → "i" letter_in_lower_case(1: "j") → "j" letter_in_lower_case(1: "k") → "k" letter_in_lower_case(1: "l") → "l" letter_in_lower_case(1: "m") → "m" letter_in_lower_case(1: "n") → "n" letter_in_lower_case(1: "o") → "o" letter_in_lower_case(1: "p") → "p" letter_in_lower_case(1: "q") → "q" letter_in_lower_case(1: "r") → "r" letter_in_lower_case(1: "s") → "s" letter_in_lower_case(1: "t") → "t" letter_in_lower_case(1: "u") → "u" letter_in_lower_case(1: "v") → "v" letter_in_lower_case(1: "w") → "w" letter_in_lower_case(1: "x") → "x" letter_in_lower_case(1: "y") → "y" letter_in_lower_case(1: "z") → "z"	A = "A"; B = "B"; C = "C"; D = "D"; E = "E"; F = "F"; G = "G"; H = "H"; I = "I"; J = "J"; K = "K"; L = "L"; M = "M"; N = "N"; O = "O"; P = "P"; Q = "Q"; R = "R"; S = "S"; T = "T"; U = "U"; V = "V"; W = "W"; X = "X"; Y = "Y"; Z = "Z"; letter_in_lower_case = a b c d e f g h i j k l m n o p q r s t u v w x y z;	A = "A"; B = "B"; C = "C"; D = "D"; E = "E"; F = "F"; G = "G"; H = "H"; I = "I"; J = "J"; K = "K"; L = "L"; M = "M"; N = "N"; O = "O"; P = "P"; Q = "Q"; R = "R"; S = "S"; T = "T"; U = "U"; V = "V"; W = "W"; X = "X"; Y = "Y"; Z = "Z"; letter_in_lower_case = a b c d e f g h i j k l m n o p q r s t u v w x y z;	\\	
letter_in_upper_case = "A" "B" "C" "D" "E" "F" "G" "H" "I" "J" "K" "L" "M" "N" "O" "P" "Q" "R" "S" "T" "U" "V" "W" "X" "Y" "Z";	letter_in_upper_case → "A" letter_in_upper_case → "B" letter_in_upper_case → "C" letter_in_upper_case → "D" letter_in_upper_case → "E" letter_in_upper_case → "F" letter_in_upper_case → "G" letter_in_upper_case → "H" letter_in_upper_case → "I" letter_in_upper_case → "J" letter_in_upper_case → "K" letter_in_upper_case → "L" letter_in_upper_case → "M" letter_in_upper_case → "N" letter_in_upper_case → "O" letter_in_upper_case → "P" letter_in_upper_case → "Q" letter_in_upper_case → "R" letter_in_upper_case → "S" letter_in_upper_case → "T" letter_in_upper_case → "U" letter_in_upper_case → "V" letter_in_upper_case → "W" letter_in_upper_case → "X" letter_in_upper_case → "Y" letter_in_upper_case → "Z"	letter_in_upper_case(1: "A") → "A" letter_in_upper_case(1: "B") → "B" letter_in_upper_case(1: "C") → "C" letter_in_upper_case(1: "D") → "D" letter_in_upper_case(1: "E") → "E" letter_in_upper_case(1: "F") → "F" letter_in_upper_case(1: "G") → "G" letter_in_upper_case(1: "H") → "H" letter_in_upper_case(1: "I") → "I" letter_in_upper_case(1: "J") → "J" letter_in_upper_case(1: "K") → "K" letter_in_upper_case(1: "L") → "L" letter_in_upper_case(1: "M") → "M" letter_in_upper_case(1: "N") → "N" letter_in_upper_case(1: "O") → "O" letter_in_upper_case(1: "P") → "P" letter_in_upper_case(1: "Q") → "Q" letter_in_upper_case(1: "R") → "R" letter_in_upper_case(1: "S") → "S" letter_in_upper_case(1: "T") → "T" letter_in_upper_case(1: "U") → "U" letter_in_upper_case(1: "V") → "V" letter_in_upper_case(1: "W") → "W" letter_in_upper_case(1: "X") → "X" letter_in_upper_case(1: "Y") → "Y" letter_in_upper_case(1: "Z") → "Z"	a = "a"; b = "b"; c = "c"; d = "d"; e = "e"; f = "f"; g = "g"; h = "h"; i = "i"; j = "j"; k = "k"; l = "l"; m = "m"; n = "n"; o = "o"; p = "p"; q = "q"; r = "r"; s = "s"; t = "t"; u = "u"; v = "v"; w = "w"; x = "x"; y = "y"; z = "z"; letter_in_upper_case = A B C D E F G H I J K L M N O P Q R S T U V W X Y Z;	a = "a"; b = "b"; c = "c"; d = "d"; e = "e"; f = "f"; g = "g"; h = "h"; i = "i"; j = "j"; k = "k"; l = "l"; m = "m"; n = "n"; o = "o"; p = "p"; q = "q"; r = "r"; s = "s"; t = "t"; u = "u"; v = "v"; w = "w"; x = "x"; y = "y"; z = "z"; letter_in_upper_case = A B C D E F G H I J K L M N O P Q R S T U V W X Y Z;	\\	
ident = "_", letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case;	ident = "_", letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case;	ident → "_", letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case	Ident(1: "_") → "_" letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case	tokenUNDERSCORE = "_"; ident = tokenUNDERSCORE >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> STRICT_BOUNDARIES;	ident = tokenUNDERSCORE = "_"; ident = tokenUNDERSCORE >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> STRICT_BOUNDARIES;	{LA_IS, { "ident_terminal" }, { "ident", {\n {LA_IS, { "" } , 1, { "ident_terminal" }}\n }}}\n
sign = sign_plus sign_minus;	sign = sign_plus sign_minus;	sign → sign_plus sign → sign_minus	sign(1: "+") → sign_plus sign(1: "-") → sign_minus	sign = sign_plus sign_minus;	sign = sign_plus sign_minus;	{LA_IS, { T_ADD_0 }, { "sign", {\n {LA_IS, { "" } , 1, { "sign_plus" }}\n }}}\n {LA_IS, { T_SUB_0 }, { "sign", {\n {LA_IS, { "" } , 1, { "sign_minus" } } }\n }}}\n
sign_plus = "+";	sign_plus = "+";	sign_plus → "+"	sign_plus → "+"	sign_plus = SAME_RULE(tokenPLUS);	sign_plus = SAME_RULE(tokenPLUS);	{LA_IS, { T_ADD_0 }, { "sign_plus", {\n {LA_IS, { "" } , 1, { T_ADD_0 }}\n }}}\n
sign_minus = "-";	sign_minus = "-";	sign_minus → "-"	sign_minus → "-"	sign_minus = SAME_RULE(tokenMINUS);	sign_minus = SAME_RULE(tokenMINUS);	{LA_IS, { T_SUB_0 }, { "sign_minus", {\n {LA_IS, { "" } , 1, { T_SUB_0 }}\n }}}\n
				STRICT_BOUNDARIES = (BOUNDARY >> *(BOUNDARY)) (!(qi::alpha qi::char_("_")));	STRICT_BOUNDARIES = (BOUNDARY >> *(BOUNDARY)) (!(qi::alpha qi::char_("_")));	\\
				BOUNDARIES = (BOUNDARY >> *(BOUNDARY) NO_BOUNDARY);	BOUNDARIES = (BOUNDARY >> *(BOUNDARY) NO_BOUNDARY);	\\
				BOUNDARY = BOUNDARY_SPACE BOUNDARY_TAB BOUNDARY_CARRIAGE_RETURN BOUNDARY_LINE_FEED BOUNDARY_NULL;	BOUNDARY = BOUNDARY_SPACE BOUNDARY_TAB BOUNDARY_CARRIAGE_RETURN BOUNDARY_LINE_FEED BOUNDARY_NULL;	\\
				BOUNDARY_SPACE = " ";	BOUNDARY_SPACE = " ";	\\
				BOUNDARY_TAB = "\t";	BOUNDARY_TAB = "\t";	\\
				BOUNDARY_CARRIAGE_RETURN = "\r";	BOUNDARY_CARRIAGE_RETURN = "\r";	\\
				BOUNDARY_LINE_FEED = "\n";	BOUNDARY_LINE_FEED = "\n";	\\
				BOUNDARY_NULL = "\0";	BOUNDARY_NULL = "\0";	\\
				NO_BOUNDARY = "";	NO_BOUNDARY = "";	\\

						<pre> \ \ { LA_IS, { T_NAME_0 }, { "program____part1", {\ { LA_IS, {"", 7, { T_NAME_0, "program_name", T_SEMICOLON_0, T_BODY_0, T_DATA_0, "declaration_optional", T_SEMICOLON_0 }}\ }}}\ \ }\ "program_rule" </pre>
--	--	--	--	--	--	---