

РБНФ №1 (опис синтаксису мови всіма допустимими засобами РБНФ)	РБНФ №2 (опис формальна граматика мови)	Опис формальної граматики мови	Опис граматики з специфікацією lookahead для LL2-аналізатора	/* Код для перевірки РБНФ №1 */	/* Код для перевірки РБНФ №2 */	/* Дані для LL2-аналізатора (лексми вже опрацьовані лексичним аналізатором) УВАГА: при копіюванні зважайте, щоб у кожному рядку після символу «\» не містилось жодних інших символів. */
		G = (N, T, P, S)	G = (N, T, P, S)			
		S → program_rule	S → program_rule			
		N = { labeled_point, goto_label, program_name, value_type, array_specify, declaration_element, array_specify__optional, other_declaration_ident, declaration, other_declaration_ident__iteration, index_action, unary_operator, unary_operation, binary_operator, binary_action, left_expression, group_expression, index_action__optional, expression, binary_action__iteration, expression_or_cond_block__with_optional_assign, assign_to_right, assign_to_right__optional, if_expression, body_for_true, false_cond_block_without_else, body_for_false, cond_block, false_cond_block_without_else__iteration, body_for_false__optional, cycle_begin_expression, cycle_end_expression, cycle_counter, cycle_counter_lr_init, cycle_counter_init, cycle_counter_last_value, cycle_body, forto_direction, forto_cycle, continue_while, break_while, statement_in_while_and_if_body, statement, block_statements_in_while_and_if_body, statement_in_while_and_if_body__iteration, while_cycle_head_expression, while_cycle, repeat_until_cycle_cond, repeat_until_cycle, statements__or__block_statements, block_statements, input_rule, argument_for_input, output_rule, statement__iteration, expression__optional, program_rule, declaration__optional, non_zero_digit, digit__iteration, digit, unsigned_value, value, sign__optional, sign, ident, letter_in_upper_case, letter_in_lower_case, sign_plus, sign_minus }	N = { labeled_point, goto_label, program_name, value_type, array_specify, declaration_element, array_specify__optional, other_declaration_ident, declaration, other_declaration_ident__iteration, index_action, unary_operator, unary_operation, binary_operator, binary_action, left_expression, group_expression, index_action__optional, expression, binary_action__iteration, expression_or_cond_block__with_optional_assign, assign_to_right, assign_to_right__optional, if_expression, body_for_true, false_cond_block_without_else, body_for_false, cond_block, false_cond_block_without_else__iteration, body_for_false__optional, cycle_begin_expression, cycle_end_expression, cycle_counter, cycle_counter_lr_init, cycle_counter_init, cycle_counter_last_value, cycle_body, forto_direction, forto_cycle, continue_while, break_while, statement_in_while_and_if_body, statement, block_statements_in_while_and_if_body, statement_in_while_and_if_body__iteration, while_cycle_head_expression, while_cycle, repeat_until_cycle_cond, repeat_until_cycle, statements__or__block_statements, block_statements, input_rule, argument_for_input, output_rule, statement__iteration, expression__optional, program_rule, declaration__optional, non_zero_digit, digit__iteration, digit, unsigned_value, value, sign__optional, sign, ident, letter_in_upper_case, letter_in_lower_case, sign_plus, sign_minus }	#define NONTERMINALS labeled_point, \ goto_label, \ program_name, \ value_type, \ array_specify, \ declaration_element, \ \ other_declaration_ident, \ declaration, \ \ index_action, \ unary_operator, \ unary_operation, \ unary_operator, \ binary_operator, \ binary_action, \ left_expression, \ group_expression, \ \ expression, \ \ expression_or_cond_block__with_optional_assign, \ assign_to_right, \ \ if_expression, \ body_for_true, \ false_cond_block_without_else, \ body_for_false, \ cond_block, \ \ \ cycle_begin_expression, \ cycle_end_expression, \ cycle_counter, \ cycle_counter_lr_init, \ cycle_counter_init, \ cycle_counter_last_value, \ cycle_body, \ forto_direction, \ forto_cycle, \ continue_while, \ break_while, \ statement_in_while_and_if_body, \ statement, \ block_statements_in_while_and_if_body, \ \ while_cycle_head_expression, \ while_cycle, \ repeat_until_cycle_cond, \ repeat_until_cycle, \ statements__or__block_statements, \ block_statements, \ input_rule, \ argument_for_input, \ output_rule, \ \ \ program_rule, \ \ non_zero_digit, \ digit__iteration, \ digit, \ unsigned_value, \ value, \ \ sign, \ ident, \ letter_in_upper_case, \ letter_in_lower_case, \ sign_plus, \ sign_minus	#define NONTERMINALS labeled_point, \ goto_label, \ program_name, \ value_type, \ array_specify, \ declaration_element, \ array_specify__optional, \ other_declaration_ident, \ declaration, \ other_declaration_ident__iteration, \ index_action, \ unary_operator, \ unary_operation, \ binary_operator, \ binary_action, \ left_expression, \ group_expression, \ index_action__optional, \ expression, \ binary_action__iteration, \ expression_or_cond_block__with_optional_assign, \ assign_to_right, \ assign_to_right__optional, \ if_expression, \ body_for_true, \ false_cond_block_without_else, \ body_for_false, \ cond_block, \ false_cond_block_without_else__iteration, \ body_for_false__optional, \ cycle_begin_expression, \ cycle_end_expression, \ cycle_counter, \ cycle_counter_lr_init, \ cycle_counter_init, \ cycle_counter_last_value, \ cycle_body, \ forto_direction, \ forto_cycle, \ continue_while, \ break_while, \ statement_in_while_and_if_body, \ statement, \ block_statements_in_while_and_if_body, \ statement_in_while_and_if_body__iteration, \ while_cycle_head_expression, \ while_cycle, \ repeat_until_cycle_cond, \ repeat_until_cycle, \ statements__or__block_statements, \ block_statements, \ input_rule, \ argument_for_input, \ output_rule, \ statement__iteration, \ expression__optional, \ program_rule, \ declaration__optional, \ non_zero_digit, \ digit__iteration, \ digit, \ unsigned_value, \ value, \ sign__optional, \ sign, \ ident, \ letter_in_upper_case, \ letter_in_lower_case, \ sign_plus, \ sign_minus	
		T = { "." " ," "GOTO", "INTEGER16", " ," "NOT", "AND", "OR", "==" , "!=", 	T = { "." " ," "GOTO", "INTEGER16", " ," "NOT", "AND", "OR", "==" , "!=", 	#define TOKENS \ tokenCOLON, \ tokenGOTO, \ tokenINTEGER16, \ tokenCOMMA, \ tokenNOT, \ tokenAND, \ tokenOR, \ tokenEQUAL, \ tokenNOTEQUAL, \	#define TOKENS \ tokenCOLON, \ tokenGOTO, \ tokenINTEGER16, \ tokenCOMMA, \ tokenNOT, \ tokenAND, \ tokenOR, \ tokenEQUAL, \ tokenNOTEQUAL, \	

				tokenGROUPEXPRESSIONBEGIN = "(" >> BOUNDARIES;	tokenGROUPEXPRESSIONBEGIN = "(" >> BOUNDARIES;	#define T_BEGIN GROUPEXPRESSION_0 "(" #define T_BEGIN GROUPEXPRESSION_1 "" #define T_BEGIN GROUPEXPRESSION_2 "" #define T_BEGIN GROUPEXPRESSION_3 ""
				tokenGROUPEXPRESSIONEND = ")" >> BOUNDARIES;	tokenGROUPEXPRESSIONEND = ")" >> BOUNDARIES;	#define T_END GROUPEXPRESSION_0 ")" #define T_END GROUPEXPRESSION_1 "" #define T_END GROUPEXPRESSION_2 "" #define T_END GROUPEXPRESSION_3 ""
				tokenLEFTSSQUAREBRACKETS = "[" >> BOUNDARIES;	tokenLEFTSSQUAREBRACKETS = "[" >> BOUNDARIES;	#define T_LEFT_SQUAREBRACKETS_0 "[" #define T_LEFT_SQUAREBRACKETS_1 "" #define T_LEFT_SQUAREBRACKETS_2 "" #define T_LEFT_SQUAREBRACKETS_3 ""
				tokenRIGHTSSQUAREBRACKETS = "]" >> BOUNDARIES;	tokenRIGHTSSQUAREBRACKETS = "]" >> BOUNDARIES;	#define T_RIGHT_SQUAREBRACKETS_0 "]" #define T_RIGHT_SQUAREBRACKETS_1 "" #define T_RIGHT_SQUAREBRACKETS_2 "" #define T_RIGHT_SQUAREBRACKETS_3 ""
				tokenBEGINBLOCK = "{" >> BOUNDARIES;	tokenBEGINBLOCK = "{" >> BOUNDARIES;	#define T_BEGIN_BLOCK_0 "{" #define T_BEGIN_BLOCK_1 "" #define T_BEGIN_BLOCK_2 "" #define T_BEGIN_BLOCK_3 ""
				tokenENDBLOCK = "}" >> BOUNDARIES;	tokenENDBLOCK = "}" >> BOUNDARIES;	#define T_END_BLOCK_0 "}" #define T_END_BLOCK_1 "" #define T_END_BLOCK_2 "" #define T_END_BLOCK_3 ""
				tokenSEMICOLON = ";" >> BOUNDARIES;	tokenSEMICOLON = ";" >> BOUNDARIES;	#define T_SEMICOLON_0 ";" #define T_SEMICOLON_1 "" #define T_SEMICOLON_2 "" #define T_SEMICOLON_3 ""
				tokenCOLON = ":" >> BOUNDARIES;	tokenCOLON = ":" >> BOUNDARIES;	#define T_COLON_0 ":" #define T_COLON_1 "" #define T_COLON_2 "" #define T_COLON_3 ""
				tokenGOTO = "GOTO" >> STRICT_BOUNDARIES;	tokenGOTO = "GOTO" >> STRICT_BOUNDARIES;	#define T_GOTO_0 "GOTO" #define T_GOTO_1 "" #define T_GOTO_2 "" #define T_GOTO_3 ""
				tokenINTEGER16 = "INTEGER16" >> STRICT_BOUNDARIES;	tokenINTEGER16 = "INTEGER16" >> STRICT_BOUNDARIES;	#define T_DATA_TYPE_0 "INTEGER16" #define T_DATA_TYPE_1 "" #define T_DATA_TYPE_2 "" #define T_DATA_TYPE_3 ""
				tokenCOMMA = "," >> BOUNDARIES;	tokenCOMMA = "," >> BOUNDARIES;	#define T_COMA_0 "," #define T_COMA_1 "" #define T_COMA_2 "" #define T_COMA_3 ""
						#define T_BITWISE_NOT_0 "~" #define T_BITWISE_NOT_1 "" #define T_BITWISE_NOT_2 "" #define T_BITWISE_NOT_3 ""
				tokenNOT = "NOT" >> STRICT_BOUNDARIES;	tokenNOT = "NOT" >> STRICT_BOUNDARIES;	#define T_NOT_0 "NOT" #define T_NOT_1 "" #define T_NOT_2 "" #define T_NOT_3 ""
						#define T_BITWISE_AND_0 "&" #define T_BITWISE_AND_1 "" #define T_BITWISE_AND_2 "" #define T_BITWISE_AND_3 ""
				tokenAND = "AND" >> STRICT_BOUNDARIES;	tokenAND = "AND" >> STRICT_BOUNDARIES;	#define T_AND_0 "AND" #define T_AND_1 "" #define T_AND_2 "" #define T_AND_3 ""
						#define T_BITWISE_OR_0 " " #define T_BITWISE_OR_1 "" #define T_BITWISE_OR_2 "" #define T_BITWISE_OR_3 ""
				tokenOR = "OR" >> STRICT_BOUNDARIES;	tokenOR = "OR" >> STRICT_BOUNDARIES;	#define T_OR_0 "OR" #define T_OR_1 "" #define T_OR_2 "" #define T_OR_3 ""
				tokenEQUAL = "==" >> BOUNDARIES;	tokenEQUAL = "==" >> BOUNDARIES;	#define T_EQUAL_0 "==" #define T_EQUAL_1 "" #define T_EQUAL_2 "" #define T_EQUAL_3 ""
				tokenNOTEQUAL = "!=" >> BOUNDARIES;	tokenNOTEQUAL = "!=" >> BOUNDARIES;	#define T_NOT_EQUAL_0 "!=" #define T_NOT_EQUAL_1 "" #define T_NOT_EQUAL_2 "" #define T_NOT_EQUAL_3 ""
				tokenLESSOREQUAL = "<=" >> BOUNDARIES;	tokenLESSOREQUAL = "<=" >> BOUNDARIES;	#define T_LESS_OR_EQUAL_0 "<="
						#define T_LESS_OR_EQUAL_1 "" #define T_LESS_OR_EQUAL_2 "" #define T_LESS_OR_EQUAL_3 ""
				tokenGREATEROREQUAL = ">=" >> BOUNDARIES;	tokenGREATEROREQUAL = ">=" >> BOUNDARIES;	#define T_GREATER_OR_EQUAL_0 ">="
						#define T_GREATER_OR_EQUAL_1 "" #define T_GREATER_OR_EQUAL_2 "" #define T_GREATER_OR_EQUAL_3 ""
				tokenLESS = "<" >> BOUNDARIES;	tokenLESS = "<" >> BOUNDARIES;	#define T_LESS_0 "<" #define T_LESS_1 "" #define T_LESS_2 "" #define T_LESS_3 ""
						#define T_GREATER_0 ">" #define T_GREATER_1 "" #define T_GREATER_2 "" #define T_GREATER_3 ""
				tokenPLUS = "+" >> BOUNDARIES;	tokenPLUS = "+" >> BOUNDARIES;	#define T_ADD_0 "+" #define T_ADD_1 "" #define T_ADD_2 "" #define T_ADD_3 ""
				tokenMINUS = "-" >> BOUNDARIES;	tokenMINUS = "-" >> BOUNDARIES;	#define T_SUB_0 "-" #define T_SUB_1 "" #define T_SUB_2 "" #define T_SUB_3 ""
				tokenMUL = "*" >> BOUNDARIES;	tokenMUL = "*" >> BOUNDARIES;	#define T_MUL_0 "*"
						#define T_MUL_1 "" #define T_MUL_2 "" #define T_MUL_3 ""
				tokenDIV = "DIV" >> STRICT_BOUNDARIES;	tokenDIV = "DIV" >> STRICT_BOUNDARIES;	#define T_DIV_0 "DIV" #define T_DIV_1 "" #define T_DIV_2 ""

						}}}\
value_type = "INTEGER16";	value_type = "INTEGER16";	value_type → "INTEGER16"	value_type(1: "INTEGER16") → "INTEGER16"		value_type = SAME_RULE(tokenINTEGER16);	{ LA_IS, {T_DATA_TYPE_0}, {"value_type", {\ LA_IS, {""}, 1, {T_DATA_TYPE_0}}}\
	array_specify = "[" , unsigned_value, "]" ;	array_specify → "[" unsigned_value "]"	array_specify(1: "[") → "[" unsigned_value "]"	value_type = SAME_RULE(tokenINTEGER16);	array_specify = "[" >> unsigned_value >> "]" ;	{ LA_IS, { "[" }, {"array_specify", {\ LA_IS, {""}, 3, { "[" , "unsigned_value", "]" }}}\
declaration_element = ident, ["[" , unsigned_value, "]"] ;	declaration_element = ident, array_specify__optional;	declaration_element → ident array_specify__optional	declaration_element(1: "ident_terminal") → ident array_specify__optional	declaration_element = ident >> -(tokenLEFTSQUAREBRACKETS >> unsigned_value >> tokenRIGHTSQUAREBRACKETS);	declaration_element = ident >> array_specify__optional;	{ LA_IS, {"ident_terminal"}, {"declaration_element", {\ LA_IS, {""}, 2, {"ident", "array_specify__optional"}}}\
	array_specify__optional = array_specify ε ;	array_specify__optional → array_specify array_specify__optional → ε	array_specify__optional(1: "[") → array_specify array_specify__optional(1: !"[") → ε		array_specify__optional = array_specify "" ;	{ LA_IS, { "[" }, {"array_specify__optional", {\ LA_IS, {""}, 1, {"array_specify"}}}\
other_declaration_ident = " , " , declaration_element ;	other_declaration_ident = " , " , declaration_element ;	other_declaration_ident → " , " , declaration_element	other_declaration_ident(1: " , ") → " , " , declaration_element	other_declaration_ident = tokenCOMMA >> declaration_element ;	other_declaration_ident = tokenCOMMA >> declaration_element ;	{ LA_IS, {T_COMA_0}, {"other_declaration_ident", {\ LA_IS, {""}, 2, {T_COMA_0, "declaration_element"}}}\
declaration = value_type , declaration_element , { other_declaration_ident } ;	declaration = value_type , declaration_element , other_declaration_ident__iteration ;	declaration → value_type declaration_element other_declaration_ident__iteration	declaration(1: "INTEGER16") → value_type declaration_element other_declaration_ident__iteration	declaration = value_type >> declaration_element >> *other_declaration_ident ;	declaration = value_type >> declaration_element >> other_declaration_ident__iteration ;	{ LA_IS, {T_DATA_TYPE_0}, {"declaration", {\ LA_IS, {""}, 3, {"value_type", "declaration_element", "other_declaration_ident__iteration"}}}\
	other_declaration_ident__iteration = other_declaration_ident, other_declaration_ident__iteration ε ;	other_declaration_ident__iteration → other_declaration_ident other_declaration_ident__iteration false_cond_block_without_else__iteration → ε	other_declaration_ident__iteration(1: " , ") → other_declaration_ident other_declaration_ident__iteration false_cond_block_without_else__iteration(1: ! " , ") → ε		other_declaration_ident__iteration = other_declaration_ident >> other_declaration_ident__iteration "" ;	{ LA_IS, {T_COMA_0}, { "other_declaration_ident__iteration", {\ LA_IS, {""}, 2, {"other_declaration_ident", "other_declaration_ident__iteration" }}\
index_action = "[" , expression , "]" ;	index_action = "[" , expression , "]" ;	index_action → "[" expression "]"	index_action(1: "[") → "[" expression "]"	index_action = tokenLEFTSQUAREBRACKETS >> expression >> tokenRIGHTSQUAREBRACKETS ;	index_action = tokenLEFTSQUAREBRACKETS >> expression >> tokenRIGHTSQUAREBRACKETS ;	{ LA_IS, { "[" }, {"index_action", {\ LA_IS, {""}, 3, { "[" , "expression", "]" }}\
unary_operator = "NOT" ;	unary_operator = "NOT" ;	unary_operator → "NOT"	unary_operator(1: "NOT") → "NOT"	unary_operator = SAME_RULE(tokenNOT) ;	unary_operator = SAME_RULE(tokenNOT) ;	{ LA_IS, {T_NOT_0}, {"unary_operator", {\ LA_IS, {""}, 1, {T_NOT_0}}\
unary_operation = unary_operator , expression ;	unary_operation = unary_operator , expression ;	unary_operation → unary_operator expression	unary_operation(1: "NOT") → unary_operator expression	unary_operation = unary_operator >> expression ;	unary_operation = unary_operator >> expression ;	{ LA_IS, {T_NOT_0}, {"unary_operation", {\ LA_IS, {""}, 2, {"unary_operator", "expression" }}\
binary_operator = "AND" "OR" "==" "!=" "<=" ">=" "<" ">" "+" "-" "*" "DIV" "MOD" ;	binary_operator = "AND" "OR" "==" "!=" "<=" ">=" "<" ">" "+" "-" "*" "DIV" "MOD" ;	binary_operator → "AND" binary_operator → "OR" binary_operator → "==" binary_operator → "!=" binary_operator → "<=" binary_operator → ">=" binary_operator → "<" binary_operator → ">" binary_operator → "+" binary_operator → "-" binary_operator → "*" binary_operator → "DIV" binary_operator → "MOD"	binary_operator(1: "AND") → "AND" binary_operator(1: "OR") → "OR" binary_operator(1: "==") → "==" binary_operator(1: "!=") → "!=" binary_operator(1: "<=") → "<=" binary_operator(1: ">=") → ">=" binary_operator(1: "<") → "<" binary_operator(1: ">") → ">" binary_operator(1: "+") → "+" binary_operator(1: "-") → "-" binary_operator(1: "*") → "*" binary_operator(1: "DIV") → "DIV" binary_operator(1: "MOD") → "MOD"	binary_operator = tokenAND tokenOR tokenEQUAL tokenNOTEQUAL tokenLESSOREQUAL tokenGREATEROREQUAL tokenLESS tokenGREATER tokenPLUS tokenMINUS tokenMUL tokenDIV tokenMOD ;	binary_operator = tokenAND tokenOR tokenEQUAL tokenNOTEQUAL tokenLESSOREQUAL tokenGREATEROREQUAL tokenLESS tokenGREATER tokenPLUS tokenMINUS tokenMUL tokenDIV tokenMOD ;	{ LA_IS, {T_AND_0}, {"binary_operator", {\ LA_IS, {""}, 1, {T_AND_0}}\
binary_action = binary_operator , expression ;	binary_action = binary_operator , expression ;	binary_action → binary_operator expression	binary_action(1: "AND", "OR", "==", "!=", "<=", ">=", "<", ">", "+", "-", "*", "DIV", "MOD") → binary_operator expression		binary_action = binary_operator >> expression ;	{ LA_IS, {T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_0, T_GREATER_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0}, {"binary_action", {\ LA_IS, {""}, 2, {"binary_operator", "expression" }}\
left_expression = group_expression unary_operation ident , { index_action__optional value cond_block } ;	left_expression = group_expression unary_operation ident , { index_action__optional value cond_block } ;	left_expression → group_expression left_expression → unary_operation left_expression → ident , { index_action__optional value cond_block } left_expression → value left_expression → cond_block	left_expression(1: "(") → group_expression left_expression(1: "NOT") → unary_operation left_expression(1: "(") → ident , { index_action__optional value cond_block } left_expression(1: "0", "1", "2", "3", "4", "5", "6", "7", "8", "9") → value	left_expression = group_expression unary_operation ident >> -index_action value cond_block ;	left_expression = group_expression unary_operation ident >> index_action__optional value cond_block ;	{ LA_IS, { "(" }, {"left_expression", {\ LA_IS, {""}, 1, {"group_expression" }}\
left_expression = group_expression unary_operation ident , { index_action } value cond_block ;	left_expression = group_expression unary_operation ident , { index_action } value cond_block ;	left_expression → group_expression left_expression → unary_operation left_expression → ident , { index_action } value cond_block	left_expression(1: "(") → group_expression left_expression(1: "NOT") → unary_operation left_expression(1: "(") → ident , { index_action } value cond_block	left_expression = group_expression unary_operation ident >> -index_action value cond_block ;	left_expression = group_expression unary_operation ident >> index_action__optional value cond_block ;	{ LA_IS, {T_NOT_0}, {"left_expression", {\ LA_IS, {""}, 1, {"unary_operation" }}\

			left_expression(1: "+", "-", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9") → value left_expression(1: "IF") → cond_block			{LA_IS, { "ident_terminal" }, { "left_expression", {\ {LA_IS, { "" }, 2, { "ident", "index_action__optional" }}}\ }};\} {LA_IS, { "unsigned_value_terminal" }, {\ "left_expression", {\ {LA_IS, { "" }, 1, { "value" }}\ }};\} {LA_IS, { T_ADD_0, T_SUB_0 }, { "left_expression", {\ {LA_IS, { "unsigned_value_terminal" }, 1, { "value" }}\ }/*{LA_NOT, { "unsigned_value_terminal" }, 1, {\ "unary_operation" }}*/\ }};\} {LA_IS, { T_IF_0 }, { "left_expression", {\ {LA_IS, { "" }, 1, { "cond_block" }}\ }};\} }};\}
	index_action__optional = index_action ε;	index_action__optional → index_action index_action__optional → ε	index_action__optional(1: " ") → index_action index_action__optional(1: !" ") → ε		index_action__optional = index_action "";	{LA_IS, { " " }, { "index_action__optional", {\ {LA_IS, { "" }, 1, { "index_action" }}}\ }};\} {LA_NOT, { " " }, { "index_action__optional", {\ {LA_IS, { "" }, 0, { "" }}}\ }};\} }};\}
expression = left_expression , {binary_action};	expression = left_expression , binary_action__iteration;	expression → left_expression binary_action__iteration	expression(1: "(" , "NOT", "+", "-", " ", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → left_expression binary_action__iteration	expression = left_expression >> binary_action__iteration;	expression = left_expression >> binary_action__iteration;	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "expression", {\ {LA_IS, { "" }, 2, { "left_expression", "binary_action__iteration" }}}\ }};\}
	binary_action__iteration = binary_action, binary_action__iteration ε;	binary_action__iteration → binary_action binary_action__iteration binary_action__iteration → ε	binary_action__iteration(1: "AND", "OR", "=", "!=" , "<=", ">=", "<", ">", "+", "-", "**", "DIV", "MOD") → binary_action binary_action__iteration binary_action__iteration(1: !"AND", !"OR", !"=", !"!=", !"<=", !">=", !"<", !">", !"+", !"-", !"*, !"DIV", !"MOD") → ε	expression = left_expression >> *binary_action;	binary_action__iteration = binary_action >> binary_action__iteration "";	IF_NONUSE_COMPARE_WITH_EQUAL(\ {LA_IS, { T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_0, T_GREATER_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0 }, {\ "binary_action__iteration", {\ {LA_IS, { "" }, 2, { "binary_action", "binary_action__iteration" }}}\ }};\} {LA_NOT, { T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_0, T_GREATER_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0 }, {\ "binary_action__iteration", {\ {LA_IS, { "" }, 0, { "" }}}\ }};\})\} IF_USE_COMPARE_WITH_EQUAL(\ {LA_IS, { T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_OR_EQUAL_0, T_GREATER_OR_EQUAL_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0 }, {\ "binary_action__iteration", {\ {LA_IS, { "" }, 2, { "binary_action", "binary_action__iteration" }}}\ }};\} {LA_NOT, { T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_OR_EQUAL_0, T_GREATER_OR_EQUAL_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0 }, {\ "binary_action__iteration", {\ {LA_IS, { "" }, 0, { "" }}}\ }};\})\}
group_expression = "(" , expression , ")";	group_expression = "(" , expression , ")";	group_expression → "(" expression ")"	group_expression(1: "(") → "(" expression ")"	group_expression = tokenGROUPEXPRESSIONBEGIN >> expression >> tokenGROUPEXPRESSIONEND;	group_expression = tokenGROUPEXPRESSIONBEGIN >> expression >> tokenGROUPEXPRESSIONEND;	{LA_IS, { "(" , { "group_expression", {\ {LA_IS, { "" }, 3, { "(" , "expression", ")" }}}\ }};\}
expression_or_cond_block__with_optional_assign = expression , assign_to_right__optional;	expression_or_cond_block__with_optional_assign = expression , assign_to_right__optional;	expression_or_cond_block__with_optional_assign → expression assign_to_right__optional	expression_or_cond_block__with_optional_assign(1: "(" , "NOT", "+", "-", " ", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression assign_to_right__optional	expression_or_cond_block__with_optional_assign = expression >> -(tokenLRASSIGN >> ident >> -index_action);	expression_or_cond_block__with_optional_assign = expression >> assign_to_right__optional;	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "expression_or_cond_block__with_optional_assign", {\ {LA_IS, { "" }, 2, { "expression", "assign_to_right__optional" }}}\ }};\}
	assign_to_right = "!=" , ident , index_action__optional;	assign_to_right → "!=" ident index_action__optional	assign_to_right(1: "!=") → "!=" ident index_action__optional		assign_to_right = tokenLRASSIGN >> ident >> index_action__optional;	{LA_IS, { T_LRASSIGN_0 }, { "assign_to_right", {\ {LA_IS, { "" }, 3, { T_LRASSIGN_0 , "ident", "index_action__optional" }}}\ }};\}
	assign_to_right__optional = assign_to_right ε;	assign_to_right__optional → assign_to_right assign_to_right__optional → ε;	assign_to_right__optional(1: "!=") → assign_to_right assign_to_right__optional(1: !"!=") → ε;		assign_to_right__optional = assign_to_right "";	{ LA_IS, { T_LRASSIGN_0 }, {\ "assign_to_right__optional", {\ { LA_IS, { "" }, 1, { "assign_to_right" }}}\ }};\} { LA_NOT, { T_LRASSIGN_0 }, {\ "assign_to_right__optional", {\ { LA_IS, { "" }, 0, { "" }}}\ }};\} }};\}
if_expression = expression;	if_expression = expression;	if_expression → expression	if_expression(1: "(" , "NOT", "+", "-", " ", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression	if_expression = SAME_RULE(expression);	if_expression = SAME_RULE(expression);	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "if_expression", {\ {LA_IS, { "" }, 1, { "expression" }}}\ }};\}
body_for_true = block_statements_in_while_and_if_body;	body_for_true = block_statements_in_while_and_if_body;	body_for_true → block_statements_in_while_and_if_body	body_for_true(1: "(") → block_statements_in_while_and_if_body	body_for_true = SAME_RULE(block_statements_in_while_and_if_body);	body_for_true = SAME_RULE(block_statements_in_while_and_if_body);	{LA_IS, { T_BEGIN_BLOCK_0 }, { "body_for_true", {\ {LA_IS, { "" }, 1, {\ "block_statements_in_while_and_if_body" }}}\ }};\}
false_cond_block_without_else = "ELSE" , "IF" , if_expression , body_for_true;	false_cond_block_without_else = "ELSE" , "IF" , if_expression , body_for_true;	false_cond_block_without_else → "ELSE" "IF" if_expression body_for_true	false_cond_block_without_else(1: "ELSE") → "ELSE" "IF" if_expression body_for_true	false_cond_block_without_else = tokenELSE >> tokenIF >> if_expression >> body_for_true;	false_cond_block_without_else = tokenELSE >> tokenIF >> if_expression >> body_for_true;	{LA_IS, { T_ELSE_IF_0 }, {\ "false_cond_block_without_else", {\ {LA_IS, { "" }, 4, { T_ELSE_IF_0, T_ELSE_IF_1, "if_expression", "body_for_true" }}}\ }};\}
body_for_false = "ELSE" , block_statements_in_while_and_if_body;	body_for_false = "ELSE" , block_statements_in_while_and_if_body;	body_for_false → "ELSE" block_statements_in_while_and_if_body	body_for_false(1: "ELSE") → "ELSE" block_statements_in_while_and_if_body	body_for_false = tokenELSE >> block_statements_in_while_and_if_body;	body_for_false = tokenELSE >> block_statements_in_while_and_if_body;	{LA_IS, { T_ELSE_BLOCK_0 }, { "body_for_false", {\ {LA_IS, { "" }, 2, { T_ELSE_BLOCK_0 , "block_statements" }}\ }};\}
cond_block = "IF" , if_expression , body_for_true, false_cond_block_without_else__iteration , body_for_false__optional;	cond_block = "IF" , if_expression , body_for_true, false_cond_block_without_else__iteration , body_for_false__optional;	cond_block → "IF" if_expression body_for_true false_cond_block_without_else__iteration body_for_false__optional	cond_block(1: "IF") → "IF" if_expression body_for_true false_cond_block_without_else__iteration body_for_false__optional	cond_block = tokenIF >> if_expression >> body_for_true >> *false_cond_block_without_else >> -body_for_false;	cond_block = tokenIF >> if_expression >> body_for_true >> false_cond_block_without_else__iteration >> body_for_false__optional;	{LA_IS, { T_IF_0 }, { "cond_block", {\ {LA_IS, { "" }, 5, { T_IF_0 , "if_expression", "body_for_true", "false_cond_block_without_else__iteration", "body_for_false__optional" }}}\ }};\}
false_cond_block_without_else__iteration = false_cond_block_without_else, false_cond_block_without_else__iteration ε;	false_cond_block_without_else__iteration = false_cond_block_without_else, false_cond_block_without_else__iteration ε;	false_cond_block_without_else__iteration → false_cond_block_without_else false_cond_block_without_else__iteration false_cond_block_without_else__iteration → ε	false_cond_block_without_else__iteration(1: "ELSE"; 2: "IF") → false_cond_block_without_else false_cond_block_without_else__iteration false_cond_block_without_else__iteration(1: "ELSE";		false_cond_block_without_else__iteration = false_cond_block_without_else >> false_cond_block_without_else__iteration "";	{LA_IS, { T_ELSE_IF_0 }, {\ "false_cond_block_without_else__iteration", {\ {LA_IS, { T_ELSE_IF_1 }, 2, {\ "false_cond_block_without_else",

						}}}\
while_cycle = "WHILE", while_cycle_head_expression , block_statements_in_while_and_if_body;	while_cycle = "WHILE", while_cycle_head_expression , block_statements_in_while_and_if_body;	while_cycle → "WHILE" while_cycle_head_expression block_statements_in_while_and_if_body	while_cycle(1: "WHILE") → "WHILE" while_cycle_head_expression block_statements_in_while_and_if_body	while_cycle = tokenWHILE >> while_cycle_head_expression >> block_statements_in_while_and_if_body;	while_cycle = tokenWHILE >> while_cycle_head_expression >> block_statements_in_while_and_if_body;	{LA_IS, {T_WHILE_0 }, {"while_cycle"}, {\ LA_IS, {""}, 3, {T_WHILE_0, "while_cycle_head_expression", "block_statements_in_while_and_if_body" }}\ }}}\
repeat_until_cycle_cond = expression;	repeat_until_cycle_cond = expression;	repeat_until_cycle_cond → expression	repeat_until_cycle_cond(1: "(" , "NOT", "+", "-", "_", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression	repeat_until_cycle_cond = SAME_RULE(expression);	repeat_until_cycle_cond = SAME_RULE(expression);	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "repeat_until_cycle_cond", {\ LA_IS, {""}, 1, { "expression" }}\ }}}\
repeat_until_cycle = "REPEAT", ((statement) block_statements), "UNTIL", repeat_until_cycle_cond;	repeat_until_cycle = "REPEAT", statements_or_block_statements, "UNTIL", repeat_until_cycle_cond;	repeat_until_cycle → "REPEAT" statements_or_block_statements "UNTIL" repeat_until_cycle_cond	repeat_until_cycle(1: "REPEAT") → "REPEAT" statements_or_block_statements "UNTIL" repeat_until_cycle_cond	repeat_until_cycle = tokenREPEAT >> (*statement block_statements) >> tokenUNTIL >> repeat_until_cycle_cond;	repeat_until_cycle = tokenREPEAT >> statements_or_block_statements >> tokenUNTIL >> repeat_until_cycle_cond;	{LA_IS, {T_REPEAT_0 }, {"repeat_until_cycle"}, {\ LA_IS, {""}, 4, {T_REPEAT_0, "statements_or_block_statements", T_UNTIL_0, "repeat_until_cycle_cond" }}\ }}}\
	statements_or_block_statements = statement__iteration block_statements;	statements_or_block_statements → statement__iteration statements_or_block_statements → block_statements	statements_or_block_statements(1: " ", "(", "NOT", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "+", "-", "IF", "FOR", "WHILE", "REPEAT", "GOTO", "GET", "PUT", ";") → statement__iteration statements_or_block_statements(1: "(") → block_statements		statements_or_block_statements = statement__iteration block_statements;	{LA_IS, { "ident_terminal", "(", T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0, T_FOR_0, T_WHILE_0, T_REPEAT_0, T_GOTO_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0 }, { "statements_or_block_statements", {\ LA_IS, {""}, 1, { "statement__iteration" }}\ }}}\ {LA_IS, {T_BEGIN_BLOCK_0 }, { "statements_or_block_statements", {\ LA_IS, {""}, 1, { "block_statements" }}\ }}}\
input_rule = "GET", (ident , [index_action] "(" , ident , [index_action] , ")");	input_rule = "GET", argument_for_input;	input_rule → "GET" argument_for_input	input_rule(1: "GET") → "GET" argument_for_input	input_rule = tokenGET >> (ident >> -index_action tokenGROUPEXPRESSIONBEGIN >> ident >> -index_action >> tokenGROUPEXPRESSIONEND);	input_rule = tokenGET >> argument_for_input;	{LA_IS, {T_INPUT_0 }, {"input_rule"}, {\ LA_IS, {""}, 2, {T_INPUT_0, "argument_for_input" }}\ }}}\
	argument_for_input = ident , index_action__optional; argument_for_input = "(" , "ident", "index_action__optional", ")";	argument_for_input → ident index_action__optional argument_for_input → "(" "ident" "index_action__optional" ")"	argument_for_input(1: " ") → ident index_action__optional argument_for_input(1: "(") → "(" "ident" "index_action__optional" ")"		argument_for_input = ident >> index_action__optional tokenGROUPEXPRESSIONBEGIN >> ident >> index_action__optional >> tokenGROUPEXPRESSIONEND;	{LA_IS, { "ident_terminal" }, {"argument_for_input", {\ LA_IS, {""}, 2, { "ident", "index_action__optional" }}\ }}}\ {LA_IS, { "(" }, { "argument_for_input", {\ LA_IS, {""}, 4, { "(", "ident", "index_action__optional", ")" }}\ }}}\
output_rule = "PUT", expression;	output_rule = "PUT", expression;	output_rule → "PUT" expression	output(1: "PUT") → "PUT" expression	output_rule = tokenPUT >> expression;	output_rule = tokenPUT >> expression;	{LA_IS, {T_OUTPUT_0 }, {"output_rule"}, {\ LA_IS, {""}, 2, {T_OUTPUT_0, "expression" }}\ }}}\
statement = labeled_point expression_or_cond_block_with_optional_assign goto_label forto_cycle while_cycle repeat_until_cycle input_rule output_rule ";"; statement = labeled_point expression_or_cond_block_with_optional_assign goto_label forto_cycle while_cycle repeat_until_cycle input_rule output_rule ";";	statement = labeled_point expression_or_cond_block_with_optional_assign goto_label forto_cycle while_cycle repeat_until_cycle input_rule output_rule ";";	statement → labeled_point statement → expression_or_cond_block_with_optional_assign statement → goto_label statement → forto_cycle statement → while_cycle statement → repeat_until_cycle statement → input_rule statement → output_rule statement → ";"	statement(1: " ", ";") → labeled_point statement(1: " "; 2: "!";) → expression_or_cond_block_with_optional_assign statement(1: "(", "NOT", "+", "-", "_", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression_or_cond_block_with_optional_assign statement(1: "GOTO") → goto_label statement(1: "FOR") → forto_cycle statement(1: "WHILE") → while_cycle statement(1: "REPEAT") → repeat_until_cycle statement(1: "GET") → input_rule statement(1: "PUT") → output_rule statement(1: ";") → ";"	statement = labeled_point /* labeled_point first*/ expression_or_cond_block_with_optional_assign goto_label forto_cycle while_cycle repeat_until_cycle input_rule output_rule tokenSEMICOLON;	statement = labeled_point /* labeled_point first*/ expression_or_cond_block_with_optional_assign goto_label forto_cycle while_cycle repeat_until_cycle input_rule tokenSEMICOLON;	{LA_IS, { "ident_terminal" }, {"statement", {\ LA_IS, {T_COLON_0 }, 1, {"labeled_point"}}\} { LA_NOT, {T_COLON_0 }, 1, {"expression_or_cond_block_with_optional_assign"}}\ }}}\ {LA_IS, { "(" , T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0 }, {"statement", {\ LA_IS, {""}, 1, {"expression_or_cond_block_with_optional_assign"}}\ }}}\ {LA_IS, {T_GOTO_0 }, {"statement", {\ LA_IS, {""}, 1, {"goto_label"}}\ }}}\ {LA_IS, {T_FOR_0 }, {"statement", {\ LA_IS, {""}, 1, {"forto_cycle"}}\ }}}\ {LA_IS, {T_WHILE_0 }, {"statement", {\ LA_IS, {""}, 1, {"while_cycle"}}\ }}}\ {LA_IS, {T_REPEAT_0 }, {"statement", {\ LA_IS, {""}, 1, {"repeat_until_cycle"}}\ }}}\ {LA_IS, {T_INPUT_0 }, {"statement", {\ LA_IS, {""}, 1, {"input_rule"}}\ }}}\ {LA_IS, {T_OUTPUT_0 }, {"statement", {\ LA_IS, {""}, 1, {"output_rule"}}\ }}}\ {LA_IS, {T_SEMICOLON_0 }, {"statement", {\ LA_IS, {""}, 1, {";"}}\ }}}\
	statement__iteration = statement, statement__iteration ε;	statement__iteration → statement statement__iteration statement__iteration → ε	statement__iteration(1: " ", "(", "NOT", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "+", "-", "_", "IF", "FOR", "WHILE", "REPEAT", "GOTO", "GET", "PUT", ";") → statement statement__iteration statement__iteration(1: !" ", !"(", !"NOT", !"0", !"1", !"2", !"3", !"4", !"5", !"6", !"7", !"8", !"9", !"+", !"-", !"IF", !"FOR", !"WHILE", !"REPEAT", !"GOTO", !"GET", !"PUT", !";") → ε		statement__iteration = statement >> statement__iteration "";	{ LA_IS, { "ident_terminal", "(", T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0, T_FOR_0, T_WHILE_0, T_REPEAT_0, T_GOTO_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0 }, { "statement__iteration", {\ LA_IS, {""}, 2, { "statement", "statement__iteration" }}\ }}}\ { LA_NOT, { "ident_terminal", "(", T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0, T_FOR_0, T_WHILE_0, T_REPEAT_0, T_GOTO_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0 }, { "statement__iteration", {\ LA_IS, {""}, 0, { "" }}\ }}}\
block_statements = "(" , {statement} , ")";	block_statements = "(" , statement__iteration , ")";	block_statements → "(" statement__iteration ")"	block_statements(1: "(") → "(" statement__iteration ")"	block_statements = tokenBEGINBLOCK >> *statement >> tokenENDBLOCK;	block_statements = tokenBEGINBLOCK >> statement__iteration >> tokenENDBLOCK;	{ LA_IS, {T_BEGIN_BLOCK_0 }, {"block_statements"}, {\ LA_IS, {""}, 3, {T_BEGIN_BLOCK_0, "statement__iteration", T_END_BLOCK_0 }}\ }}}\
	expression__optional = expression "";	expression__optional → expression expression__optional → ε	expression__optional(1: "(" , "NOT", "+", "-", "_", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression expression__optional(1: !"(", !"NOT", !"+", !"-", !"_", !"0", !"1", !"2", !"3", !"4", !"5", !"6", !"7", !"8", !"9", !"IF") → ε		expression__optional = expression "";	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "expression__optional", {\ LA_IS, {""}, 1, { "expression" }}\ }}}\ {LA_NOT, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "expression__optional", {\ LA_IS, {""}, 0, { "" }}\ }}}\
program_rule = "NAME", program_name , ";", "BODY", "DATA", declaration__optional , ";", statement__iteration , "END";	program_rule = "NAME", program_name , ";", "BODY", "DATA", declaration__optional , ";", statement__iteration , "END";	program_rule → "NAME" program_name ";", "BODY" "DATA" declaration__optional ";", statement__iteration "END"	program_rule(1: "NAME") → "NAME" program_name ";", "BODY" "DATA" declaration__optional ";", statement__iteration "END"	program_rule = BOUNDARIES >> tokenNAME >> program_name >> tokenSEMICOLON >> tokenBODY >> tokenDATA >> (- declaration) >> tokenSEMICOLON >> *statement >> tokenEND;	program_rule = BOUNDARIES >> tokenNAME >> program_name >> tokenSEMICOLON >> tokenBODY >> tokenDATA >> declaration__optional >> tokenSEMICOLON >> statement__iteration >> tokenEND;	{ LA_IS, {T_NAME_0 }, {"program_rule"}, {\ LA_IS, {""}, 9, {T_NAME_0, "program_name", T_SEMICOLON_0, T_BODY_0, T_DATA_0, "declaration__optional", T_SEMICOLON_0, "statement__iteration", T_END_0 }}\ }}}\
	declaration__optional = declaration "";	declaration__optional → declaration	declaration__optional(1: "INTEGER16") →		declaration__optional = declaration "";	{ LA_IS, {T_DATA_TYPE_0 }, {"declaration__optional"}, {\

		letter_in_upper_case → "v" letter_in_upper_case → "W" letter_in_upper_case → "x" letter_in_upper_case → "Y" letter_in_upper_case → "Z"	letter_in_upper_case(1: "V") → "v" letter_in_upper_case(1: "W") → "W" letter_in_upper_case(1: "X") → "x" letter_in_upper_case(1: "Y") → "Y" letter_in_upper_case(1: "Z") → "Z"	v = "v"; w = "w"; x = "x"; y = "y"; z = "z"; letter_in_upper_case = A B C D E F G H I J K L M N O P Q R S T U V W X Y Z;	v = "v"; w = "w"; x = "x"; y = "y"; z = "z"; letter_in_upper_case = A B C D E F G H I J K L M N O P Q R S T U V W X Y Z;	
				STRICT_BOUNDARIES = (BOUNDARY >> *(BOUNDARY)) (!{(q!::alpha q!::char_("_"))}); BOUNDARIES = (BOUNDARY >> *(BOUNDARY) NO_BOUNDARY); BOUNDARY = BOUNDARY__SPACE BOUNDARY__TAB BOUNDARY__VERTICAL_TAB BOUNDARY__FORM_FEED BOUNDARY__CARRIAGE_RETURN BOUNDARY__LINE_FEED BOUNDARY__NULL; BOUNDARY__SPACE = " "; BOUNDARY__TAB = "\t"; BOUNDARY__VERTICAL_TAB = "\v"; BOUNDARY__FORM_FEED = "\f"; BOUNDARY__CARRIAGE_RETURN = "\r"; BOUNDARY__LINE_FEED = "\n"; BOUNDARY__NULL = "\0"; NO_BOUNDARY = ""; #define WHITESPACES \ STRICT_BOUNDARIES, \ BOUNDARIES, \ BOUNDARY, \ BOUNDARY__SPACE, \ BOUNDARY__TAB, \ BOUNDARY__VERTICAL_TAB, \ BOUNDARY__FORM_FEED, \ BOUNDARY__CARRIAGE_RETURN, \ BOUNDARY__LINE_FEED, \ BOUNDARY__NULL, \ NO_BOUNDARY	STRICT_BOUNDARIES = (BOUNDARY >> *(BOUNDARY)) !(q!::alpha q!::char_("_")); BOUNDARIES = (BOUNDARY >> *(BOUNDARY) NO_BOUNDARY); BOUNDARY = BOUNDARY__SPACE BOUNDARY__TAB BOUNDARY__VERTICAL_TAB BOUNDARY__FORM_FEED BOUNDARY__CARRIAGE_RETURN BOUNDARY__LINE_FEED BOUNDARY__NULL; BOUNDARY__SPACE = " "; BOUNDARY__TAB = "\t"; BOUNDARY__VERTICAL_TAB = "\v"; BOUNDARY__FORM_FEED = "\f"; BOUNDARY__CARRIAGE_RETURN = "\r"; BOUNDARY__LINE_FEED = "\n"; BOUNDARY__NULL = "\0"; NO_BOUNDARY = ""; #define WHITESPACES \ STRICT_BOUNDARIES, \ BOUNDARIES, \ BOUNDARY, \ BOUNDARY__SPACE, \ BOUNDARY__TAB, \ BOUNDARY__VERTICAL_TAB, \ BOUNDARY__FORM_FEED, \ BOUNDARY__CARRIAGE_RETURN, \ BOUNDARY__LINE_FEED, \ BOUNDARY__NULL, \ NO_BOUNDARY	\ \ \ { LA_IS, { T_NAME_0 }, { "program____part1",\ { LA_IS, {""}, 7, { T_NAME_0, "program_name", T_SEMICOLON_0, T_BODY_0, T_DATA_0, "declaration_optional", T_SEMICOLON_0 }}\ }}};\ \ },\ "program_rule"
						\ \ \ { LA_IS, { T_NAME_0 }, { "program____part1",\ { LA_IS, {""}, 7, { T_NAME_0, "program_name", T_SEMICOLON_0, T_BODY_0, T_DATA_0, "declaration_optional", T_SEMICOLON_0 }}\ }}};\ \ },\ "program_rule"