

РБНФ №1 (опис синтаксису всіма допустимими засобами РБНФ)	РБНФ №2 (опис формальної граматики засобами РБНФ)	Формальна граматика	Формальна граматика з специфікацією lookahead у правилах для LL(2)-аналізатора	/* Перевірка РБНФ №1 за допомогою коду (помістити у файл "EBNF_N1.h") */	/* Перевірка РБНФ №2 за допомогою коду (помістити у файл "EBNF_N2.h") */	/* Перевірка прототипу LL(2)-синтаксичного аналізатора (спеціальна структура) та прототипу лексичного аналізатора (регулярні вирази) за допомогою коду. Лексеми для синтаксичного аналізатора обробляються лексичним аналізатором, тому синтаксичний аналізатор не аналізує їх повторно (як показано в РБНФ). (помістити у файл "LexicaByRegExAndSyntaxByLL2protototype.h") УВАГА: при копіюванні зажайте, щоб у кожному рядку після символу «\» не містилось жодних інших символів. */
		G = (N, T, P, S)	G = (N, T, P, S)			
		S → program_rule	S → program_rule			
		N = { labeled_point, goto_label, program_name, value_type, array_specify, declaration_element, array_specify_optional, other_declaration_ident, declaration, other_declaration_ident_iteration, index_action, unary_operator, unary_operation, binary_operator, binary_action, left_expression, group_expression, index_action_optional, expression, binary_action_iteration, expression_or_cond_block_with_optional_assign, assign_to_right, assign_to_right_optional, if_expression, body_for_true, false_cond_block_without_else, body_for_false, cond_block, false_cond_block_without_else_iteration, body_for_false_optional, statement, block_statements, input_rule, argument_for_input, output_rule, statement_iteration, expression_optional, program_rule, declaration_optional, non_zero_digit, digit_iteration, digit, unsigned_value, value, sign_optional, sign, ident, letter_in_upper_case, letter_in_lower_case, sign_plus, sign_minus }	N = { labeled_point, goto_label, program_name, value_type, array_specify, declaration_element, array_specify_optional, other_declaration_ident, declaration, other_declaration_ident_iteration, index_action, unary_operator, unary_operation, binary_operator, binary_action, left_expression, group_expression, index_action_optional, expression, binary_action_iteration, expression_or_cond_block_with_optional_assign, assign_to_right, assign_to_right_optional, if_expression, body_for_true, false_cond_block_without_else, body_for_false, cond_block, false_cond_block_without_else_iteration, body_for_false_optional, statement, block_statements, input_rule, argument_for_input, output_rule, statement_iteration, expression_optional, program_rule, declaration_optional, non_zero_digit, digit_iteration, digit, unsigned_value, value, sign_optional, sign, ident, letter_in_upper_case, letter_in_lower_case, sign_plus, sign_minus }	#define NONTERMINALS labeled_point, \ goto_label, \ program_name, \ value_type, \ array_specify, \ declaration_element, \ \ other_declaration_ident, \ declaration, \ \ index_action, \ unary_operator, \ unary_operation, \ binary_operator, \ binary_action, \ left_expression, \ group_expression, \ \ expression, \ \ expression_or_cond_block_with_optional_assign, \ assign_to_right, \ \ if_expression, \ body_for_true, \ false_cond_block_without_else, \ body_for_false, \ cond_block, \ \ \ statement,\ block_statements, \ input_rule, \ argument_for_input, \ output_rule, \ \ \ program_rule, \ \ non_zero_digit, \ digit_iteration, \ digit, \ unsigned_value, \ value, \ \ sign, \ ident, \ letter_in_upper_case, \ letter_in_lower_case, \ sign_plus, \ sign_minus	#define NONTERMINALS labeled_point, \ goto_label, \ program_name, \ value_type, \ array_specify, \ declaration_element, \ array_specify_optional, \ other_declaration_ident, \ declaration, \ other_declaration_ident_iteration, \ index_action, \ unary_operator, \ unary_operation, \ binary_operator, \ binary_action, \ left_expression, \ group_expression, \ index_action_optional, \ expression, \ binary_action_iteration, \ expression_or_cond_block_with_optional_assign, \ assign_to_right, \ assign_to_right_optional, \ if_expression, \ body_for_true, \ false_cond_block_without_else, \ body_for_false, \ cond_block, \ false_cond_block_without_else_iteration, \ body_for_false_optional, \ statement,\ block_statements, \ input_rule, \ argument_for_input, \ output_rule, \ statement_iteration, \ expression_optional, \ program_rule, \ declaration_optional, \ non_zero_digit, \ digit_iteration, \ digit, \ unsigned_value, \ value, \ sign_optional, \ sign, \ ident, \ letter_in_upper_case, \ letter_in_lower_case, \ sign_plus, \ sign_minus	
		T = { ",", ",", ",", "GOTO", "INTEGER16", ",", ",", "NOT", "AND", "OR", "==", "!=", "<", ">", "+", "-", "*", "/", "DIV", "MOD", "(", ")", "=", "ELSE", "IF",	T = { ",", ",", ",", "GOTO", "INTEGER16", ",", ",", "NOT", "AND", "OR", "==", "!=", "<", ">", "+", "-", "*", "/", "DIV", "MOD", "(", ")", "=", "ELSE", "IF",	#define TOKENS \ tokenCOLON, \ tokenGOTO, \ tokenINTEGER16, \ tokenCOMMA, \ tokenNOT, \ tokenAND, \ tokenOR, \ tokenEQUAL, \ tokenNOTEQUAL, \ tokenLESS, \ tokenGREATER, \ tokenPLUS, \ tokenMINUS, \ tokenMUL, \ tokenDIV, \ tokenMOD, \ tokenGROUPEXPRESSIONBEGIN, \ tokenGROUPEXPRESSIONEND, \ tokenLRASSIGN, \ tokenELSE, \ tokenIF, \ 	#define TOKENS \ tokenCOLON, \ tokenGOTO, \ tokenINTEGER16, \ tokenCOMMA, \ tokenNOT, \ tokenAND, \ tokenOR, \ tokenEQUAL, \ tokenNOTEQUAL, \ tokenLESS, \ tokenGREATER, \ tokenPLUS, \ tokenMINUS, \ tokenMUL, \ tokenDIV, \ tokenMOD, \ tokenGROUPEXPRESSIONBEGIN, \ tokenGROUPEXPRESSIONEND, \ tokenLRASSIGN, \ tokenELSE, \ tokenIF, \ 	

				tokenSEMICOLON = ";;" >> BOUNDARIES;	tokenSEMICOLON = ";;" >> BOUNDARIES;	#define T_SEMICOLON_0 ";" #define T_SEMICOLON_1 "" #define T_SEMICOLON_2 "" #define T_SEMICOLON_3 ""
				tokenCOLON = ":" >> BOUNDARIES;	tokenCOLON = ":" >> BOUNDARIES;	#define T_COLON_0 ":" #define T_COLON_1 "" #define T_COLON_2 "" #define T_COLON_3 ""
				tokenGOTO = "GOTO" >> STRICT_BOUNDARIES;	tokenGOTO = "GOTO" >> STRICT_BOUNDARIES;	#define T_GOTO_0 "GOTO" #define T_GOTO_1 "" #define T_GOTO_2 "" #define T_GOTO_3 ""
				tokenINTEGER16 = "INTEGER16" >> STRICT_BOUNDARIES;	tokenINTEGER16 = "INTEGER16" >> STRICT_BOUNDARIES;	#define T_DATA_TYPE_0 "INTEGER16" #define T_DATA_TYPE_1 "" #define T_DATA_TYPE_2 "" #define T_DATA_TYPE_3 ""
				tokenCOMMA = "," >> BOUNDARIES;	tokenCOMMA = "," >> BOUNDARIES;	#define T_COMA_0 "," #define T_COMA_1 "" #define T_COMA_2 "" #define T_COMA_3 ""
						#define T_BITWISE_NOT_0 "~" #define T_BITWISE_NOT_1 "" #define T_BITWISE_NOT_2 "" #define T_BITWISE_NOT_3 ""
				tokenNOT = "NOT" >> STRICT_BOUNDARIES;	tokenNOT = "NOT" >> STRICT_BOUNDARIES;	#define T_NOT_0 "NOT" #define T_NOT_1 "" #define T_NOT_2 "" #define T_NOT_3 ""
						#define T_BITWISE_AND_0 "&" #define T_BITWISE_AND_1 "" #define T_BITWISE_AND_2 "" #define T_BITWISE_AND_3 ""
				tokenAND = "AND" >> STRICT_BOUNDARIES;	tokenAND = "AND" >> STRICT_BOUNDARIES;	#define T_AND_0 "AND" #define T_AND_1 "" #define T_AND_2 "" #define T_AND_3 ""
						#define T_BITWISE_OR_0 " " #define T_BITWISE_OR_1 "" #define T_BITWISE_OR_2 "" #define T_BITWISE_OR_3 ""
				tokenOR = "OR" >> STRICT_BOUNDARIES;	tokenOR = "OR" >> STRICT_BOUNDARIES;	#define T_OR_0 "OR" #define T_OR_1 "" #define T_OR_2 "" #define T_OR_3 ""
				tokenEQUAL = "==" >> BOUNDARIES;	tokenEQUAL = "==" >> BOUNDARIES;	#define T_EQUAL_0 "==" #define T_EQUAL_1 "" #define T_EQUAL_2 "" #define T_EQUAL_3 ""
				tokenNOTEQUAL = "!=" >> BOUNDARIES;	tokenNOTEQUAL = "!=" >> BOUNDARIES;	#define T_NOT_EQUAL_0 "!=" #define T_NOT_EQUAL_1 "" #define T_NOT_EQUAL_2 "" #define T_NOT_EQUAL_3 ""
				tokenLESS = "<" >> BOUNDARIES;	tokenLESS = "<" >> BOUNDARIES;	#define T_LESS_0 "<" #define T_LESS_1 "" #define T_LESS_2 "" #define T_LESS_3 ""
				tokenGREATER = ">" >> BOUNDARIES;	tokenGREATER = ">" >> BOUNDARIES;	#define T_GREATER_0 ">" #define T_GREATER_1 "" #define T_GREATER_2 "" #define T_GREATER_3 ""
				tokenPLUS = "+" >> BOUNDARIES;	tokenPLUS = "+" >> BOUNDARIES;	#define T_ADD_0 "+" #define T_ADD_1 "" #define T_ADD_2 "" #define T_ADD_3 ""
				tokenMINUS = "-" >> BOUNDARIES;	tokenMINUS = "-" >> BOUNDARIES;	#define T_SUB_0 "-" #define T_SUB_1 "" #define T_SUB_2 "" #define T_SUB_3 ""
				tokenMUL = "*" >> BOUNDARIES;	tokenMUL = "*" >> BOUNDARIES;	#define T_MUL_0 "" #define T_MUL_1 "" #define T_MUL_2 "" #define T_MUL_3 ""
				tokenDIV = "DIV" >> STRICT_BOUNDARIES;	tokenDIV = "DIV" >> STRICT_BOUNDARIES;	#define T_DIV_0 "DIV" #define T_DIV_1 "" #define T_DIV_2 "" #define T_DIV_3 ""
				tokenMOD = "MOD" >> STRICT_BOUNDARIES;	tokenMOD = "MOD" >> STRICT_BOUNDARIES;	#define T_MOD_0 "MOD" #define T_MOD_1 "" #define T_MOD_2 "" #define T_MOD_3 ""
				tokenLRASSIGN = "=:;" >> BOUNDARIES;	tokenLRASSIGN = "=:;" >> BOUNDARIES;	#define T_LRASSIGN_0 "=:;" #define T_LRASSIGN_1 "" #define T_LRASSIGN_2 "" #define T_LRASSIGN_3 ""
						#define T_THEN_BLOCK_0 "{" #define T_THEN_BLOCK_1 "" #define T_THEN_BLOCK_2 "" #define T_THEN_BLOCK_3 ""
				tokenELSE = "ELSE" >> STRICT_BOUNDARIES;	tokenELSE = "ELSE" >> STRICT_BOUNDARIES;	#define T_ELSE_BLOCK_0 "ELSE" #define T_ELSE_BLOCK_1 T_BEGIN_BLOCK_0 #define T_ELSE_BLOCK_2 "" #define T_ELSE_BLOCK_3 ""
				tokenIF = "IF" >> STRICT_BOUNDARIES;	tokenIF = "IF" >> STRICT_BOUNDARIES;	#define T_IF_0 "IF" #define T_IF_1 "" #define T_IF_2 "" #define T_IF_3 ""
						#define T_ELSE_IF_0 "ELSE" #define T_ELSE_IF_1 T_IF_0 #define T_ELSE_IF_2 "" #define T_ELSE_IF_3 ""
				tokenEXIT = "EXIT" >> STRICT_BOUNDARIES;	tokenEXIT = "EXIT" >> STRICT_BOUNDARIES;	#define T_EXIT_0 "EXIT" #define T_EXIT_1 "" #define T_EXIT_2 "" #define T_EXIT_3 ""
				tokenGET = "GET" >> STRICT_BOUNDARIES;	tokenGET = "GET" >> STRICT_BOUNDARIES;	#define T_INPUT_0 "GET" #define T_INPUT_1 "" #define T_INPUT_2 ""

						#define T_INPUT_3 ""
				tokenPUT = "PUT" >> STRICT_BOUNDARIES;	tokenPUT = "PUT" >> STRICT_BOUNDARIES;	#define T_OUTPUT_0 "PUT" #define T_OUTPUT_1 "" #define T_OUTPUT_2 "" #define T_OUTPUT_3 ""
				tokenNAME = "NAME" >> STRICT_BOUNDARIES;	tokenNAME = "NAME" >> STRICT_BOUNDARIES;	#define T_NAME_0 "NAME" #define T_NAME_1 "" #define T_NAME_2 "" #define T_NAME_3 ""
				tokenBODY = "BODY" >> STRICT_BOUNDARIES;	tokenBODY = "BODY" >> STRICT_BOUNDARIES;	#define T_BODY_0 "BODY" #define T_BODY_1 "" #define T_BODY_2 "" #define T_BODY_3 ""
				tokenDATA = "DATA" >> STRICT_BOUNDARIES;	tokenDATA = "DATA" >> STRICT_BOUNDARIES;	#define T_DATA_0 "DATA" #define T_DATA_1 "" #define T_DATA_2 "" #define T_DATA_3 ""
				tokenBEGIN = "BEGIN" >> STRICT_BOUNDARIES;	tokenBEGIN = "BEGIN" >> STRICT_BOUNDARIES;	#define T_BEGIN_0 "BEGIN" #define T_BEGIN_1 "" #define T_BEGIN_2 "" #define T_BEGIN_3 ""
				tokenEND = "END" >> STRICT_BOUNDARIES;	tokenEND = "END" >> STRICT_BOUNDARIES;	#define T_END_0 "END" #define T_END_1 "" #define T_END_2 "" #define T_END_3 ""
						#define T_NULL_STATEMENT_0 "NULL" #define T_NULL_STATEMENT_1 "STATEMENT" #define T_NULL_STATEMENT_2 "" #define T_NULL_STATEMENT_3 ""
						#define GRAMMAR_LL2_2025 {\
labeled_point = ident , ":";	labeled_point = ident , ":";	labeled_point → ident ":"	labeled_point(1: "ident_terminal") → ident ":"	labeled_point = ident >> tokenCOLON;	labeled_point = ident >> tokenCOLON;	{ LA_IS, {"ident_terminal"}, {"labeled_point"}, {\
goto_label = "GOTO" , ident;	goto_label = "GOTO" , ident;	goto_label → "GOTO" ident	goto_label(1: "GOTO") → "GOTO" ident	goto_label = tokenGOTO >> ident;	goto_label = tokenGOTO >> ident;	{ LA_IS, {T_GOTO_0}, {"goto_label"}, {\
program_name = ident;	program_name = ident;	program_name → ident	program_name(1: "ident_terminal") → ident	program_name = SAME_RULE(ident);	program_name = SAME_RULE(ident);	{ LA_IS, {"ident_terminal"}, {"program_name"}, {\
value_type = "INTEGER16";	value_type = "INTEGER16";	value_type → "INTEGER16"	value_type(1: "INTEGER16") → "INTEGER16"	value_type = SAME_RULE(tokenINTEGER16);	value_type = SAME_RULE(tokenINTEGER16);	{ LA_IS, {T_DATA_TYPE_0}, {"value_type"}, {\
	array_specify = "[" , unsigned_value , "]" ;	array_specify → "[" unsigned_value "]"	array_specify(1: "[") → "[" unsigned_value "]"		array_specify = "[" >> unsigned_value >> "]" ;	{ LA_IS, {"["}, {"array_specify"}, {\
declaration_element = ident , ["[" , unsigned_value , "]"] ;	declaration_element = ident , array_specify__optional;	declaration_element → ident array_specify__optional	declaration_element(1: "ident_terminal") → ident array_specify__optional	declaration_element = ident >> -(tokenLEFTSQUAREBRACKETS >> unsigned_value >> tokenRIGHTSQUAREBRACKETS);	declaration_element = ident >> array_specify__optional;	{ LA_IS, {"ident_terminal"}, {"declaration_element"}, {\
	array_specify__optional = array_specify ε;	array_specify__optional → array_specify array_specify__optional → ε	array_specify__optional(1: "[") → array_specify array_specify__optional(1: ! "[") → ε		array_specify__optional = array_specify "";	{ LA_IS, {"["}, {"array_specify__optional"}, {\
other_declaration_ident = " , " , declaration_element;	other_declaration_ident = " , " , declaration_element;	other_declaration_ident → " , " , declaration_element	other_declaration_ident(1: " , ") → " , " , declaration_element	other_declaration_ident = tokenCOMMA >> declaration_element;	other_declaration_ident = tokenCOMMA >> declaration_element;	{ LA_IS, {T_COMA_0}, {"other_declaration_ident"}, {\
declaration = value_type , declaration_element , {other_declaration_ident};	declaration = value_type , declaration_element , other_declaration_ident__iteration;	declaration → value_type declaration_element other_declaration_ident__iteration	declaration(1: "INTEGER16") → value_type declaration_element other_declaration_ident__iteration	declaration = value_type >> declaration_element >> *other_declaration_ident;	declaration = value_type >> declaration_element >> other_declaration_ident__iteration;	{ LA_IS, {T_DATA_TYPE_0}, {"declaration"}, {\
	other_declaration_ident__iteration = other_declaration_ident , other_declaration_ident__iteration ε;	other_declaration_ident__iteration → other_declaration_ident other_declaration_ident__iteration false_cond_block_without_else__iteration → ε	other_declaration_ident__iteration(1: " , ") → other_declaration_ident other_declaration_ident__iteration false_cond_block_without_else__iteration(1: ! " , ") → ε		other_declaration_ident__iteration = other_declaration_ident >> other_declaration_ident__iteration "";	{ LA_IS, {T_COMA_0}, {\
index_action = "[" , expression , "]" ;	index_action = "[" , expression , "]" ;	index_action → "[" expression "]"	index_action(1: "[") → "[" expression "]"	index_action = tokenLEFTSQUAREBRACKETS >> expression >> tokenRIGHTSQUAREBRACKETS;	index_action = tokenLEFTSQUAREBRACKETS >> expression >> tokenRIGHTSQUAREBRACKETS;	{ LA_IS, {"["}, {"index_action"}, {\
unary_operator = "NOT";	unary_operator = "NOT";	unary_operator → "NOT"	unary_operator(1: "NOT") → "NOT"	unary_operator = SAME_RULE(tokenNOT);	unary_operator = SAME_RULE(tokenNOT);	{ LA_IS, {T_NOT_0}, {"unary_operator"}, {\
unary_operation = unary_operator , expression;	unary_operation = unary_operator , expression;	unary_operation → unary_operator expression	unary_operation(1: "NOT") → unary_operator expression	unary_operation = unary_operator >> expression;	unary_operation = unary_operator >> expression;	{ LA_IS, {T_NOT_0}, {"unary_operation"}, {\
binary_operator = "AND" "OR" "==" " =" "<" ">" "+" "-" "*" "DIV" "MOD";	binary_operator = "AND" "OR" "==" " =" "<" ">" "+" "-" "*" "DIV" "MOD";	binary_operator → "AND" binary_operator → "OR" binary_operator → "==" binary_operator → " =" binary_operator → "<" binary_operator → ">" binary_operator → "+" binary_operator → "*" binary_operator → "-" binary_operator → "*" binary_operator → "DIV" binary_operator → "MOD"	binary_operator(1: "AND") → "AND" binary_operator(1: "OR") → "OR" binary_operator(1: "==") → "==" binary_operator(1: " =") → " =" binary_operator(1: "<") → "<" binary_operator(1: ">") → ">" binary_operator(1: "+") → "+" binary_operator(1: "*") → "*" binary_operator(1: "-") → "-" binary_operator(1: "*") → "*" binary_operator(1: "DIV") → "DIV" binary_operator(1: "MOD") → "MOD"	binary_operator = tokenAND tokenOR tokenEQUAL tokenNOTEQUAL tokenLESS tokenGREATER tokenPLUS tokenMINUS tokenMUL tokenDIV tokenMOD;	binary_operator = tokenAND tokenOR tokenEQUAL tokenNOTEQUAL tokenLESS tokenGREATER tokenPLUS tokenMINUS tokenMUL tokenDIV tokenMOD;	{ LA_IS, {T_AND_0}, {"binary_operator"}, {\

			false_cond_block_without_else__iteration(1: !"ELSE") → ε			{LA_NOT, { T_ELSE_IF_1 }, 0, { "" }}\ }};\
	body_for_false__optional = body_for_false ε;	body_for_false__optional → body_for_false body_for_false__optional → ε	body_for_false__optional(1: "FALSE") → body_for_false body_for_false__optional(1: !"FALSE") → ε		body_for_false__optional = body_for_false "";	{LA_IS, { T_ELSE_BLOCK_0 }, { "body_for_false__optional", \\ {LA_IS, {""}, 1, { "body_for_false" }}\} }};\
input_rule = "GET" , (ident , [index_action] "(" , ident , [index_action] , ")");	input_rule = "GET", argument_for_input;	input_rule → "GET" argument_for_input	input_rule(1: "GET") → "GET" argument_for_input	input_rule = tokenGET >> (ident >> -index_action tokenGROUPEXPRESSIONBEGIN >> ident >> -index_action >> tokenGROUPEXPRESSIONEND);	input_rule = tokenGET >> argument_for_input;	{LA_IS, { T_INPUT_0 }, { "input_rule", \\ {LA_IS, {""}, 2, { T_INPUT_0, "argument_for_input" }}\} }};\
	argument_for_input = ident , index_action__optional; argument_for_input = "(" , "ident" , "index_action__optional" , ")" ;	argument_for_input → ident index_action__optional argument_for_input → "(" "ident" "index_action__optional" ")"	argument_for_input(1: "_") → ident index_action__optional argument_for_input(1: "(") → "(" "ident" "index_action__optional" ")"		argument_for_input = ident >> index_action__optional tokenGROUPEXPRESSIONBEGIN >> ident >> index_action__optional >> tokenGROUPEXPRESSIONEND;	{LA_IS, { " ident_terminal " }, { "argument_for_input", \\ {LA_IS, {""}, 2, { "ident", "index_action__optional" }}\} }};\
output_rule = "PUT" , expression;	output_rule = "PUT", expression;	output_rule → "PUT" expression	output(1: "PUT") → "PUT" expression	output_rule = tokenPUT >> expression;	output_rule = tokenPUT >> expression;	{LA_IS, { T_OUTPUT_0 }, { "output_rule", \\ {LA_IS, {""}, 2, { T_OUTPUT_0, "expression" }}\} }};\
statement = labeled_point expression_or_cond_block__with_optional_assign goto_label input_rule output_rule ";;";	statement = labeled_point expression_or_cond_block__with_optional_assign goto_label input_rule output_rule ";;";	statement → labeled_point statement → expression_or_cond_block__with_optional_assign statement → goto_label statement → input_rule statement → output_rule statement → ";"	statement(1: "_" , ":") → labeled_point statement(1: "_" ; 2: !":") → expression_or_cond_block__with_optional_assign statement(1: "(" , "NOT" , "+", "-", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression_or_cond_block__with_optional_assign statement(1: "GOTO") → goto_label statement(1: "GET") → input_rule statement(1: "PUT") → output_rule statement(1: ":") → ";"	statement = labeled_point /* labeled_point first*/ expression_or_cond_block__with_optional_assign goto_label input_rule output_rule tokenSEMICOLON;	statement = labeled_point /* labeled_point first*/ expression_or_cond_block__with_optional_assign goto_label input_rule output_rule tokenSEMICOLON;	{LA_IS, { " ident_terminal " }, { "statement", \\ {LA_IS, { T_COLON_0 }, 1, { "labeled_point" }}\}, \\ {LA_NOT, { T_COLON_0 }, 1, { "expression_or_cond_block__with_optional_assign" }}\} }};\
	statement__iteration = statement, statement__iteration ε;	statement__iteration → statement statement__iteration statement__iteration → ε	statement__iteration(1: "_" , "(" , "NOT" , "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "+", "-", "IF", "GOTO", "GET", "PUT", ":") → statement statement__iteration statement__iteration(1: ! "_" , ! "(" , ! "NOT" , ! "0", ! "1", ! "2", ! "3", ! "4", ! "5", ! "6", ! "7", ! "8", ! "9", ! "+", ! "-", ! "IF", ! "GOTO", ! "GET", ! "PUT", ! ":") → ε		statement__iteration = statement >> statement__iteration "";	{LA_IS, { " ident_terminal " , "(" , T_NOT_0, " unsigned_value_terminal ", T_ADD_0, T_SUB_0, T_IF_0, T_GOTO_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0 }, { "statement__iteration", \\ {LA_IS, {""}, 2, { "statement", "statement__iteration" }}\} }};\
block_statements = "(" , {statement} , ")" ;	block_statements = "(" , statement__iteration , ")";	block_statements → "(" statement__iteration ")"	block_statements(1: "(") → "(" statement__iteration ")"	block_statements = tokenBEGINBLOCK >> *statement >> tokenENDBLOCK;	block_statements = tokenBEGINBLOCK >> statement__iteration >> tokenENDBLOCK;	{LA_IS, { T_BEGIN_BLOCK_0 }, { "block_statements", \\ {LA_IS, {""}, 3, { T_BEGIN_BLOCK_0, "statement__iteration", T_END_BLOCK_0 }}\} }};\
	expression__optional = expression "";	expression__optional → expression expression__optional → ε	expression__optional(1: "(" , "NOT" , "+", "-", "_" , "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression expression__optional(1: ! "(" , ! "NOT" , ! "+", ! "-", ! "_" , ! "0", ! "1", ! "2", ! "3", ! "4", ! "5", ! "6", ! "7", ! "8", ! "9", ! "IF") → ε		expression__optional = expression "";	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "expression__optional", \\ {LA_IS, {""}, 1, { "expression" }}\} }};\
program_rule = "NAME" , program_name , ";" , "BODY" , "DATA" , declaration__optional , ":" , statement__iteration , "END";	program_rule = "NAME", program_name , ";" , "BODY" , "DATA" , declaration__optional , ":" , statement__iteration , "END";	program_rule → "NAME" program_name ";" "BODY" "DATA" declaration__optional ":" statement__iteration "END"	program_rule(1: "NAME") → "NAME" program_name ";" "BODY" "DATA" declaration__optional ":" statement__iteration "END"	program_rule = BOUNDARIES >> tokenNAME >> program_name >> tokenSEMICOLON >> tokenBODY >> tokenDATA >> (- declaration) >> tokenSEMICOLON >> *statement >> tokenEND;	program_rule = BOUNDARIES >> tokenNAME >> program_name >> tokenSEMICOLON >> tokenBODY >> tokenDATA >> declaration__optional >> tokenSEMICOLON >> statement__iteration >> tokenEND;	{LA_IS, { T_NAME_0 }, { "program_rule", \\ {LA_IS, {""}, 9, { T_NAME_0, "program_name", T_SEMICOLON_0, T_BODY_0, T_DATA_0, "declaration__optional", T_SEMICOLON_0, "statement__iteration", T_END_0 }}\} }};\
	declaration__optional = declaration "";	declaration__optional → declaration declaration__optional → ε	declaration__optional(1: "INTEGER16") → declaration declaration__optional(1: !"INTEGER16") → ε		declaration__optional = declaration "";	{LA_IS, { T_DATA_TYPE_0 }, { "declaration__optional", \\ {LA_IS, {""}, 1, { "declaration" }}\} }};\
value = [sign] , unsigned_value;	value = sign__optional, unsigned_value;	value → sign__optional unsigned_value	value(1: "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "+", "-") → sign__optional unsigned_value	value = -sign >> unsigned_value >> BOUNDARIES;	value = sign__optional >> unsigned_value >> BOUNDARIES;	{LA_IS, { "unsigned_value_terminal", T_ADD_0, T_SUB_0 }, { "value", \\ {LA_IS, {""}, 2, { "sign__optional", "unsigned_value" }}\} }};\
	sign__optional = sign ε;	sign__optional → sign sign__optional → ε	sign__optional(1: "+" , "-") → sign sign__optional(1: ! "+" , ! "-") → ε		sign__optional = sign "";	{LA_IS, { T_ADD_0, T_SUB_0 }, { "sign__optional", \\ {LA_IS, {""}, 1, { "sign" }}\} }};\
sign = sign_plus sign_minus;	sign = sign_plus sign_minus;	sign → sign_plus sign → sign_minus	sign(1: "+") → sign_plus sign(1: "-") → sign_minus	sign = sign_plus sign_minus;	sign = sign_plus sign_minus;	{LA_IS, { T_ADD_0 }, { "sign", \\ {LA_IS, {""}, 1, { "sign_plus" }}\} }};\
sign_plus = "+";	sign_plus = "+";	sign_plus → "+"	sign_plus(1: "+") → "+"	sign_plus = SAME_RULE(tokenPLUS);	sign_plus = SAME_RULE(tokenPLUS);	{LA_IS, { T_ADD_0 }, { "sign_plus", \\ {LA_IS, {""}, 1, { T_ADD_0 }}\}

						}}}\
sign_minus = "-";	sign_minus = "-";	sign_minus → "-"	sign_minus(1: "-") → "-"	sign_minus = SAME_RULE(tokenMINUS);	sign_minus = SAME_RULE(tokenMINUS);	{LA_IS, {T_SUB_0 }, { "sign_minus", {\
unsigned_value = non_zero_digit , {digit} "0";	unsigned_value = non_zero_digit , digit__iteration "0";	unsigned_value → non_zero_digit digit__iteration unsigned_value → "0"	unsigned_value(1: "1", "2", "3", "4", "5", "6", "7", "8", "9") → non_zero_digit digit__iteration unsigned_value(1: "0") → "0"	unsigned_value = {non_zero_digit >> *digit digit_0 >> BOUNDARIES;	unsigned_value = {non_zero_digit >> digit__iteration digit_0 >> BOUNDARIES;	/* unsigned_value_token represents unsigned_value in lexical analyzer */\
	digit__iteration = digit, digit__iteration ε;	digit__iteration → digit digit__iteration digit__iteration → ε	digit__iteration(1: "0", "1", "2", "3", "4", "5", "6", "7", "8", "9") → digit digit__iteration digit__iteration(1: !"0", !"1", !"2", !"3", !"4", !"5", !"6", !"7", !"8", !"9") → ε		digit__iteration = digit >> digit__iteration "";	\
digit = "0" non_zero_digit;	digit = "0" non_zero_digit;	digit → "0" digit → non_zero_digit	digit(1: "0") → "0" digit(1: "1", "2", "3", "4", "5", "6", "7", "8", "9",) → non_zero_digit	digit_0 = '0'; digit = digit_0 non_zero_digit;	digit_0 = '0'; digit = digit_0 non_zero_digit;	\
non_zero_digit = "1" "2" "3" "4" "5" "6" "7" "8" "9";	non_zero_digit = "1" "2" "3" "4" "5" "6" "7" "8" "9";	non_zero_digit → "1" non_zero_digit → "2" non_zero_digit → "3" non_zero_digit → "4" non_zero_digit → "5" non_zero_digit → "6" non_zero_digit → "7" non_zero_digit → "8" non_zero_digit → "9"	non_zero_digit(1: "1") → "1" non_zero_digit(1: "2") → "2" non_zero_digit(1: "3") → "3" non_zero_digit(1: "4") → "4" non_zero_digit(1: "5") → "5" non_zero_digit(1: "6") → "6" non_zero_digit(1: "7") → "7" non_zero_digit(1: "8") → "8" non_zero_digit(1: "9") → "9"	digit_1 = '1'; digit_2 = '2'; digit_3 = '3'; digit_4 = '4'; digit_5 = '5'; digit_6 = '6'; digit_7 = '7'; digit_8 = '8'; digit_9 = '9'; non_zero_digit = digit_1 digit_2 digit_3 digit_4 digit_5 digit_6 digit_7 digit_8 digit_9;	digit_1 = '1'; digit_2 = '2'; digit_3 = '3'; digit_4 = '4'; digit_5 = '5'; digit_6 = '6'; digit_7 = '7'; digit_8 = '8'; digit_9 = '9'; non_zero_digit = digit_1 digit_2 digit_3 digit_4 digit_5 digit_6 digit_7 digit_8 digit_9;	\
ident = "_", letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case ;	ident = "_", letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case ;	ident → "_" letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case	Ident(1: "_") → "_" letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case	tokenUNDERSCORE = "_"; ident = {! tokenCOLON tokenGOTO tokenINTEGER16 tokenCOMMA tokenNOT tokenAND tokenOR tokenEQUAL tokenNOTEQUAL tokenLESS tokenGREATER tokenPLUS tokenMINUS tokenMUL tokenDIV tokenMOD tokenGROUPEXPRESSIONBEGIN tokenGROUPEXPRESSIONEND tokenLRASSIGN tokenELSE tokenIF tokenEXIT tokenGET tokenPUT tokenNAME tokenBODY tokenDATA tokenBEGIN tokenEND tokenBEGINBLOCK tokenENDBLOCK tokenLEFTSQUAREBRACKETS tokenRIGHTSQUAREBRACKETS tokenSEMICOLON }>> tokenUNDERSCORE >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> STRICT_BOUNDARIES;	tokenUNDERSCORE = "_"; ident = {! tokenCOLON tokenGOTO tokenINTEGER16 tokenCOMMA tokenNOT tokenAND tokenOR tokenEQUAL tokenNOTEQUAL tokenLESS tokenGREATER tokenPLUS tokenMINUS tokenMUL tokenDIV tokenMOD tokenGROUPEXPRESSIONBEGIN tokenGROUPEXPRESSIONEND tokenLRASSIGN tokenELSE tokenIF tokenEXIT tokenGET tokenPUT tokenNAME tokenBODY tokenDATA tokenBEGIN tokenEND tokenBEGINBLOCK tokenENDBLOCK tokenLEFTSQUAREBRACKETS tokenRIGHTSQUAREBRACKETS tokenSEMICOLON }>> tokenUNDERSCORE >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> STRICT_BOUNDARIES;	/* ident_token represents ident in lexical analyzer */\
letter_in_lower_case = "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z";	letter_in_lower_case = "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z";	letter_in_lower_case → "a" letter_in_lower_case → "b" letter_in_lower_case → "c" letter_in_lower_case → "d" letter_in_lower_case → "e" letter_in_lower_case → "f" letter_in_lower_case → "g" letter_in_lower_case → "h" letter_in_lower_case → "i" letter_in_lower_case → "j" letter_in_lower_case → "k" letter_in_lower_case → "l" letter_in_lower_case → "m" letter_in_lower_case → "n" letter_in_lower_case → "o" letter_in_lower_case → "p" letter_in_lower_case → "q" letter_in_lower_case → "r" letter_in_lower_case → "s" letter_in_lower_case → "t" letter_in_lower_case → "u" letter_in_lower_case → "v" letter_in_lower_case → "w" letter_in_lower_case → "x" letter_in_lower_case → "y" letter_in_lower_case → "z"	letter_in_lower_case(1: "a") → "a" letter_in_lower_case(1: "b") → "b" letter_in_lower_case(1: "c") → "c" letter_in_lower_case(1: "d") → "d" letter_in_lower_case(1: "e") → "e" letter_in_lower_case(1: "f") → "f" letter_in_lower_case(1: "g") → "g" letter_in_lower_case(1: "h") → "h" letter_in_lower_case(1: "i") → "i" letter_in_lower_case(1: "j") → "j" letter_in_lower_case(1: "k") → "k" letter_in_lower_case(1: "l") → "l" letter_in_lower_case(1: "m") → "m" letter_in_lower_case(1: "n") → "n" letter_in_lower_case(1: "o") → "o" letter_in_lower_case(1: "p") → "p" letter_in_lower_case(1: "q") → "q" letter_in_lower_case(1: "r") → "r" letter_in_lower_case(1: "s") → "s" letter_in_lower_case(1: "t") → "t" letter_in_lower_case(1: "u") → "u" letter_in_lower_case(1: "v") → "v" letter_in_lower_case(1: "w") → "w" letter_in_lower_case(1: "x") → "x" letter_in_lower_case(1: "y") → "y" letter_in_lower_case(1: "z") → "z"	A = "A"; B = "B"; C = "C"; D = "D"; E = "E"; F = "F"; G = "G"; H = "H"; I = "I"; J = "J"; K = "K"; L = "L"; M = "M"; N = "N"; O = "O"; P = "P"; Q = "Q"; R = "R"; S = "S"; T = "T"; U = "U"; V = "V"; W = "W"; X = "X"; Y = "Y"; Z = "Z"; letter_in_lower_case = a b c d e f g h i j k l m n o p q r s t u v w x y z;	A = "A"; B = "B"; C = "C"; D = "D"; E = "E"; F = "F"; G = "G"; H = "H"; I = "I"; J = "J"; K = "K"; L = "L"; M = "M"; N = "N"; O = "O"; P = "P"; Q = "Q"; R = "R"; S = "S"; T = "T"; U = "U"; V = "V"; W = "W"; X = "X"; Y = "Y"; Z = "Z"; letter_in_lower_case = a b c d e f g h i j k l l m n o p q r s t u v w x y z;	\
letter_in_upper_case = "A" "B" "C" "D" "E" "F" "G" "H" "I" "J" "K" "L" "M" "N" "O" "P" "Q" "R" "S" "T" "U" "V" "W" "X" "Y" "Z";	letter_in_upper_case = "A" "B" "C" "D" "E" "F" "G" "H" "I" "J" "K" "L" "M" "N" "O" "P" "Q" "R" "S" "T" "U" "V" "W" "X" "Y" "Z";	letter_in_upper_case → "A" letter_in_upper_case → "B" letter_in_upper_case → "C" letter_in_upper_case → "D" letter_in_upper_case → "E" letter_in_upper_case → "F" letter_in_upper_case → "G" letter_in_upper_case → "H"	letter_in_upper_case(1: "A") → "A" letter_in_upper_case(1: "B") → "B" letter_in_upper_case(1: "C") → "C" letter_in_upper_case(1: "D") → "D" letter_in_upper_case(1: "E") → "E" letter_in_upper_case(1: "F") → "F" letter_in_upper_case(1: "G") → "G" letter_in_upper_case(1: "H") → "H"	a = "a"; b = "b"; c = "c"; d = "d"; e = "e"; f = "f"; g = "g"; h = "h";	a = "a"; b = "b"; c = "c"; d = "d"; e = "e"; f = "f"; g = "g"; h = "h";	\

		letter_in_upper_case → "I" letter_in_upper_case → "J" letter_in_upper_case → "K" letter_in_upper_case → "L" letter_in_upper_case → "M" letter_in_upper_case → "N" letter_in_upper_case → "O" letter_in_upper_case → "P" letter_in_upper_case → "Q" letter_in_upper_case → "R" letter_in_upper_case → "S" letter_in_upper_case → "T" letter_in_upper_case → "U" letter_in_upper_case → "V" letter_in_upper_case → "W" letter_in_upper_case → "X" letter_in_upper_case → "Y" letter_in_upper_case → "Z"	letter_in_upper_case(1: "I") → "I" letter_in_upper_case(1: "J") → "J" letter_in_upper_case(1: "K") → "K" letter_in_upper_case(1: "L") → "L" letter_in_upper_case(1: "M") → "M" letter_in_upper_case(1: "N") → "N" letter_in_upper_case(1: "O") → "O" letter_in_upper_case(1: "P") → "P" letter_in_upper_case(1: "Q") → "Q" letter_in_upper_case(1: "R") → "R" letter_in_upper_case(1: "S") → "S" letter_in_upper_case(1: "T") → "T" letter_in_upper_case(1: "U") → "U" letter_in_upper_case(1: "V") → "V" letter_in_upper_case(1: "W") → "W" letter_in_upper_case(1: "X") → "X" letter_in_upper_case(1: "Y") → "Y" letter_in_upper_case(1: "Z") → "Z"	i = "i"; j = "j"; k = "k"; l = "l"; m = "m"; n = "n"; o = "o"; p = "p"; q = "q"; r = "r"; s = "s"; t = "t"; u = "u"; v = "v"; w = "w"; x = "x"; y = "y"; z = "z"; letter_in_upper_case = A B C D E F G H I J K L M N O P Q R S T U V W X Y Z;	i = "i"; j = "j"; k = "k"; l = "l"; m = "m"; n = "n"; o = "o"; p = "p"; q = "q"; r = "r"; s = "s"; t = "t"; u = "u"; v = "v"; w = "w"; x = "x"; y = "y"; z = "z"; letter_in_upper_case = A B C D E F G H I J K L M N O P Q R S T U V W X Y Z;	
				STRICT_BOUNDARIES = (BOUNDARY >> *(BOUNDARY)) (!(qi::alpha qi::char_("_ "))); BOUNDARIES = (BOUNDARY >> *(BOUNDARY) NO_BOUNDARY); BOUNDARY = BOUNDARY__SPACE BOUNDARY__TAB BOUNDARY__VERTICAL_TAB BOUNDARY__FORM_FEED BOUNDARY__CARRIAGE_RETURN BOUNDARY__LINE_FEED BOUNDARY__NULL; BOUNDARY__SPACE = " "; BOUNDARY__TAB = "t"; BOUNDARY__VERTICAL_TAB = "v"; BOUNDARY__FORM_FEED = "f"; BOUNDARY__CARRIAGE_RETURN = "r"; BOUNDARY__LINE_FEED = "n"; BOUNDARY__NULL = "\0"; NO_BOUNDARY = ""; #define WHITESPACES \ STRICT_BOUNDARIES, \ BOUNDARIES, \ BOUNDARY, \ BOUNDARY__SPACE, \ BOUNDARY__TAB, \ BOUNDARY__VERTICAL_TAB, \ BOUNDARY__FORM_FEED, \ BOUNDARY__CARRIAGE_RETURN, \ BOUNDARY__LINE_FEED, \ BOUNDARY__NULL, \ NO_BOUNDARY	STRICT_BOUNDARIES = (BOUNDARY >> *(BOUNDARY)) (!(qi::alpha qi::char_("_ "))); BOUNDARIES = (BOUNDARY >> *(BOUNDARY) NO_BOUNDARY); BOUNDARY = BOUNDARY__SPACE BOUNDARY__TAB BOUNDARY__VERTICAL_TAB BOUNDARY__FORM_FEED BOUNDARY__CARRIAGE_RETURN BOUNDARY__LINE_FEED BOUNDARY__NULL; BOUNDARY__SPACE = " "; BOUNDARY__TAB = "t"; BOUNDARY__VERTICAL_TAB = "v"; BOUNDARY__FORM_FEED = "f"; BOUNDARY__CARRIAGE_RETURN = "r"; BOUNDARY__LINE_FEED = "n"; BOUNDARY__NULL = "\0"; NO_BOUNDARY = ""; #define WHITESPACES \ STRICT_BOUNDARIES, \ BOUNDARIES, \ BOUNDARY, \ BOUNDARY__SPACE, \ BOUNDARY__TAB, \ BOUNDARY__VERTICAL_TAB, \ BOUNDARY__FORM_FEED, \ BOUNDARY__CARRIAGE_RETURN, \ BOUNDARY__LINE_FEED, \ BOUNDARY__NULL, \ NO_BOUNDARY	\ \ \ { LA_IS, { T_NAME_0 }, { "program____part1", { { LA_IS, { "" }, 7, { T_NAME_0, "program_name", T_SEMICOLON_0, T_BODY_0, T_DATA_0, "declaration_optional", T_SEMICOLON_0 } } } } \ } \ } \ "program_rule"
						\ \ \ { LA_IS, { T_NAME_0 }, { "program____part1", { { LA_IS, { "" }, 7, { T_NAME_0, "program_name", T_SEMICOLON_0, T_BODY_0, T_DATA_0, "declaration_optional", T_SEMICOLON_0 } } } \ } } } \ } \ } \ "program_rule"