

епРБНФ №1 (опис синтаксису всіма допустимими засобами РБНФ)	РБНФ №2 (опис формальної граматики засобами РБНФ)	Формальна граматика	Формальна граматика з специфікацією lookahead у правилах для LL(2)-аналізатора	/* Перевірка РБНФ №1 за допомогою коду (помістити у файл "EBNF_N1.h") */	/* Перевірка РБНФ №2 за допомогою коду (помістити у файл "EBNF_N2.h") */	/* Перевірка прототипу LL(2)-синтаксичного аналізатора (спеціальна структура) та прототипу лексичного аналізатора (регулярні вирази) за допомогою коду. Лексеми для синтаксичного аналізатора обробляються лексичним аналізатором, тому синтаксичний аналізатор не аналізує їх повторно (як показано в РБНФ). (помістити у файл "LexicaByRegExAndSyntaxByLL2protototype.h") УВАГА: при копіюванні зважайте, щоб у кожному рядку після символу «\» не містилось жодних інших символів. */
		G = {N, T, P, S}	G = {N, T, P, S}			
		S → program_rule	S → program_rule			
		N = { labeled_point, goto_label, program_name, value_type, array_specify, declaration_element, array_specify_optional, other_declaration_ident, declaration, other_declaration_ident_iteration, index_action, unary_operator, unary_operation, binary_operator, binary_action, left_expression, group_expression, index_action_optional, expression, binary_action_iteration, expression_or_cond_block_with_optional_assign, assign_to_right, assign_to_right_optional, if_expression, body_for_true, false_cond_block_without_else, body_for_false, cond_block, false_cond_block_without_else_iteration, body_for_false_optional, cycle_begin_expression, cycle_end_expression, cycle_counter, cycle_counter_lr_init, cycle_counter_init, cycle_counter_last_value, cycle_body, forto_direction, forto_cycle, continue_while, break_while, statement_in_while_and_if_body, statement, block_statements_in_while_and_if_body, statement_in_while_and_if_body_iteration, while_cycle_head_expression, while_cycle, repeat_until_cycle_cond, repeat_until_cycle, statements_or_block_statements, block_statements, input_rule, argument_for_input, output_rule, statement_iteration, expression_optional, program_rule, declaration_optional, non_zero_digit, digit_iteration, digit, unsigned_value, value, sign_optional, sign, ident, letter_in_upper_case, letter_in_lower_case, sign_plus, sign_minus }	N = { labeled_point, goto_label, program_name, value_type, array_specify, declaration_element, array_specify_optional, other_declaration_ident, declaration, other_declaration_ident_iteration, index_action, unary_operator, unary_operation, binary_operator, binary_action, left_expression, group_expression, index_action_optional, expression, binary_action_iteration, expression_or_cond_block_with_optional_assign, assign_to_right, assign_to_right_optional, if_expression, body_for_true, false_cond_block_without_else, body_for_false, cond_block, false_cond_block_without_else_iteration, body_for_false_optional, cycle_begin_expression, cycle_end_expression, cycle_counter, cycle_counter_lr_init, cycle_counter_init, cycle_counter_last_value, cycle_body, forto_direction, forto_cycle, continue_while, break_while, statement_in_while_and_if_body, statement, block_statements_in_while_and_if_body, statement_in_while_and_if_body_iteration, while_cycle_head_expression, while_cycle, repeat_until_cycle_cond, repeat_until_cycle, statements_or_block_statements, block_statements, input_rule, argument_for_input, output_rule, statement_iteration, expression_optional, program_rule, declaration_optional, non_zero_digit, digit_iteration, digit, unsigned_value, value, sign_optional, sign, ident, letter_in_upper_case, letter_in_lower_case, sign_plus, sign_minus }	#define NONTERMINALS labeled_point, \ goto_label, \ program_name, \ value_type, \ array_specify, \ declaration_element, \ \ other_declaration_ident, \ declaration, \ \ index_action, \ unary_operator, \ unary_operation, \ binary_operator, \ binary_action, \ left_expression, \ group_expression, \ \ expression, \ \ expression_or_cond_block_with_optional_assign, \ assign_to_right, \ \ if_expression, \ body_for_true, \ false_cond_block_without_else, \ body_for_false, \ cond_block, \ \ cycle_begin_expression, \ cycle_end_expression, \ cycle_counter, \ cycle_counter_lr_init, \ cycle_counter_init, \ cycle_counter_last_value, \ cycle_body, \ forto_direction, \ forto_cycle, \ continue_while, \ break_while, \ statement_in_while_and_if_body, \ statement, \ block_statements_in_while_and_if_body, \ \ while_cycle_head_expression, \ while_cycle, \ repeat_until_cycle_cond, \ repeat_until_cycle, \ statements_or_block_statements, \ block_statements, \ input_rule, \ argument_for_input, \ output_rule, \ \ \ program_rule, \ \ non_zero_digit, \ digit_iteration, \ digit, \ unsigned_value, \ value, \ \ sign, \ ident, \ letter_in_upper_case, \ letter_in_lower_case, \ sign_plus, \ sign_minus \ \ #define TOKENS \ tokenCOLON, \ tokenGOTO, \ \ #define NONTERMINALS labeled_point, \ goto_label, \ program_name, \ value_type, \ array_specify, \ declaration_element, \ array_specify_optional, \ other_declaration_ident, \ declaration, \ other_declaration_ident_iteration, \ index_action, \ unary_operator, \ unary_operation, \ binary_operator, \ binary_action, \ left_expression, \ group_expression, \ index_action_optional, \ expression, \ binary_action_iteration, \ expression_or_cond_block_with_optional_assign, \ assign_to_right, \ assign_to_right_optional, \ if_expression, \ body_for_true, \ false_cond_block_without_else, \ body_for_false, \ cond_block, \ false_cond_block_without_else_iteration, \ body_for_false_optional, \ cycle_begin_expression, \ cycle_end_expression, \ cycle_counter, \ cycle_counter_lr_init, \ cycle_counter_init, \ cycle_counter_last_value, \ cycle_body, \ forto_direction, \ forto_cycle, \ continue_while, \ break_while, \ statement_in_while_and_if_body, \ statement, \ block_statements_in_while_and_if_body, \ statement_in_while_and_if_body_iteration, \ while_cycle_head_expression, \ while_cycle, \ repeat_until_cycle_cond, \ repeat_until_cycle, \ statements_or_block_statements, \ block_statements, \ input_rule, \ argument_for_input, \ output_rule, \ statement_iteration, \ expression_optional, \ program_rule, \ declaration_optional, \ non_zero_digit, \ digit_iteration, \ digit, \ unsigned_value, \ value, \ sign_optional, \ sign, \ ident, \ letter_in_upper_case, \ letter_in_lower_case, \ sign_plus, \ sign_minus		
		T = { ";", "GOTO",	T = { ";", "GOTO",			

		<pre>"INTEGER16", " ", "NOT", "AND", "OR", "==", "!=", "<=", ">=", "+", "-", "*", "/", "DIV", "MOD", "(", ")", "=", "ELSE", "IF", "DO", "FOR", "TO", "DOWNT0", "WHILE", "CONTINUE", "BREAK", "EXIT", "REPEAT", "UNTIL", "GET", "PUT", "NAME", "BODY", "DATA", "BEGIN", "END", "[", "]", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", " ", " ", "A", "B", "C", "D", "E", "F", "G", "H", "I", "J", "K", "L", "M", "N", "O", "P", "Q", "R", "S", "T", "U", "V", "W", "X", "Y", "Z", "a", "b", "c", "d", "e", "f", "g", "h", "i", "j", "k", "l", "m", "n", "o", "p", "q", "r", "s", "t", "u", "v", "w", "x", "y", "z" }</pre>	<pre>"INTEGER16", " ", "NOT", "AND", "OR", "==", "!=", "<=", ">=", "+", "-", "*", "/", "DIV", "MOD", "(", ")", "=", "ELSE", "IF", "DO", "FOR", "TO", "DOWNT0", "WHILE", "CONTINUE", "BREAK", "EXIT", "REPEAT", "UNTIL", "GET", "PUT", "NAME", "BODY", "DATA", "BEGIN", "END", "[", "]", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", " ", " ", "A", "B", "C", "D", "E", "F", "G", "H", "I", "J", "K", "L", "M", "N", "O", "P", "Q", "R", "S", "T", "U", "V", "W", "X", "Y", "Z", "a", "b", "c", "d", "e", "f", "g", "h", "i", "j", "k", "l", "m", "n", "o", "p", "q", "r", "s", "t", "u", "v", "w", "x", "y", "z" }</pre>	<pre>tokenINTEGER16, \ tokenCOMMA, \ tokenNOT, \ tokenAND, \ tokenOR, \ tokenEQUAL, \ tokenNOTEQUAL, \ tokenLESSOREQUAL, \ tokenGREATEROREQUAL, \ tokenPLUS, \ tokenMINUS, \ tokenMUL, \ tokenDIV, \ tokenMOD, \ tokenGROUPEXPRESSIONBEGIN, \ tokenGROUPEXPRESSIONEND, \ tokenLRASSIGN, \ tokenELSE, \ tokenIF, \ tokenDO, \ tokenFOR, \ tokenTO, \ tokenDOWNT0, \ tokenWHILE, \ tokenCONTINUE, \ tokenBREAK, \ tokenEXIT, \ tokenREPEAT, \ tokenUNTIL, \ tokenGET, \ tokenPUT, \ tokenNAME, \ tokenBODY, \ tokenDATA, \ tokenBEGIN, \ tokenEND, \ tokenBEGINBLOCK, \ tokenENDBLOCK, \ tokenLEFTSQUAREBRACKETS, \ tokenRIGHTSQUAREBRACKETS, \ tokenSEMICOLON, \ digit_0, \ digit_1, \ digit_2, \ digit_3, \ digit_4, \ digit_5, \ digit_6, \ digit_7, \ digit_8, \ digit_9, \ tokenUNDERSCORE, \ A, \ B, \ C, \ D, \ E, \ F, \ G, \ H, \ I, \ J, \ K, \ L, \ M, \ N, \ O, \ P, \ Q, \ R, \ S, \ T, \ U, \ V, \ W, \ X, \ Y, \ Z, \ a, \ b, \ c, \ d, \ e, \ f, \ g, \ h, \ i, \ j, \ k, \ l, \ m, \ n, \ o, \ p, \ q, \ r, \ s, \ t, \ u, \ v, \ w, \ x, \ y, \ z</pre>	<pre>tokenINTEGER16, \ tokenCOMMA, \ tokenNOT, \ tokenAND, \ tokenOR, \ tokenEQUAL, \ tokenNOTEQUAL, \ tokenLESSOREQUAL, \ tokenGREATEROREQUAL, \ tokenPLUS, \ tokenMINUS, \ tokenMUL, \ tokenDIV, \ tokenMOD, \ tokenGROUPEXPRESSIONBEGIN, \ tokenGROUPEXPRESSIONEND, \ tokenLRASSIGN, \ tokenELSE, \ tokenIF, \ tokenDO, \ tokenFOR, \ tokenTO, \ tokenDOWNT0, \ tokenWHILE, \ tokenCONTINUE, \ tokenBREAK, \ tokenEXIT, \ tokenREPEAT, \ tokenUNTIL, \ tokenGET, \ tokenPUT, \ tokenNAME, \ tokenBODY, \ tokenDATA, \ tokenBEGIN, \ tokenEND, \ tokenBEGINBLOCK, \ tokenENDBLOCK, \ tokenLEFTSQUAREBRACKETS, \ tokenRIGHTSQUAREBRACKETS, \ tokenSEMICOLON, \ digit_0, \ digit_1, \ digit_2, \ digit_3, \ digit_4, \ digit_5, \ digit_6, \ digit_7, \ digit_8, \ digit_9, \ tokenUNDERSCORE, \ A, \ B, \ C, \ D, \ E, \ F, \ G, \ H, \ I, \ J, \ K, \ L, \ M, \ N, \ O, \ P, \ Q, \ R, \ S, \ T, \ U, \ V, \ W, \ X, \ Y, \ Z, \ a, \ b, \ c, \ d, \ e, \ f, \ g, \ h, \ i, \ j, \ k, \ l, \ m, \ n, \ o, \ p, \ q, \ r, \ s, \ t, \ u, \ v, \ w, \ x, \ y, \ z</pre>	<pre>#define COMMENT_BEGIN_STR "##" #define COMMENT_END_STR "##" #define COMMENT_BEGIN_STR "##" #define COMMENT_END_STR "##" #define TOKENS_RE ";:=[<=> \\+ - * . , < > { \\[\\] \\(\\ \\) < > [L_0-9A-Za-z]+ \\{^\\ \\ \\w\\n\\}"</pre>
--	--	--	--	---	---	--

						#define T_BEGIN_GROUPEXPRESSION_0 "(" #define T_BEGIN_GROUPEXPRESSION_1 "" #define T_BEGIN_GROUPEXPRESSION_2 "" #define T_BEGIN_GROUPEXPRESSION_3 ""
						#define T_END_GROUPEXPRESSION_0 ")" #define T_END_GROUPEXPRESSION_1 "" #define T_END_GROUPEXPRESSION_2 "" #define T_END_GROUPEXPRESSION_3 ""
						#define T_LEFT_SQUAREBRACKETS_0 "[" #define T_LEFT_SQUAREBRACKETS_1 "" #define T_LEFT_SQUAREBRACKETS_2 "" #define T_LEFT_SQUAREBRACKETS_3 ""
						#define T_RIGHT_SQUAREBRACKETS_0 "]" #define T_RIGHT_SQUAREBRACKETS_1 "" #define T_RIGHT_SQUAREBRACKETS_2 "" #define T_RIGHT_SQUAREBRACKETS_3 ""
						#define T_BEGIN_BLOCK_0 "{" #define T_BEGIN_BLOCK_1 "" #define T_BEGIN_BLOCK_2 "" #define T_BEGIN_BLOCK_3 ""
						#define T_END_BLOCK_0 "}" #define T_END_BLOCK_1 "" #define T_END_BLOCK_2 "" #define T_END_BLOCK_3 ""
						#define T_SEMICOLON_0 ";" #define T_SEMICOLON_1 "" #define T_SEMICOLON_2 "" #define T_SEMICOLON_3 ""
						#define T_COLON_0 ":" #define T_COLON_1 "" #define T_COLON_2 "" #define T_COLON_3 ""
						#define T_GOTO_0 "GOTO" #define T_GOTO_1 "" #define T_GOTO_2 "" #define T_GOTO_3 ""
						#define T_DATA_TYPE_0 "INTEGER16" #define T_DATA_TYPE_1 "" #define T_DATA_TYPE_2 "" #define T_DATA_TYPE_3 ""
						#define T_COMA_0 "," #define T_COMA_1 "" #define T_COMA_2 "" #define T_COMA_3 ""
						#define T_BITWISE_NOT_0 "~" #define T_BITWISE_NOT_1 "" #define T_BITWISE_NOT_2 "" #define T_BITWISE_NOT_3 ""
						#define T_NOT_0 "NOT" #define T_NOT_1 "" #define T_NOT_2 "" #define T_NOT_3 ""
						#define T_BITWISE_AND_0 "&" #define T_BITWISE_AND_1 "" #define T_BITWISE_AND_2 "" #define T_BITWISE_AND_3 ""
						#define T_AND_0 "AND" #define T_AND_1 "" #define T_AND_2 "" #define T_AND_3 ""
						#define T_BITWISE_OR_0 " " #define T_BITWISE_OR_1 "" #define T_BITWISE_OR_2 "" #define T_BITWISE_OR_3 ""
						#define T_OR_0 "OR" #define T_OR_1 "" #define T_OR_2 "" #define T_OR_3 ""
						#define T_EQUAL_0 "=" #define T_EQUAL_1 "" #define T_EQUAL_2 "" #define T_EQUAL_3 ""
						#define T_NOT_EQUAL_0 "!=" #define T_NOT_EQUAL_1 "" #define T_NOT_EQUAL_2 "" #define T_NOT_EQUAL_3 ""
						#define T_LESS_OR_EQUAL_0 "<=" #define T_LESS_OR_EQUAL_1 "" #define T_LESS_OR_EQUAL_2 "" #define T_LESS_OR_EQUAL_3 ""
						#define T_GREATER_OR_EQUAL_0 ">=" #define T_GREATER_OR_EQUAL_1 "" #define T_GREATER_OR_EQUAL_2 "" #define T_GREATER_OR_EQUAL_3 ""
						#define T_ADD_0 "+" #define T_ADD_1 "" #define T_ADD_2 "" #define T_ADD_3 ""
						#define T_SUB_0 "-" #define T_SUB_1 "" #define T_SUB_2 "" #define T_SUB_3 ""
						#define T_MUL_0 "*" #define T_MUL_1 "" #define T_MUL_2 "" #define T_MUL_3 ""
						#define T_DIV_0 "DIV" #define T_DIV_1 "" #define T_DIV_2 "" #define T_DIV_3 ""
						#define T_MOD_0 "MOD" #define T_MOD_1 ""

						#define T_MOD_2 "" #define T_MOD_3 ""
				tokenLRASSIGN = "=" >> BOUNDARIES;	tokenLRASSIGN = "=" >> BOUNDARIES;	#define T_LRASSIGN_0 "=" #define T_LRASSIGN_1 "" #define T_LRASSIGN_2 "" #define T_LRASSIGN_3 ""
						#define T_THEN_BLOCK_0 "[" #define T_THEN_BLOCK_1 "" #define T_THEN_BLOCK_2 "" #define T_THEN_BLOCK_3 ""
				tokenELSE = "ELSE" >> STRICT_BOUNDARIES;	tokenELSE = "ELSE" >> STRICT_BOUNDARIES;	#define T_ELSE_BLOCK_0 "ELSE" #define T_ELSE_BLOCK_1 T_BEGIN_BLOCK_0 #define T_ELSE_BLOCK_2 "" #define T_ELSE_BLOCK_3 ""
				tokenIF = "IF" >> STRICT_BOUNDARIES;	tokenIF = "IF" >> STRICT_BOUNDARIES;	#define T_IF_0 "IF" #define T_IF_1 "" #define T_IF_2 "" #define T_IF_3 ""
						#define T_ELSE_IF_0 T_ELSE_BLOCK_0 #define T_ELSE_IF_1 T_IF_0 #define T_ELSE_IF_2 "" #define T_ELSE_IF_3 ""
				tokenDO = "DO" >> STRICT_BOUNDARIES;	tokenDO = "DO" >> STRICT_BOUNDARIES;	#define T_DO_0 "DO" #define T_DO_1 "" #define T_DO_2 "" #define T_DO_3 ""
				tokenFOR = "FOR" >> STRICT_BOUNDARIES;	tokenFOR = "FOR" >> STRICT_BOUNDARIES;	#define T_FOR_0 "FOR" #define T_FOR_1 "" #define T_FOR_2 "" #define T_FOR_3 ""
				tokenTO = "TO" >> STRICT_BOUNDARIES;	tokenTO = "TO" >> STRICT_BOUNDARIES;	#define T_TO_0 "TO" #define T_TO_1 "" #define T_TO_2 "" #define T_TO_3 ""
				tokenDOWNT0 = "DOWNT0" >> STRICT_BOUNDARIES;	tokenDOWNT0 = "DOWNT0" >> STRICT_BOUNDARIES;	#define T_DOWNT0_0 "DOWNT0" #define T_DOWNT0_1 "" #define T_DOWNT0_2 "" #define T_DOWNT0_3 ""
				tokenWHILE = "WHILE" >> STRICT_BOUNDARIES;	tokenWHILE = "WHILE" >> STRICT_BOUNDARIES;	#define T_WHILE_0 "WHILE" #define T_WHILE_1 "" #define T_WHILE_2 "" #define T_WHILE_3 ""
				tokenCONTINUE = "CONTINUE" >> STRICT_BOUNDARIES;	tokenCONTINUE = "CONTINUE" >> STRICT_BOUNDARIES;	#define T_CONTINUE_WHILE_0 "CONTINUE" #define T_CONTINUE_WHILE_1 "" #define T_CONTINUE_WHILE_2 "" #define T_CONTINUE_WHILE_3 ""
				tokenBREAK = "BREAK" >> STRICT_BOUNDARIES;	tokenBREAK = "BREAK" >> STRICT_BOUNDARIES;	#define T_EXIT_WHILE_0 "BREAK" #define T_EXIT_WHILE_1 "" #define T_EXIT_WHILE_2 "" #define T_EXIT_WHILE_3 ""
				tokenEXIT = "EXIT" >> STRICT_BOUNDARIES;	tokenEXIT = "EXIT" >> STRICT_BOUNDARIES;	#define T_EXIT_0 "EXIT" #define T_EXIT_1 "" #define T_EXIT_2 "" #define T_EXIT_3 ""
				tokenREPEAT = "REPEAT" >> STRICT_BOUNDARIES;	tokenREPEAT = "REPEAT" >> STRICT_BOUNDARIES;	#define T_REPEAT_0 "REPEAT" #define T_REPEAT_1 "" #define T_REPEAT_2 "" #define T_REPEAT_3 ""
				tokenUNTIL = "UNTIL" >> STRICT_BOUNDARIES;	tokenUNTIL = "UNTIL" >> STRICT_BOUNDARIES;	#define T_UNTIL_0 "UNTIL" #define T_UNTIL_1 "" #define T_UNTIL_2 "" #define T_UNTIL_3 ""
				tokenGET = "GET" >> STRICT_BOUNDARIES;	tokenGET = "GET" >> STRICT_BOUNDARIES;	#define T_INPUT_0 "GET" #define T_INPUT_1 "" #define T_INPUT_2 "" #define T_INPUT_3 ""
				tokenPUT = "PUT" >> STRICT_BOUNDARIES;	tokenPUT = "PUT" >> STRICT_BOUNDARIES;	#define T_OUTPUT_0 "PUT" #define T_OUTPUT_1 "" #define T_OUTPUT_2 "" #define T_OUTPUT_3 ""
				tokenNAME = "NAME" >> STRICT_BOUNDARIES;	tokenNAME = "NAME" >> STRICT_BOUNDARIES;	#define T_NAME_0 "NAME" #define T_NAME_1 "" #define T_NAME_2 "" #define T_NAME_3 ""
				tokenBODY = "BODY" >> STRICT_BOUNDARIES;	tokenBODY = "BODY" >> STRICT_BOUNDARIES;	#define T_BODY_0 "BODY" #define T_BODY_1 "" #define T_BODY_2 "" #define T_BODY_3 ""
				tokenDATA = "DATA" >> STRICT_BOUNDARIES;	tokenDATA = "DATA" >> STRICT_BOUNDARIES;	#define T_DATA_0 "DATA" #define T_DATA_1 "" #define T_DATA_2 "" #define T_DATA_3 ""
				tokenBEGIN = "BEGIN" >> STRICT_BOUNDARIES;	tokenBEGIN = "BEGIN" >> STRICT_BOUNDARIES;	#define T_BEGIN_0 "BEGIN" #define T_BEGIN_1 "" #define T_BEGIN_2 "" #define T_BEGIN_3 ""
				tokenEND = "END" >> STRICT_BOUNDARIES;	tokenEND = "END" >> STRICT_BOUNDARIES;	#define T_END_0 "END" #define T_END_1 "" #define T_END_2 "" #define T_END_3 ""
						#define T_NULL_STATEMENT_0 "NULL" #define T_NULL_STATEMENT_1 "STATEMENT" #define T_NULL_STATEMENT_2 "" #define T_NULL_STATEMENT_3 ""
						#define GRAMMAR_LL2__2025 {\
labeled_point = ident , ",";	labeled_point = ident , ",";	labeled_point → ident ":"	labeled_point(1: "ident_terminal") → ident ":"	labeled_point = ident >> tokenCOLON;	labeled_point = ident >> tokenCOLON;	{ LA_IS, {"ident_terminal"}, {"labeled_point"}, {\
goto_label = "GOTO" , ident;	goto_label = "GOTO" , ident;	goto_label → "GOTO" ident	goto_label(1: "GOTO") → "GOTO" ident	goto_label = tokenGOTO >> ident;	goto_label = tokenGOTO >> ident;	{ LA_IS, {T_GOTO_0}, {"goto_label"}, {\
program_name = ident;	program_name = ident;	program_name → ident	program_name(1: "ident_terminal") → ident	program_name = SAME_RULE{ident};	program_name = SAME_RULE{ident};	{ LA_IS, {"ident_terminal"}, {"program_name"}, {\
value_type = "INTEGER16";	value_type = "INTEGER16";	value_type → "INTEGER16"	value_type(1: "INTEGER16") → "INTEGER16"	value_type = SAME_RULE(tokenINTEGER16);	value_type = SAME_RULE(tokenINTEGER16);	{ LA_IS, {T_DATA_TYPE_0}, {"value_type"}, {\

					}}}\
	array_specify = "[" , unsigned_value , "]" ;	array_specify → "[" unsigned_value "]"	array_specify(1: "[") → "[" unsigned_value "]"		array_specify = "[" >> unsigned_value >> "]" ;
declaration_element = ident , ["[" , unsigned_value , "]"] ;	declaration_element = ident , array_specify__optional ;	declaration_element → ident array_specify__optional	declaration_element(1: "ident_terminal") → ident array_specify__optional	declaration_element = ident >> -(tokenLEFTSQUAREBRACKETS >> unsigned_value >> tokenRIGHTSQUAREBRACKETS) ;	declaration_element = ident >> array_specify__optional ;
	array_specify__optional = array_specify ε ;	array_specify__optional → array_specify array_specify__optional → ε	array_specify__optional(1: "[") → array_specify array_specify__optional(1: !"[") → ε		array_specify__optional = array_specify "" ;
other_declaration_ident = " , " , declaration_element ;	other_declaration_ident = " , " , declaration_element ;	other_declaration_ident → " , " declaration_element	other_declaration_ident(1: " , ") → " , " declaration_element	other_declaration_ident = tokenCOMMA >> declaration_element ;	other_declaration_ident = tokenCOMMA >> declaration_element ;
declaration = value_type , declaration_element , { other_declaration_ident } ;	declaration = value_type , declaration_element , other_declaration_ident__iteration ;	declaration → value_type declaration_element other_declaration_ident__iteration	declaration(1: "INTEGER16") → value_type declaration_element other_declaration_ident__iteration	declaration = value_type >> declaration_element >> *other_declaration_ident ;	declaration = value_type >> declaration_element >> other_declaration_ident__iteration ;
	other_declaration_ident__iteration = other_declaration_ident , other_declaration_ident__iteration ε ;	other_declaration_ident__iteration → other_declaration_ident other_declaration_ident__iteration false_cond_block_without_else__iteration → ε	other_declaration_ident__iteration(1: " , ") → other_declaration_ident other_declaration_ident__iteration false_cond_block_without_else__iteration(1: !" , ") → ε		other_declaration_ident__iteration = other_declaration_ident >> other_declaration_ident__iteration "" ;
index_action = "[" , expression , "]" ;	index_action = "[" , expression , "]" ;	index_action → "[" expression "]"	index_action(1: "[") → "[" expression "]"	index_action = tokenLEFTSQUAREBRACKETS >> expression >> tokenRIGHTSQUAREBRACKETS ;	index_action = tokenLEFTSQUAREBRACKETS >> expression >> tokenRIGHTSQUAREBRACKETS ;
unary_operator = "NOT" ;	unary_operator = "NOT" ;	unary_operator → "NOT"	unary_operator(1: "NOT") → "NOT"		unary_operator = SAME_RULE(tokenNOT) ;
unary_operation = unary_operator , expression ;	unary_operation = unary_operator , expression ;	unary_operation → unary_operator expression	unary_operation(1: "NOT") → unary_operator expression	unary_operator = SAME_RULE(tokenNOT) ;	unary_operation = unary_operator >> expression ;
binary_operator = "AND" "OR" "==" "!=" "<=" ">=" "+" "-" "*" "DIV" "MOD" ;	binary_operator = "AND" "OR" "==" "!=" "<=" ">=" "+" "-" "*" "DIV" "MOD" ;	binary_operator → "AND" binary_operator → "OR" binary_operator → "==" binary_operator → "!=" binary_operator → "<=" binary_operator → ">=" binary_operator → "+" binary_operator → "-" binary_operator → "*" binary_operator → "DIV" binary_operator → "MOD"	binary_operator(1: "AND") → "AND" binary_operator(1: "OR") → "OR" binary_operator(1: "==") → "==" binary_operator(1: "!=") → "!=" binary_operator(1: "<=") → "<=" binary_operator(1: ">=") → ">=" binary_operator(1: "+") → "+" binary_operator(1: "-") → "-" binary_operator(1: "*") → "*" binary_operator(1: "DIV") → "DIV" binary_operator(1: "MOD") → "MOD"		binary_operator = tokenAND tokenOR tokenEQUAL tokenNOTEQUAL tokenLESSOREQUAL tokenGREATEROREQUAL tokenPLUS tokenMINUS tokenMUL tokenDIV tokenMOD ;
binary_action = binary_operator , expression ;	binary_action = binary_operator , expression ;	binary_action → binary_operator expression	binary_action(1: "AND", "OR", "==", "!=" , "<=" , ">=" , "+", "-", "*", "DIV", "MOD") → binary_operator expression	binary_action = binary_operator >> expression ;	binary_action = binary_operator >> expression ;
left_expression = group_expression unary_operation cond_block value ident , [index_action] ;	left_expression = group_expression unary_operation cond_block value ident , index_action__optional ;	left_expression → group_expression left_expression → unary_operation left_expression → cond_block left_expression → value left_expression → ident , index_action__optional	left_expression(1: "[") → group_expression left_expression(1: "NOT") → unary_operation left_expression(1: "IF") → cond_block left_expression(1: "0", "1", "2", "3", "4", "5", "6", "7", "8", "9") → value left_expression(1: "+", "-"; 2: "0", "1", "2", "3", "4", "5", "6", "7", "8", "9") → value left_expression(1: " , ") → ident , index_action__optional	left_expression = group_expression unary_operation cond_block value ident >> index_action__optional ;	left_expression = group_expression unary_operation cond_block value ident >> index_action__optional ;
index_action__optional = index_action ε ;	index_action__optional = index_action ε ;	index_action__optional → index_action index_action__optional → ε	index_action__optional(1: "[") → index_action index_action__optional(1: !"[") → ε		index_action__optional = index_action "" ;
expression = left_expression , { binary_action } ;	expression = left_expression , binary_action__iteration ;	expression → left_expression binary_action__iteration	expression(1: "(", "NOT", "+", "-", " , " , "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") →	expression = left_expression >> *binary_action ;	expression = left_expression >> binary_action__iteration ;

			left_expression binary_action__iteration			{ "expression",{\n {LA_IS, (""), 2, { "left_expression", "binary_action__iteration" }}}\n}};\n
	binary_action__iteration = binary_action, binary_action__iteration ε;	binary_action__iteration → binary_action binary_action__iteration binary_action__iteration → ε	binary_action__iteration(1: "AND", "OR", "=", "!=", "<=", ">=", "+", "-", "*", "DIV", "MOD") → binary_action binary_action__iteration binary_action__iteration(1: !"AND", !"OR", !"=", !"!=", !"<=", !">=", !"+", !"-", !"*, !"DIV", !"MOD") → ε		binary_action__iteration = binary_action >> binary_action__iteration "";	{LA_IS, {T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_OR_EQUAL_0, T_GREATER_OR_EQUAL_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0}, {\n "binary_action__iteration",{\n {LA_IS, (""), 2, { "binary_action", "binary_action__iteration" }}}\n}};\n{LA_NOT, {T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_OR_EQUAL_0, T_GREATER_OR_EQUAL_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0}, {\n "binary_action__iteration",{\n {LA_IS, (""), 0, { "" }}}\n}};\n
group_expression = "(" , expression , ")";	group_expression = "(" , expression , ")";	group_expression → "(" expression ")"	group_expression(1: "(") → "(" expression ")"	group_expression = tokenGROUPEXPRESSIONBEGIN >> expression >> tokenGROUPEXPRESSIONEND;	group_expression = tokenGROUPEXPRESSIONBEGIN >> expression >> tokenGROUPEXPRESSIONEND;	{LA_IS, { "(" }, { "group_expression",{\n {LA_IS, (""), 3, { "(", "expression", ")" }}}\n}};\n
expression_or_cond_block_with_optional_assign = expression , assign_to_right__optional;	expression_or_cond_block_with_optional_assign = expression , assign_to_right__optional;	expression_or_cond_block_with_optional_assign → expression assign_to_right__optional	expression_or_cond_block_with_optional_assign(1: "(" , "NOT", "+", "-", "*", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression assign_to_right__optional	expression_or_cond_block_with_optional_assign = expression >> -(tokenLRASSIGN >> ident >> -index_action);	expression_or_cond_block_with_optional_assign = expression >> assign_to_right__optional;	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\n "expression_or_cond_block_with_optional_assign",{\n {LA_IS, (""), 2, { "expression", "assign_to_right__optional" }}}\n}};\n
	assign_to_right = "=: " , ident , index_action__optional;	assign_to_right → "=: " ident index_action__optional	assign_to_right(1: "=: ") → "=: " ident index_action__optional		assign_to_right = tokenLRASSIGN >> ident >> index_action__optional;	{LA_IS, {T_LRASSIGN_0}, {\n "assign_to_right",{\n {LA_IS, (""), 3, { T_LRASSIGN_0, "ident", "index_action__optional" }}}\n}};\n
	assign_to_right__optional = assign_to_right ε;	assign_to_right__optional → assign_to_right assign_to_right__optional → ε;	assign_to_right__optional(1: "=: ") → assign_to_right assign_to_right__optional(1: !"=: ") → ε;		assign_to_right__optional = assign_to_right "";	{ LA_IS, {T_LRASSIGN_0}, {\n "assign_to_right__optional",{\n { LA_IS, (""), 1, { "assign_to_right" }}}\n}};\n{ LA_NOT, {T_LRASSIGN_0}, {\n "assign_to_right__optional",{\n { LA_IS, (""), 0, { "" }}}\n}};\n
if_expression = expression;	if_expression = expression;	if_expression → expression	if_expression(1: "(" , "NOT", "+", "-", "*", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression	if_expression = SAME_RULE(expression);	if_expression = SAME_RULE(expression);	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\n "if_expression",{\n {LA_IS, (""), 1, { "expression" }}}\n}};\n
body_for_true = block_statements_in_while_and_if_body;	body_for_true = block_statements_in_while_and_if_body;	body_for_true → block_statements_in_while_and_if_body	body_for_true(1: "{") → block_statements_in_while_and_if_body	body_for_true = SAME_RULE(block_statements_in_while_and_if_body);	body_for_true = SAME_RULE(block_statements_in_while_and_if_body);	{LA_IS, {T_BEGIN_BLOCK_0}, {\n "body_for_true",{\n {LA_IS, (""), 1, {\n "block_statements_in_while_and_if_body" }}}\n}};\n
false_cond_block_without_else = "ELSE" , "IF" , if_expression , body_for_true;	false_cond_block_without_else = "ELSE" , "IF" , if_expression , body_for_true;	false_cond_block_without_else → "ELSE" "IF" if_expression body_for_true	false_cond_block_without_else(1: "ELSE") → "ELSE" "IF" if_expression body_for_true	false_cond_block_without_else = tokenELSE >> tokenIF >> if_expression >> body_for_true;	false_cond_block_without_else = tokenELSE >> tokenIF >> if_expression >> body_for_true;	{LA_IS, {T_ELSE_IF_0}, {\n "false_cond_block_without_else",{\n {LA_IS, (""), 4, {T_ELSE_IF_0, T_ELSE_IF_1, "if_expression", "body_for_true" }}}\n}};\n
body_for_false = "ELSE" , block_statements_in_while_and_if_body;	body_for_false = "ELSE" , block_statements_in_while_and_if_body;	body_for_false → "ELSE" block_statements_in_while_and_if_body	body_for_false(1: "ELSE") → "ELSE" block_statements_in_while_and_if_body	body_for_false = tokenELSE >> block_statements_in_while_and_if_body;	body_for_false = tokenELSE >> block_statements_in_while_and_if_body;	{LA_IS, {T_ELSE_BLOCK_0}, {\n "body_for_false",{\n {LA_IS, (""), 2, { T_ELSE_BLOCK_0, "block_statements" }}}\n}};\n
cond_block = "IF" , if_expression , body_for_true, false_cond_block_without_else__iteration , body_for_false__optional;	cond_block = "IF" , if_expression , body_for_true, false_cond_block_without_else__iteration , body_for_false__optional;	cond_block → "IF" if_expression body_for_true false_cond_block_without_else__iteration body_for_false__optional	cond_block(1: "IF") → "IF" if_expression body_for_true false_cond_block_without_else__iteration body_for_false__optional	cond_block = tokenIF >> if_expression >> body_for_true >> *false_cond_block_without_else >> -body_for_false;	cond_block = tokenIF >> if_expression >> body_for_true >> false_cond_block_without_else__iteration >> body_for_false__optional;	{LA_IS, {T_IF_0}, {\n "cond_block",{\n {LA_IS, (""), 5, {T_IF_0, "if_expression", "body_for_true", "false_cond_block_without_else__iteration", "body_for_false__optional" }}}\n}};\n
	false_cond_block_without_else__iteration = false_cond_block_without_else, false_cond_block_without_else__iteration ε;	false_cond_block_without_else__iteration → false_cond_block_without_else false_cond_block_without_else__iteration false_cond_block_without_else__iteration → ε	false_cond_block_without_else__iteration(1: "ELSE"; 2: "IF") → false_cond_block_without_else false_cond_block_without_else__iteration false_cond_block_without_else__iteration(1: "ELSE"; 2: !"IF") → ε false_cond_block_without_else__iteration(1: !"ELSE") → ε		false_cond_block_without_else__iteration = false_cond_block_without_else >> false_cond_block_without_else__iteration "";	{LA_IS, {T_ELSE_IF_0}, {\n "false_cond_block_without_else__iteration",{\n {LA_IS, {T_ELSE_IF_1}, 2, {\n "false_cond_block_without_else", "false_cond_block_without_else__iteration" }}}\n {LA_NOT, {T_ELSE_IF_1}, 0, { "" }}}\n}};\n{LA_NOT, {T_ELSE_IF_0}, {\n "false_cond_block_without_else__iteration",{\n {LA_IS, (""), 0, { "" }}}\n}};\n
	body_for_false__optional = body_for_false ε;	body_for_false__optional → body_for_false body_for_false__optional → ε	body_for_false__optional(1: "FALSE") → body_for_false body_for_false__optional(1: !"FALSE") → ε		body_for_false__optional = body_for_false "";	{LA_IS, {T_ELSE_BLOCK_0}, {\n "body_for_false__optional",{\n {LA_IS, (""), 1, {\n "body_for_false" }}}\n}};\n{LA_NOT, {T_ELSE_BLOCK_0}, {\n "body_for_false__optional",{\n {LA_IS, (""), 0, { "" }}}\n}};\n
cycle_begin_expression = expression;	cycle_begin_expression = expression;	cycle_begin_expression → expression	cycle_begin_expression(1: "(" , "NOT", "+", "-", "*", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression	cycle_begin_expression = SAME_RULE(expression);	cycle_begin_expression = SAME_RULE(expression);	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\n "cycle_begin_expression",{\n {LA_IS, (""), 1, { "expression" }}}\n}};\n
cycle_end_expression = expression;	cycle_end_expression = expression;	cycle_end_expression → expression	cycle_end_expression(1: "(" , "NOT", "+", "-", "*", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression	cycle_end_expression = SAME_RULE(expression);	cycle_end_expression = SAME_RULE(expression);	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\n "cycle_end_expression",{\n {LA_IS, (""), 1, { "expression" }}}\n}};\n
cycle_counter = ident;	cycle_counter = ident;	cycle_counter → ident	cycle_counter(1: "_") → ident	cycle_counter = SAME_RULE(ident);	cycle_counter = SAME_RULE(ident);	{LA_IS, {\n "ident_terminal" }, {\n "cycle_counter",{\n {LA_IS, (""), 1, {\n "ident" }}}\n}};\n
cycle_counter_lr_init = cycle_begin_expression , "=: " , cycle_counter;	cycle_counter_lr_init = cycle_begin_expression , "=: " , cycle_counter;	cycle_counter_lr_init → cycle_begin_expression "=: " cycle_counter	cycle_counter_lr_init(1: "(" , "NOT", "+", "-", "*", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → cycle_begin_expression "=: " cycle_counter	cycle_counter_lr_init = cycle_begin_expression >> tokenLRASSIGN >> cycle_counter;	cycle_counter_lr_init = cycle_begin_expression >> tokenLRASSIGN >> cycle_counter;	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\n "cycle_counter_lr_init",{\n {LA_IS, (""), 3, {\n "cycle_begin_expression", T_LRASSIGN_0, "cycle_counter" }}}\n}};\n
cycle_counter_init = cycle_counter_lr_init;	cycle_counter_init = cycle_counter_lr_init;	cycle_counter_init → cycle_counter_lr_init	cycle_counter_init(1: "(" , "NOT", "+", "-", "*", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → cycle_counter_lr_init	cycle_counter_init = SAME_RULE(cycle_counter_lr_init);	cycle_counter_init = SAME_RULE(cycle_counter_lr_init);	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\n "cycle_counter_init",{\n {LA_IS, {" "" }, 1, {\n "cycle_counter_lr_init" }}}\n}};\n

digit = "0" non_zero_digit;	digit = "0" non_zero_digit;	digit → "0" digit → non_zero_digit	digit(1: "0") → "0" digit(1: "1", "2", "3", "4", "5", "6", "7", "8", "9",) → non_zero_digit	digit_0 = '0'; digit = digit_0 non_zero_digit;	digit_0 = '0'; digit = digit_0 non_zero_digit;	\\
non_zero_digit = "1" "2" "3" "4" "5" "6" "7" "8" "9";	non_zero_digit = "1" "2" "3" "4" "5" "6" "7" "8" "9";	non_zero_digit → "1" non_zero_digit → "2" non_zero_digit → "3" non_zero_digit → "4" non_zero_digit → "5" non_zero_digit → "6" non_zero_digit → "7" non_zero_digit → "8" non_zero_digit → "9"	non_zero_digit(1: "1") → "1" non_zero_digit(1: "2") → "2" non_zero_digit(1: "3") → "3" non_zero_digit(1: "4") → "4" non_zero_digit(1: "5") → "5" non_zero_digit(1: "6") → "6" non_zero_digit(1: "7") → "7" non_zero_digit(1: "8") → "8" non_zero_digit(1: "9") → "9"	digit_1 = '1'; digit_2 = '2'; digit_3 = '3'; digit_4 = '4'; digit_5 = '5'; digit_6 = '6'; digit_7 = '7'; digit_8 = '8'; digit_9 = '9'; non_zero_digit = digit_1 digit_2 digit_3 digit_4 digit_5 digit_6 digit_7 digit_8 digit_9;	digit_1 = '1'; digit_2 = '2'; digit_3 = '3'; digit_4 = '4'; digit_5 = '5'; digit_6 = '6'; digit_7 = '7'; digit_8 = '8'; digit_9 = '9'; non_zero_digit = digit_1 digit_2 digit_3 digit_4 digit_5 digit_6 digit_7 digit_8 digit_9;	\\
ident = "_", letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case;	ident = "_", letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case, letter_in_upper_case;	ident → "_", letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case	Ident(1: "_") → "_", letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case	tokenUNDERSCORE = "_"; ident = (tokenCOLON tokenGOTO tokenINTEGER16 tokenCOMMA tokenNOT tokenAND tokenOR tokenEQUAL tokenNOTEQUAL tokenLESSOREQUAL tokenGREATEROREQUAL tokenPLUS tokenMINUS tokenMUL tokenDIV tokenMOD tokenGROUPEXPRESSIONBEGIN tokenGROUPEXPRESSIONEND tokenLRASSIGN tokenELSE tokenIF tokenDO tokenFOR tokenTO tokenDOWNTWO tokenWHILE tokenCONTINUE tokenBREAK tokenEXIT tokenREPEAT tokenUNTIL tokenGET tokenPUT tokenNAME tokenBODY tokenDATA tokenBEGIN tokenEND tokenBEGINBLOCK tokenENDBLOCK tokenLEFTSQUAREBRACKETS tokenRIGHTSQUAREBRACKETS tokenSEMICOLON)>> tokenUNDERSCORE >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> STRICT_BOUNDARIES;	tokenUNDERSCORE = "_"; ident = (tokenCOLON tokenGOTO tokenINTEGER16 tokenCOMMA tokenNOT tokenAND tokenOR tokenEQUAL tokenNOTEQUAL tokenLESSOREQUAL tokenGREATEROREQUAL tokenPLUS tokenMINUS tokenMUL tokenDIV tokenMOD tokenGROUPEXPRESSIONBEGIN tokenGROUPEXPRESSIONEND tokenLRASSIGN tokenELSE tokenIF tokenDO tokenFOR tokenTO tokenDOWNTWO tokenWHILE tokenCONTINUE tokenBREAK tokenEXIT tokenREPEAT tokenUNTIL tokenGET tokenPUT tokenNAME tokenBODY tokenDATA tokenBEGIN tokenEND tokenBEGINBLOCK tokenENDBLOCK tokenLEFTSQUAREBRACKETS tokenRIGHTSQUAREBRACKETS tokenSEMICOLON)>> tokenUNDERSCORE >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> STRICT_BOUNDARIES;	/* ident_token represents ident in lexical analyzer */ {LA_IS, { "ident_terminal" }, { "ident", { {LA_IS, {""}, 1, { "ident_terminal" } } }}};\
letter_in_lower_case = "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z";	letter_in_lower_case = "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z";	letter_in_lower_case → "a" letter_in_lower_case → "b" letter_in_lower_case → "c" letter_in_lower_case → "d" letter_in_lower_case → "e" letter_in_lower_case → "f" letter_in_lower_case → "g" letter_in_lower_case → "h" letter_in_lower_case → "i" letter_in_lower_case → "j" letter_in_lower_case → "k" letter_in_lower_case → "l" letter_in_lower_case → "m" letter_in_lower_case → "n" letter_in_lower_case → "o" letter_in_lower_case → "p" letter_in_lower_case → "q" letter_in_lower_case → "r" letter_in_lower_case → "s" letter_in_lower_case → "t" letter_in_lower_case → "u" letter_in_lower_case → "v" letter_in_lower_case → "w" letter_in_lower_case → "x" letter_in_lower_case → "y" letter_in_lower_case → "z"	letter_in_lower_case(1: "a") → "a" letter_in_lower_case(1: "b") → "b" letter_in_lower_case(1: "c") → "c" letter_in_lower_case(1: "d") → "d" letter_in_lower_case(1: "e") → "e" letter_in_lower_case(1: "f") → "f" letter_in_lower_case(1: "g") → "g" letter_in_lower_case(1: "h") → "h" letter_in_lower_case(1: "i") → "i" letter_in_lower_case(1: "j") → "j" letter_in_lower_case(1: "k") → "k" letter_in_lower_case(1: "l") → "l" letter_in_lower_case(1: "m") → "m" letter_in_lower_case(1: "n") → "n" letter_in_lower_case(1: "o") → "o" letter_in_lower_case(1: "p") → "p" letter_in_lower_case(1: "q") → "q" letter_in_lower_case(1: "r") → "r" letter_in_lower_case(1: "s") → "s" letter_in_lower_case(1: "t") → "t" letter_in_lower_case(1: "u") → "u" letter_in_lower_case(1: "v") → "v" letter_in_lower_case(1: "w") → "w" letter_in_lower_case(1: "x") → "x" letter_in_lower_case(1: "y") → "y" letter_in_lower_case(1: "z") → "z"	A = "A"; B = "B"; C = "C"; D = "D"; E = "E"; F = "F"; G = "G"; H = "H"; I = "I"; J = "J"; K = "K"; L = "L"; M = "M"; N = "N"; O = "O"; P = "P"; Q = "Q"; R = "R"; S = "S"; T = "T"; U = "U"; V = "V"; W = "W"; X = "X"; Y = "Y"; Z = "Z"; letter_in_lower_case = a b c d e f g h i j k l m n o p q r s t u v w x y z;	A = "A"; B = "B"; C = "C"; D = "D"; E = "E"; F = "F"; G = "G"; H = "H"; I = "I"; J = "J"; K = "K"; L = "L"; M = "M"; N = "N"; O = "O"; P = "P"; Q = "Q"; R = "R"; S = "S"; T = "T"; U = "U"; V = "V"; W = "W"; X = "X"; Y = "Y"; Z = "Z"; letter_in_lower_case = a b c d e f g h i j k l m n o p q r s t u v w x y z;	\\
letter_in_upper_case = "A" "B" "C" "D" "E" "F" "G" "H" "I" "J" "K" "L" "M" "N" "O" "P" "Q" "R" "S" "T" "U" "V" "W" "X" "Y" "Z";	letter_in_upper_case = "A" "B" "C" "D" "E" "F" "G" "H" "I" "J" "K" "L" "M" "N" "O" "P" "Q" "R" "S" "T" "U" "V" "W" "X" "Y" "Z";	letter_in_upper_case → "A" letter_in_upper_case → "B" letter_in_upper_case → "C" letter_in_upper_case → "D" letter_in_upper_case → "E" letter_in_upper_case → "F" letter_in_upper_case → "G" letter_in_upper_case → "H" letter_in_upper_case → "I" letter_in_upper_case → "J" letter_in_upper_case → "K" letter_in_upper_case → "L" letter_in_upper_case → "M" letter_in_upper_case → "N"	letter_in_upper_case(1: "A") → "A" letter_in_upper_case(1: "B") → "B" letter_in_upper_case(1: "C") → "C" letter_in_upper_case(1: "D") → "D" letter_in_upper_case(1: "E") → "E" letter_in_upper_case(1: "F") → "F" letter_in_upper_case(1: "G") → "G" letter_in_upper_case(1: "H") → "H" letter_in_upper_case(1: "I") → "I" letter_in_upper_case(1: "J") → "J" letter_in_upper_case(1: "K") → "K" letter_in_upper_case(1: "L") → "L" letter_in_upper_case(1: "M") → "M" letter_in_upper_case(1: "N") → "N"	a = "a"; b = "b"; c = "c"; d = "d"; e = "e"; f = "f"; g = "g"; h = "h"; i = "i"; j = "j"; k = "k"; l = "l"; m = "m"; n = "n";	a = "a"; b = "b"; c = "c"; d = "d"; e = "e"; f = "f"; g = "g"; h = "h"; i = "i"; j = "j"; k = "k"; l = "l"; m = "m"; n = "n";	\\

