

РБНФ №1 (опис синтаксису мови всіма допустимими засобами РБНФ)	РБНФ №2 (опис формальна граматика мови)	Опис формальної граматики мови	Опис грамматики з специфікацією lookahead для LL2-аналізатора	/* Код для перевірки РБНФ №2 */	/* Дані для LL2-аналізатора (лексеми вже опрацьовані лексичним аналізатором) УВАГА: при копіюванні зважайте, щоб у кожному рядку після символу «\» не містилось жодних інших символів. */
		G = (N, T, P, S)	G = (N, T, P, S)		
		S → program_rule	S → program_rule		
		N = { labeled_point, Ident, goto_label, program_name, value_type, array_specify, declaration_element, array_specify_optional, other_declaration_ident, declaration, other_declaration_ident_iteration, index_action, unary_operator, unary_operation, binary_operator, binary_action, left_expression, group_expression, value, index_action_optional, expression, binary_action_iteration, expression_or_cond_block_with_optional_assign, assign_to_right, assign_to_right_optional, if_expression, body_for_true, false_cond_block_without_else, body_for_false, cond_block, false_cond_block_without_else_iteration, body_for_false_optional, cycle_begin_expression, cycle_end_expression, cycle_counter, cycle_counter_lr_init, cycle_counter_init, cycle_counter_last_value, cycle_body, forto_direction, forto_cycle, continue_while, break_while, statement_in_while_and_if_body, statement, block_statements_in_while_and_if_body, statement_in_while_and_if_body_iteration, while_cycle_head_expression, while_cycle, repeat_until_cycle_cond, repeat_until_cycle, statements_or_block_statements, block_statements, input_rule, argument_for_input, output_rule, statement_iteration, expression_optional, program_rule, declaration_optional, unsigned_value, value, sign_optional, sign, ident, sign_plus, sign_minus }	N = { labeled_point, Ident, goto_label, program_name, value_type, array_specify, declaration_element, array_specify_optional, other_declaration_ident, declaration, other_declaration_ident_iteration, index_action, unary_operator, unary_operation, binary_operator, binary_action, left_expression, group_expression, value, index_action_optional, expression, binary_action_iteration, expression_or_cond_block_with_optional_assign, assign_to_right, assign_to_right_optional, if_expression, body_for_true, false_cond_block_without_else, body_for_false, cond_block, false_cond_block_without_else_iteration, body_for_false_optional, cycle_begin_expression, cycle_end_expression, cycle_counter, cycle_counter_lr_init, cycle_counter_init, cycle_counter_last_value, cycle_body, forto_direction, forto_cycle, continue_while, break_while, statement_in_while_and_if_body, statement, block_statements_in_while_and_if_body, statement_in_while_and_if_body_iteration, while_cycle_head_expression, while_cycle, repeat_until_cycle_cond, repeat_until_cycle, statements_or_block_statements, block_statements, input_rule, argument_for_input, output_rule, statement_iteration, expression_optional, program_rule, declaration_optional, unsigned_value, value, sign_optional, sign, ident, sign_plus, sign_minus }		
		T = { ":", "GOTO", "INTEGER16", " ", "!", "NOT", "AND", "OR", "=", "!=", "<=", ">=", "<", ">", "+", "-", "*", "DIV", "MOD", "(", ")", "=", "ELSE", "IF", "DO", "FOR", "TO", "DOWNT", "WHILE", }	T = { ":", "GOTO", "INTEGER16", " ", "!", "NOT", "AND", "OR", "=", "!=", "<=", ">=", "<", ">", "+", "-", "*", "DIV", "MOD", "(", ")", "=", "ELSE", "IF", "DO", "FOR", "TO", "DOWNT", "WHILE", }		

		"CONTINUE", "BREAK", "EXIT", "REPEAT", "UNTIL", "GET", "PUT", "NAME", "BODY", "DATA", "BEGIN", "END", "(", ")", "[", "]", "(", ")", "(", ")", "(", ")", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", " ", "a", "b", "c", "d", "e", "f", "g", "h", "i", "j", "k", "l", "m", "n", "o", "p", "q", "r", "s", "t", "u", "v", "w", "x", "y", "z", "A", "B", "C", "D", "E", "F", "G", "H", "I", "J", "K", "L", "M", "N", "O", "P", "Q", "R", "S", "T", "U", "V", "W", "X", "Y", "Z", }	"CONTINUE", "BREAK", "EXIT", "REPEAT", "UNTIL", "GET", "PUT", "NAME", "BODY", "DATA", "BEGIN", "END", "(", ")", "[", "]", "(", ")", "(", ")", "(", ")", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", " ", "a", "b", "c", "d", "e", "f", "g", "h", "i", "j", "k", "l", "m", "n", "o", "p", "q", "r", "s", "t", "u", "v", "w", "x", "y", "z", "A", "B", "C", "D", "E", "F", "G", "H", "I", "J", "K", "L", "M", "N", "O", "P", "Q", "R", "S", "T", "U", "V", "W", "X", "Y", "Z", }			
				tokenGROUPEXPRESSI​ONBEGIN = "{" >> BOUNDARIES;	tokenGROUPEXPRESSI​ONBEGIN = "{" >> BOUNDARIES;	#define T_BEGIN_GROUPEXPRESSI​ON_0 "(" #define T_BEGIN_GROUPEXPRESSI​ON_1 "" #define T_BEGIN_GROUPEXPRESSI​ON_2 "" #define T_BEGIN_GROUPEXPRESSI​ON_3 ""
				tokenGROUPEXPRESSI​ONEND = "}" >> BOUNDARIES;	tokenGROUPEXPRESSI​ONEND = "}" >> BOUNDARIES;	#define T_END_GROUPEXPRESSI​ON_0 "]" #define T_END_GROUPEXPRESSI​ON_1 "" #define T_END_GROUPEXPRESSI​ON_2 "" #define T_END_GROUPEXPRESSI​ON_3 ""
				tokenLEFTSQUAREBRACKETS = "[" >> BOUNDARIES;	tokenLEFTSQUAREBRACKETS = "[" >> BOUNDARIES;	#define T_LEFT_SQUAREBRACKETS_0 "[" #define T_LEFT_SQUAREBRACKETS_1 "" #define T_LEFT_SQUAREBRACKETS_2 "" #define T_LEFT_SQUAREBRACKETS_3 ""
				tokenRIGHTSQUAREBRACKETS = "]" >> BOUNDARIES;	tokenRIGHTSQUAREBRACKETS = "]" >> BOUNDARIES;	#define T_RIGHT_SQUAREBRACKETS_0 "]" #define T_RIGHT_SQUAREBRACKETS_1 "" #define T_RIGHT_SQUAREBRACKETS_2 "" #define T_RIGHT_SQUAREBRACKETS_3 ""
				tokenBEGINBLOCK = "{" >> BOUNDARIES;	tokenBEGINBLOCK = "{" >> BOUNDARIES;	#define T_BEGIN_BLOCK_0 "{" #define T_BEGIN_BLOCK_1 "" #define T_BEGIN_BLOCK_2 "" #define T_BEGIN_BLOCK_3 ""
				tokenENDBLOCK = "}" >> BOUNDARIES;	tokenENDBLOCK = "}" >> BOUNDARIES;	#define T_END_BLOCK_0 "]" #define T_END_BLOCK_1 "" #define T_END_BLOCK_2 "" #define T_END_BLOCK_3 ""

				tokenSEMICOLON = ";" >> BOUNDARIES;	tokenSEMICOLON = ";" >> BOUNDARIES;	#define T_SEMICOLON_0 ";" #define T_SEMICOLON_1 "" #define T_SEMICOLON_2 "" #define T_SEMICOLON_3 ""			
				tokenCOLON = ":" >> BOUNDARIES;	tokenCOLON = ":" >> BOUNDARIES;	#define T_COLON_0 ":" #define T_COLON_1 "" #define T_COLON_2 "" #define T_COLON_3 ""			
				tokenGOTO = "GOTO" >> STRICT_BOUNDARIES;	tokenGOTO = "GOTO" >> STRICT_BOUNDARIES;	#define T_GOTO_0 "GOTO" #define T_GOTO_1 "" #define T_GOTO_2 "" #define T_GOTO_3 ""			
				tokenINTEGER16 = "INTEGER16" >> STRICT_BOUNDARIES;	tokenINTEGER16 = "INTEGER16" >> STRICT_BOUNDARIES;	#define T_DATA_TYPE_0 "INTEGER16" #define T_DATA_TYPE_1 "" #define T_DATA_TYPE_2 "" #define T_DATA_TYPE_3 ""			
				tokenCOMMA = "," >> BOUNDARIES;	tokenCOMMA = "," >> BOUNDARIES;	#define T_COMA_0 "," #define T_COMA_1 "" #define T_COMA_2 "" #define T_COMA_3 ""			
						#define T_BITWISE_NOT_0 "~" #define T_BITWISE_NOT_1 "" #define T_BITWISE_NOT_2 "" #define T_BITWISE_NOT_3 ""			
				tokenNOT = "NOT" >> STRICT_BOUNDARIES;	tokenNOT = "NOT" >> STRICT_BOUNDARIES;	#define T_NOT_0 "NOT" #define T_NOT_1 "" #define T_NOT_2 "" #define T_NOT_3 ""			
						#define T_BITWISE_AND_0 "&" #define T_BITWISE_AND_1 "" #define T_BITWISE_AND_2 "" #define T_BITWISE_AND_3 ""			
				tokenAND = "AND" >> STRICT_BOUNDARIES;	tokenAND = "AND" >> STRICT_BOUNDARIES;	#define T_AND_0 "AND" #define T_AND_1 "" #define T_AND_2 "" #define T_AND_3 ""			
						#define T_BITWISE_OR_0 " " #define T_BITWISE_OR_1 "" #define T_BITWISE_OR_2 "" #define T_BITWISE_OR_3 ""			
				tokenOR = "OR" >> STRICT_BOUNDARIES;	tokenOR = "OR" >> STRICT_BOUNDARIES;	#define T_OR_0 "OR" #define T_OR_1 "" #define T_OR_2 "" #define T_OR_3 ""			
				tokenEQUAL = "==" >> BOUNDARIES;	tokenEQUAL = "==" >> BOUNDARIES;	#define T_EQUAL_0 "==" #define T_EQUAL_1 "" #define T_EQUAL_2 "" #define T_EQUAL_3 ""			
				tokenNOTEQUAL = "!=" >> BOUNDARIES;	tokenNOTEQUAL = "!=" >> BOUNDARIES;	#define T_NOT_EQUAL_0 "!=" #define T_NOT_EQUAL_1 "" #define T_NOT_EQUAL_2 "" #define T_NOT_EQUAL_3 ""			
				tokenLESSOREQUAL = "<=" >> BOUNDARIES;	tokenLESSOREQUAL = "<=" >> BOUNDARIES;	#define T_LESS_OR_EQUAL_0 "<="	#define T_LESS_OR_EQUAL_1 ""	#define T_LESS_OR_EQUAL_2 ""	#define T_LESS_OR_EQUAL_3 ""
				tokenGREATEROREQUAL = ">=" >> BOUNDARIES;	tokenGREATEROREQUAL = ">=" >> BOUNDARIES;	#define T_GREATER_OR_EQUAL_0 ">="	#define T_GREATER_OR_EQUAL_1 ""	#define T_GREATER_OR_EQUAL_2 ""	#define T_GREATER_OR_EQUAL_3 ""
				tokenLESS = "<" >> BOUNDARIES;	tokenLESS = "<" >> BOUNDARIES;	#define T_LESS_0 "<"	#define T_LESS_1 ""	#define T_LESS_2 ""	#define T_LESS_3 ""
				tokenGREATER = ">" >> BOUNDARIES;	tokenGREATER = ">" >> BOUNDARIES;	#define T_GREATER_0 ">"	#define T_GREATER_1 ""	#define T_GREATER_2 ""	#define T_GREATER_3 ""
				tokenPLUS = "+" >> BOUNDARIES;	tokenPLUS = "+" >> BOUNDARIES;	#define T_ADD_0 "+"	#define T_ADD_1 ""	#define T_ADD_2 ""	#define T_ADD_3 ""
				tokenMINUS = "-" >> BOUNDARIES;	tokenMINUS = "-" >> BOUNDARIES;	#define T_SUB_0 "-"	#define T_SUB_1 ""	#define T_SUB_2 ""	#define T_SUB_3 ""
				tokenMUL = "*" >> BOUNDARIES;	tokenMUL = "*" >> BOUNDARIES;	#define T_MUL_0 "*"	#define T_MUL_1 ""	#define T_MUL_2 ""	#define T_MUL_3 ""
				tokenDIV = "DIV" >> STRICT_BOUNDARIES;	tokenDIV = "DIV" >> STRICT_BOUNDARIES;	#define T_DIV_0 "DIV"	#define T_DIV_1 ""	#define T_DIV_2 ""	#define T_DIV_3 ""
				tokenMOD = "MOD" >> STRICT_BOUNDARIES;	tokenMOD = "MOD" >> STRICT_BOUNDARIES;	#define T_MOD_0 "MOD"	#define T_MOD_1 ""	#define T_MOD_2 ""	#define T_MOD_3 ""
				tokenLRASSIGN = "=:;" >> BOUNDARIES;	tokenLRASSIGN = "=:;" >> BOUNDARIES;	#define T_LRASSIGN_0 "=:;"	#define T_LRASSIGN_1 ""	#define T_LRASSIGN_2 ""	#define T_LRASSIGN_3 ""
						#define T_THEN_BLOCK_0 "{"	#define T_THEN_BLOCK_1 ""	#define T_THEN_BLOCK_2 ""	#define T_THEN_BLOCK_3 ""
				tokenELSE = "ELSE" >> STRICT_BOUNDARIES;	tokenELSE = "ELSE" >> STRICT_BOUNDARIES;	#define T_ELSE_BLOCK_0 "ELSE"	#define T_ELSE_BLOCK_1 T_BEGIN_BLOCK_0	#define T_ELSE_BLOCK_2 ""	#define T_ELSE_BLOCK_3 ""
				tokenIF = "IF" >> STRICT_BOUNDARIES;	tokenIF = "IF" >> STRICT_BOUNDARIES;	#define T_IF_0 "IF"	#define T_IF_1 ""	#define T_IF_2 ""	#define T_IF_3 ""
						#define T_ELSE_IF_0 "ELSE"	#define T_ELSE_IF_1 T_IF_0	#define T_ELSE_IF_2 ""	

						#define T_ELSE_IF_3 ""
				tokenDO = "DO" >> STRICT_BOUNDARIES;	tokenDO = "DO" >> STRICT_BOUNDARIES;	#define T_DO_0 "DO" #define T_DO_1 "" #define T_DO_2 "" #define T_DO_3 ""
				tokenFOR = "FOR" >> STRICT_BOUNDARIES;	tokenFOR = "FOR" >> STRICT_BOUNDARIES;	#define T_FOR_0 "FOR" #define T_FOR_1 "" #define T_FOR_2 "" #define T_FOR_3 ""
				tokenTO = "TO" >> STRICT_BOUNDARIES;	tokenTO = "TO" >> STRICT_BOUNDARIES;	#define T_TO_0 "TO" #define T_TO_1 "" #define T_TO_2 "" #define T_TO_3 ""
				tokenDOWNT0 = "DOWNT0" >> STRICT_BOUNDARIES;	tokenDOWNT0 = "DOWNT0" >> STRICT_BOUNDARIES;	#define T_DOWNT0_0 "DOWNT0" #define T_DOWNT0_1 "" #define T_DOWNT0_2 "" #define T_DOWNT0_3 ""
				tokenWHILE = "WHILE" >> STRICT_BOUNDARIES;	tokenWHILE = "WHILE" >> STRICT_BOUNDARIES;	#define T_WHILE_0 "WHILE" #define T_WHILE_1 "" #define T_WHILE_2 "" #define T_WHILE_3 ""
				tokenCONTINUE = "CONTINUE" >> STRICT_BOUNDARIES;	tokenCONTINUE = "CONTINUE" >> STRICT_BOUNDARIES;	#define T_CONTINUE_WHILE_0 "CONTINUE" #define T_CONTINUE_WHILE_1 "" #define T_CONTINUE_WHILE_2 "" #define T_CONTINUE_WHILE_3 ""
				tokenBREAK = "BREAK" >> STRICT_BOUNDARIES;	tokenBREAK = "BREAK" >> STRICT_BOUNDARIES;	#define T_EXIT_WHILE_0 "BREAK" #define T_EXIT_WHILE_1 "" #define T_EXIT_WHILE_2 "" #define T_EXIT_WHILE_3 ""
				tokenEXIT = "EXIT" >> STRICT_BOUNDARIES;	tokenEXIT = "EXIT" >> STRICT_BOUNDARIES;	#define T_EXIT_0 "EXIT" #define T_EXIT_1 "" #define T_EXIT_2 "" #define T_EXIT_3 ""
				tokenREPEAT = "REPEAT" >> STRICT_BOUNDARIES;	tokenREPEAT = "REPEAT" >> STRICT_BOUNDARIES;	#define T_REPEAT_0 "REPEAT" #define T_REPEAT_1 "" #define T_REPEAT_2 "" #define T_REPEAT_3 ""
				tokenUNTIL = "UNTIL" >> STRICT_BOUNDARIES;	tokenUNTIL = "UNTIL" >> STRICT_BOUNDARIES;	#define T_UNTIL_0 "UNTIL" #define T_UNTIL_1 "" #define T_UNTIL_2 "" #define T_UNTIL_3 ""
				tokenGET = "GET" >> STRICT_BOUNDARIES;	tokenGET = "GET" >> STRICT_BOUNDARIES;	#define T_INPUT_0 "GET" #define T_INPUT_1 "" #define T_INPUT_2 "" #define T_INPUT_3 ""
				tokenPUT = "PUT" >> STRICT_BOUNDARIES;	tokenPUT = "PUT" >> STRICT_BOUNDARIES;	#define T_OUTPUT_0 "PUT" #define T_OUTPUT_1 "" #define T_OUTPUT_2 "" #define T_OUTPUT_3 ""
				tokenNAME = "NAME" >> STRICT_BOUNDARIES;	tokenNAME = "NAME" >> STRICT_BOUNDARIES;	#define T_NAME_0 "NAME" #define T_NAME_1 "" #define T_NAME_2 "" #define T_NAME_3 ""
				tokenBODY = "BODY" >> STRICT_BOUNDARIES;	tokenBODY = "BODY" >> STRICT_BOUNDARIES;	#define T_BODY_0 "BODY" #define T_BODY_1 "" #define T_BODY_2 "" #define T_BODY_3 ""
				tokenDATA = "DATA" >> STRICT_BOUNDARIES;	tokenDATA = "DATA" >> STRICT_BOUNDARIES;	#define T_DATA_0 "DATA" #define T_DATA_1 "" #define T_DATA_2 "" #define T_DATA_3 ""
				tokenBEGIN = "BEGIN" >> STRICT_BOUNDARIES;	tokenBEGIN = "BEGIN" >> STRICT_BOUNDARIES;	#define T_BEGIN_0 "BEGIN" #define T_BEGIN_1 "" #define T_BEGIN_2 "" #define T_BEGIN_3 ""
				tokenEND = "END" >> STRICT_BOUNDARIES;	tokenEND = "END" >> STRICT_BOUNDARIES;	#define T_END_0 "END" #define T_END_1 "" #define T_END_2 "" #define T_END_3 ""
						#define T_NULL_STATEMENT_0 "NULL" #define T_NULL_STATEMENT_1 "STATEMENT" #define T_NULL_STATEMENT_2 "" #define T_NULL_STATEMENT_3 ""
abeled_point = ident, ":";	labeled_point = ident, ":";	labeled_point → ident ":"	labeled_point(1: "ident_terminal") → ident ":"	labeled_point = ident >> tokenCOLON;	labeled_point = ident >> tokenCOLON;	{ LA_JS, ("ident_terminal"), { "labeled_point", {\ LA_JS, ("", 2, {"ident", T_COLON_0})} } };\
goto_label = "GOTO", ident;	goto_label = "GOTO", ident;	goto_label → "GOTO" ident	goto_label(1: "GOTO") → "GOTO" ident	goto_label = tokenGOTO >> ident;	goto_label = tokenGOTO >> ident;	{ LA_JS, {T_GOTO_0}, { "goto_label", {\ LA_JS, ("", 2, {T_GOTO_0, "ident"})} } };\
rogram_name = ident;	program_name = ident;	program_name → ident	program_name(1: "ident_terminal") → ident	program_name = SAME_RULE(ident);	program_name = SAME_RULE(ident);	{ LA_JS, ("ident_terminal"), { "program_name", {\ LA_JS, ("", 1, {"ident"})} } };\
value_type = "INTEGER16";	value_type = "INTEGER16";	value_type → "INTEGER16"	value_type(1: "INTEGER16") → "INTEGER16"	value_type = SAME_RULE(tokenINTEGER16);	value_type = SAME_RULE(tokenINTEGER16);	{ LA_JS, {T_DATA_TYPE_0}, { "value_type", {\ LA_JS, ("", 1, {T_DATA_TYPE_0})} } };\
array_specify = "[" unsigned_value, "]"	array_specify = "[" unsigned_value, "]"	array_specify → "[" unsigned_value "]"	array_specify(1: "[") → "[" unsigned_value "]"		array_specify = "[" >> unsigned_value >> "]"	{ LA_JS, {"["}, { "array_specify", {\ LA_JS, ("", 3, {"[", "unsigned_value", "]"})} } };\
declaration_element = ident, ["[" unsigned_value, "]"]	declaration_element = ident, array_specify__optional	declaration_element → ident array_specify__optional	declaration_element(1: "ident_terminal") → ident array_specify__optional	declaration_element = ident >> -(tokenLEFTSQUAREBRACKETS >> unsigned_value >> tokenRIGHTSQUAREBRACKETS);	declaration_element = ident >> array_specify__optional;	{ LA_JS, ("ident_terminal"), { "declaration_element", {\ LA_JS, ("", 2, {"ident", "array_specify__optional"})} } };\
	array_specify__optional = array_specify ε	array_specify__optional → array_specify array_specify__optional → ε	array_specify__optional(1: "[") → array_specify array_specify__optional(1: !"[") → ε		array_specify__optional = array_specify ""	{ LA_JS, {"["}, { "array_specify__optional", {\ LA_JS, ("", 1, {"array_specify"})} } };\
other_declaration_ident = ",", declaration_element	other_declaration_ident = ",", declaration_element	other_declaration_ident → ",", declaration_element	other_declaration_ident(1: ",") → ",", declaration_element	other_declaration_ident = tokenCOMMA >> declaration_element;	other_declaration_ident = tokenCOMMA >> declaration_element;	{ LA_JS, {T_COMA_0}, { "other_declaration_ident", {\ LA_JS, ("", 2, {T_COMA_0, "declaration_element"})} } };\
declaration = value_type, declaration_element, {other_declaration_ident};	declaration = value_type, declaration_element, other_declaration_ident__iteration;	declaration → value_type declaration_element other_declaration_ident__iteration	declaration(1: "INTEGER16") → value_type declaration_element other_declaration_ident__iteration	declaration = value_type >> declaration_element >> *other_declaration_ident;	declaration = value_type >> declaration_element >> other_declaration_ident__iteration;	{ LA_JS, {T_DATA_TYPE_0}, { "declaration", {\ LA_JS, ("", 3, {"value_type", "declaration_element", "other_declaration_ident__iteration"})} } };\

						{LA_IS, {""}, 2, { "left_expression", "binary_action__iteration" }}\ }}\
	binary_action__iteration = binary_action, binary_action__iteration ε;	binary_action__iteration → binary_action binary_action__iteration binary_action__iteration → ε	binary_action__iteration(1: "AND", "OR", "=", "!=", "<=", ">=", "<", ">", "+", "-", "*", "DIV", "MOD") → binary_action binary_action__iteration binary_action__iteration(1: !"AND", !"OR", !=", !"!=", !"<=", !">=", !"<", !">", !"+", !"-", !"*", !"DIV", !"MOD") → ε		binary_action__iteration = binary_action >> binary_action__iteration "";	IF_NONUSE_COMPARE_WITH_EQUAL(\ {LA_IS, { T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_0, T_GREATER_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0 }, { "binary_action__iteration", {\ {LA_IS, {""}, 2, { "binary_action", "binary_action__iteration" }}\ }}\} {LA_NOT, { T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_0, T_GREATER_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0 }, { "binary_action__iteration", {\ {LA_IS, {""}, 0, { "" }}\ }}\})\ IF_USE_COMPARE_WITH_EQUAL(\ {LA_IS, { T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_OR_EQUAL_0, T_GREATER_OR_EQUAL_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0 }, { "binary_action__iteration", {\ {LA_IS, {""}, 2, { "binary_action", "binary_action__iteration" }}\ }}\} {LA_NOT, { T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_OR_EQUAL_0, T_GREATER_OR_EQUAL_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0 }, { "binary_action__iteration", {\ {LA_IS, {""}, 0, { "" }}\ }}\})\
group_expression = "(" , expression , ")";	group_expression = "(" , expression , ")";	group_expression → "(" expression ")"	group_expression(1: "(" → "(" expression ")")	group_expression = tokenGROUPEXPRESSIONBEGIN >> expression >> tokenGROUPEXPRESSIONEND;	group_expression = tokenGROUPEXPRESSIONBEGIN >> expression >> tokenGROUPEXPRESSIONEND;	{LA_IS, { "(" }, { "group_expression", {\ {LA_IS, {""}, 3, { "(", "expression", ")" }}\ }}\
expression_or_cond_block__with_optional_assign = expression , ["=" , ident , index_action]];	expression_or_cond_block__with_optional_assign = expression , assign_to_right__optional;	expression_or_cond_block__with_optional_assign → expression assign_to_right__optional	expression_or_cond_block__with_optional_assign(1: "(" , "NOT", "+", "-", "_", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression assign_to_right__optional	expression_or_cond_block__with_optional_assign = expression >> -(tokenLRASSIGN >> ident >> -index_action);	expression_or_cond_block__with_optional_assign = expression >> assign_to_right__optional;	{LA_IS, { "(", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "expression_or_cond_block__with_optional_assign", {\ {LA_IS, {""}, 2, { "expression", "assign_to_right__optional" }}\ }}\
	assign_to_right = "=", ident , index_action__optional;	assign_to_right → "=" ident index_action__optional	assign_to_right(1: "=") → "=" ident index_action__optional		assign_to_right = tokenLRASSIGN >> ident >> index_action__optional;	{LA_IS, { T_LRASSIGN_0 }, { "assign_to_right", {\ {LA_IS, {""}, 3, { T_LRASSIGN_0, "ident", "index_action__optional" }}\ }}\
	assign_to_right__optional = assign_to_right ε;	assign_to_right__optional → assign_to_right assign_to_right__optional → ε;	assign_to_right__optional(1: "=") → assign_to_right assign_to_right__optional(1: !=":") → ε;		assign_to_right__optional = assign_to_right "";	{ LA_IS, { T_LRASSIGN_0 }, { "assign_to_right__optional", {\ { LA_IS, {""}, 1, { "assign_to_right" }}\ }}\} { LA_NOT, { T_LRASSIGN_0 }, { "assign_to_right__optional", {\ { LA_IS, {""}, 0, { "" }}\ }}\}
if_expression = expression;	if_expression = expression;	if_expression → expression	if_expression(1: "(" , "NOT", "+", "-", "_", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression	if_expression = SAME_RULE(expression);	if_expression = SAME_RULE(expression);	{LA_IS, { "(", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "if_expression", {\ {LA_IS, {""}, 1, { "expression" }}\ }}\
body_for_true = block_statements_in_while_and_if_body;	body_for_true = block_statements_in_while_and_if_body;	body_for_true → block_statements_in_while_and_if_body	body_for_true(1: "(") → block_statements_in_while_and_if_body	body_for_true = SAME_RULE(block_statements_in_while_and_if_body);	body_for_true = SAME_RULE(block_statements_in_while_and_if_body);	{LA_IS, { T_BEGIN_BLOCK_0 }, { "body_for_true", {\ {LA_IS, {""}, 1, { "block_statements_in_while_and_if_body" }}\ }}\
false_cond_block_without_else = "ELSE" , "IF" , if_expression , body_for_true;	false_cond_block_without_else = "ELSE" , "IF" , if_expression , body_for_true;	false_cond_block_without_else → "ELSE" "IF" if_expression body_for_true	false_cond_block_without_else(1: "ELSE") → "ELSE" "IF" if_expression body_for_true	false_cond_block_without_else = tokenELSE >> tokenIF >> if_expression >> body_for_true;	false_cond_block_without_else = tokenELSE >> tokenIF >> if_expression >> body_for_true;	{LA_IS, { T_ELSE_IF_0 }, { "false_cond_block_without_else", {\ {LA_IS, {""}, 4, { T_ELSE_IF_0, T_ELSE_IF_1, "if_expression", "body_for_true" }}\ }}\
body_for_false = "ELSE" , block_statements_in_while_and_if_body;	body_for_false = "ELSE" , block_statements_in_while_and_if_body;	body_for_false → "ELSE" block_statements_in_while_and_if_body	body_for_false(1: "ELSE") → "ELSE" block_statements_in_while_and_if_body	body_for_false = tokenELSE >> block_statements_in_while_and_if_body;	body_for_false = tokenELSE >> block_statements_in_while_and_if_body;	{LA_IS, { T_ELSE_BLOCK_0 }, { "body_for_false", {\ {LA_IS, {""}, 2, { T_ELSE_BLOCK_0, "block_statements" }}\ }}\
cond_block = "IF" , if_expression , body_for_true, { false_cond_block_without_else } , body_for_false;	cond_block = "IF" , if_expression , body_for_true, { false_cond_block_without_else } , body_for_false__optional;	cond_block → "IF" if_expression body_for_true false_cond_block_without_else__iteration body_for_false__optional	cond_block(1: "IF") → "IF" if_expression body_for_true false_cond_block_without_else__iteration body_for_false__optional	cond_block = tokenIF >> if_expression >> body_for_true >> *false_cond_block_without_else >> -body_for_false;	cond_block = tokenIF >> if_expression >> body_for_true >> false_cond_block_without_else__iteration >> body_for_false__optional;	{LA_IS, { T_IF_0 }, { "cond_block", {\ {LA_IS, {""}, 5, { T_IF_0, "if_expression", "body_for_true", "false_cond_block_without_else__iteration", "body_for_false__optional" }}\ }}\
false_cond_block_without_else__iteration = false_cond_block_without_else, false_cond_block_without_else__iteration ε;	false_cond_block_without_else__iteration = false_cond_block_without_else, false_cond_block_without_else__iteration ε;	false_cond_block_without_else__iteration → false_cond_block_without_else false_cond_block_without_else__iteration false_cond_block_without_else__iteration → ε	false_cond_block_without_else__iteration(1: "ELSE"; 2: !"IF") → false_cond_block_without_else false_cond_block_without_else__iteration false_cond_block_without_else__iteration(1: "ELSE"; 2: !"IF") → ε false_cond_block_without_else__iteration(1: !"ELSE") → ε		false_cond_block_without_else__iteration = false_cond_block_without_else, false_cond_block_without_else__iteration "";	{LA_IS, { T_ELSE_IF_0 }, { "false_cond_block_without_else__iteration", {\ {LA_IS, { T_ELSE_IF_1 }, 2, { "false_cond_block_without_else", "false_cond_block_without_else__iteration" }}\, {LA_NOT, { T_ELSE_IF_1 }, 0, { "" }}\ }}\} {LA_NOT, { T_ELSE_IF_0 }, { "false_cond_block_without_else__iteration", {\ {LA_IS, {""}, 0, { "" }}\ }}\}
body_for_false__optional = body_for_false ε;	body_for_false__optional = body_for_false ε;	body_for_false__optional → body_for_false body_for_false__optional → ε	body_for_false__optional(1: "FALSE") → body_for_false body_for_false__optional(1: !"FALSE") → ε		body_for_false__optional = body_for_false "";	{LA_IS, { T_ELSE_BLOCK_0 }, { "body_for_false__optional", {\ {LA_IS, {""}, 1, { "body_for_false" }}\ }}\} {LA_NOT, { T_ELSE_BLOCK_0 }, { "body_for_false__optional", {\ {LA_IS, {""}, 0, { "" }}\ }}\}
cycle_begin_expression = expression;	cycle_begin_expression = expression;	cycle_begin_expression → expression	cycle_begin_expression(1: "(" , "NOT", "+", "-", "_", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression	cycle_begin_expression = SAME_RULE(expression);	cycle_begin_expression = SAME_RULE(expression);	{LA_IS, { "(", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "cycle_begin_expression", {\ {LA_IS, {""}, 1, { "expression" }}\ }}\
cycle_end_expression = expression;	cycle_end_expression = expression;	cycle_end_expression → expression	cycle_end_expression(1: "(" , "NOT", "+", "-", "_", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression	cycle_end_expression = SAME_RULE(expression);	cycle_end_expression = SAME_RULE(expression);	{LA_IS, { "(", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "cycle_end_expression", {\ {LA_IS, {""}, 1, { "expression" }}\ }}\

						statements__or_block_statements",{ {LA_IS,{""},1,{ "block_statements" }}\ }}\
input_rule = "GET" , (ident , [index_action] "(" , ident , [index_action] , ")");	input_rule = "GET", argument_for_input;	input_rule → "GET" argument_for_input	input_rule(1: "GET") → "GET" argument_for_input	input_rule = tokenGET >> (ident >> -index_action tokenGROUPEXPRESSIONBEGIN >> ident >> -index_action >> tokenGROUPEXPRESSIONEND);	input_rule = tokenGET >> argument_for_input;	{LA_IS,{ T_INPUT_0 }, { "input_rule",{ {LA_IS,{ "" }, 2, { T_INPUT_0, "argument_for_input" }}\ }}\
	argument_for_input = ident , index_action__optional; argument_for_input = "(" , "ident" , "index_action__optional" , ")" ;	argument_for_input → ident index_action__optional argument_for_input → "(" "ident" "index_action__optional" ")"	argument_for_input(1: "-") → ident index_action__optional argument_for_input(1: "(") → "(" "ident" "index_action__optional" ")"		argument_for_input = ident >> index_action__optional tokenGROUPEXPRESSIONBEGIN >> ident >> index_action__optional >> tokenGROUPEXPRESSIONEND;	{LA_IS,{ " ident_terminal " }, { "argument_for_input",{ {LA_IS,{ "" }, 2, { "ident", "index_action__optional" }}\ }}\ {LA_IS,{ "(" }, { "argument_for_input",{ {LA_IS,{ "" }, 4, { "(" , "ident", "index_action__optional", ")" }}\ }}\
output = "PUT" , expression;	output = "PUT", expression;	output → "PUT" expression	output(1: "PUT") → "PUT" expression	output = tokenPUT >> expression;	output = tokenPUT >> expression;	{LA_IS,{ T_OUTPUT_0 }, { "output_rule",{ {LA_IS,{ "" }, 2, { T_OUTPUT_0, "expression" }}\ }}\
statement = expression_or_cond_block__with_optional_assign labeled_point goto_label forto_cycle while_cycle repeat_until_cycle input_rule output_rule ";" ;	statement = expression_or_cond_block__with_optional_assign labeled_point goto_label forto_cycle while_cycle repeat_until_cycle input_rule output_rule ";" ;	statement → expression_or_cond_block__with_optional_assign statement → goto_label statement → labeled_point statement → forto_cycle statement → while_cycle statement → repeat_until_cycle statement → input_rule statement → output_rule statement → ";"	statement(1: "(" , "NOT" , "+" , "-" , "0" , " 1 " , " 3 " , " 4 " , " 5 " , " 6 " , " 7 " , " 8 " , " 9 " , "IF") → expression_or_cond_block__with_optional_assign statement(1: "-" ; 2: !" ;") → expression_or_cond_block__with_optional_assign statement(1: "-" , "-" ;") → labeled_point statement(1: "GOTO") → goto_label statement(1: "FOR") → forto_cycle statement(1: "WHILE") → while_cycle statement(1: "REPEAT") → repeat_until_cycle statement(1: "GET") → input_rule statement(1: "PUT") → output_rule statement(1: ";") → ";"	statement = expression_or_cond_block__with_optional_assign labeled_point goto_label forto_cycle while_cycle repeat_until_cycle input_rule output_rule tokenSEMICOLON;	statement = expression_or_cond_block__with_optional_assign labeled_point goto_label forto_cycle while_cycle repeat_until_cycle input_rule output_rule tokenSEMICOLON;	{LA_IS,{ ("", T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0 }, { "statement", { {LA_IS,{ "" }, 1, { "expression_or_cond_block__with_optional_assign" }}\ }}\ {LA_IS,{ " ident_terminal " }, { "statement", { {LA_NOT,{ T_COLON_0 }, 1, { "expression_or_cond_block__with_optional_assign" }}\ {LA_IS,{ T_COLON_0 }, 1, { "labeled_point" }}\ }}\ {LA_IS,{ T_GOTO_0 }, { "statement", { {LA_IS,{ "" }, 1, { "goto_label" }}\ }}\ {LA_IS,{ T_FOR_0 }, { "statement", { {LA_IS,{ "" }, 1, { "forto_cycle" }}\ }}\ {LA_IS,{ T_WHILE_0 }, { "statement", { {LA_IS,{ "" }, 1, { "while_cycle" }}\ }}\ {LA_IS,{ T_REPEAT_0 }, { "statement", { {LA_IS,{ "" }, 1, { "repeat_until_cycle" }}\ }}\ {LA_IS,{ T_INPUT_0 }, { "statement", { {LA_IS,{ "" }, 1, { "input_rule" }}\ }}\ {LA_IS,{ T_OUTPUT_0 }, { "statement", { {LA_IS,{ "" }, 1, { "output_rule" }}\ }}\ {LA_IS,{ T_SEMICOLON_0 }, { "statement", { {LA_IS,{ "" }, 1, { "" }}\ }}\
	statement__iteration = statement, statement__iteration ε;	statement__iteration → statement statement__iteration statement__iteration → ε	statement__iteration(1: "-" , "(" , "NOT" , "0" , " 1 " , " 2 " , " 3 " , " 4 " , " 5 " , " 6 " , " 7 " , " 8 " , " 9 " , "+" , "-" , "IF" , "FOR" , "WHILE" , "REPEAT" , "GOTO" , "GET" , "PUT" , ";") → statement statement__iteration statement__iteration(1: ! "-" , ! "(" , ! "NOT" , ! "0" , ! " 1 " , ! " 2 " , ! " 3 " , ! " 4 " , ! " 5 " , ! " 6 " , ! " 7 " , ! " 8 " , ! " 9 " , ! "+" , ! "-" , ! "IF" , ! "FOR" , ! "WHILE" , ! "REPEAT" , ! "GOTO" , ! "GET" , ! "PUT" , ! ";") → ε		statement__iteration = statement >> statement__iteration "";	{LA_IS,{ "ident_terminal" , "(" , T_NOT_0, "unsigned_value_terminal" , T_ADD_0, T_SUB_0, T_IF_0, T_FOR_0, T_WHILE_0, T_REPEAT_0, T_GOTO_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0 }, { "statement__iteration",{ {LA_IS,{ "" }, 2, { "statement", "statement__iteration" }}\ }}\ {LA_NOT,{ "ident_terminal" , "(" , T_NOT_0, "unsigned_value_terminal" , T_ADD_0, T_SUB_0, T_IF_0, T_FOR_0, T_WHILE_0, T_REPEAT_0, T_GOTO_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0 }, { "statement__iteration",{ {LA_IS,{ "" }, 0, { "" }}\ }}\
block_statements = "(" {statement} , ")" ;	block_statements = "(" {statement__iteration , "}" ;	block_statements → "(" {statement__iteration}"	block_statements(1: "(") → "(" {statement__iteration "}"	block_statements = tokenBEGINBLOCK >> *statement >> tokenENDBLOCK;	block_statements = tokenBEGINBLOCK >> statement__iteration >> tokenENDBLOCK;	{LA_IS,{ T_BEGIN_BLOCK_0 }, { "block_statements",{ {LA_IS,{ "" }, 3, { T_BEGIN_BLOCK_0, "statement__iteration" , T_END_BLOCK_0 }}\ }}\
	expression__optional = expression "";	expression__optional → expression expression__optional → ε	expression__optional(1: "(" , "NOT" , "+" , "-" , "-" , "0" , " 1 " , " 2 " , " 3 " , " 4 " , " 5 " , " 6 " , " 7 " , " 8 " , " 9 " , "IF") → expression expression__optional(1: ! "(" , ! "NOT" , ! "+" , ! "-" , ! "-" , ! "0" , ! " 1 " , ! " 2 " , ! " 3 " , ! " 4 " , ! " 5 " , ! " 6 " , ! " 7 " , ! " 8 " , ! " 9 " , ! "IF") → ε		expression__optional = expression "";	{LA_IS,{ ("", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal" , "unsigned_value_terminal" , T_IF_0 }, { "expression__optional",{ {LA_IS,{ "" }, 1, { "expression" }}\ }}\ {LA_NOT,{ ("", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal" , "unsigned_value_terminal" , T_IF_0 }, { "expression__optional",{ {LA_IS,{ "" }, 0, { "" }}\ }}\
program_rule = "NAME" , program_name , ";" , "BODY" , "DATA" , declaration__optional , ";" , statement__iteration , "END" ;	program_rule = "NAME" , program_name ";" "BODY" "DATA" declaration__optional ";" statement__iteration "END"	program_rule → "NAME" program_name ";" "BODY" "DATA" declaration__optional ";" statement__iteration "END"	program_rule(1: "NAME") → "NAME" program_name ";" "BODY" "DATA" declaration__optional ";" statement__iteration "END"	program_rule = BOUNDARIES >> tokenNAME >> program_name >> tokenSEMICOLON >> tokenBODY >> tokenDATA >> (-declaration) >> tokenSEMICOLON >> *statement >> tokenEND;	program_rule = BOUNDARIES >> tokenNAME >> program_name >> tokenSEMICOLON >> tokenBODY >> tokenDATA >> declaration__optional >> tokenSEMICOLON >> statement__iteration >> tokenEND;	{LA_IS,{ T_NAME_0 }, { "program_rule",{ {LA_IS,{ "" }, 9, { T_NAME_0 , "program_name", T_SEMICOLON_0, T_BODY_0, T_DATA_0, "declaration__optional", T_SEMICOLON_0, "statement__iteration", T_END_0 }}\ }}\
	declaration__optional = declaration "";	declaration__optional → declaration declaration__optional → ε	declaration__optional(1: "INTEGER16") → declaration declaration__optional(1: ! "INTEGER16") → ε		declaration__optional = declaration "";	{LA_IS,{ T_DATA_TYPE_0 }, { "declaration__optional",{ {LA_IS,{ "" }, 1, { "declaration" }}\ }}\ {LA_NOT,{ T_DATA_TYPE_0 }, { "declaration__optional",{ {LA_IS,{ "" }, 0, { "" }}\ }}\
value = [sign] , unsigned_value ;	value = sign__optional , unsigned_value ;	value → sign__optional unsigned_value	value(1: "0" , "1" , "2" , "3" , "4" , "5" , "6" , "7" , "8" , "9" , "+" , "-") → sign__optional unsigned_value	value = -sign >> unsigned_value >> BOUNDARIES;	value = sign__optional >> unsigned_value >> BOUNDARIES;	{LA_IS,{ "unsigned_value_terminal" , T_ADD_0, T_SUB_0 }, { "value", { {LA_IS,{ "" }, 2, { "sign__optional", "unsigned_value" }}\ }}\
	sign__optional = sign ε;	sign__optional → sign sign__optional → ε	sign__optional(1: "+" , "-") → sign sign__optional(1: ! "+" , ! "-") → ε		sign__optional = sign "";	{LA_IS,{ T_ADD_0, T_SUB_0 }, { "sign__optional", { {LA_IS,{ "" }, 1, { "sign" }}\ }}\ {LA_NOT,{ T_ADD_0, T_SUB_0 }, { "sign__optional", { {LA_IS,{ "" }, 0, { "" }}\ }}\
sign = sign_plus sign_minus;	sign → sign_plus sign → sign_minus	sign → sign_plus sign → sign_minus	sign(1: "+") → sign_plus sign(1: "-") → sign_minus	sign = sign_plus sign_minus;	sign = sign_plus sign_minus;	{LA_IS,{ T_ADD_0 }, { "sign", { {LA_IS,{ "" }, 1, { "sign_plus" }}\ }}\ {LA_IS,{ T_SUB_0 }, { "sign", { {LA_IS,{ "" }, 1, { "sign_minus" }}\ }}\
sign_plus = "+" ;	sign_plus = "+" ;	sign_plus → "+"	sign_plus(1: "+") → "+"	sign_plus = SAME_RULE(tokenPLUS);	sign_plus = SAME_RULE(tokenPLUS);	{LA_IS,{ T_ADD_0 }, { "sign_plus", { {LA_IS,{ "" }, 1, { T_ADD_0 }}\

						}};\
sign_minus = "-";	sign_minus = "-";	sign_minus → "-"	sign_minus(1: "-") → "-"	sign_minus = SAME_RULE(tokenMINUS);	sign_minus = SAME_RULE(tokenMINUS);	{LA_IS, {T_SUB_0 }, { "sign_minus", {\
	unsigned_value = non_zero_digit , digit_iteration "0";	unsigned_value → non_zero_digit digit_iteration unsigned_value → "0"	unsigned_value(1: "1", "2", "3", "4", "5", "6", "7", "8", "9") → non_zero_digit digit_iteration unsigned_value(1: "0") → "0"		unsigned_value = (non_zero_digit >> digit digit_0) >> BOUNDARIES;	/* unsigned_value token represents unsigned_value in lexical analyzer */\
unsigned_value = non_zero_digit , {digit} "0";						{LA_IS, { "unsigned_value_terminal" }, {\
	digit_iteration = digit, digit_iteration ε;	digit_iteration → digit digit_iteration digit_iteration → ε	digit_iteration(1: "0", "1", "2", "3", "4", "5", "6", "7", "8", "9") → digit digit_iteration digit_iteration(1: !"0", !"1", !"2", !"3", !"4", !"5", !"6", !"7", !"8", !"9") → ε		digit_iteration = digit, digit_iteration "";	}};\
digit = "0" non_zero_digit;	digit = "0" non_zero_digit;	digit → "0" digit → non_zero_digit	digit(1: "0") → "0" digit(1: "1", "2", "3", "4", "5", "6", "7", "8", "9",) → non_zero_digit	digit_0 = '0'; digit = digit_0 non_zero_digit;	digit_0 = '0'; digit = digit_0 non_zero_digit;	\
non_zero_digit = "1" "2" "3" "4" "5" "6" "7" "8" "9";	non_zero_digit = "1" "2" "3" "4" "5" "6" "7" "8" "9";	non_zero_digit → "1" non_zero_digit → "2" non_zero_digit → "3" non_zero_digit → "4" non_zero_digit → "5" non_zero_digit → "6" non_zero_digit → "7" non_zero_digit → "8" non_zero_digit → "9"	non_zero_digit(1: "1") → "1" non_zero_digit(1: "2") → "2" non_zero_digit(1: "3") → "3" non_zero_digit(1: "4") → "4" non_zero_digit(1: "5") → "5" non_zero_digit(1: "6") → "6" non_zero_digit(1: "7") → "7" non_zero_digit(1: "8") → "8" non_zero_digit(1: "9") → "9"	digit_1 = '1'; digit_2 = '2'; digit_3 = '3'; digit_4 = '4'; digit_5 = '5'; digit_6 = '6'; digit_7 = '7'; digit_8 = '8'; digit_9 = '9'; non_zero_digit = digit_1 digit_2 digit_3 digit_4 digit_5 digit_6 digit_7 digit_8 digit_9;	digit_1 = '1'; digit_2 = '2'; digit_3 = '3'; digit_4 = '4'; digit_5 = '5'; digit_6 = '6'; digit_7 = '7'; digit_8 = '8'; digit_9 = '9'; non_zero_digit = digit_1 digit_2 digit_3 digit_4 digit_5 digit_6 digit_7 digit_8 digit_9;	\
ident = "_", letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case ; etter_in_upper_case;	ident = "_", letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case ;	ident → "_" letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case	Ident(1: "_") → "_" letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case	tokenUNDERSCORE = "_"; ident = tokenUNDERSCORE >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> STRICT_BOUNDARIES;	tokenUNDERSCORE = "_"; ident = tokenUNDERSCORE >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> STRICT_BOUNDARIES;	/* ident token represents ident in lexical analyzer */\
	letter_in_lower_case = "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z";	letter_in_lower_case → "a" letter_in_lower_case → "b" letter_in_lower_case → "c" letter_in_lower_case → "d" letter_in_lower_case → "e" letter_in_lower_case → "f" letter_in_lower_case → "g" letter_in_lower_case → "h" letter_in_lower_case → "i" letter_in_lower_case → "j" letter_in_lower_case → "k" letter_in_lower_case → "l" letter_in_lower_case → "m" letter_in_lower_case → "n" letter_in_lower_case → "o" letter_in_lower_case → "p" letter_in_lower_case → "q" letter_in_lower_case → "r" letter_in_lower_case → "s" letter_in_lower_case → "t" letter_in_lower_case → "u" letter_in_lower_case → "v" letter_in_lower_case → "w" letter_in_lower_case → "x" letter_in_lower_case → "y" letter_in_lower_case → "z"	letter_in_lower_case(1: "a") → "a" letter_in_lower_case(1: "b") → "b" letter_in_lower_case(1: "c") → "c" letter_in_lower_case(1: "d") → "d" letter_in_lower_case(1: "e") → "e" letter_in_lower_case(1: "f") → "f" letter_in_lower_case(1: "g") → "g" letter_in_lower_case(1: "h") → "h" letter_in_lower_case(1: "i") → "i" letter_in_lower_case(1: "j") → "j" letter_in_lower_case(1: "k") → "k" letter_in_lower_case(1: "l") → "l" letter_in_lower_case(1: "m") → "m" letter_in_lower_case(1: "n") → "n" letter_in_lower_case(1: "o") → "o" letter_in_lower_case(1: "p") → "p" letter_in_lower_case(1: "q") → "q" letter_in_lower_case(1: "r") → "r" letter_in_lower_case(1: "s") → "s" letter_in_lower_case(1: "t") → "t" letter_in_lower_case(1: "u") → "u" letter_in_lower_case(1: "v") → "v" letter_in_lower_case(1: "w") → "w" letter_in_lower_case(1: "x") → "x" letter_in_lower_case(1: "y") → "y" letter_in_lower_case(1: "z") → "z"	A = "A"; B = "B"; C = "C"; D = "D"; E = "E"; F = "F"; G = "G"; H = "H"; I = "I"; J = "J"; K = "K"; L = "L"; M = "M"; N = "N"; O = "O"; P = "P"; Q = "Q"; R = "R"; S = "S"; T = "T"; U = "U"; V = "V"; W = "W"; X = "X"; Y = "Y"; Z = "Z"; letter_in_lower_case = a b c d e f g h i j k l m n o p q r s t u v w x y z;	A = "A"; B = "B"; C = "C"; D = "D"; E = "E"; F = "F"; G = "G"; H = "H"; I = "I"; J = "J"; K = "K"; L = "L"; M = "M"; N = "N"; O = "O"; P = "P"; Q = "Q"; R = "R"; S = "S"; T = "T"; U = "U"; V = "V"; W = "W"; X = "X"; Y = "Y"; Z = "Z"; letter_in_lower_case = a b c d e f g h i j k l m n o p q r s t u v w x y z;	\
	letter_in_upper_case = "A" "B" "C" "D" "E" "F" "G" "H" "I" "J" "K" "L" "M" "N" "O" "P" "Q" "R" "S" "T" "U" "V" "W" "X" "Y" "Z";	letter_in_upper_case → "A" letter_in_upper_case → "B" letter_in_upper_case → "C" letter_in_upper_case → "D" letter_in_upper_case → "E" letter_in_upper_case → "F" letter_in_upper_case → "G" letter_in_upper_case → "H" letter_in_upper_case → "I" letter_in_upper_case → "J" letter_in_upper_case → "K" letter_in_upper_case → "L" letter_in_upper_case → "M" letter_in_upper_case → "N" letter_in_upper_case → "O" letter_in_upper_case → "P" letter_in_upper_case → "Q" letter_in_upper_case → "R" letter_in_upper_case → "S" letter_in_upper_case → "T" letter_in_upper_case → "U" letter_in_upper_case → "V" letter_in_upper_case → "W" letter_in_upper_case → "X" letter_in_upper_case → "Y" letter_in_upper_case → "Z"	letter_in_upper_case(1: "A") → "A" letter_in_upper_case(1: "B") → "B" letter_in_upper_case(1: "C") → "C" letter_in_upper_case(1: "D") → "D" letter_in_upper_case(1: "E") → "E" letter_in_upper_case(1: "F") → "F" letter_in_upper_case(1: "G") → "G" letter_in_upper_case(1: "H") → "H" letter_in_upper_case(1: "I") → "I" letter_in_upper_case(1: "J") → "J" letter_in_upper_case(1: "K") → "K" letter_in_upper_case(1: "L") → "L" letter_in_upper_case(1: "M") → "M" letter_in_upper_case(1: "N") → "N" letter_in_upper_case(1: "O") → "O" letter_in_upper_case(1: "P") → "P" letter_in_upper_case(1: "Q") → "Q" letter_in_upper_case(1: "R") → "R" letter_in_upper_case(1: "S") → "S" letter_in_upper_case(1: "T") → "T" letter_in_upper_case(1: "U") → "U" letter_in_upper_case(1: "V") → "V" letter_in_upper_case(1: "W") → "W" letter_in_upper_case(1: "X") → "X" letter_in_upper_case(1: "Y") → "Y" letter_in_upper_case(1: "Z") → "Z"	a = "a"; b = "b"; c = "c"; d = "d"; e = "e"; f = "f"; g = "g"; h = "h"; i = "i"; j = "j"; k = "k"; l = "l"; m = "m"; n = "n"; o = "o"; p = "p"; q = "q"; r = "r"; s = "s"; t = "t"; u = "u"; v = "v"; w = "w"; x = "x"; y = "y"; z = "z"; letter_in_upper_case = A B C D E F G H I J K L M N O P Q R S T U V W X Y Z;	a = "a"; b = "b"; c = "c"; d = "d"; e = "e"; f = "f"; g = "g"; h = "h"; i = "i"; j = "j"; k = "k"; l = "l"; m = "m"; n = "n"; o = "o"; p = "p"; q = "q"; r = "r"; s = "s"; t = "t"; u = "u"; v = "v"; w = "w"; x = "x"; y = "y"; z = "z"; letter_in_upper_case = A B C D E F G H I J K L M N O P Q R S T U V W X Y Z;	\
				STRICT_BOUNDARIES = (BOUNDARY >> *(BOUNDARY)) (!(qi::alpha qi::char ("_")));	STRICT_BOUNDARIES = (BOUNDARY >> *(BOUNDARY)) (!(qi::alpha qi::char ("_")));	\
				BOUNDARIES = (BOUNDARY >> *(BOUNDARY) NO_BOUNDARY);	BOUNDARIES = (BOUNDARY >> *(BOUNDARY) NO_BOUNDARY);	\
				BOUNDARY = BOUNDARY_SPACE BOUNDARY_TAB BOUNDARY_CARRIAGE_RETURN BOUNDARY_LINE_FEED BOUNDARY_NULL;	BOUNDARY = BOUNDARY_SPACE BOUNDARY_TAB BOUNDARY_CARRIAGE_RETURN BOUNDARY_LINE_FEED BOUNDARY_NULL;	\
				BOUNDARY_SPACE = " ";	BOUNDARY_SPACE = " ";	\
				BOUNDARY_TAB = "\t";	BOUNDARY_TAB = "\t";	\
				BOUNDARY_CARRIAGE_RETURN = "\r";	BOUNDARY_CARRIAGE_RETURN = "\r";	\
				BOUNDARY_LINE_FEED = "\n";	BOUNDARY_LINE_FEED = "\n";	\

