

РБНФ №1 (опис синтаксису всіма допустимими засобами РБНФ)	РБНФ №2 (опис формальної граматики засобами РБНФ)	Формальна граматика	Формальна граматика з специфікацією lookahead у правилах для LL(2)-аналізатора	Перевірка РБНФ №1 за допомогою коду <i>(помістити у файл "EBNF_N1.h")</i> */	Перевірка РБНФ №2 за допомогою коду <i>(помістити у файл "EBNF_N2.h")</i> */	Перевірки прототипу LL(2)-синтаксичного аналізатора (спеціальна структура) та прототипу лексичного аналізатора (регулярні вирази) за допомогою коду. Лексеми для синтаксичного аналізатора обробляються лексичним аналізатором, тому синтаксичний аналізатор не аналізує їх повторно (як показано в РБНФ). <i>(помістити у файл "LexicaByRegExAndSyntaxByLL2prototype.h")</i> УВАГА: при копіюванні зважайте, щоб у кожному рядку після символу «\» не містилось жодних інших символів. */
		G = {N, T, P, S}	G = {N, T, P, S}			
		S → program_rule	S → program_rule			
		N = { program_name, value_type, array_specify, declaration_element, array_specify_optional, other_declaration_ident, declaration, other_declaration_ident__iteration, index_action, unary_operator, unary_operation, binary_operator, binary_action, left_expression, group_expression, index_action_optional, expression, binary_action__iteration, expression_or_cond_block__with_optional_assign, assign_to_right, assign_to_right_optional, if_expression, body_for_true, false_cond_block_without_else, body_for_false, cond_block, false_cond_block_without_else__iteration, body_for_false_optional, cycle_begin_expression, cycle_end_expression, cycle_counter, cycle_counter_lr_init, cycle_counter_init, cycle_counter_last_value, cycle_body, forto_cycle, statement, statement_or__block_statements, block_statements, input_rule, argument_for_input, output_rule, statement__iteration, expression_optional, program_rule, declaration_optional, non_zero_digit, digit__iteration, digit, unsigned_value, value, sign_optional, sign, ident, letter_in_upper_case, letter_in_lower_case, sign_plus, sign_minus }	N = { program_name, value_type, array_specify, declaration_element, array_specify_optional, other_declaration_ident, declaration, other_declaration_ident__iteration, index_action, unary_operator, unary_operation, binary_operator, binary_action, left_expression, group_expression, index_action_optional, expression, binary_action__iteration, expression_or_cond_block__with_optional_assign, assign_to_right, assign_to_right_optional, if_expression, body_for_true, false_cond_block_without_else, body_for_false, cond_block, false_cond_block_without_else__iteration, body_for_false_optional, cycle_begin_expression, cycle_end_expression, cycle_counter, cycle_counter_lr_init, cycle_counter_init, cycle_counter_last_value, cycle_body, forto_cycle, statement, statement_or__block_statements, block_statements, input_rule, argument_for_input, output_rule, statement__iteration, expression_optional, program_rule, declaration_optional, non_zero_digit, digit__iteration, digit, unsigned_value, value, sign_optional, sign, ident, letter_in_upper_case, letter_in_lower_case, sign_plus, sign_minus }	#define NONTERMINALS program_name, \ value_type, \ array_specify, \ declaration_element, \ \ other_declaration_ident, \ declaration, \ \ index_action, \ unary_operator, \ unary_operation, \ binary_operator, \ binary_action, \ left_expression, \ group_expression, \ \ expression, \ \ expression_or_cond_block__with_optional_assign, \ assign_to_right, \ \ if_expression, \ body_for_true, \ false_cond_block_without_else, \ body_for_false, \ cond_block, \ \ \ cycle_begin_expression, \ cycle_end_expression, \ cycle_counter, \ cycle_counter_lr_init, \ cycle_counter_init, \ cycle_counter_last_value, \ cycle_body, \ forto_cycle, \ statement, \ statement_or__block_statements, \ block_statements, \ input_rule, \ argument_for_input, \ output_rule, \ \ \ program_rule, \ \ non_zero_digit, \ digit__iteration, \ digit, \ unsigned_value, \ value, \ \ sign, \ ident, \ letter_in_upper_case, \ letter_in_lower_case, \ sign_plus, \ sign_minus	#define NONTERMINALS program_name, \ value_type, \ array_specify, \ declaration_element, \ \ other_declaration_ident, \ declaration, \ \ other_declaration_ident__iteration, \ index_action, \ unary_operator, \ unary_operation, \ binary_operator, \ binary_action, \ left_expression, \ group_expression, \ index_action_optional, \ expression, \ \ binary_action__iteration, \ expression_or_cond_block__with_optional_assign, \ assign_to_right, \ assign_to_right_optional, \ if_expression, \ body_for_true, \ false_cond_block_without_else, \ body_for_false, \ cond_block, \ false_cond_block_without_else__iteration, \ body_for_false_optional, \ cycle_begin_expression, \ cycle_end_expression, \ cycle_counter, \ cycle_counter_lr_init, \ cycle_counter_init, \ cycle_counter_last_value, \ cycle_body, \ forto_cycle, \ statement, \ statement_or__block_statements, \ block_statements, \ input_rule, \ argument_for_input, \ output_rule, \ statement__iteration, \ expression_optional, \ program_rule, \ declaration_optional, \ non_zero_digit, \ digit__iteration, \ digit, \ unsigned_value, \ value, \ sign_optional, \ sign, \ ident, \ letter_in_upper_case, \ letter_in_lower_case, \ sign_plus, \ sign_minus	
		T = { "INTEGER16", " ", "NOT", "AND", "OR", "==", "!=", "<", ">", "*", "-", "DIV", "MOD",	T = { "INTEGER16", " ", "NOT", "AND", "OR", "==", "!=", "<", ">", "*", "-", "DIV", "MOD",	#define TOKENS \ tokenINTEGER16, \ tokenCOMMA, \ tokenNOT, \ tokenAND, \ tokenOR, \ tokenEQUAL, \ tokenNOTEQUAL, \ tokenLESS, \ tokenGREATER, \ tokenPLUS, \ tokenMINUS, \ tokenMUL, \ tokenDIV, \ tokenMOD, \	#define TOKENS \ tokenINTEGER16, \ tokenCOMMA, \ tokenNOT, \ tokenAND, \ tokenOR, \ tokenEQUAL, \ tokenNOTEQUAL, \ tokenLESS, \ tokenGREATER, \ tokenPLUS, \ tokenMINUS, \ tokenMUL, \ tokenDIV, \ tokenMOD, \	

		<pre>"(", ")", "=", "ELSE", "IF", "DO", "FOR", "TO", "EXIT", "GET", "PUT", "NAME", "BODY", "DATA", "BEGIN", "END", "[", "]", "[", "]", " ", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", " _", "A", "B", "C", "D", "E", "F", "G", "H", "I", "J", "K", "L", "M", "N", "O", "P", "Q", "R", "S", "T", "U", "V", "W", "X", "Y", "Z", "a", "b", "c", "d", "e", "f", "g", "h", "i", "j", "k", "l", "m", "n", "o", "p", "q", "r", "s", "t", "u", "v", "w", "x", "y", "z"} </pre>	<pre>"(", ")", "=", "ELSE", "IF", "DO", "FOR", "TO", "EXIT", "GET", "PUT", "NAME", "BODY", "DATA", "BEGIN", "END", "[", "]", "[", "]", " ", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", " _", "A", "B", "C", "D", "E", "F", "G", "H", "I", "J", "K", "L", "M", "N", "O", "P", "Q", "R", "S", "T", "U", "V", "W", "X", "Y", "Z", "a", "b", "c", "d", "e", "f", "g", "h", "i", "j", "k", "l", "m", "n", "o", "p", "q", "r", "s", "t", "u", "v", "w", "x", "y", "z"} </pre>	<pre>tokenGROUPEXPRESSIONBEGIN, \ tokenGROUPEXPRESSIONEND, \ tokenLRASSIGN, \ tokenELSE, \ tokenIF, \ tokenDO, \ tokenFOR, \ tokenTO, \ tokenEXIT, \ tokenGET, \ tokenPUT, \ tokenNAME, \ tokenBODY, \ tokenDATA, \ tokenBEGIN, \ tokenEND, \ tokenBEGINBLOCK, \ tokenENDBLOCK, \ tokenLEFTSQUAREBRACKETS, \ tokenRIGHTSQUAREBRACKETS, \ tokenSEMICOLON, \ digit_0, \ digit_1, \ digit_2, \ digit_3, \ digit_4, \ digit_5, \ digit_6, \ digit_7, \ digit_8, \ digit_9, \ tokenUNDERSCORE, \ A, \ B, \ C, \ D, \ E, \ F, \ G, \ H, \ I, \ J, \ K, \ L, \ M, \ N, \ O, \ P, \ Q, \ R, \ S, \ T, \ U, \ V, \ W, \ X, \ Y, \ Z, \ a, \ b, \ c, \ d, \ e, \ f, \ g, \ h, \ i, \ j, \ k, \ l, \ m, \ n, \ o, \ p, \ q, \ r, \ s, \ t, \ u, \ v, \ w, \ x, \ y, \ z </pre>	<pre>tokenGROUPEXPRESSIONBEGIN, \ tokenGROUPEXPRESSIONEND, \ tokenLRASSIGN, \ tokenELSE, \ tokenIF, \ tokenDO, \ tokenFOR, \ tokenTO, \ tokenEXIT, \ tokenGET, \ tokenPUT, \ tokenNAME, \ tokenBODY, \ tokenDATA, \ tokenBEGIN, \ tokenEND, \ tokenBEGINBLOCK, \ tokenENDBLOCK, \ tokenLEFTSQUAREBRACKETS, \ tokenRIGHTSQUAREBRACKETS, \ tokenSEMICOLON, \ digit_0, \ digit_1, \ digit_2, \ digit_3, \ digit_4, \ digit_5, \ digit_6, \ digit_7, \ digit_8, \ digit_9, \ tokenUNDERSCORE, \ A, \ B, \ C, \ D, \ E, \ F, \ G, \ H, \ I, \ J, \ K, \ L, \ M, \ N, \ O, \ P, \ Q, \ R, \ S, \ T, \ U, \ V, \ W, \ X, \ Y, \ Z, \ a, \ b, \ c, \ d, \ e, \ f, \ g, \ h, \ i, \ j, \ k, \ l, \ m, \ n, \ o, \ p, \ q, \ r, \ s, \ t, \ u, \ v, \ w, \ x, \ y, \ z </pre>	<pre>#define COMMENT_BEGIN_STR "##" #define COMMENT_END_STR "##" #define TOKENS_RE "[: = < > + - * . , ; ' \" \\\\\\\\ \\\\\\\\\\\\\\\\ \\\\\\\\\\\\\\\\\\\\\\\\ < > [_0-9A-Za-z]+ \"[^\"]*\" '[^']*' \\s+" #define IDENTIFIERS_RE "[_A-Z][A-Z][A-Z][A-Z][A-Z][A-Z]" #define UNSIGNEDVALUES_RE "[0][1-9][0-9]+"</pre>
				<pre>tokenGROUPEXPRESSIONBEGIN = "(" >> BOUNDARIES;</pre>	<pre>tokenGROUPEXPRESSIONBEGIN = "(" >> BOUNDARIES;</pre>	<pre>#define T_BEGIN GROUPEXPRESSION_0 "(" #define T_BEGIN GROUPEXPRESSION_1 "" #define T_BEGIN GROUPEXPRESSION_2 "" #define T_BEGIN GROUPEXPRESSION_3 ""</pre>
				<pre>tokenGROUPEXPRESSIONEND = ")" >> BOUNDARIES;</pre>	<pre>tokenGROUPEXPRESSIONEND = ")" >> BOUNDARIES;</pre>	<pre>#define T_END GROUPEXPRESSION_0 ")" #define T_END GROUPEXPRESSION_1 "" #define T_END GROUPEXPRESSION_2 "" #define T_END GROUPEXPRESSION_3 ""</pre>
				<pre>tokenLEFTSQUAREBRACKETS = "[" >> BOUNDARIES;</pre>	<pre>tokenLEFTSQUAREBRACKETS = "[" >> BOUNDARIES;</pre>	<pre>#define T_LEFT SQUAREBRACKETS_0 "[" #define T_LEFT SQUAREBRACKETS_1 "" #define T_LEFT SQUAREBRACKETS_2 "" #define T_LEFT SQUAREBRACKETS_3 ""</pre>
				<pre>tokenRIGHTSQUAREBRACKETS = "]" >> BOUNDARIES;</pre>	<pre>tokenRIGHTSQUAREBRACKETS = "]" >> BOUNDARIES;</pre>	<pre>#define T_RIGHT SQUAREBRACKETS_0 "]" #define T_RIGHT SQUAREBRACKETS_1 "" #define T_RIGHT SQUAREBRACKETS_2 "" #define T_RIGHT SQUAREBRACKETS_3 ""</pre>

				tokenBEGINBLOCK = "{" >> BOUNDARIES;	tokenBEGINBLOCK = "{" >> BOUNDARIES;	#define T_BEGIN_BLOCK_0 "{" #define T_BEGIN_BLOCK_1 "" #define T_BEGIN_BLOCK_2 "" #define T_BEGIN_BLOCK_3 ""
				tokenENDBLOCK = "}" >> BOUNDARIES;	tokenENDBLOCK = "}" >> BOUNDARIES;	#define T_END_BLOCK_0 "}" #define T_END_BLOCK_1 "" #define T_END_BLOCK_2 "" #define T_END_BLOCK_3 ""
				tokenSEMICOLON = ";" >> BOUNDARIES;	tokenSEMICOLON = ";" >> BOUNDARIES;	#define T_SEMICOLON_0 ";" #define T_SEMICOLON_1 "" #define T_SEMICOLON_2 "" #define T_SEMICOLON_3 ""
				tokenINTEGER16 = "INTEGER16" >> STRICT_BOUNDARIES;	tokenINTEGER16 = "INTEGER16" >> STRICT_BOUNDARIES;	#define T_DATA_TYPE_0 "INTEGER16" #define T_DATA_TYPE_1 "" #define T_DATA_TYPE_2 "" #define T_DATA_TYPE_3 ""
				tokenCOMMA = "," >> BOUNDARIES;	tokenCOMMA = "," >> BOUNDARIES;	#define T_COMA_0 "," #define T_COMA_1 "" #define T_COMA_2 "" #define T_COMA_3 ""
						#define T_BITWISE_NOT_0 "~" #define T_BITWISE_NOT_1 "" #define T_BITWISE_NOT_2 "" #define T_BITWISE_NOT_3 ""
				tokenNOT = "NOT" >> STRICT_BOUNDARIES;	tokenNOT = "NOT" >> STRICT_BOUNDARIES;	#define T_NOT_0 "NOT" #define T_NOT_1 "" #define T_NOT_2 "" #define T_NOT_3 ""
						#define T_BITWISE_AND_0 "&" #define T_BITWISE_AND_1 "" #define T_BITWISE_AND_2 "" #define T_BITWISE_AND_3 ""
				tokenAND = "AND" >> STRICT_BOUNDARIES;	tokenAND = "AND" >> STRICT_BOUNDARIES;	#define T_AND_0 "AND" #define T_AND_1 "" #define T_AND_2 "" #define T_AND_3 ""
						#define T_BITWISE_OR_0 " " #define T_BITWISE_OR_1 "" #define T_BITWISE_OR_2 "" #define T_BITWISE_OR_3 ""
				tokenOR = "OR" >> STRICT_BOUNDARIES;	tokenOR = "OR" >> STRICT_BOUNDARIES;	#define T_OR_0 "OR" #define T_OR_1 "" #define T_OR_2 "" #define T_OR_3 ""
				tokenEQUAL = "==" >> BOUNDARIES;	tokenEQUAL = "==" >> BOUNDARIES;	#define T_EQUAL_0 "==" #define T_EQUAL_1 "" #define T_EQUAL_2 "" #define T_EQUAL_3 ""
				tokenNOTEQUAL = "!=" >> BOUNDARIES;	tokenNOTEQUAL = "!=" >> BOUNDARIES;	#define T_NOT_EQUAL_0 "!=" #define T_NOT_EQUAL_1 "" #define T_NOT_EQUAL_2 "" #define T_NOT_EQUAL_3 ""
				tokenLESS = "<" >> BOUNDARIES;	tokenLESS = "<" >> BOUNDARIES;	#define T_LESS_0 "<" #define T_LESS_1 "" #define T_LESS_2 "" #define T_LESS_3 ""
				tokenGREATER = ">" >> BOUNDARIES;	tokenGREATER = ">" >> BOUNDARIES;	#define T_GREATER_0 ">" #define T_GREATER_1 "" #define T_GREATER_2 "" #define T_GREATER_3 ""
				tokenPLUS = "+" >> BOUNDARIES;	tokenPLUS = "+" >> BOUNDARIES;	#define T_ADD_0 "+" #define T_ADD_1 "" #define T_ADD_2 "" #define T_ADD_3 ""
				tokenMINUS = "-" >> BOUNDARIES;	tokenMINUS = "-" >> BOUNDARIES;	#define T_SUB_0 "-" #define T_SUB_1 "" #define T_SUB_2 "" #define T_SUB_3 ""
				tokenMUL = "*" >> BOUNDARIES;	tokenMUL = "*" >> BOUNDARIES;	#define T_MUL_0 "*" #define T_MUL_1 "" #define T_MUL_2 "" #define T_MUL_3 ""
				tokenDIV = "DIV" >> STRICT_BOUNDARIES;	tokenDIV = "DIV" >> STRICT_BOUNDARIES;	#define T_DIV_0 "DIV" #define T_DIV_1 "" #define T_DIV_2 "" #define T_DIV_3 ""
				tokenMOD = "MOD" >> STRICT_BOUNDARIES;	tokenMOD = "MOD" >> STRICT_BOUNDARIES;	#define T_MOD_0 "MOD" #define T_MOD_1 "" #define T_MOD_2 "" #define T_MOD_3 ""
				tokenLRASSIGN = "=:;" >> BOUNDARIES;	tokenLRASSIGN = "=:;" >> BOUNDARIES;	#define T_LRASSIGN_0 "=:;" #define T_LRASSIGN_1 "" #define T_LRASSIGN_2 "" #define T_LRASSIGN_3 ""
						#define T_THEN_BLOCK_0 "{" #define T_THEN_BLOCK_1 "" #define T_THEN_BLOCK_2 "" #define T_THEN_BLOCK_3 ""
				tokenELSE = "ELSE" >> STRICT_BOUNDARIES;	tokenELSE = "ELSE" >> STRICT_BOUNDARIES;	#define T_ELSE_BLOCK_0 "ELSE" #define T_ELSE_BLOCK_1 T_BEGIN_BLOCK_0 #define T_ELSE_BLOCK_2 "" #define T_ELSE_BLOCK_3 ""
				tokenIF = "IF" >> STRICT_BOUNDARIES;	tokenIF = "IF" >> STRICT_BOUNDARIES;	#define T_IF_0 "IF" #define T_IF_1 "" #define T_IF_2 "" #define T_IF_3 ""
						#define T_ELSE_IF_0 "ELSE" #define T_ELSE_IF_1 T_IF_0 #define T_ELSE_IF_2 "" #define T_ELSE_IF_3 ""
				tokenDO = "DO" >> STRICT_BOUNDARIES;	tokenDO = "DO" >> STRICT_BOUNDARIES;	#define T_DO_0 "DO" #define T_DO_1 "" #define T_DO_2 "" #define T_DO_3 ""
				tokenFOR = "FOR" >> STRICT_BOUNDARIES;	tokenFOR = "FOR" >> STRICT_BOUNDARIES;	#define T_FOR_0 "FOR" #define T_FOR_1 "" #define T_FOR_2 ""

					#define T_FOR_3 ""
				tokenTO = "TO" >> STRICT_BOUNDARIES;	#define T_TO_0 "TO" #define T_TO_1 "" #define T_TO_2 "" #define T_TO_3 ""
				tokenEXIT = "EXIT" >> STRICT_BOUNDARIES;	#define T_EXIT_0 "EXIT" #define T_EXIT_1 "" #define T_EXIT_2 "" #define T_EXIT_3 ""
				tokenGET = "GET" >> STRICT_BOUNDARIES;	#define T_INPUT_0 "GET" #define T_INPUT_1 "" #define T_INPUT_2 "" #define T_INPUT_3 ""
				tokenPUT = "PUT" >> STRICT_BOUNDARIES;	#define T_OUTPUT_0 "PUT" #define T_OUTPUT_1 "" #define T_OUTPUT_2 "" #define T_OUTPUT_3 ""
				tokenNAME = "NAME" >> STRICT_BOUNDARIES;	#define T_NAME_0 "NAME" #define T_NAME_1 "" #define T_NAME_2 "" #define T_NAME_3 ""
				tokenBODY = "BODY" >> STRICT_BOUNDARIES;	#define T_BODY_0 "BODY" #define T_BODY_1 "" #define T_BODY_2 "" #define T_BODY_3 ""
				tokenDATA = "DATA" >> STRICT_BOUNDARIES;	#define T_DATA_0 "DATA" #define T_DATA_1 "" #define T_DATA_2 "" #define T_DATA_3 ""
				tokenBEGIN = "BEGIN" >> STRICT_BOUNDARIES;	#define T_BEGIN_0 "BEGIN" #define T_BEGIN_1 "" #define T_BEGIN_2 "" #define T_BEGIN_3 ""
				tokenEND = "END" >> STRICT_BOUNDARIES;	#define T_END_0 "END" #define T_END_1 "" #define T_END_2 "" #define T_END_3 ""
					#define T_NULL_STATEMENT_0 "NULL" #define T_NULL_STATEMENT_1 "STATEMENT" #define T_NULL_STATEMENT_2 "" #define T_NULL_STATEMENT_3 ""
					#define GRAMMAR_LL2_2025 {\
program_name = ident;	program_name = ident;	program_name → ident	program_name(1: "ident_terminal") → ident	program_name = SAME_RULE(ident);	{ LA_IS, ("ident_terminal"), { "program_name", {\
value_type = "INTEGER16";	value_type = "INTEGER16";	value_type → "INTEGER16"	value_type(1: "INTEGER16") → "INTEGER16"	value_type = SAME_RULE(tokenINTEGER16);	{ LA_IS, (T_DATA_TYPE_0), { "value_type", {\
	array_specify = "[", unsigned_value, "]"	array_specify → "[", unsigned_value "]"	array_specify(1: "[" → "[", unsigned_value "]"		{ LA_IS, ("["), { "array_specify", {\
declaration_element = ident, array_specify__optional;	declaration_element = ident, array_specify__optional;	declaration_element → ident array_specify__optional	declaration_element(1: "ident_terminal") → ident array_specify__optional	declaration_element = ident >> -(tokenLEFTSQUAREBRACKETS >> unsigned_value >> tokenRIGHTSQUAREBRACKETS);	{ LA_IS, ("ident_terminal"), { "declaration_element", {\
	array_specify__optional = array_specify ε;	array_specify__optional → array_specify array_specify__optional → ε	array_specify__optional(1: "[" → array_specify array_specify__optional(1: !"[" → ε		{ LA_IS, ("["), { "array_specify__optional", {\
other_declaration_ident = " ,", declaration_element;	other_declaration_ident = " ,", declaration_element;	other_declaration_ident → " ,", declaration_element	other_declaration_ident(1: " ,") → " ,", declaration_element	other_declaration_ident = tokenCOMMA >> declaration_element;	{ LA_IS, (T_COMA_0), { "other_declaration_ident", {\
declaration = value_type , declaration_element , other_declaration_ident__iteration;	declaration = value_type , declaration_element , other_declaration_ident__iteration;	declaration → value_type declaration_element other_declaration_ident__iteration	declaration(1: "INTEGER16") → value_type declaration_element other_declaration_ident__iteration	declaration = value_type >> declaration_element >> *other_declaration_ident;	{ LA_IS, (T_DATA_TYPE_0), { "declaration", {\
	other_declaration_ident__iteration = other_declaration_ident, other_declaration_ident__iteration ε;	other_declaration_ident__iteration → other_declaration_ident other_declaration_ident__iteration false_cond_block_without_else__iteration → ε	other_declaration_ident__iteration(1: " ,") → other_declaration_ident other_declaration_ident__iteration false_cond_block_without_else__iteration(1: !" ,") → ε		{ LA_IS, (T_COMA_0), { "other_declaration_ident__iteration", {\
index_action = "[", expression , "]"	index_action = "[", expression , "]"	index_action → "[", expression "]"	index_action(1: "[" → "[", expression "]"	index_action = tokenLEFTSQUAREBRACKETS >> expression >> tokenRIGHTSQUAREBRACKETS;	{ LA_IS, ("["), { "index_action", {\
unary_operator = "NOT";	unary_operator = "NOT";	unary_operator → "NOT"	unary_operator(1: "NOT") → "NOT"	unary_operator = SAME_RULE(tokenNOT);	{ LA_IS, (T_NOT_0), { "unary_operator", {\
unary_operation = unary_operator , expression;	unary_operation = unary_operator , expression;	unary_operation → unary_operator expression	unary_operation(1: "NOT") → unary_operator expression	unary_operation = unary_operator >> expression;	{ LA_IS, (T_NOT_0), { "unary_operation", {\
binary_operator = "AND" "OR" "==" "!=" "<" ">" "+" "-" "*" "DIV" "MOD";	binary_operator = "AND" "OR" "==" "!=" "<" ">" "+" "-" "*" "DIV" "MOD";	binary_operator → "AND" binary_operator → "OR" binary_operator → "==" binary_operator → "!=" binary_operator → "<" binary_operator → ">" binary_operator → "+" binary_operator → "-" binary_operator → "*" binary_operator → "DIV" binary_operator → "MOD"	binary_operator(1: "AND") → "AND" binary_operator(1: "OR") → "OR" binary_operator(1: "==") → "==" binary_operator(1: "!=") → "!=" binary_operator(1: "<") → "<" binary_operator(1: ">") → ">" binary_operator(1: "+") → "+" binary_operator(1: "-") → "-" binary_operator(1: "*") → "*" binary_operator(1: "DIV") → "DIV" binary_operator(1: "MOD") → "MOD"	binary_operator = tokenAND tokenOR tokenEQUAL tokenNOTEQUAL tokenLESS tokenGREATER tokenPLUS tokenMINUS tokenMUL tokenDIV tokenMOD;	{ LA_IS, (T_AND_0), { "binary_operator", {\

						{ LA_IS, { T_SUB_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_SUB_0 }}\ }};\ { LA_IS, { T_MUL_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_MUL_0 }}\ }};\ { LA_IS, { T_DIV_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_DIV_0 }}\ }};\ { LA_IS, { T_MOD_0 }, { "binary_operator", {\ { LA_IS, { "" }, 1, { T_MOD_0 }}\ }};\ }
binary_action = binary_operator , expression;	binary_action = binary_operator , expression;	binary_action → binary_operator expression	binary_action(1: "AND", "OR", "=", "!=", "<", ">", "+", "-", "*", "DIV", "MOD") → binary_operator expression	binary_action = binary_operator >> expression;		{ LA_IS, { T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_0, T_GREATER_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0 }, {\ "binary_action", {\ { LA_IS, { "" }, 2, { "binary_operator", "expression" }}\ }};\ }
left_expression = group_expression unary_operation ident , [index_action] value cond_block;	left_expression = group_expression unary_operation ident , index_action__optional value cond_block;	left_expression → group_expression left_expression → unary_operation left_expression → ident , index_action__optional left_expression → value left_expression → cond_block	left_expression(1: "(" → group_expression left_expression(1: "NOT") → unary_operation left_expression(1: "-") → ident , index_action__optional left_expression(1: "0", "1", "2", "3", "4", "5", "6", "7", "8", "9") → value left_expression(1: "+", "-", "; 2: "0", "1", "2", "3", "4", "5", "6", "7", "8", "9") → value left_expression(1: "IF") → cond_block	left_expression = group_expression unary_operation ident >> -index_action value cond_block;	left_expression = group_expression unary_operation ident >> index_action__optional value cond_block;	{LA_IS, { "(" }, { "left_expression", {\ { LA_IS, { "" }, 1, { "group_expression" }}\ }};\ {LA_IS, { T_NOT_0 }, { "left_expression", {\ { LA_IS, { "" }, 1, { "unary_operation" }}\ }};\ {LA_IS, { "ident_terminal" }, { "left_expression", {\ { LA_IS, { "" }, 2, { "ident", "index_action__optional" }}\ }};\ {LA_IS, { "unsigned_value_terminal" }, { "left_expression", {\ "left_expression", {\ { LA_IS, { "" }, 1, { "value" }}\ }};\ {LA_IS, { T_ADD_0, T_SUB_0 }, { "left_expression", {\ { LA_IS, { "unsigned_value_terminal" }, 1, { "value" }};\ /*{LA_NOT, { "unsigned_value_terminal" }, 1, { "unary_operation" }}*\ }};\ {LA_IS, { T_IF_0 }, { "left_expression", {\ { LA_IS, { "" }, 1, { "cond_block" }}\ }};\ }
	index_action__optional = index_action ε;	index_action__optional → index_action index_action__optional → ε	index_action__optional(1: "(" → index_action index_action__optional(1: "!=") → ε		index_action__optional = index_action "";	{LA_IS, { "(" }, { "index_action__optional", {\ { LA_IS, { "" }, 1, { "index_action" }}\ }};\ {LA_NOT, { "(" }, { "index_action__optional", {\ { LA_IS, { "" }, 0, { "" }}\ }};\ }
expression = left_expression , {binary_action};	expression = left_expression , binary_action__iteration;	expression → left_expression binary_action__iteration	expression(1: "(" , "NOT", "+", "-", " ", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → left_expression binary_action__iteration	expression = left_expression >> *binary_action;	expression = left_expression >> binary_action__iteration;	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\ "expression", {\ { LA_IS, { "" }, 2, { "left_expression", "binary_action__iteration" }}\ }};\ }
	binary_action__iteration = binary_action, binary_action__iteration ε;	binary_action__iteration → binary_action binary_action__iteration binary_action__iteration → ε	binary_action__iteration(1: "AND", "OR", "=", "!=", "<", ">", "+", "-", "*", "DIV", "MOD") → binary_action binary_action__iteration binary_action__iteration(1: "!"AND", "!"OR", "!=" , "!=" , "!"<", "!">", "!" +", "!" -", "!" *", "!"DIV", "!"MOD") → ε		binary_action__iteration = binary_action >> binary_action__iteration "";	{LA_IS, { T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_0, T_GREATER_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0 }, {\ "binary_action__iteration", {\ { LA_IS, { "" }, 2, { "binary_action", "binary_action__iteration" }}\ }};\ {LA_NOT, { T_AND_0, T_OR_0, T_EQUAL_0, T_NOT_EQUAL_0, T_LESS_0, T_GREATER_0, T_ADD_0, T_SUB_0, T_MUL_0, T_DIV_0, T_MOD_0 }, {\ "binary_action__iteration", {\ { LA_IS, { "" }, 0, { "" }}\ }};\ }
group_expression = "(" , expression , ")";	group_expression = "(" , expression , ")";	group_expression → "(" expression ")"	group_expression(1: "(" → "(" expression ")"	group_expression = tokenGROUPEXPRESSSIONBEGIN >> expression >> tokenGROUPEXPRESSSIONEND;	group_expression = tokenGROUPEXPRESSSIONBEGIN >> expression >> tokenGROUPEXPRESSSIONEND;	{LA_IS, { "(" }, { "group_expression", {\ { LA_IS, { "" }, 3, { "(" , "expression", ")" }}\ }};\ }
expression_or_cond_block__with_optional_assign = expression , ["=" , ident , [index_action]];	expression_or_cond_block__with_optional_assign = expression , assign_to_right__optional;	expression_or_cond_block__with_optional_assign → expression assign_to_right__optional	expression_or_cond_block__with_optional_assign(1: "(" , "NOT", "+", "-", " ", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression assign_to_right__optional	expression_or_cond_block__with_optional_assign = expression >> -(tokenLRASSIGN >> ident >> -index_action);	expression_or_cond_block__with_optional_assign = expression >> assign_to_right__optional;	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\ "expression_or_cond_block__with_optional_assign", {\ { LA_IS, { "" }, 2, { "expression", "assign_to_right__optional" }}\ }};\ }
	assign_to_right = "=", ident , index_action__optional;	assign_to_right → "=" ident index_action__optional	assign_to_right(1: "=" → "=" ident index_action__optional		assign_to_right = tokenLRASSIGN >> ident >> index_action__optional;	{LA_IS, { T_LRASSIGN_0 }, {\ "assign_to_right", {\ { LA_IS, { "" }, 3, { T_LRASSIGN_0, "ident", "index_action__optional" }}\ }};\ }
	assign_to_right__optional = assign_to_right ε;	assign_to_right__optional → assign_to_right assign_to_right__optional → ε;	assign_to_right__optional(1: "=" → assign_to_right assign_to_right__optional(1: "!=") → ε;		assign_to_right__optional = assign_to_right "";	{ LA_IS, { T_LRASSIGN_0 }, {\ "assign_to_right__optional", {\ { LA_IS, { "" }, 1, { "assign_to_right" }}\ }};\ { LA_NOT, { T_LRASSIGN_0 }, {\ "assign_to_right__optional", {\ { LA_IS, { "" }, 0, { "" }}\ }};\ }
if_expression = expression;	if_expression = expression;	if_expression → expression	if_expression(1: "(" , "NOT", "+", "-", " ", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression	if_expression = SAME_RULE(expression);	if_expression = SAME_RULE(expression);	{LA_IS, { "(" , T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\ "if_expression", {\ { LA_IS, { "" }, 1, { "expression" }}\ }};\ }
body_for_true = block_statements;	body_for_true = block_statements;	body_for_true → block_statements	body_for_true(1: "(" → block_statements	body_for_true = SAME_RULE(block_statements);	body_for_true = SAME_RULE(block_statements);	{LA_IS, { T_BEGIN_BLOCK_0 }, {\ "body_for_true", {\ { LA_IS, { "" }, 1, { "block_statements" }}\ }};\ }
false_cond_block_without_else = "ELSE" , "IF" , if_expression , body_for_true;	false_cond_block_without_else = "ELSE" , "IF" , if_expression , body_for_true;	false_cond_block_without_else → "ELSE" "IF" if_expression body_for_true	false_cond_block_without_else(1: "ELSE") → "ELSE" "IF" if_expression body_for_true	false_cond_block_without_else = tokenELSE >> tokenIF >> if_expression >> body_for_true;	false_cond_block_without_else = tokenELSE >> tokenIF >> if_expression >> body_for_true;	{LA_IS, { T_ELSE_IF_0 }, {\ "false_cond_block_without_else", {\ { LA_IS, { "" }, 4, { T_ELSE_IF_0, T_ELSE_IF_1, "if_expression", "body_for_true" }}\ }};\ }
body_for_false = "ELSE" , block_statements;	body_for_false = "ELSE" , block_statements;	body_for_false → "ELSE" block_statements	body_for_false(1: "ELSE") → "ELSE" block_statements	body_for_false = tokenELSE >> block_statements;	body_for_false = tokenELSE >> block_statements;	{LA_IS, { T_ELSE_BLOCK_0 }, {\ "body_for_false", {\ { LA_IS, { "" }, 2, { T_ELSE_BLOCK_0, "block_statements" }}\ }};\ }
cond_block = "IF" , if_expression , body_for_true, false_cond_block_without_else__iteration , body_for_false__optional;	cond_block = "IF" , if_expression , body_for_true, false_cond_block_without_else__iteration , body_for_false__optional;	cond_block → "IF" if_expression body_for_true false_cond_block_without_else__iteration body_for_false__optional	cond_block(1: "IF") → "IF" if_expression body_for_true false_cond_block_without_else__iteration body_for_false__optional	cond_block = tokenIF >> if_expression >> body_for_true >> *false_cond_block_without_else >> -body_for_false;	cond_block = tokenIF >> if_expression >> body_for_true >> false_cond_block_without_else__iteration >> body_for_false__optional;	{LA_IS, { T_IF_0 }, {\ "cond_block", {\ { LA_IS, { "" }, 5, { T_IF_0, "if_expression", "body_for_true", "false_cond_block_without_else__iteration", "body_for_false__optional" }}\ }};\ }

	false_cond_block_without_else__iteration = false_cond_block_without_else; false_cond_block_without_else__iteration ε;	false_cond_block_without_else__iteration → false_cond_block_without_else false_cond_block_without_else__iteration false_cond_block_without_else__iteration → ε	false_cond_block_without_else__iteration(1: "ELSE"; 2: "IF") → false_cond_block_without_else false_cond_block_without_else__iteration false_cond_block_without_else__iteration(1: "ELSE"; 2: !"IF") → ε false_cond_block_without_else__iteration(1: !"ELSE") → ε		false_cond_block_without_else__iteration = false_cond_block_without_else >> false_cond_block_without_else__iteration "";	{LA_IS, { T_ELSE_IF_0 }, { "false_cond_block_without_else__iteration", {\n LA_IS, {T_ELSE_IF_1}, 2, {\n "false_cond_block_without_else", "false_cond_block_without_else__iteration" }}\n {\n LA_NOT, { T_ELSE_IF_1 }, 0, { "" } }\n }}\n {\n LA_NOT, { T_ELSE_IF_0 }, {\n "false_cond_block_without_else__iteration", {\n LA_IS, {""}, 0, { "" } }\n }}\n }\n }\n }
	body_for_false__optional = body_for_false ε;	body_for_false__optional → body_for_false body_for_false__optional → ε	body_for_false__optional(1: "FALSE") → body_for_false body_for_false__optional(1: !"FALSE") → ε		body_for_false__optional = body_for_false "";	{LA_IS, { T_ELSE_BLOCK_0 }, {\n "body_for_false__optional", {\n LA_IS, {""}, 1, { "body_for_false" } }\n }}\n {\n LA_NOT, { T_ELSE_BLOCK_0 }, {\n "body_for_false__optional", {\n LA_IS, {""}, 0, { "" } }\n }}\n }\n }\n }
cycle_begin_expression = expression;	cycle_begin_expression = expression;	cycle_begin_expression → expression	cycle_begin_expression(1: "(!", "NOT", "+", "-", "_", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression	cycle_begin_expression = SAME_RULE(expression);	cycle_begin_expression = SAME_RULE(expression);	{LA_IS, { "(!", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\n "cycle_begin_expression", {\n LA_IS, {""}, 1, { "expression" } }\n }}\n }\n }\n }
cycle_end_expression = expression;	cycle_end_expression = expression;	cycle_end_expression → expression	cycle_end_expression(1: "(!", "NOT", "+", "-", "_", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression	cycle_end_expression = SAME_RULE(expression);	cycle_end_expression = SAME_RULE(expression);	{LA_IS, { "(!", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\n "cycle_end_expression", {\n LA_IS, {""}, 1, { "expression" } }\n }}\n }\n }\n }
cycle_counter = ident;	cycle_counter = ident;	cycle_counter → ident	cycle_counter(1: "-") → ident	cycle_counter = SAME_RULE(ident);	cycle_counter = SAME_RULE(ident);	{LA_IS, { "ident_terminal" }, {\n "cycle_counter", {\n LA_IS, {""}, 1, { "ident" } }\n }}\n }\n }\n }
cycle_counter_lr_init = cycle_begin_expression , "=" , cycle_counter;	cycle_counter_lr_init = cycle_begin_expression , "=" , cycle_counter;	cycle_counter_lr_init → cycle_begin_expression "=" cycle_counter	cycle_counter_lr_init(1: "(!", "NOT", "+", "-", "_", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → cycle_begin_expression "=" cycle_counter	cycle_counter_lr_init = cycle_begin_expression >> tokenLRASSIGN >> cycle_counter;	cycle_counter_lr_init = cycle_begin_expression >> tokenLRASSIGN >> cycle_counter;	{LA_IS, { "(!", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\n "cycle_counter_lr_init", {\n LA_IS, {""}, 3, {\n "cycle_begin_expression", T_LRASSIGN_0, "cycle_counter" } }\n }}\n }\n }\n }
cycle_counter_init = cycle_counter_lr_init;	cycle_counter_init = cycle_counter_lr_init;	cycle_counter_init → cycle_counter_lr_init	cycle_counter_init(1: "(!", "NOT", "+", "-", "_", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → cycle_counter_lr_init	cycle_counter_init = SAME_RULE(cycle_counter_lr_init);	cycle_counter_init = SAME_RULE(cycle_counter_lr_init);	{LA_IS, { "(!", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\n "cycle_counter_init", {\n LA_IS, {""}, 1, {\n "cycle_counter_lr_init" } }\n }}\n }\n }\n }
cycle_counter_last_value = cycle_end_expression;	cycle_counter_last_value = cycle_end_expression;	cycle_counter_last_value → cycle_end_expression	cycle_counter_last_value(1: "(!", "NOT", "+", "-", "_", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → cycle_end_expression	cycle_counter_last_value = SAME_RULE(cycle_end_expression);	cycle_counter_last_value = SAME_RULE(cycle_end_expression);	{LA_IS, { "(!", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, {\n "cycle_counter_last_value", {\n LA_IS, {""}, 1, {\n "cycle_end_expression" } }\n }}\n }\n }\n }
cycle_body = "DO" , ({statement} block_statements);	cycle_body = "DO" , statement__or__block_statements;	cycle_body → "DO" statement__or__block_statements	cycle_body(1: "DO") → "DO" statement__or__block_statements	cycle_body = tokenDO >> (statement block_statements);	cycle_body = tokenDO >> statement__or__block_statements;	{LA_IS, { T_DO_0 }, {\n "cycle_body", {\n LA_IS, {""}, 2, {\n T_DO_0, "statement__or__block_statements" } }\n }}\n }\n }\n }
forto_cycle = "FOR" , cycle_counter_init , "TO", cycle_counter_last_value , cycle_body;	forto_cycle = "FOR" , cycle_counter_init , "TO", cycle_counter_last_value , cycle_body;	forto_cycle → "FOR" cycle_counter_init "TO", cycle_counter_last_value cycle_body	forto_cycle(1: "FOR") → "FOR" cycle_counter_init "TO", cycle_counter_last_value cycle_body	forto_cycle = tokenFOR >> cycle_counter_init >> tokenTO >> cycle_counter_last_value >> cycle_body;	forto_cycle = tokenFOR >> cycle_counter_init >> tokenTO >> cycle_counter_last_value >> cycle_body;	{LA_IS, { T_FOR_0 }, {\n "forto_cycle", {\n LA_IS, {""}, 5, {\n T_FOR_0, "cycle_counter_init", T_TO_0, "cycle_counter_last_value", "cycle_body" } }\n }}\n }\n }\n }
	statement__or__block_statements = statement block_statements;	statement__or__block_statements → statement block_statements	statement__or__block_statements(1: "(!") → statement statement__or__block_statements(1: "(!") → block_statements		statement__or__block_statements = statement block_statements;	{LA_IS, { "ident_terminal", "(!", T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0, T_FOR_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0 }, {\n "statement__or__block_statements", {\n LA_IS, {""}, 1, {\n "statement" } }\n }}\n {\n LA_IS, { T_BEGIN_BLOCK_0 }, {\n "statement__or__block_statements", {\n LA_IS, {""}, 1, {\n "block_statements" } }\n }}\n }\n }\n }
input_rule = "GET" , (ident , [index_action] "(!", ident , [index_action] , ")");	input_rule = "GET", argument_for_input;	input_rule → "GET" argument_for_input	input_rule(1: "GET") → "GET" argument_for_input	input_rule = tokenGET >> (ident >> -index_action tokenGROUPEXPRESSIONBEGIN >> ident >> -index_action >> tokenGROUPEXPRESSIONEND);	input_rule = tokenGET >> argument_for_input;	{LA_IS, { T_INPUT_0 }, {\n "input_rule", {\n LA_IS, {""}, 2, {\n T_INPUT_0, "argument_for_input" } }\n }}\n }\n }\n }
	argument_for_input = ident , index_action__optional; argument_for_input = "(!", "ident", "index_action__optional", ")";	argument_for_input → ident index_action__optional; argument_for_input → "(!" "ident" "index_action__optional" ")")	argument_for_input(1: "-") → ident index_action__optional argument_for_input(1: "(!") → "(!" "ident" "index_action__optional" ")")		argument_for_input = ident >> index_action__optional tokenGROUPEXPRESSIONBEGIN >> ident >> index_action__optional >> tokenGROUPEXPRESSIONEND;	{LA_IS, { "ident_terminal" }, {\n "argument_for_input", {\n LA_IS, {""}, 2, {\n "ident", "index_action__optional" } }\n }}\n {\n LA_IS, { "(!" }, {\n "argument_for_input", {\n LA_IS, {""}, 4, {\n "(!", "ident", "index_action__optional", ")" } }\n }}\n }\n }\n }
output_rule = "PUT" , expression;	output_rule = "PUT", expression;	output_rule → "PUT" expression	output(1: "PUT") → "PUT" expression	output_rule = tokenPUT >> expression;	output_rule = tokenPUT >> expression;	{LA_IS, { T_OUTPUT_0 }, {\n "output_rule", {\n LA_IS, {""}, 2, {\n T_OUTPUT_0, "expression" } }\n }}\n }\n }\n }
statement = expression_or_cond_block__with_optional_assign forto_cycle input_rule output_rule ";" ;	statement = expression_or_cond_block__with_optional_assign forto_cycle input_rule output_rule ";" ;	statement → expression_or_cond_block__with_optional_assign statement → forto_cycle statement → input_rule statement → output_rule statement → ";" ;	statement(1: "(!", "NOT", "+", "-", "_", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "IF") → expression_or_cond_block__with_optional_assign statement(1: "FOR") → forto_cycle statement(1: "GET") → input_rule statement(1: "PUT") → output_rule statement(1: ";") → ";" ;	statement = expression_or_cond_block__with_optional_assign forto_cycle input_rule output_rule tokenSEMICOLON;	statement = expression_or_cond_block__with_optional_assign forto_cycle input_rule output_rule tokenSEMICOLON;	{LA_IS, { "(!", T_NOT_0, "ident_terminal", "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0 }, {\n "statement", {\n LA_IS, {""}, 1, {\n "expression_or_cond_block__with_optional_assign" } }\n }}\n {\n LA_IS, { T_FOR_0 }, {\n "statement", {\n LA_IS, {""}, 1, {\n "forto_cycle" } }\n }}\n }\n {\n LA_IS, { T_INPUT_0 }, {\n "statement", {\n LA_IS, {""}, 1, {\n "input_rule" } }\n }}\n }\n {\n LA_IS, { T_OUTPUT_0 }, {\n "statement", {\n LA_IS, {""}, 1, {\n "output_rule" } }\n }}\n }\n }\n {\n LA_IS, { T_SEMICOLON_0 }, {\n "statement", {\n LA_IS, {""}, 1, {";" } }\n }}\n }\n }\n }
statement = expression_or_cond_block__with_optional_assign output_rule ";" ;	statement__iteration = statement, statement__iteration ε;	statement__iteration → statement statement__iteration statement__iteration → ε	statement__iteration(1: "-" , "(!", "NOT", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "+", "-", "IF", "FOR", "GET", "PUT", ";") → statement statement__iteration statement__iteration(1: !"_" , !"(!", !"NOT", !"0", !"1", !"2", !"3", !"4", !"5", !"6", !"7", !"8", !"9", !"+", !"-", !"IF", !"FOR", !"GET", !"PUT", !";") → ε		statement__iteration = statement >> statement__iteration "";	{LA_IS, { "ident_terminal", "(!", T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0, T_FOR_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0 }, {\n "statement__iteration", {\n LA_IS, {""}, 2, {\n "statement", "statement__iteration" } }\n }}\n }\n {\n LA_NOT, { "ident_terminal", "(!", T_NOT_0, "unsigned_value_terminal", T_ADD_0, T_SUB_0, T_IF_0, T_FOR_0, T_INPUT_0, T_OUTPUT_0, T_SEMICOLON_0 }, {\n

						{ "statement__iteration", {\ LA_IS, { "" }, 0, { "" } } } \ } } \ }
block_statements = "{ (" , {statement} , ")";	block_statements = "{ (" , statement__iteration , ")";	block_statements → "{ (" statement__iteration ")" }	block_statements(1: "{ (" → "{ (" statement__iteration ")" }	block_statements = tokenBEGINBLOCK >> tokenENDBLOCK;	block_statements = tokenBEGINBLOCK >> statement__iteration >> tokenENDBLOCK;	{ LA_IS, { T_BEGIN_BLOCK_0 }, { "block_statements", {\ LA_IS, { "" }, 3, { T_BEGIN_BLOCK_0, "statement__iteration", T_END_BLOCK_0 } } } \ }
	expression__optional = expression "";	expression__optional → expression expression__optional → ε	expression__optional(1: !"(", !"NOT", !"+", !"-", " ", "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", !"F") → expression expression__optional(1: !"(", !"NOT", !"+", !"-", " ", !"0", !"1", !"2", !"3", !"4", !"5", !"6", !"7", !"8", !"9", !"F") → ε		expression__optional = expression "";	{LA_IS, { "(", T_NOT_0, T_ADD_0, T_SUB_0, "ident_terminal", "unsigned_value_terminal", T_IF_0 }, { "expression__optional", {\ LA_IS, { "" }, 1, { "expression" } } } \ }
program_rule = "NAME" , program_name , "," , "BODY" , "DATA" , [declaration] , ";" , {statement} , "END";	program_rule = "NAME" , program_name , "," , "BODY" , "DATA" , declaration__optional , "," , statement__iteration , "END";	program_rule → "NAME" program_name ";" , "BODY" "DATA" declaration__optional ";" , statement__iteration "END"	program_rule(1: "NAME") → "NAME" program_name ";" , "BODY" "DATA" declaration__optional ";" , statement__iteration "END"	program_rule = BOUNDARIES >> tokenNAME >> program_name >> tokenSEMICOLON >> tokenBODY >> tokenDATA >> (- declaration) >> tokenSEMICOLON >> *statement >> tokenEND;	program_rule = BOUNDARIES >> tokenNAME >> program_name >> tokenSEMICOLON >> tokenBODY >> tokenDATA >> tokenSEMICOLON >> statement__iteration >> tokenEND;	{LA_IS, { T_NAME_0 }, { "program_rule", {\ LA_IS, { "" }, 9, { T_NAME_0 , "program_name", T_SEMICOLON_0, T_BODY_0, T_DATA_0, "declaration__optional", T_SEMICOLON_0, "statement__iteration", T_END_0 } } } \ }
	declaration__optional = declaration "";	declaration__optional → declaration declaration__optional → ε	declaration__optional(1: !"INTEGER16") → declaration declaration__optional(1: !"INTEGER16") → ε		declaration__optional = declaration "";	{ LA_IS, { T_DATA_TYPE_0 }, { "declaration__optional", {\ LA_IS, { "" }, 1, { "declaration" } } } \ }
value = [sign] , unsigned_value;	value = sign__optional, unsigned_value;	value → sign__optional unsigned_value	value(1: "0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "+", "-") → sign__optional unsigned_value	value = -sign >> unsigned_value >> BOUNDARIES;	value = sign__optional >> unsigned_value >> BOUNDARIES;	{LA_IS, { "unsigned_value_terminal", T_ADD_0, T_SUB_0 }, { "value", {\ LA_IS, { "" }, 2, { "sign__optional", "unsigned_value" } } } \ }
	sign__optional = sign ε;	sign__optional → sign sign__optional → ε	sign__optional(1: "+", "-") → sign sign__optional(1: !"+", !"-") → ε		sign__optional = sign "";	{LA_IS, { T_ADD_0, T_SUB_0 }, { "sign__optional", {\ LA_IS, { "" }, 1, { "sign" } } } \ }
sign = sign_plus sign_minus;	sign = sign_plus sign_minus;	sign → sign_plus sign → sign_minus	sign(1: "+") → sign_plus sign(1: "-") → sign_minus	sign = sign_plus sign_minus;	sign = sign_plus sign_minus;	{LA_IS, { T_ADD_0 }, { "sign", {\ LA_IS, { "" }, 1, { "sign_plus" } } } \ }
sign_plus = "+";	sign_plus = "+";	sign_plus → "+"	sign_plus(1: "+") → "+"	sign_plus = SAME_RULE(tokenPLUS);	sign_plus = SAME_RULE(tokenPLUS);	{LA_IS, { T_ADD_0 }, { "sign_plus", {\ LA_IS, { "" }, 1, {T_ADD_0} } } \ }
sign_minus = "-";	sign_minus = "-";	sign_minus → "-"	sign_minus(1: "-") → "-"	sign_minus = SAME_RULE(tokenMINUS);	sign_minus = SAME_RULE(tokenMINUS);	{LA_IS, { T_SUB_0 }, { "sign_minus", {\ LA_IS, { "" }, 1, {T_SUB_0} } } \ }
unsigned_value = non_zero_digit , {digit} "0";	unsigned_value = non_zero_digit , digit__iteration "0";	unsigned_value → non_zero_digit digit__iteration unsigned_value → "0"	unsigned_value(1: "1", "2", "3", "4", "5", "6", "7", "8", "9") → non_zero_digit digit__iteration unsigned_value(1: "0") → "0"	unsigned_value = (non_zero_digit >> *digit digit_0) >> BOUNDARIES;	unsigned_value = (non_zero_digit >> digit__iteration digit_0) >> BOUNDARIES;	/* unsigned_value_token represents unsigned_value in lexical analyzer */\{LA_IS, { "unsigned_value_terminal" }, { "unsigned_value", {\ LA_IS, { "" }, 1, { "unsigned_value_terminal" } } } \ }
	digit__iteration = digit, digit__iteration ε;	digit__iteration → digit digit__iteration digit__iteration → ε	digit__iteration(1: "0", "1", "2", "3", "4", "5", "6", "7", "8", "9") → digit digit__iteration digit__iteration(1: !"0", !"1", !"2", !"3", !"4", !"5", !"6", !"7", !"8", !"9") → ε		digit__iteration = digit >> digit__iteration "";	\
digit = "0" non_zero_digit;	digit = "0" non_zero_digit;	digit → "0" digit → non_zero_digit	digit(1: "0") → "0" digit(1: "1", "2", "3", "4", "5", "6", "7", "8", "9") → non_zero_digit	digit_0 = '0'; digit = digit_0 non_zero_digit;	digit_0 = '0'; digit = digit_0 non_zero_digit;	\
non_zero_digit = "1" "2" "3" "4" "5" "6" "7" "8" "9";	non_zero_digit = "1" "2" "3" "4" "5" "6" "7" "8" "9";	non_zero_digit → "1" non_zero_digit → "2" non_zero_digit → "3" non_zero_digit → "4" non_zero_digit → "5" non_zero_digit → "6" non_zero_digit → "7" non_zero_digit → "8" non_zero_digit → "9"	non_zero_digit(1: "1") → "1" non_zero_digit(1: "2") → "2" non_zero_digit(1: "3") → "3" non_zero_digit(1: "4") → "4" non_zero_digit(1: "5") → "5" non_zero_digit(1: "6") → "6" non_zero_digit(1: "7") → "7" non_zero_digit(1: "8") → "8" non_zero_digit(1: "9") → "9"	digit_1 = '1'; digit_2 = '2'; digit_3 = '3'; digit_4 = '4'; digit_5 = '5'; digit_6 = '6'; digit_7 = '7'; digit_8 = '8'; digit_9 = '9'; non_zero_digit = digit_1 digit_2 digit_3 digit_4 digit_5 digit_6 digit_7 digit_8 digit_9;	digit_1 = '1'; digit_2 = '2'; digit_3 = '3'; digit_4 = '4'; digit_5 = '5'; digit_6 = '6'; digit_7 = '7'; digit_8 = '8'; digit_9 = '9'; non_zero_digit = digit_1 digit_2 digit_3 digit_4 digit_5 digit_6 digit_7 digit_8 digit_9;	\
ident = "_" , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case ;	ident = "_" , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case , letter_in_upper_case ;	ident → "_" letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case	Ident(1: "_") → "_" letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case letter_in_upper_case	tokenUNDERSCORE = "_" ; ident = tokenUNDERSCORE >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> STRICT_BOUNDARIES;	tokenUNDERSCORE = "_" ; ident = tokenUNDERSCORE >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> letter_in_upper_case >> STRICT_BOUNDARIES;	/* ident_token represents ident in lexical analyzer */\{LA_IS, { "ident_terminal" }, { "ident", {\ LA_IS, { "" }, 1, { "ident_terminal" } } } \ }
letter_in_lower_case = "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z";	letter_in_lower_case = "a" "b" "c" "d" "e" "f" "g" "h" "i" "j" "k" "l" "m" "n" "o" "p" "q" "r" "s" "t" "u" "v" "w" "x" "y" "z";	letter_in_lower_case → "a" letter_in_lower_case → "b" letter_in_lower_case → "c" letter_in_lower_case → "d" letter_in_lower_case → "e" letter_in_lower_case → "f" letter_in_lower_case → "g" letter_in_lower_case → "h" letter_in_lower_case → "i" letter_in_lower_case → "j" letter_in_lower_case → "k" letter_in_lower_case → "l" letter_in_lower_case → "m" letter_in_lower_case → "n" letter_in_lower_case → "o" letter_in_lower_case → "p" letter_in_lower_case → "q" letter_in_lower_case → "r" letter_in_lower_case → "s" letter_in_lower_case → "t" letter_in_lower_case → "u" letter_in_lower_case → "v" letter_in_lower_case → "w" letter_in_lower_case → "x" letter_in_lower_case → "y" letter_in_lower_case → "z";	letter_in_lower_case(1: "a") → "a" letter_in_lower_case(1: "b") → "b" letter_in_lower_case(1: "c") → "c" letter_in_lower_case(1: "d") → "d" letter_in_lower_case(1: "e") → "e" letter_in_lower_case(1: "f") → "f" letter_in_lower_case(1: "g") → "g" letter_in_lower_case(1: "h") → "h" letter_in_lower_case(1: "i") → "i" letter_in_lower_case(1: "j") → "j" letter_in_lower_case(1: "k") → "k" letter_in_lower_case(1: "l") → "l" letter_in_lower_case(1: "m") → "m" letter_in_lower_case(1: "n") → "n" letter_in_lower_case(1: "o") → "o" letter_in_lower_case(1: "p") → "p" letter_in_lower_case(1: "q") → "q" letter_in_lower_case(1: "r") → "r" letter_in_lower_case(1: "s") → "s" letter_in_lower_case(1: "t") → "t" letter_in_lower_case(1: "u") → "u" letter_in_lower_case(1: "v") → "v" letter_in_lower_case(1: "w") → "w" letter_in_lower_case(1: "x") → "x"	A = "A"; B = "B"; C = "C"; D = "D"; E = "E"; F = "F"; G = "G"; H = "H"; I = "I"; J = "J"; K = "K"; L = "L"; M = "M"; N = "N"; O = "O"; P = "P"; Q = "Q"; R = "R"; S = "S"; T = "T"; U = "U"; V = "V"; W = "W"; X = "X";	A = "A"; B = "B"; C = "C"; D = "D"; E = "E"; F = "F"; G = "G"; H = "H"; I = "I"; J = "J"; K = "K"; L = "L"; M = "M"; N = "N"; O = "O"; P = "P"; Q = "Q"; R = "R"; S = "S"; T = "T"; U = "U"; V = "V"; W = "W"; X = "X";	\

		letter_in_lower_case → "y" letter_in_lower_case → "z"	letter_in_lower_case(1: "y") → "y" letter_in_lower_case(1: "z") → "z"	Y = "Y"; Z = "Z"; letter_in_lower_case = a b c d e f g h i j k l m n o p q r s t u v w x y z;	Y = "Y"; Z = "Z"; letter_in_lower_case = a b c d e f g h i j k l m n o p q r s t u v w x y z;	
letter_in_upper_case = "A" "B" "C" "D" "E" "F" "G" "H" "I" "J" "K" "L" "M" "N" "O" "P" "Q" "R" "S" "T" "U" "V" "W" "X" "Y" "Z";	letter_in_upper_case = "A" "B" "C" "D" "E" "F" "G" "H" "I" "J" "K" "L" "M" "N" "O" "P" "Q" "R" "S" "T" "U" "V" "W" "X" "Y" "Z";	letter_in_upper_case → "A" letter_in_upper_case → "B" letter_in_upper_case → "C" letter_in_upper_case → "D" letter_in_upper_case → "E" letter_in_upper_case → "F" letter_in_upper_case → "G" letter_in_upper_case → "H" letter_in_upper_case → "I" letter_in_upper_case → "J" letter_in_upper_case → "K" letter_in_upper_case → "L" letter_in_upper_case → "M" letter_in_upper_case → "N" letter_in_upper_case → "O" letter_in_upper_case → "P" letter_in_upper_case → "Q" letter_in_upper_case → "R" letter_in_upper_case → "S" letter_in_upper_case → "T" letter_in_upper_case → "U" letter_in_upper_case → "V" letter_in_upper_case → "W" letter_in_upper_case → "X" letter_in_upper_case → "Y" letter_in_upper_case → "Z"	letter_in_upper_case(1: "A") → "A" letter_in_upper_case(1: "B") → "B" letter_in_upper_case(1: "C") → "C" letter_in_upper_case(1: "D") → "D" letter_in_upper_case(1: "E") → "E" letter_in_upper_case(1: "F") → "F" letter_in_upper_case(1: "G") → "G" letter_in_upper_case(1: "H") → "H" letter_in_upper_case(1: "I") → "I" letter_in_upper_case(1: "J") → "J" letter_in_upper_case(1: "K") → "K" letter_in_upper_case(1: "L") → "L" letter_in_upper_case(1: "M") → "M" letter_in_upper_case(1: "N") → "N" letter_in_upper_case(1: "O") → "O" letter_in_upper_case(1: "P") → "P" letter_in_upper_case(1: "Q") → "Q" letter_in_upper_case(1: "R") → "R" letter_in_upper_case(1: "S") → "S" letter_in_upper_case(1: "T") → "T" letter_in_upper_case(1: "U") → "U" letter_in_upper_case(1: "V") → "V" letter_in_upper_case(1: "W") → "W" letter_in_upper_case(1: "X") → "X" letter_in_upper_case(1: "Y") → "Y" letter_in_upper_case(1: "Z") → "Z"	a = "a"; b = "b"; c = "c"; d = "d"; e = "e"; f = "f"; g = "g"; h = "h"; i = "i"; j = "j"; k = "k"; l = "l"; m = "m"; n = "n"; o = "o"; p = "p"; q = "q"; r = "r"; s = "s"; t = "t"; u = "u"; v = "v"; w = "w"; x = "x"; y = "y"; z = "z"; letter_in_upper_case = A B C D E F G H I J K L M N O P Q R S T U V W X Y Z;	a = "a"; b = "b"; c = "c"; d = "d"; e = "e"; f = "f"; g = "g"; h = "h"; i = "i"; j = "j"; k = "k"; l = "l"; m = "m"; n = "n"; o = "o"; p = "p"; q = "q"; r = "r"; s = "s"; t = "t"; u = "u"; v = "v"; w = "w"; x = "x"; y = "y"; z = "z"; letter_in_upper_case = A B C D E F G H I J K L M N O P Q R S T U V W X Y Z;	\
				STRICT_BOUNDARIES = (BOUNDARY >> *(BOUNDARY) (!(qi::alpha qi::char_("_.")))); BOUNDARIES = (BOUNDARY >> *(BOUNDARY) NO_BOUNDARY); BOUNDARY = BOUNDARY__SPACE BOUNDARY__TAB BOUNDARY__VERTICAL_TAB BOUNDARY__FORM_FEED BOUNDARY__CARRIAGE_RETURN BOUNDARY__LINE_FEED BOUNDARY__NULL; BOUNDARY__SPACE = " "; BOUNDARY__TAB = "\t"; BOUNDARY__VERTICAL_TAB = "\v"; BOUNDARY__FORM_FEED = "\f"; BOUNDARY__CARRIAGE_RETURN = "\r"; BOUNDARY__LINE_FEED = "\n"; BOUNDARY__NULL = "\0"; NO_BOUNDARY = ""; #define WHITESPACES \ STRICT_BOUNDARIES, \ BOUNDARIES, \ BOUNDARY, \ BOUNDARY__SPACE, \ BOUNDARY__TAB, \ BOUNDARY__VERTICAL_TAB, \ BOUNDARY__FORM_FEED, \ BOUNDARY__CARRIAGE_RETURN, \ BOUNDARY__LINE_FEED, \ BOUNDARY__NULL, \ NO_BOUNDARY	STRICT_BOUNDARIES = (BOUNDARY >> *(BOUNDARY)) (!(qi::alpha qi::char_("_."))); BOUNDARIES = (BOUNDARY >> *(BOUNDARY) NO_BOUNDARY); BOUNDARY = BOUNDARY__SPACE BOUNDARY__TAB BOUNDARY__VERTICAL_TAB BOUNDARY__FORM_FEED BOUNDARY__CARRIAGE_RETURN BOUNDARY__LINE_FEED BOUNDARY__NULL; BOUNDARY__SPACE = " "; BOUNDARY__TAB = "\t"; BOUNDARY__VERTICAL_TAB = "\v"; BOUNDARY__FORM_FEED = "\f"; BOUNDARY__CARRIAGE_RETURN = "\r"; BOUNDARY__LINE_FEED = "\n"; BOUNDARY__NULL = "\0"; NO_BOUNDARY = ""; #define WHITESPACES \ STRICT_BOUNDARIES, \ BOUNDARIES, \ BOUNDARY, \ BOUNDARY__SPACE, \ BOUNDARY__TAB, \ BOUNDARY__VERTICAL_TAB, \ BOUNDARY__FORM_FEED, \ BOUNDARY__CARRIAGE_RETURN, \ BOUNDARY__LINE_FEED, \ BOUNDARY__NULL, \ NO_BOUNDARY	\
						\ \ \ { LA_IS, { T_NAME_0 }, { "program____part1", { { LA_IS, { "" }, 7, { T_NAME_0, "program_name", T_SEMICOLON_0, T_BODY_0, T_DATA_0, "declaration_optional", T_SEMICOLON_0 } } } } \ } \ } \ "program_rule"