Bachelor Thesis

Benchmark of RISC-V in BTOR2

Jan Krister Möller

Examiner: Dr. Mathias Fleury

University of Freiburg

Faculty of Engineering

Department of Computer Science

Chair of Computer Architecture

September 21, 2025

Writing Period

24. 06. 2025 – 24. 09. 2025

Examiner

Dr. Mathias Fleury

Declaration

I hereby declare that I am the sole author and composer of my thesis and that no other sources or learning aids, other than those listed, have been used. Furthermore, I declare that I have acknowledged the work of others by providing detailed references of said work.
I hereby also declare that my Thesis has not been prepared for another examination or assignment, either wholly or excerpts thereof.

Place, Date	Signature

Declaration on Usage of Generative AI

I hereby declare that, with the approval of my examiner, I have employed the generative AI tool "GitHub Copilot" during the preparation of this thesis solely for spellchecking and enhancing the formality of my written expression. Furthermore, I expressly confirm that this tool was not used to generate data or as a source of factual information or content for this thesis.

Place, Date	Signature

Abstract

foo bar [1] [2] [3]

Contents

List of Figures

List of Tables

List of Algorithms

1 Introduction

(TODO: Write this ?!)

2 RISC-V

As the first foundation for my benchmarks and, consequently, this thesis, I will discuss RISC-V and its operational principles.

2.1 Overview

RISC-V is an open-source instruction set architecture (ISA) first published in May 2011 by A. Waterman et al. [4]. As indicated by its name, it is based on the RISC design philosophy. **(TODO: Explain RISC (compare wiki))** Since 2015, the development of RISC-V has been coordinated by the RISC-V International Association, a non-profit corporation based in Switzerland since 2020 [5]. Its objectives include providing an *open* ISA that is freely available to all, a *real* ISA suitable for native hardware implementation, and an ISA divided into a *small* base integer ISA usable independently, for example in educational contexts, with optional standard extensions to support general-purpose software development [1, Chapter 1].

Currently, RISC-V comprises four base ISAs: RV32I, RV64I, RV32E, and RV64E, which can be extended with one or more of the 47 ratified extension ISAs [1, Preface].

(EXTEND: Additional content may be required here)

For the purposes of this work, I focus on a subset of the RV64I ISA.

2.2 The RV64I ISA

RV64I is not overly complex, but its structure is essential for understanding the subsequent work presented in this thesis. Therefore, I will explain all elements relevant to my work.

RV64I features 32 64-bit registers, labeled $x0$–$x31$, where $x0$ is hardwired to zero across all bits. Registers $x1$–$x31$ are general-purpose and may be interpreted by various instructions as collections of booleans, two's complement signed binary integers, or unsigned integers. Additionally, there is a non-accessible register called *pc*, which serves as the program counter and holds the address of the current instruction [1, Chapters 4.1, 2.1].

In RV64I, memory addresses are 64 bits in size. As the memory model is defined to be single-byte addressable, the address space of RV64I encompasses 2^{64} bytes [1, Chapter 1.4]. The format of the memory is little endian, so the lower bits of a number are placed at lower addresses.

Like nearly all standard ISAs of RISC-V, RV64I employs a standard instruction encoding length of 32 bits, or one *word*. Only the compressed extension named C introduces instructions with a length of 16 bits [1, Chapter 1.5], but this special case is not considered here. All RV64I instructions are encoded in one of the six formats illustrated in Figure 1. These formats may consist of

- The *opcode*:
  The opcode is used to differentiate between groups of instructions. It also defines the format type of the instruction.

- *rd*:
  This is the destination register.



Figure 1: RV64I encoding formats, used in [1, Chapter 2.3]

- $funct3$:

  This is used to differentiate between instructions with the same *opcode*.

- $rs1$ & $rs2$:

  These are the source registers.

- $funct7$:

  This is used for further distinctions between instructions if there are more than eight instructions in an opcode group and $funct3$ does not suffice.

- imm:

  This is an immediate value. In square brackets after imm is designated a subfield of the immediate which is represented by these bits. From these subfields, non-defined lower bits are filled with zeros whereas the highest defined bit is sign-extended to fill all non-defined higher bits.

The design of these formats results in the following features:

- Due to RISC-V's little-endian nature, the *opcode*, which encodes the general instruction, is always read first. Further specification of the instruction via $funct3$ and $funct7$ is consistently located at the same positions.

- If utilized by the instruction, rd, $rs1$, and $rs2$ are also always found in the same locations, simplifying decoding.

- The highest bit of imm is always bit 31, making it straightforward to sign-extend the immediate value.

The instructions relevant to my work are listed in Table 1 I have divided the instructions in Table 1 into nine groups based on their operations.

`LUI` and `AUIPC` move a high immediate into rd. In the case of `AUIPC`, the pc is added to this value. `JAL` and `JALR` instructions are unconditional jumps, where for `JAL` imm is added to pc and for `JALR` imm is added to $rs1$ and set as pc. Both link to the next instruction (current $pc + 4$) in rd.

branch instructions are conditional jumps. $rs1$ is compared to $rs2$ and if the comparison holds, imm is added to pc. The comparisons are $=$ for `BEQ`, $\neq$ for `BNE`, $<$ for `BLT`, and $\geq$ for `BGE`. In these instructions, the values in $rs1$ and $rs2$ are handled as two's complement integers. The suffix `*U` in an instruction generally designates an unsigned operation. In this case, the values in $rs1$ and $rs2$ are handled as unsigned integers. Apart from this, they work as their counterpart without the suffix.

load instructions load values from memory at address $(rs1 + imm)$ into rd, either at `Byte`, `Halfword`, `Word`, or `Doubleword` length. By default, the value is sign-extended, and the suffix `*U` designates the loading of a non-sign-extended value. Conversely, *store* instructions write values from $rs2$ at the address $(rs1 + imm)$ to memory. Here also the distinction between the different lengths is made, and the lowest byte, halfword, word, or the whole doubleword is stored at the address.

All further instructions can be seen as generic operations, differentiated by their suffixes. To simplify the explanation process, all operations without any suffix and their behavior are listed in Table 2. This is almost exactly the group with opcode *op*, except the `SLTU` instruction, which is not suffix-free. However, as with all other

Instr	*opcode*	Type
LUI	*lui*	U
AUIPC	*auipc*	
JAL	*jal*	J
JALR	*jalr*	I
BEQ	*branch*	B
BNE		
BLT		
BGE		
BLTU		
BGEU		
LB	*load*	I
LH		
LW		
LD		
LBU		
LHU		
LWU		

Instr	*opcode*	Type
SB	*store*	S
SH		
SW		
SD		
ADDI	*op-imm*	I
SLTI		
SLTIU		
XORI		
ORI		
ANDI		
SLLI		I*
SRLI		
SRAI		
ADDIW	*op-imm-32*	I
SLLIW		I**
SRLIW		
SRAIW		

Instr	*opcode*	Type
ADD	*op*	R
SUB		
SLT		
SLTU		
XOR		
OR		
AND		
SLL		
SRL		
SRA		
ADDW	*op-32*	R
SUBW		
SLLW		
SRLW		
SRAW		

Table 1: Subset of RV64I instructions **(TODO: Maybe rework, not happy yet)**

instructions with the unsigned suffix, it behaves as its signed counterpart except for handling both $rs1$ and $rs2$ as unsigned integers.

These operations can be extended by the *I suffix, which is designated by the opcode $op-imm$. This replaces $rs2$ with imm in the behavior. Again, SLTI can be extended to an unsigned version SLTIU, which behaves as expected. A SUBI instruction does not exist as it is redundant; its behavior can be achieved by using ADDI with a negative immediate.

Additionally, the operations ADD, SUB, SLL, SRL, and SRA can be extended with the *W suffix. This forms the group with the opcode $op-32$. In contrast to the base instructions, these new ones behave as if the registers are only 32 bits. The result is placed in the low 32 bits of rd and sign-extended to the full 64 bits. Overflows are ignored.

The last group is the combination of both suffixes *IW with the opcode $op-imm-32$. The behavior differs from the base instructions, as expected, by a replacement of $rs2$

Instr	Behavior
ADD	$rd := rs1 + rs2$
SUB	$rd := rs1 - rs2$
SLT	$rd := 1$ if $rs1 < rs2$ else $rd := 0$
XOR	$rd := rs1 \oplus rs2$, bitwise
OR	$rd := rs1 \vee rs2$, bitwise
AND	$rd := rs1 \wedge rs2$, bitwise
SLL	$rd := rs1$ shifted left by $rs2$, new bits are zeros
SRL	$rd := rs1$ shifted right by $rs2$, new bits are zeros
SRA	$rd := rs1$ shifted right by $rs2$, sign extend

Table 2: All suffix free operations in RV64I and their behavior. All values are handled either bitwise or as signed twos complement integers

with *imm* and only operating on 32 bits. Again, a `SUBIW` instruction is redundant as a negative immediate with `ADDIW` achieves the same result.

Compared to the full RV64I ISA, I have omitted the `FENCE`, `ECALL`, and `EBREAK` instructions, as without I/O interaction or an environment such as an OS or a debugger, these are not required.

2.3 Simulation of RISC-V

In a previous project **(TODO: Must be more precise)**, I implemented a simulation of this subset of RV64I in C [6]. As I will use it to test my BTOR2 model, I explain the inner workings of the program here.

(TODO: related work in simulation)

First, I implemented a structure to represent a simple RISC-V processor.

2.3.1 Representing the State of a RISC-V Processor

The state requires a representation for all registers. *pc* is defined as a 64-bit integer, and the other 32 registers are implemented as an array, allowing each register to

```c
typedef struct memory_cell
{
    uint64_t address;
    uint8_t content;
    struct memory_cell *next_cell;
} memory_cell;
```

```c
typedef struct memory_table
{
    memory_cell *memory[TABLESIZE];
    uint64_t initialised_cells;
} memory_table;
```

```c
typedef struct state
{
    uint64_t pc;
    uint64_t regs_values[32];
    bool regs_init[32];
    memory_table *memory;
} state;
```

Figure 2: State representation of a RISC-V processor in the simulation [6]

be referenced by its number. Additionally, I implemented an array of flags, one for each register, to differentiate between initialized and non-initialized registers. The memory is built from single memory cells, each holding an address and its byte of content. These are accumulated in a hash table called "memorytable", hashing on the address. If adding a new cell causes a collision, it is appended to the cells already in the bucket, forming a linked list. These structures are shown in Figure 2.

2.3.2 Running an Instruction

After fetching the current instruction from the hash table, it must be decoded. The easiest way to do this is using a decision tree. First, I mask out the opcode and match it over all implemented opcodes. From there, either this is an endpoint and the instruction is identified, or $funct3$ must be masked and matched. A final differentiation over $funct7$ might be needed, but after this every leaf in the tree coincides with an instruction. At every leaf, the state can be changed according to the corresponding instruction. **(TODO: Graph of the decision tree?)**

$\langle 64bitHex \rangle$ ::= up to 16 digits of [0-9a-fA-F]
$\langle 32bitHex \rangle$ ::= up to 8 digits of [0-9a-fA-F]
$\langle 16bitHex \rangle$ ::= up to 4 digits of [0-9a-fA-F]
$\langle 8bitHex \rangle$ ::= up to 2 digits of [0-9a-fA-F]
$\langle memContent \rangle$ ::= $\langle 8bitHex \rangle$
| $\langle 16bitHex \rangle$
| $\langle 32bitHex \rangle$
| $\langle 64bitHex \rangle$
$\langle cell \rangle$ ::= $\langle 64bitHex \rangle$`:`$\langle memContent \rangle$
| $\langle cell \rangle\langle cell \rangle$
$\langle regNum \rangle$ ::= `0 |...| 31`
$\langle reg \rangle$ ::= `PC:`$\langle 64bitHex \rangle$`\n`
| `x`$\langle regNum \rangle$`:`$\langle 64bitHex \rangle$`\n`
| $\langle reg \rangle\langle reg \rangle$
$\langle memory \rangle$ ::= `MEMORY:\n`$\langle cell \rangle$
$\langle registers \rangle$ ::= `REGISTERS:\n`$\langle reg \rangle$
$\langle state \rangle$ ::= $\langle registers \rangle$`\n`$\langle memory \rangle$`\n`

Figure 3: Construction of .state files

2.3.3 Saving the State of a RISC-V Processor

To preserve the current state of a RISC-V processor, both the registers and memory must be stored. For this purpose, I have devised the format shown in Figure 3. The RISC-V simulation uses this format as input and output. The minimal file consists only of the two designators "REGISTERS:" and "MEMORY:" and one empty line between them. Under "REGISTERS:", all registers can be listed with their corresponding value. Of course, x0 cannot be different from 0. I included the option to reference it nonetheless to have the complete state included. Under "MEMORY:", after giving an address, the memory can be filled with 1-, 2-, 4-, or 8-byte sized memory content. The given address is the starting address of the content, with every byte after the first filling the next higher address.

3 BTOR2

The second foundation of my benchmarks is BTOR2, a word-level model checking format published by A. Niemetz et al. [2]. Before explaining the format, an overview of bounded model checking is necessary.

3.1 Bounded Model Checking

Bounded model checking (BMC) is a formal verification technique employed to detect errors in hardware or software systems by systematically exploring the state space of a finite-state model up to a specified bound, typically defined by the number of iterations or steps. As described by A. Biere in the "Handbook of Satisfiability", BMC is primarily utilized for falsification and testing, with a focus on identifying violations of temporal properties [7]. Nevertheless, BMC can also be extended to prove properties within the given bound.

In practice, BMC translates the verification problem into a satisfiability problem, determining whether a property violation can occur within the specified bound. The model comprises a finite state machine and a set of properties to be verified. The model checker systematically explores all possible state transitions up to the bound and evaluates whether the property holds. If a violation is detected, the tool generates a *witness*, which is a trace demonstrating how the property is violated. If no violation is found within the bound, the system is considered safe up to that bound, although this does not guarantee correctness for all possible executions.

For word-level hardware model checking, the BTOR2 format has become a de facto standard for describing models and is currently used in the "Hardware Model Checking Competition" [8]. Another format is AIGER [9], from which BTOR2 is derived [2], and which is used in the bit-level track of the HWMCC [8]. In software model checking, the "Competition on Software Verification" utilizes the C and Java programming languages as input formats [10]. Additionally, a translator from BTOR2 models to C programs has been presented to bridge the gap between hardware and software verification [11]. As this work focuses on BTOR2, the following section provides a detailed overview of the format.

3.2 The BTOR2 Language

In BTOR2, each line represents either a sort or a node, with the line number typically serving as an identifier. A sort functions similarly to a type, defining either the length of a bitvector or the size of an array of bitvectors. Nodes represent values of a defined sort and can be constants, operations, or constraints. These values can be referenced by their node identifier, i.e., the line number. The syntax of BTOR2 is detailed in [2, Figure 1], and the available operators are listed in [2, Table 1].

Key features of BTOR2 include its support for sequential operations, which facilitates the implementation of a RISC-V structure. The primary feature is the `state` operator, which defines a node that is updated sequentially. An `init` node assigns an initial value to this state, while a `next` node specifies its subsequent value. `bad` nodes can be used to define endpoints for a model, indicating either the occurrence of an unintended event or, as in this work, the discovery of the intended information. In both cases, the resulting model produces a witness. Additionally, an `input` node allows an input to the model, with assignments to this node handled by the model checker. These inputs can be constrained by `constraint` nodes, which describe invariants for the inputs of the model. An example model with these sequential nodes is shown in Figure 4. This

BTOR2 model					Comments
1	sort	bitvec	1		*bit "type"*
2	sort	bitvec	8		*byte "type"*
3	constd	2	99		*comparison constant*
4	zero	2			
5	input	2		*i1*	*input i1*
6	input	2		*i2*	*input i2*
7	eq	1	6 5		
8	constraint	-6			$i1 \neq i2$ *must hold*
9	state	2		*accu*	*sequential node accu*
10	init	2	9 4		*initialization accu*
11	add	2	6 5		$i1 + i2$
12	next	2	9 11		*next accu is* $i1 + i2$
13	eq	1	3 9		$accu = constant$
14	bad	13			*property:* $accu \neq constant$

Figure 4: An example BTOR2 model finding two numbers that are not equal and added together equal 99

model can now be checked by a model checker, which should produce a witness with an assignment of the two inputs $i1$ and $i2$ such that $s1 = i1 + i2 = constant$. Let us examine this witness in more detail.

3.3 The BTOR2 Witness

Running the model in Figure 20 through BtorMC [2] with the option `-trace-gen-full` produces the complete witness shown in Figure 5. The syntax of BTOR2 witnesses is described in [2, Figure 2], but I will explain the example witness in Figure 5 line by line for clarity.

The witness begins with `sat`, indicating that a property in the model is satisfiable. The second line specifies the constraint that was triggered. In this case, only one `bad` node exists in the model, and the witness shows that `b0`, meaning the first occurring `bad` node, was violated.

```
sat
b0
#0
0 00000000 accu#0
@0
0 11101000 i1@0
1 01111011 i2@0
#1
0 01100011 accu0#1
@1
0 00000100 i1@1
1 00000000 i2@1
.
```

Figure 5: The complete witness of the model in Figure 4

Subsequent lines list the iterations of the counterexample for the property. For each sequential iteration, the witness first presents—marked with `#`x, where x is the iteration number—a representation of all states in the current iteration with their respective values in binary. Second, marked with `@`x, all inputs for the iteration are listed, similar to the states. Note that the nodes of the inputs and the state in Figure 4 include a symbol, which is used in the witness to name the states and inputs. Examining the witness, it is evident that the counterexample requires two iterations to reach the violated property. In the first iteration, the state `accu` is initialized with 0, and `i1` and `i2` are assigned values that add up to 99 (01100011b). In the next iteration, this sum is set as the new value for `accu`, which violates the property.

4 Transforming RISC-V to BTOR2

(TODO: Explain naming conventions for the model nodes)

This chapter addresses the central problem of this thesis: transforming a RISC-V state into the BTOR2 format for benchmarking purposes. F. Schrögendorfer conducted similar work in his master's thesis "Bounded Model Checking in Lockless Programs" [3], where he describes, among other topics, an encoding concept for a minimal machine in a multiprocessor context [3, Chapter 2]. In [3, Chapter 8], he outlines a method to encode programs for his machine model into a BTOR2 model. This approach cannot be directly replicated here, as his model assumes the entire program is known at encoding time, whereas I aim to preserve the RISC-V property that allows for self-modifying programs during execution. If this property were to be disregarded, it would be possible to analyze the complete behavior of a program by parsing the memory, but this is beyond the scope of this work. Even so, I let myself inspire by his structuring of the model.

4.1 The Concept

To successfully execute a RISC-V instruction, three fundamental steps must occur in sequence:

- Fetch the current instruction from memory
- Identify the instruction

- Execute the instruction

Due to the fixed instruction length of RISC-V, as mentioned in Section 2.2, fetching the current instruction is straightforward. Ultimately, a node is required that retrieves a *word* from memory at the location specified by *pc*.

For basic identification, the *opcode* must be extracted and checked. Depending on the opcode, further distinctions between instructions require extracting and checking $funct3$ and, if necessary, $funct7$. Ultimately, a node for each instruction is needed, holding a boolean value indicating whether this instruction was fetched.

To execute the instruction, the values of the immediate imm and, if used, the registers $rs1$ and $rs2$ must be extracted. All instructions only modify rd, *pc*, or memory. Therefore, the next-state logic can be generalized for these three cases.

Memory is only modified when a store instruction is identified. As all store instructions share the same type, computing the memory address is consistent across them. The final step is overwriting the memory at this address.

For the *pc*, except for jump commands, it always increments to point to the next instruction. The two unconditional jumps, `JAL` and `JALR`, must be handled separately. For branch instructions, after determining whether the relevant condition for the instruction holds, a general approach can be applied, as all branch instructions execute the same operation from this point onward.

With rd, generalization across instructions is not feasible. However, it is possible to generalize across all possible registers by adding a check in each register's update function to determine whether the register in question is rd.

4.2 Encoding

For improved visualization in the BTOR2 code, all sort-IDs are marked in gray, all node-IDs in red, and all non-ID numbers in blue. As described in the BTOR2 syntax [2, Figure 1], each line can have an accompanying symbol. Unfortunately, these cannot be used as aliases for the line numbers, but for clarity, in the following figures I use them as such aliases. This allows each new figure to start with the relative line number `n`, making it feasible to describe processes with algorithms. It is implied that `n` is sufficiently incremented after adding to the model so that IDs do not overlap. The following sections describe how a BTOR2 model is constructed from a RISC-V state file.

4.2.1 Constants

First, I added the sorts and non-progressive constants needed in the BTOR2 model, as shown in Figure 6. This is extended by a set of progressive constants used for comparison, e.g., against the register number. Algorithm 1 describes how these are added.

Of note is the representation of memory as an array of addressable memory cells, each 1 byte. The chosen address space of 16 bits is significantly smaller than the expected 64-bit address space, but representing a 64-bit addressable memory with 2^{64} bytes ($\approx$ 18 exabytes) is not feasible. Therefore, I selected a 16-bit address space as a practical minimum, providing approximately 65kB and supporting programs with potentially over 10,000 instructions, which I consider sufficient for most use cases. The encoding is implemented so that the address space can be modified as needed. **(TODO: Change code to make address space modifiable by an option?)** **(TODO: Explain progressive constants)**

```
1  sort    bitvec  1          Bool
2  sort    bitvec  16         AS
3  sort    bitvec  8          B
4  sort    bitvec  16         H
5  sort    bitvec  32         W
6  sort    bitvec  64         D
7  sort    array   2       3  Mem

8  one     Bool               true
9  zero    Bool               false
10 one     AS                 addressInc
11 constd  AS      4          pcInc
12 zero    B                  emptyCell
13 one     W                  bitPicker
14 zero    D                  emptyReg

15 consth  W       01F        5Bitmask
16 consth  W       03F        6Bitmask
17 consth  W       07F        7Bitmask
18 consth  W       0FFF       12Bitmask
19 consth  W       0FFFFF     20Bitmask

20 constd  W       7          shiftToRd
21 constd  W       15         shiftToRs1
22 constd  W       20         shiftToRs2
23 constd  W       12         shiftToFunct3
24 constd  W       25         shiftToFunct7
25 constd  W       5          shiftBy5
26 constd  W       11         shiftBy11

27 constd  W       3          load
28 constd  W       19         opImm
29 constd  W       23         auipc
30 constd  W       27         opImm32
31 constd  W       35         store
32 constd  W       51         op
33 constd  W       55         lui
34 constd  W       59         op32
35 constd  W       99         branch
36 constd  W       103        jalr
37 constd  W       111        jal
```

(TODO: Maybe neusortieren, andere constanten aufnehmen. Explain)

Figure 6: Sorts and non-progressive Constants for encoding RISC-V in BTOR2

```
for i from 0 to 31 do
    add to model:
      n   constd   W   i          iConst
end
```

Algorithm 1: progressive constants for encoding RISC-V in BTOR2

(n + 0)	state	D	*x0*
(n + 1)	state	D	*x1*
(n + 2)	state	D	*x2*
(n + 3)	state	D	*x3*
(n + 4)	state	D	*x4*
(n + 5)	state	D	*x5*
(n + 6)	state	D	*x6*
(n + 7)	state	D	*x7*
(n + 8)	state	D	*x8*
(n + 9)	state	D	*x9*
(n + 10)	state	D	*x10*
(n + 11)	state	D	*x11*
(n + 12)	state	D	*x12*
(n + 13)	state	D	*x13*
(n + 14)	state	D	*x14*
(n + 15)	state	D	*x15*
(n + 16)	state	D	*x16*
(n + 17)	state	D	*x17*
(n + 18)	state	D	*x18*
(n + 19)	state	D	*x19*
(n + 20)	state	D	*x20*
(n + 21)	state	D	*x21*
(n + 22)	state	D	*x22*
(n + 23)	state	D	*x23*
(n + 24)	state	D	*x24*
(n + 25)	state	D	*x25*
(n + 26)	state	D	*x26*
(n + 27)	state	D	*x27*
(n + 28)	state	D	*x28*
(n + 29)	state	D	*x29*
(n + 30)	state	D	*x30*
(n + 31)	state	D	*x31*
(n + 32)	state	AS	*pc*
(n + 33)	state	Mem	*memory*

Figure 7: State representation for encoding

4.2.2 State Representation

The next logical step is defining a representation of a RISC-V state. This is straightforward, as shown in Figure 7. I also introduced a flag for each register in my code to track whether the register was written to, enabling the transformation of a witness to a state file containing only the relevant registers. As these flags do not affect the operation of the BTOR2 model and are only included for an aesthetic choice, they are not included in my description and will not be discussed further.

4.2.3 Initialization

To initialize a state in BTOR2 from a RISC-V state file, the values in the registers must be loaded as constants, and for each memory address mentioned in the state file, the value and address must be loaded as constants. Due to the inability to represent a full 64-bit address space, I must manage the reduction of the address space from the state file to the BTOR2 model. I chose to initialize only the addresses up to the BTOR2 model's address space maximum and omit all others from the state file, as this provides the most predictable behavior. All addresses not mentioned in the state file are zero-initialized. Finally, these constants are used to initialize the state. For the registers, this is straightforward; for memory, all memory addresses are first written into a placeholder array, which is then used to initialize the actual memory. Due to BTOR2 constraints, these constants must be defined **before** the states, but initialization with the values must occur after the states. Thus, this initialization process **wraps around** the state representation. The generation of constants is shown in Algorithm 2, while the actual initialization is shown in Algorithm 3.

4.2.4 Fetching the Current Instruction

To fetch the current instruction, I read the four bytes of the instruction and concatenate them, as shown in Figure 8.

4.2.5 Deconstruction of the Instruction

With the instruction available, it can be deconstructed to extract the *opcode*, rd, $rs1$, $rs2$, $funct3$, $funct7$, and imm. For everything except imm, this can be accomplished by shifting and masking, as shown in Figure 9.

The immediate, however, must first be constructed from its subfields, which are referenced in Figure 1. In the BTOR2 model, this is shown in Figure 10. **(TODO:**

$truePc \leftarrow$ value of pc in state file
$maxPc \leftarrow$ number of addresses in BTOR2 model
pcValue $\leftarrow$ $truePc$ modulo $maxPc$
add to model:

n	constd	AS	*pcValue*	*pcConst*

for every register x_i **do**
  if register is initialised in state file **then**
    $registerValue \leftarrow$ value of x_i
    if $registerValue \neq 0$ **then**
      add to model:

n	constd	D	*registerValue*	x_i*Const*

    end
  end
end

add to model:

(n + 0)	state	Mem		*memPH*
(n + 1)	init	Mem	*memPH* (n + 0)	

$lastPH \leftarrow memPH$
$allInitialCells \leftarrow$ all initialised memory cells in the state file
$cutInitialCells \leftarrow$ remove all cells with address over maxPc
for every cell c in $cutInitialCells$ **do**
  $address \leftarrow$ address of c
  $value \leftarrow$ value of c
  add to model:

(n + 0)	constd	AS	*address*			
(n + 1)	constd	B	*value*			
(n + 2)	write	Mem	*lastPH*	(n + 0)	(n + 1)	*PHAfterC*

  $lastPH \leftarrow PHAfterC$
end
keep $lastPH$ for initialisation

Algorithm 2: Generating initialisation constants from state file in BTOR2

add to model:

n	init	AS	*pc*	*pcConst*

for every register x_i **do**
  if x_iConst was defined **then**
    add to model:

n	init	D	x_i	x_i*Const*

  end
end

add to model:

n	init	Mem	*memory*	*lastPh*

Algorithm 3: Initialising states in the BTOR2 model

(n + 0)	read	B	*memory*	*pc*	*instrB1*
(n + 1)	add	AS	*addressInc*	*pc*	*pc+1*
(n + 2)	read	B	*memory*	*pc+1*	*instrB2*
(n + 3)	add	AS	*addressInc*	*pc+1*	*pc+2*
(n + 4)	read	B	*memory*	*pc+2*	*instrB3*
(n + 5)	add	AS	*addressInc*	*pc+2*	*pc+3*
(n + 6)	read	B	*memory*	*pc+3*	*instrB4*
(n + 7)	concat	H	*instrB2*	*instrB1*	*instrH1*
(n + 8)	concat	H	*instrB4*	*instrB3*	*instrH2*
(n + 9)	concat	W	*instrH2*	*instrH1*	*instr*

Figure 8: Fetching the current instruction from memory

(n + 0)	and	W	*instr*	*7Bitmask*	*opcode*
(n + 1)	srl	W	*instr*	*shiftToRd*	*rdPre*
(n + 2)	and	W	*rdPre*	*5Bitmask*	*rd*
(n + 3)	srl	W	*instr*	*shiftToRs1*	*rs1Pre*
(n + 4)	and	W	*rs1Pre*	*5Bitmask*	*rs1*
(n + 5)	srl	W	*instr*	*shiftToRs2*	*rs2Pre*
(n + 6)	and	W	*rs2Pre*	*5Bitmask*	*rs2*
(n + 7)	srl	W	*instr*	*shiftToFunct3*	*funct3Pre*
(n + 8)	and	W	*funct3Pre*	*shiftRd*	*funct3*
(n + 9)	srl	W	*instr*	*shiftToFunct7*	*funct7*

Figure 9: Extraction of values from the instruction without *imm*

Reference to same method in riscvsim) Three points are noteworthy: First, some immediate subfields overlap exactly. This is utilized in lines (n + 1) with the overlap of $imm[11:5]$ for I- and S-type, and (n + 21) with J- and B-types $imm[10:5]$ overlap. Second, as described in Section 2.2, the immediate is always sign-extended. This is achieved using arithmetic right shifts, which perform sign extension and correctly position the highest immediate bit. Third, at line (n + 8), sign extension requires a right shift by 19. As this matches the opcode for arithmetic instructions with immediate, I reused this constant.

Now, *iTypeImm*, *sTypeImm*, *bTypeImm*, *uTypeImm*, and *jTypeImm* are available. However, it is preferable to have a single node *imm* referencing the immediate value regardless of instruction. This is accomplished in Figure 11, where booleans are defined to check all opcodes that are neither R-type nor I-type. Then, if-then-else nodes are chained to select instructions of J-type, U-type, B-type, or S-type. If the instruction is none of these, I default to I-type, as R-type does not use an immediate value. Finally, *imm* is extended to the 64-bit width required by RV64I.

At this stage, the values of the designated $rs1$ and $rs2$ registers can also be extracted. This is shown for $rs1$ in Figure 4; the process is identical for $rs2$, with only the names changed. The starting equality comparisons can be omitted for $rs2$, as they are already defined for $rs1$ and can be referenced.

(n + 0)	sra	W	*instr*	*shiftToRs2*	*iTypeImm*
(n + 1)	and	W	*iTypeImm*	*-5Bitmask*	*s[11:5]*
(n + 2)	add	W	*s[11:5]*	*rd*	*sTypeImm*
(n + 3)	and	W	*rd*	*-bitPicker*	*b[4:0]*
(n + 4)	and	W	*funct7*	*6Bitmask*	*b[10:5]Pre*
(n + 5)	sll	W	*b10:5Pre*	*shiftBy5*	*b[10:5]*
(n + 6)	and	W	*bitPicker*	*rd*	*b[11]Pre*
(n + 7)	sll	W	*b[11]Pre*	*shiftBy11*	*b[11]*
(n + 8)	sra	W	*instr*	*mathI*	*b[31:12]Pre*
(n + 9)	and	W	*b[31:12]Pre*	*12Bitmask*	*b[31:12]*
(n + 10)	add	W	*b[10:5]*	*b[4:0]*	*b[10:0]*
(n + 11)	add	W	*b[11]*	*b[10:0]*	*b[11:0]*
(n + 12)	add	W	*b[31:12]*	*b[11:0]*	*bTypeImm*
(n + 13)	and	W	*instr*	*-12Bitmask*	*uTypeImm*
(n + 14)	and	W	*rs2*	*-bitPicker*	*j[4:0]*
(n + 15)	and	W	*rs2*	*bitPicker*	*j[11]Pre*
(n + 16)	sll	W	*j[11]Pre*	*shiftBy11*	*j[11]*
(n + 17)	sll	W	*funct3*	*shiftToFunct3*	*j[14:12]*
(n + 18)	sll	W	*rs1*	*shiftToRs1*	*j[19:15]*
(n + 19)	sra	W	*instr*	*shiftBy11*	*j[31:20]Pre*
(n + 20)	and	W	*j[31:20]Pre*	*-20Bitmask*	*j[31:20]*
(n + 21)	add	W	*b[10:5]*	*j[4:0]*	*j[10:0]*
(n + 22)	add	W	*j[11]*	*j[10:0]*	*j[11:0]*
(n + 23)	add	W	*j[14:12]*	*j[11:0]*	*j[14:0]*
(n + 24)	add	W	*j[19:15]*	*j[14:0]*	*j[19:0]*
(n + 25)	add	W	*j[31:20]*	*j[19:0]*	*jTypeImm*

Figure 10: Extraction of all *imm* types from the instruction

(n + 0)	eq	Bool	*opcode*	*store*		*isSType*
(n + 1)	eq	Bool	*opcode*	*branch*		*isBType*
(n + 2)	eq	Bool	*opcode*	*auipc*		*uType1*
(n + 3)	eq	Bool	*opcode*	*lui*		*uType2*
(n + 4)	or	Bool	*uType1*	*uType2*		*isUType*
(n + 5)	eq	Bool	*opcode*	*jal*		*isJType*
(n + 6)	ite	W	*isSType*	*sTypeImm*	*iTypeImm*	*checkS*
(n + 7)	ite	W	*isBType*	*bTypeImm*	*checkS*	*checkB*
(n + 8)	ite	W	*isUType*	*uTypeImm*	*checkB*	*checkU*
(n + 9)	ite	W	*isJType*	*jTypeImm*	*checkU*	*imm32*
(n + 10)	sext	D	*imm32*	*32*		*imm*

Figure 11: Finding the correct immediate by opcode

for i from 1 to 31 **do**

add to model:

n	eq	Bool	*rs1*	*iConst*	*isRs1Xi*

end

add to model:

n	ite	D	*isRs1X1*	*x1*	*x0*	*checkX1*

for i from 2 to 30 **do**

add to model:

n	ite	D	*isRs1Xi*	*xi*	*checkX(i - 1)*	*checkXi*

end

add to model:

n	ite	D	*isRs1X31*	*x31*	*checkX30*	*rs1val*

Algorithm 4: Extracting the value of the register designated by $rs1$

(*isJALR* already exists)					
n	and	Bool	*isLoad*	*is5Funct3*	*isLHU*
(n + 0)	consth	W	*20*		*SUBWf7*
(n + 1)	eq	Bool	*funct7*	*SUBWf7*	*fitsF7SUBW*
(n + 2)	and	Bool	*is0Funct3*	*fitsF7SUBW*	*fitsF3SUBW*
(n + 3)	and	Bool	*isLoad*	*fitsF3SUBW*	*isSUBW*

(TODO: Use subfigs)

Figure 12: Instruction detection of `JALR`, `LHU` and `SUBW` as described in Algorithm 5

4.2.6 Instruction Detection

For the next-state logic, it is essential to determine the current command. Therefore, I defined a check *isInstruction* for each instruction. As this is repetitive, Algorithm 5 describes a generalized approach to obtain these booleans. An example for each instruction subgroup in Algorithm 5 is provided in Figure 12. The funct7 checks from the $needsf7$ subgroup can be reused if multiple instructions share the same funct7.

4.2.7 Next-State Logic

The next-state logic is the core of the model. Almost everything else supports this point. The goal is to create the changes each instruction would make and then apply only the changes specific to the instruction in the state. Each state node in the model must have an accompanying next node to function correctly. First, the changed values are computed.

Creating All Values of Instruction Execution

It is unnecessary to detail all instructions, as this simply follows the RV64I ISA. Instead, I provide examples for each group of instructions as divided in Table 1. Examples for `AUIPC`, `JALR`, `BEQ`, `LHU`, `SD`, `ANDI`, `SLLIW`, `SLT`, and `SUBW` are shown in Figure 13. These examples illustrate overlaps that can be utilized, such as addresses for load and store instructions or the 32-bit versions of word instructions. The `SD`

add to model:

(n + 0)	eq	Bool	*opcode*	*load*	*isLoad*
(n + 1)	eq	Bool	*opcode*	*opImm*	*isOpImm*
(n + 2)	eq	Bool	*opcode*	*auipc*	*isAUIPC*
(n + 3)	eq	Bool	*opcode*	*opImm32*	*isOpImm32*
(n + 4)	eq	Bool	*opcode*	*store*	*isStore*
(n + 5)	eq	Bool	*opcode*	*op*	*isOp*
(n + 6)	eq	Bool	*opcode*	*lui*	*isLUI*
(n + 7)	eq	Bool	*opcode*	*op32*	*isOp32*
(n + 8)	eq	Bool	*opcode*	*branch*	*isBranch*
(n + 9)	eq	Bool	*opcode*	*jalr*	*isJALR*
(n + 10)	eq	Bool	*opcode*	*jal*	*isJAL*

for i from 0 to 7 **do**
  add to model:

n	eq	Bool	*funct3*	*iConst*	*isiFunct3*

end
onlyOp ← [LUI, AUIPC, JAL, JALR]
needsf7 ← [SRL, SRA, SRLI, SRAI, SRLW, SRAW, SRLWI, SRAWI, ADD, SUB, ADDW, SUBW]
rest ←[all other instructions]

for all instructions I in *onlyOp* **do**
  isI is already defined
end
for all instructions I in *rest* **do**
  opname ← opcode name of I
  f3val ← expected funct3 of I as digit
  add to model:

n	and	Bool	*isopname*	*isf3valFunct3*	*isI*

end
for all instructions I in *needsf7* **do**
  opname ← opcode name of I
  f3val ← expected funct3 of I as digit
  f7hex ← expected funct7 of I as hexadecimal number
  add to model:

(n + 0)	consth	W	*f7hex*		*If7*
(n + 1)	eq	Bool	*funct7*	*If7*	*fitsF7I*
(n + 2)	and	Bool	*isf3valFunct3*	*fitsF7I*	*fitsF3I*
(n + 3)	and	Bool	*isopname*	*fitsF3I*	*isI*

end

Algorithm 5: Generalised approach to instruction detection

n	add	D	*imm*	*pc*	*rdAUIPC*

13.1: AUIPC

Figure 13: Instruction execution for chosen instructions

(n + 0)	add	AS	*pc*	*pcInc*	*nextPc*
(n + 1)	add	D	*imm*	*rs1val*	*pcJALR64pre*
(n + 2)	and	D	*-1Const*	*pcJALR64pre*	*pcJALR64*
(n + 3)	slice	AS	*pcJALR64*	*15*	*pcJALR*
(n + 4)	uext	D	*nextPc*	*48*	*rdJALR*

(TODO: pc overflow erwähnen)

13.2: JALR

Figure 13: Instruction execution for chosen instructions

example demonstrates that all other store instructions are interim results of preparing SD. Load instructions are similar, but each requires sign extension to 64 bits.

With this, each change can be assigned to its instruction.

The Next Memory

Defining the next memory array is straightforward. All store instructions are cascaded through if-then-else nodes, with the final 'else' set as the current memory array; if no 'if' matches, the array remains unchanged. This is shown in Figure 14.

(n + 0)	add	AS	*pc*	*pcInc*		*nextPc*
(n + 1)	slice	AS	*imm*	*15*	*0*	*ImmAS*
(n + 2)	add	AS	*pc*	*ImmAS*		*pcBranch*
(n + 3)	eq	Bool	*rs1val*	*rs2val*		*isBEQcond*
(n + 4)	ite	AS	*isBEQcond*	*pcBranch*	*nextPc*	*pcBEQ*

13.3: BEQ

Figure 13: Instruction execution for chosen instructions

(n + 0)	add	D	*rs1val*	*imm*		*1stAddrPre*
(n + 1)	slice	AS	*1stAddrPre*	*15*	*0*	*1stAddr*
(n + 2)	add	AS	*1stAddr*	*addressInc*		*2ndAddr*
(n + 3)	read	B	*memory*	*1stAddr*		*loadB1*
(n + 4)	read	B	*memory*	*2ndAddr*		*loadB2*
(n + 5)	concat	H	*loadB2*	*loadB1*		*loadB2B1*
(n + 6)	uext	D	*loadB2B1*	*48*	*0*	*rdLHU*

13.4: LHU

Figure 13: Instruction execution for chosen instructions

(n + 0)	add	D	*rs1val*	*imm*		*1stAddrPre*
(n + 1)	slice	AS	*1stAddrPre*	*15*	*0*	*1stAddr*
(n + 2)	add	AS	*1stAddr*	*addressInc*		*2ndAddr*
(n + 3)	add	AS	*2ndAddr*	*addressInc*		*3rdAddr*
(n + 4)	add	AS	*3rdAddr*	*addressInc*		*4thAddr*
(n + 5)	add	AS	*4thAddr*	*addressInc*		*5thAddr*
(n + 6)	add	AS	*5thAddr*	*addressInc*		*6thAddr*
(n + 7)	add	AS	*6thAddr*	*addressInc*		*7thAddr*
(n + 8)	add	AS	*7thAddr*	*addressInc*		*8thAddr*
(n + 9)	slice	B	*rs2val*	*7*	*0*	*storeB1*
(n + 10)	slice	B	*rs2val*	*15*	*8*	*storeB2*
(n + 11)	slice	B	*rs2val*	*23*	*16*	*storeB3*
(n + 12)	slice	B	*rs2val*	*31*	*24*	*storeB4*
(n + 13)	slice	B	*rs2val*	*39*	*32*	*storeB5*
(n + 14)	slice	B	*rs2val*	*47*	*40*	*storeB6*
(n + 15)	slice	B	*rs2val*	*55*	*48*	*storeB7*
(n + 16)	slice	B	*rs2val*	*63*	*56*	*storeB8*
(n + 17)	write	Mem	*memory*	*1stAddr*	*storeB1*	*memorySB*
(n + 18)	write	Mem	*memorySB*	*2ndAddr*	*storeB2*	*memorySH*
(n + 19)	write	Mem	*memorySH*	*3rdAddr*	*storeB3*	*memoryB3*
(n + 20)	write	Mem	*memoryB3*	*4thAddr*	*storeB4*	*memorySW*
(n + 21)	write	Mem	*memorySW*	*5thAddr*	*storeB5*	*memoryB5*
(n + 22)	write	Mem	*memoryB5*	*6thAddr*	*storeB6*	*memoryB6*
(n + 23)	write	Mem	*memoryB6*	*7thAddr*	*storeB7*	*memoryB7*
(n + 24)	write	Mem	*memoryB7*	*8thAddr*	*storeB8*	*memorySD*

13.5: SD

Figure 13: Instruction execution for chosen instructions

n	and	D	*rs1val*	*imm*	*rdANDI*

13.6: ANDI

Figure 13: Instruction execution for chosen instructions

(n + 0)	and	W	*imm32*	*5Bitmask*		*shamtIW*
(n + 1)	slice	W	*rs1val*	*31*	*0*	*rs1val32*
(n + 2)	sll	W	*rs1val32*	*shamtIW*		*rdSLLIWpre*
(n + 3)	sext	D	*rs1val32*	*32*		*rdSLLIW*

13.7: SLLIW

Figure 13: Instruction execution for chosen instructions

(n + 0)	slt	Bool	*rs1val*	*rs2val*	*rdSLTpre*
(n + 1)	uext	D	*rdSLTpre*	*63*	*rdSLT*

13.8: SLT

Figure 13: Instruction execution for chosen instructions

(n + 0)	slice	W	*rs1val*	*31*	*0*	*rs1val32*
(n + 1)	slice	W	*rs2val*	*31*	*0*	*rs2val32*
(n + 2)	sub	W	*rs1val32*	*rs2val32*		*rdSUBWpre*
(n + 3)	sext	D	*rdSUBWpre*	*32*		*rdSUBW*

13.9: SUBW

Figure 13: Instruction execution for chosen instructions

(n + 0)	ite	Mem	*isSB*	*memorySB*	*memory*	*newMem3*
(n + 1)	ite	Mem	*isSH*	*memorySH*	*newMem3*	*newMem2*
(n + 2)	ite	Mem	*isSW*	*memorySW*	*newMem2*	*newMem1*
(n + 3)	ite	Mem	*isSD*	*memorySD*	*newMem1*	*newMem*
(n + 4)	next	Mem	*memory*	*newMem*		

Figure 14: Next-State logic for the memory array

(n + 0)	ite	AS	*isBGEU*	*pcBGEU*	*nextPc*	*newPc7*
(n + 1)	ite	AS	*isBLTU*	*pcBLTU*	*newPc7*	*newPc6*
(n + 2)	ite	AS	*isBGE*	*pcBGE*	*newPc6*	*newPc5*
(n + 3)	ite	AS	*isBLT*	*pcBLT*	*newPc5*	*newPc4*
(n + 4)	ite	AS	*isBNE*	*pcBNE*	*newPc4*	*newPc3*
(n + 5)	ite	AS	*isBEQ*	*pcBEQ*	*newPc3*	*newPc2*
(n + 6)	ite	AS	*isJALR*	*pcJALR*	*newPc2*	*newPc1*
(n + 7)	ite	AS	*isJAL*	*pcJAL*	*newPc1*	*newPc*
(n + 8)	next	AS	*pc*	*newPc*		

Figure 15: Next-State logic for the pc register

The Next pc

For the next pc, the approach is similar, as shown in Figure 15. The only difference is that if no 'if' matches, pc must point to the next instruction to execute. The nextPc value was already computed for the JAL and JALR instructions and is reused here. The unconditional jumps also modify the value in rd, which is handled in the next section.

The Next rd

At last, the remaining registers must be updated. The procedure is defined in Figure 6. With the exception of x0, this is the same for all registers. The process is similar to defining the next memory or pc, but instead of a handful of instructions, all 39 relevant instructions must be considered, as only branch and store instructions do not modify rd. For brevity, the cascade for all relevant instructions is not shown in full in Algorithm 6, but only indicated.

4.2.8 Constraints

The final step is to define constraints to terminate the model checker. The primary constraint is reaching a set number of iterations, as shown in Figure 16.

add to model:

n	next	D	x0	x0

for i from 1 to 31 **do**

add to model:

(n + 0)	ite	D	*isLUI*	*rdLUI*	*xi*	*newXi-49*
⋮	ite	D	⋮	⋮	⋮	⋮
(n + 47)	ite	D	*isSRAW*	*rdSRAW*	*newXi-2*	*newXi-1*
(n + 48)	eq	Bool	*rd*	*iConst*		*isRdXi*
(n + 49)	ite	D	*isRdXi*	*newXi-1*	*xi*	*newXi*
(n + 50)	next	D	*xi*	*newXi*		

end

Algorithm 6: Next-state logic for all x registers

(n + 0)	one	D			*counterInc*
(n + 1)	constd	D	*nIterations*		*maxIterations*
(n + 2)	state	D			*counter*
(n + 3)	init	D	*counter*	*emptyReg*	
(n + 4)	add	D	*counter*	*counterInc*	*newCounter*
(n + 5)	next	D	*counter*	*newCounter*	
(n + 6)	eq	Bool	*counter*	*maxIterations*	*isMaxIter*
(n + 7)	bad		*isMaxIter*		

Figure 16: Constraining the model by iteration count

Additional constraints are defined to check for invalid instructions. The first checks if the opcode is valid for the model. The second constraint detects if the instruction cannot be identified even when the opcode is valid, as shown in Figure 17. The constraint in Figure 18 handles instruction-address-misaligned exceptions for jump instructions.

Other constraints can be defined, such as terminating on a specific pc value or when a register reaches a specified value.

(TODO: Maybe add examples on how to do this)

(TODO: Maybe internal references in figures should be numbers...)

(n + 0)	or	Bool	*isLoad*	*isOpImm*	*isOpcodeValid9*
(n + 1)	or	Bool	*isAUIPC*	*isOpcodeValid9*	*isOpcodeValid8*
(n + 2)	or	Bool	*isOpImm32*	*isOpcodeValid8*	*isOpcodeValid7*
(n + 3)	or	Bool	*isStore*	*isOpcodeValid7*	*isOpcodeValid6*
(n + 4)	or	Bool	*isOp*	*isOpcodeValid6*	*isOpcodeValid5*
(n + 5)	or	Bool	*isLUI*	*isOpcodeValid5*	*isOpcodeValid4*
(n + 6)	or	Bool	*isOp32*	*isOpcodeValid4*	*isOpcodeValid3*
(n + 7)	or	Bool	*isBranch*	*isOpcodeValid3*	*isOpcodeValid2*
(n + 8)	or	Bool	*isJALR*	*isOpcodeValid2*	*isOpcodeValid1*
(n + 9)	or	Bool	*isJAL*	*isOpcodeValid1*	*isOpcodeValid*
(n + 10)	bad		-*isOpcodeValid*		
(n + 11)	or	Bool	*isLUI*	*isAUIPC*	*isInstrValid47*
(n + 12)	or	Bool	*isJAL*	*isInstrValid47*	*isInstrValid46*
⋮	or	Bool	⋮	⋮	⋮
(n + 58)	or	Bool	*isSRAW*	*isInstrValid1*	*isInstrValid*
(n + 59)	and	Bool	-*isInstrValid*	*isOpcodeValid*	*unknownInstr*
(n + 60)	bad		*unknownInstr*		

Figure 17: Constraining the model on unknown instructions

(n + 0)	zero	AS			*pcZero*
(n + 1)	constd	AS	*3*		*pcBitmask*
(n + 2)	and	AS	*pcBitmask*	*pcJAL*	*lowbitsJAL*
(n + 3)	and	AS	*pcBitmask*	*pcJALR*	*lowbitsJALR*
(n + 4)	and	AS	*pcBitmask*	*pcBEQ*	*lowbitsBEQ*
⋮	and	AS	*pcBitmask*	⋮	⋮
(n + 9)	and	AS	*pcBitmask*	*pcBGEU*	*lowbitsBGEU*
(n + 10)	neq	Bool	*pcZero*	*lowbitsJAL*	*pcMsaJAL*
(n + 11)	neq	Bool	*pcZero*	*lowbitsJALR*	*pcMsaJALR*
(n + 12)	neq	Bool	*pcZero*	*lowbitsBEQ*	*pcMsaBEQ*
⋮	neq	Bool	*pcZero*	⋮	⋮
(n + 17)	neq	Bool	*pcZero*	*lowbitsBGEU*	*pcMsaBGEU*
(n + 18)	or	Bool	*pcMsaJAL*	*pcMsaJALR*	*pcMsa6*
(n + 19)	or	Bool	*pcMsaBEQ*	*pcBEQ*	*pcMsa5*
⋮	or	Bool	⋮	⋮	⋮
(n + 24)	or	Bool	*pcMsaBGEU*	*pcMsa1*	*pcMsa*
(n + 25)	bad		*pcMsa*		

Figure 18: Constraining the model on misaligned addresses

4.3 Testing for Correctness

To test my model, I compared its results to those of my RISC-V simulator (Section 2.3).

Given a state, both the simulation and the BTOR2 model are run with the iteration maximum set to 1. The resulting BTOR2 witness cannot be directly compared to the resulting state of the simulation. Therefore, I implemented a simple converter from witness to state [12, src/restate_witness.c]. These two states can then be compared. A shell script for this purpose is provided at [12, sh_utils/compare_iterations.sh].

To generate RISC-V states, I implemented a fuzzer [12, src/state_fuzzer.c] that generates randomized states with one valid instruction at the address of pc. The fuzzer first selects an instruction to test and fills all variable parts of the instruction, such as *rd* or *imm*. All registers relevant to the instruction are then assigned random 64-bit values. A pc value is generated to ensure the instruction fits within the limited address space of the BTOR2 model. If a jump instruction is chosen, possible address misalignment is corrected and address overflow is prevented. This simplifies later comparison of the resulting states, as correct execution of the instruction always results in the same state, despite differences between the simulation and the BTOR2 model.

With this setup, a series of tests can be conducted. For this, I implemented a shell script [12, sh_utils/test_btor2_model.sh]. As the number of tests increases, it becomes more challenging to track failed tests. To address this, I wrote a script to aggregate all failed tests into one file and add additional information such as instruction name or immediate value [12, sh_utils/diff_logger.sh].

I have executed approximately 5,000,000 tests on this model without a single failure, which leads me to conclude that my implementation is correct.

5 Benchmarks

With the model implemented, I was able to evaluate its performance. All benchmarks were executed on an Intel Core i5-6200U using the btormc model checker, which is distributed with the BTOR2 format [2]. Each test was run five times, and the resulting times were averaged. I also attempted to run the tests with the model checkers AVR [13] and Pono [14]. The challenges encountered with these tools are discussed in Section 5.2.

5.1 Tests

I devised two basic tests, each composed of four RISC-V instructions as illustrated in Figure 19. One test includes a memory operation, while the other does not, allowing for measurement of the impact of memory operations on the model's performance. The programs for these tests are intentionally similar: both feature three instructions forming a loop and one instruction serving as a "workhorse". The test names, `add` and `write_mem`, are derived from this key instruction. The program is embedded into a state, as exemplified in Figure 20, where the `add` program is configured for 256 loops. In this setup, x1 acts as a loop limiter, x2 as a loop counter, and x3 as an accumulator. The instructions are placed in the initial bytes of memory. In contrast, the memory operation test uses x2 as an address to store the first byte of a register, with x3 serving as this register. Both tests were also implemented with increasing loop counts up to 2048 to provide a reference for processing more iterations.

```
        bge x2 x1 0x10          jump out of program if x1 = x2
add x3 x3 x2 |                  either (add counter onto x3)
             | sb x3 0x14(x2)   or (store the first byte of x3 at counter + 0x14)
        addi x2 x2 0x1          increment counter in x2
        jalr x0 x0 0x0          jump back to address 0
```

Figure 19: Base test cases for the benchmarks

```
REGISTERS:
PC:0
x1:100
x2:0

MEMORY:
0:001158E3 # BGE x2 x1 0x10
4:002181B3 # ADD x3 x3 x2
8:00110113 # ADDI x2 x2 1
c:00000067 # JALR x0 x0 0
```

Figure 20: Example state for benchmark add_0256

Additionally, I evaluated the impact of initialized memory on runtime . For this, I introduced tests with the prefix `fullmem`, where memory addresses 0x18 to 0xfff were filled with the bit pattern '0101'. The first four words of memory were filled with the test program. The fifth word could also be filled , but I opted to leave it zero-initialized to ensure the test terminates by jumping to this address and not finding a valid instruction. This guarantees termination. To further extend this evaluation, I added tests with double the initialized memory, filling up to address 0x1fff.**(TODO: benchmark them, add times)**

I also investigated the impact of address space size by generating models from `add_0256`, `add_1024`, `write_mem_0256`, and `write_mem_1024` with extended address space. These tests use the prefix "extaddr_x", where x denotes the maximum address length in bits.

Furthermore, I implemented the base `add` tests in a manner similar to the BTOR2 model described by F. Schrögendorfer in his master thesis [3, Chapter 8]. These tests

use the prefix “nopc”, as the program counter is abstracted to activation flags for each instruction. The model generation is demonstrated using `nopc_add_0256` as an example. First, the necessary sorts and constants for RISC-V are defined:

```
 1  sort    bitvec  1     bool
 2  sort    bitvec  8     memcell
 3  sort    bitvec  16    addressspace
 4  sort    bitvec  64    register
 5  sort    array   3 2   Memory
 6  zero    1             false
 7  one     1             true
 8  zero    2             emptymem
 9  zero    4             emptyreg
10  zero    3             pcinit
11  consth  3       4     pcinc
12  consth  3       10    instr1_pcmod
13  consth  4       100   nloops
```

With this now the registers and memory can be defined:

```
 99  state  3  pc      110  state  4  x10     121  state  4  x21
100  state  4  x0      111  state  4  x11     122  state  4  x22
101  state  4  x1      112  state  4  x12     123  state  4  x23
102  state  4  x2      113  state  4  x13     124  state  4  x24
103  state  4  x3      114  state  4  x14     125  state  4  x25
104  state  4  x4      115  state  4  x15     126  state  4  x26
105  state  4  x5      116  state  4  x16     127  state  4  x27
106  state  4  x6      117  state  4  x17     128  state  4  x28
107  state  4  x7      118  state  4  x18     129  state  4  x29
108  state  4  x8      119  state  4  x19     130  state  4  x30
109  state  4  x09     120  state  4  x20     131  state  4  x31
```

Note that node IDs 14-98 are skipped. As BTOR2 requires unique but not continuous node IDs, I assigned each register node ID to equal the register number plus 100 for clarity when writing models manually.
Next, the initial memory is defined:

```
144  state   5
145  init    5  14 8
146  consth  3  0
147  consth  2  e3
148  write   5  144 146 147
149  consth  3  1
150  consth  2  58
151  write   5  148 149 150
152  consth  3  2
153  consth  2  11
154  write   5  151 152 153
155  consth  3  3
156  consth  2  00
157  write   5  154 155 156
158  consth  3  4
159  consth  2  b3
160  write   5  157 158 159
161  consth  3  5
162  consth  2  81
163  write   5  16 161 162
164  consth  3  6
165  consth  2  21
166  write   5  16 164 165
167  consth  3  7
168  consth  2  00
169  write   5  166 167 168
170  consth  3  8
171  consth  2  13
172  write   5  169 170 171
173  consth  3  9
174  consth  2  01
175  write   5  172 173 174
176  consth  3  a
177  consth  2  11
178  write   5  175 176 177
179  consth  3  b
180  consth  2  00
181  write   5  178 179 180
182  consth  3  c
183  consth  2  67
184  write   5  181 182 183
185  consth  3  d
186  consth  2  00
187  write   5  184 185 186
188  consth  3  e
189  consth  2  00
190  write   5  187 188 189
191  consth  3  f
192  consth  2  00
193  write   5  190 191 192
```

Due to BTOR2 constraints, initial memory must be defined before the intended memory state node. Node 144 serves only for memory initialization, as previously described in Section 4.2.3.

The actual memory state and instruction flags are then defined. I renamed the flags from `stmt` (Schrögendorfer) to `instr` for clarity. An exit code is unnecessary, as differentiation between model terminations is not required; only the termination time is of interest.

```
199  state  5  memory
200  state  1  instr0
201  state  1  instr1
202  state  1  instr2
203  state  1  instr3
204  state  1  endflag
```

Next up would be the inputs and constraints for these. Both are not needed for the RISC-V model because neither are threads needed as I do not model parallel processing, nor is flushing as I use a naive memory model. And without inputs, the constraints are also nonexistent. So really, next up is initialization and transitions of the states. First is pc:

```
300  init  3  99   10              | pc is zero initialized
301  add   3  99   11              | normal pc operation
302  add   3  99   12              | instr1 jump
303  eq    1  101  102             | instr1 branch condition
304  ite   3  303  302  301        | IF condition THEN jump ELSE increment
305  ite   3  200  304  99         | IF instr1 THEN check ELSE leave pc
306  or    1  201  202             | instr2-3
307  ite   3  306  301  305        | IF instr2-3 THEN increment ELSE instr1
308  ite   3  203  10   307        | IF instr4 THEN jump0 ELSE try instr2-3
309  next  3  99   308
```

As the transition for pc are quite possibly the most complex I added some explanation. x0 and x1 are skipped for now, so next registers x2 and x3:

```
314  init  4  102  9
315  one   4
316  add   4  102  315
317  ite   4  202  316  102
318  next  4  102  317

319  init  4  103  9
320  add   4  102  103
321  ite   4  201  320  103
322  next  4  103  321
```

x2 increments by one each time the third instruction is run and x3 adds x2 every time the second instruction is run. All other registers and the memory do not change during execution, so I show them in one big block:

```
310  init 4 100 9
311  next 4 100 100
312  init 4 101 13
313  next 4 101 101
323  init 4 104 9
324  next 4 104 104
325  init 4 105 9
326  next 4 105 105
327  init 4 106 9
328  next 4 106 106
329  init 4 107 9
330  next 4 107 107
331  init 4 108 9
332  next 4 108 108
333  init 4 109 9
334  next 4 109 109
335  init 4 110 9
336  next 4 110 110
337  init 4 111 9
338  next 4 111 111
339  init 4 112 9

340  next 4 112 112
341  init 4 113 9
342  next 4 113 113
343  init 4 114 9
344  next 4 114 114
345  init 4 115 9
346  next 4 115 115
347  init 4 116 9
348  next 4 116 116
349  init 4 117 9
350  next 4 117 117
351  init 4 118 9
352  next 4 118 118
353  init 4 119 9
354  next 4 119 119
355  init 4 120 9
356  next 4 120 120
357  init 4 121 9
358  next 4 121 121
359  init 4 122 9
360  next 4 122 122

361  init 4 123 9
362  next 4 123 123
363  init 4 124 9
364  next 4 124 124
365  init 4 125 9
366  next 4 125 125
367  init 4 126 9
368  next 4 126 126
369  init 4 127 9
370  next 4 127 127
371  init 4 128 9
372  next 4 128 128
373  init 4 129 9
374  next 4 129 129
375  init 4 130 9
376  next 4 130 130
377  init 4 131 9
378  next 4 131 131
379  init 5 199 193
380  next 5 199 199
```

Now only the instruction flags are left to handle:

```
381  init  1    200 7      instr0 executes initally
382  next  1    200 203    instr0 only after instr3
383  init  1    201 6
384  and   1    200 -303   instr0 and no branch
385  next  1    201 384    instr1 only after non-branching instr0
386  init  1    202 6
387  next  1    202 201    instr2 only after instr2
388  init  1    203 6
389  next  1    203 202    instr3 only after instr3
390  init  1    204 6
391  and   1    200 303
392  next  1    204 391    endflag if instr0 branches
400  bad   204             endflag terminates
```

And with this, the model is can be run. The whole suite of add tests can be derived from this model by changing the constant value of node 13 to the appropriate loop count.

5.2 Results

To start I placed all iterations based benchmarks with btormc into Table 3 and the benchmarks of extended address space into Table 4. From Table 4 one can assume that the extension of address space does not impact the runtime of the model checker in a meaningful way. As seen in Table 5, with rising loop counts, memory operations need increasingly more time in comparison to their respective non-memory operation benchmarks. Also with rising loop counts the impact of large amounts of memory initialised is reduced, which was to be expected.

The `nopc` benchmark is significantly faster than my model. This was to be expected, as Schrögendorfer models one RISC-V program specifically whereas I model the processor and feed it different programs by initialization. In this perspective, it is not surprising that a specialised model is faster than a generalised one. **(TODO: Add example for finding an instruction?)**

I also attempted to benchmark with the AVR and Pono model checkers, as they ranked first and second in the 2024 hardware model checking competition. Unfortunately, AVR did not terminate within 15 minutes when checking the `add_0256` benchmark.

loops	base		fullmem		nopc
	add	writemem	add	writemem	add
0256	2.635	2.877	9.759	13.344	0.136
0512	6.195	7.306	16.402	24.209	0.268
0768	10.802	13.283	24.093	36.388	0.414
1024	16.306	21.004	32.732	50.376	0.569
1280	23.032	30.200	42.410	65.746	0.728
1536	30.669	41.262	52.961	83.036	0.898
1792	39.463	53.940	64.598	101.475	1.075
2048	48.944	68.521	77.084	122.189	1.276

Table 3: Times of iterations based benchmarks

bits of address space	16	17	18	19	20
add_0256	2.635	2.632	2.626	2.626	2.624
add_1024	16.306	16.464	16.511	16.452	16.460
writemem_0256	2.877	2.88	2.890	2.889	2.890
writemem_1024	21.004	21.131	21.215	21.181	21.163

Table 4: Times of extended address space benchmarks

loops	$\frac{add}{writemem}$	$\frac{fullmem\_add}{fullmem\_writemem}$	$\frac{add}{fullmem\_add}$	$\frac{writemem}{fullmem\_writemem}$	$\frac{add}{nopc\_add}$
0256	0.92	0.73	0.27	0.22	19.38
0512	0.85	0.68	0.38	0.3	23.12
0768	0.81	0.66	0.45	0.37	26.09
1024	0.78	0.65	0.5	0.42	28.66
1280	0.76	0.65	0.54	0.46	31.64
1536	0.74	0.64	0.58	0.5	34.15
1792	0.73	0.64	0.61	0.53	36.71
2048	0.71	0.63	0.63	0.56	38.36

Table 5: Relative runtime of benchmarks

Pono determined that this benchmark is satisfiable, but required nearly six minutes using the `-smt-solver cvc5` option. With `-smt-solver bzla`, Pono was slower but functional; other solvers reported inability to handle arrays. These results suggest that model checkers considered superior in general are not necessarily optimal for my model, whereas btormc, despite being unmaintained since August 2024, performed best. I suspect that newer model checkers are optimized for handling inputs, as most competition benchmarks involve at least one input beyond a clock signal, while my model operates solely with known constants and its execution time is dependent on rapid state iteration.

Another issue with AVR and Pono is their inability to generate a "complete" witness, as produced by the btormc option `-trace-gen-full`, which provides the values of all states in the final frame. Without this feature, it is not possible to reconstruct a state from their output after execution.

6 Conclusion

I developed tools to transition from a state to a model and from a witness of this model back to a state. Additionally, I implemented a fuzzer for the states to verify the correct functioning of the model, as well as a set of basic tests to benchmark its performance. Finally, I presented and discussed the results of these benchmarks, concluding that model checkers which appear superior in general are not necessarily better suited for this specific case.

ToDo Counters

To Dos: 18; 1, 2, **??**, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18

Parts to extend: 1; 1

Draft parts: 0;

Bibliography

[1] *The RISC-V Instruction Set Manual Volume I: Unprivileged ISA*, 2025, version 20250508. [Online]. Available: https://lf-riscv.atlassian.net/wiki/spaces/HOME/pages/16154769/RISC-V+Technical+Specifications

[2] A. Niemetz, M. Preiner, C. Wolf, and A. Biere, "Btor2 , BtorMC and Boolector 3.0," in *Computer Aided Verification*, H. Chockler and G. Weissenbacher, Eds. Cham: Springer International Publishing, 2018, pp. 587–595.

[3] F. Schrögendorfer, "Bounded Model Checking of Lockless Programs," Master's thesis, Johannes Kepler University Linz, August 2021. [Online]. Available: https://epub.jku.at/obvulihs/download/pdf/6579523

[4] A. Waterman, Y. Lee, D. A. Patterson, and K. Asanović, "The risc-v instruction set manual, volume i: Base user-level isa," UC Berkeley, Tech. Rep. UCB/EECS-2011-62, May 2011. [Online]. Available: http://www2.eecs.berkeley.edu/Pubs/TechRpts/2011/EECS-2011-62.html

[5] "History of RISC-V," https://riscv.org/about/, accessed: 15.08.2025.

[6] "RISC-V-Simulator," https://github.com/Kr1mo/Risc-V-Simulator.

[7] A. Biere, "Bounded model checking," in *Handbook of Satisfiability*, 2nd ed., ser. Frontiers in Artificial Intelligence and Applications, A. Biere, M. Heule, H. van Maaren, and T. Walsh, Eds. IOS Press, 2021, vol. 336, pp. 739–764. [Online]. Available: https://doi.org/10.3233/FAIA201002

[8] "HWMCC 2024," https://hwmcc.github.io/2024/.

[9] A. Biere, "The AIGER And-Inverter Graph (AIG) format version 20071012," Institute for Formal Models and Verification, Johannes Kepler University, Altenbergerstr. 69, 4040 Linz, Austria, Tech. Rep. 07/1, 2007.

[10] D. Beyer and J. Strejček, "Improvements in software verification and witness validation: SV-COMP 2025," in *Proc. TACAS (3)*, ser. LNCS 15698. Springer, 2025, pp. 151–186.

[11] D. Beyer, P.-C. Chien, and N.-Z. Lee, "Bridging hardware and software analysis with btor2c: A word-level-circuit-to-c translator," in *Tools and Algorithms for the Construction and Analysis of Systems*, S. Sankaranarayanan and N. Sharygina, Eds. Cham: Springer Nature Switzerland, 2023, pp. 152–172.

[12] "RISC-V_to_BTOR2," https://github.com/Kr1mo/RISC-V_to_BTOR2.

[13] A. Goel and K. Sakallah, "Avr: Abstractly verifying reachability," in *Tools and Algorithms for the Construction and Analysis of Systems*, A. Biere and D. Parker, Eds. Cham: Springer International Publishing, 2020, pp. 413–422.

[14] M. Mann, A. Irfan, F. Lonsing, Y. Yang, H. Zhang, K. Brown, A. Gupta, and C. Barrett, "Pono: A flexible and extensible smt-based model checker," in *Computer Aided Verification: 33rd International Conference, CAV 2021, Virtual Event, July 20–23, 2021, Proceedings, Part II*. Berlin, Heidelberg: Springer-Verlag, 2021, p. 461–474. [Online]. Available: https://doi.org/10.1007/978-3-030-81688-9_22

(TODO: Add repo versions)