
Welcome

General is for creating topics and configuring the bot. A working topic is a conversation with your OpenCodez agent.

> Press **New topic**, check the title and model, create the topic, and start writing.

The default name is a historical or evocative Russian word with random capitalization. Another word draws again; Title lets you enter your own. Disable the mode in Settings.

FILES collects files. AUDIO turns voice notes and audio files into text. You can finish these connections later.



Topic creation example: the full model ID is visible and actions stay close together. The working topic remains a clean conversation.

Create with the wizard

New topic in General, or `/new` without arguments, opens a creation card in the chat. Only the user who opened it can operate its controls.

Field	What to choose
Title	Keep the random word, choose Another word, or enter your own. With random names disabled, the bot asks for a name immediately.
Profile	Saved model, reasoning, System and agent. The initial choice comes from your launch preferences.
Server	The OpenCodez connection that will run the task. A single-server installation has a fixed choice.
Working directory	An absolute path on the chosen server. `/default` restores its default directory.

Check the exact provider/model and reasoning. If the level is missing or unavailable, choose one supported for this topic. This does not change the saved profile. Changing server resets the default directory and checks the model again.

If the model, System or server is unavailable, select another profile/server or restore the connection and provider in OpenCodez. A profile changed while you were choosing requires confirmation again.

> **Create topic** first creates the Telegram topic. The OpenCodez session starts after your first ordinary prompt message. You can then use `/q` and check the launch with `/session`.

The selected name and parameters stay in the draft until creation. Close cancels the draft; `/cancel` cancels only the current field. Drafts last 15 minutes and disappear when the bot restarts.

The Topic ready card is deleted after two minutes. Restarting the bot preserves the deletion deadline.

Quick creation: /new

With arguments, the command creates a topic immediately. General form; square brackets mark optional parts:

```
/new [server] [profile] [dir:<path>] [title]
```

`local` below is an example ID from the server list; `sol` is a saved profile name. Substitute your own values.

Command	Result
`/new`	Topic creation wizard
`/new Title`	Custom name, other settings use defaults
`/new sol`	Profile sol, default server
`/new local`	Server local, default launch preferences
`/new sol Title`	Profile and custom name
`/new local Title`	Server and custom name
`/new local sol`	Server and profile
`/new local sol Title`	Server, profile and custom name

Omit the server to use the default; omit the profile to use default launch preferences. Omit the name to draw a random word. With random names disabled, the initial name comes from the profile or server.

`dir:` and `directory:` are equivalent and work with any command form. The path belongs to the selected server; omitting it uses its configured directory or the OpenCodez default.

```
/new local sol dir:/workspace Title
```

Quote paths containing spaces. A title can contain multiple words:

```
/new local sol "dir:/workspace/My Project" My project
```

> The server is recognized first, then the profile. Only exact configured IDs and names are recognized; a typo can become part of the title. To name a topic after a server or profile, specify both explicitly: `/new local sol sol` names it “sol”.

Profiles and models

A profile saves the model, reasoning, and optional System and agent. Create, copy, edit and delete profiles in General → Profiles. Restore deleted profiles from Deleted.

Choose Make default to set the main profile. To use another for just one topic, select it in the wizard or put it after the server in `/new`.

The catalog comes from the selected OpenCodez server. Models are grouped by provider and family; search accepts names, IDs and providers. Refresh reloads the catalog. Choose a model and supported reasoning level, then save the profile.

Catalogs and variants can differ between servers. A listed model does not guarantee provider quota. Check the provider connection and plan in OpenCodez, or choose another model.

> Saving, deleting or changing the default profile does not alter running sessions. New topics receive their own displayed settings; the model and reasoning chosen during creation are kept for later restarts.

Everyday work

Send the first task as an ordinary message in the new topic. Attach images or files to the text. Files without captions wait for your next text message.

Command	Action
`/session`	Tap-to-copy session ID, server, model and status; details identify this command's topic and file/audio destinations
`/q prompt`	Send or queue a task in an existing session
`/q` or `/q status`	View the queue
`/q delete N`	Remove a queue item by number
`/kill`	Stop and clear the queue
`/repeat`	Stop, clear the queue and resend the last prompt verbatim with attachments
`/compact`	Compact an idle session

`/export` sends a Markdown document with prompts and final answers from the entire current session to this topic. See the Session export guide page.

One `/q` at the start is enough for a long prompt: parts become one task after two seconds of quiet. In a Rich Message, the command can start a paragraph or heading; text and photos stay together. A new `/q` starts a separate task.

Answer agent questions directly in Telegram. The card walks through questions; buttons toggle multiple choices. For your own answer, simply reply to the card — no extra button. At the end of a questionnaire, review and send your answers together. A lone single-choice question is answered immediately. Choices survive bot restarts.

The bot shows agent text and final answers. Ordinary tool actions are hidden by default.

After a failure, check `/session` before retrying: the server may already have accepted the prompt. If a new topic is still waiting for its first launch, restore the connection and submit the task again there.

> To stop the agent before closing or deleting a topic, run `/kill` first. Closing disables mirroring and clears the queue, while the server session is preserved.

Reset and rewind

`/reset` stops the current run, clears the queue and prepares a new session in the same topic. The previous session remains in OpenCodez; the new one starts with your next prompt.

Command	What stays or changes
`/reset`	Same profile, server and directory
`/reset solm`	Another profile, same server and directory
`/reset local`	Another server, its default directory
`/reset solm local`	Another profile and server

The order is the reverse of `/new`: profile first, server second. IDs must be configured. If a name matches both a profile and server, specify both. The topic name stays; its server suffix updates. Before the first prompt, reset changes the pending launch. For another directory, create a topic with `/new ... dir:...`.

> **Replying to an earlier user prompt rewinds that turn.** The bot discards the later branch and submits your reply in place of that prompt, allowing you to correct it and continue from that point.

`/context` exports recent completed or interrupted turns; `/context N` chooses a count from 1 to 10. Save the depth in personal settings or with `/set_context N`. Internal compaction and reminders do not count as separate prompts.

Session export: /export

Send `/export` without arguments in a working topic. The bot reads its current OpenCodez session and sends one `.md` document to the same topic. The command does not change the session or start the agent.

> **In the file:** your verbatim prompt — the model's verbatim final text answer, then the next pair, in order. Repeated user prompts remain separate blocks.

Reasoning, commentary, tool calls, intermediate answers, automatic replays/reminders and compaction summaries are excluded from completed pairs.

A prompt without a final answer is retained with an explicit notice. **Progress notes are included only for the latest prompt**, when it has no final answer but does have intermediate messages. They appear in a separate section **at the end of the file**, with the prompt number and a “not a final answer” label. Older prompts' notes are excluded. No appendix is added if the latest prompt has a final answer or no notes.

The document heading is the session's own title from OpenCodez. Headings and text fences clearly separate user and model. The contents are preserved without summaries or editing, including spaces, line breaks and Markdown. You can attach the entire file to a new prompt.

Files and audio

FILES receives results the agent sends at your request. Drop a file there to save it on the configured server; the bot returns its path.

> **Files up to 2 GB.** A local Telegram Bot API sends files up to 2000 MB and removes the cloud's 20 MB download limit. The cloud API sends files up to 50 MB.

The local API is a separate service on the bot's host. It needs `api_id` and `api_hash` from my.telegram.org, a running service and a bot endpoint switch. Entering credentials alone does not enable it. Setup instructions. Configured bot and model limits still apply.

AUDIO transcribes voice notes and audio files. Copy the text and send it to the agent yourself.

> A transcript never starts an agent automatically.

Connect Groq through Setup. Whisper Large V3 Turbo is recommended. The free tier has limits.

Spoken answers are a separate setting. Reply `/speak` to an answer for a one-off voice summary when providers are configured.

Settings and notifications

Final-answer, question and failure alerts arrive in your private chat. Open the bot and press Start once. Final-answer notifications can be disabled in settings.

`/setup` checks connections and continues unfinished setup. Running it again does not recreate service topics.

Language, random topic names, tool visibility and voice options are in General → Settings. `/update` checks bot updates.

> The General panel moves to a fresh message daily. `/menu` moves it to the bottom immediately.

▼ Advanced options

Original-prompt reminders after automatic compaction are enabled by default. Change them in advanced settings or with `/reminder on|off`. You can also show tool actions and add diagnostics to private notifications. Spoken answers have separate synthesis-profile, voice, length and summary-prompt settings.