

Pf sense openvpn config

Servers

Clients

Client Specific Overrides

Wizards

Client Export

General Information

Description

open

A description of this VPN for administrative reference.

Disabled

☐ Disable this server

Set this option to disable this server without removing it from the list.

Unique VPN ID

Server 1 (ovpns1)

Mode Configuration

Server mode

Remote Access (SSL/TLS + User Auth)

Backend for authentication

Local Database

Device mode

tun - Layer 3 Tunnel Mode

"tun" mode carries IPv4 and IPv6 (OSI layer 3) and is the most common and compatible mode across all platforms.
"tap" mode is capable of carrying 802.3 (OSI Layer 2.)

Endpoint Configuration

Protocol

UDP on IPv4 only

Interface

WAN

The interface or Virtual IP address where OpenVPN will receive client connections.

Local port

1194

The port used by OpenVPN to receive client connections.

Cryptographic Settings

TLS Configuration

☒ Use a TLS Key

A TLS key enhances security of an OpenVPN connection by requiring both parties to have a common key before a peer can perform a TLS handshake. This layer of HMAC authentication allows control channel packets without the proper key to be dropped, protecting the peers from attack or unauthorized connections.The TLS Key does not have any effect on tunnel data.

TLS Key

```
#
# 2048 bit OpenVPN static key
#
-----BEGIN OpenVPN Static key V1-----
ee9cc25ca0f72b35de614c32f6aaa8ab
```

Paste the TLS key here.

OpenV...

Activate Windows
Go to Settings to activate Windows.

<u>TLS Key Usage Mode</u>	TLS Authentication	In Authentication mode the TLS key is used only as HMAC authentication for the control channel, protecting the peers from unauthorized connections. Encryption and Authentication mode also encrypts control channel communication, providing more privacy and traffic control channel obfuscation.
<u>.S keydir direction</u>	Use default direction	The TLS Key Direction must be set to complementary values on the client and server. For example, if the server is set to 0, the client must be set to 1. Both may be set to omit the direction, in which case the TLS Key will be used bidirectionally.
<u>Peer Certificate Authority</u>	myvpn-ca	
<u>Peer Certificate Revocation list</u>	WAN (CA: myvpn-ca)	
<u>OCSP Check</u>	☐ Check client certificates with OCSP	
<u>Server certificate</u>	opnvpn -server -cert (Server: Yes, CA: myvpn-ca, In Use)	
<u>DH Parameter Length</u>	2048 bit	Diffie-Hellman (DH) parameter set used for key exchange. i
<u>ECDH Curve</u>	Use Default	The Elliptic Curve to use for key exchange. Microsoft 365 Copilot The curve from the server certificate is used by default when the server uses an ECDSA certificate. Otherwise, secp256k1 is used as a fallback.
<u>Data Encryption Algorithms</u>	AES-128-CBC (128 bit key, 128 bit block) AES-128-CFB (128 bit key, 128 bit block) AES-128-CFB1 (128 bit key, 128 bit block) AES-128-CFB8 (128 bit key, 128 bit block) AES-128-GCM (128 bit key, 128 bit block) AES-128-OFB (128 bit key, 128 bit block) AES-192-CBC (192 bit key, 128 bit block) AES-192-CFB (192 bit key, 128 bit block) AES-192-CFB1 (192 bit key, 128 bit block) AES-192-CFB8 (192 bit key, 128 bit block) Available Data Encryption Algorithms Click to add or remove an algorithm from the list i The order of the selected Data Encryption Algorithms is respected by OpenVPN. This list is ignored in Shared Key mode. AES-128-CBC Allowed Data Encryption Algorithms. Click an algorithm name to remove it from the list	
<u>Fallback Data Encryption Algorithm</u>	AES-256-CBC (256 bit key, 128 bit block)	The Fallback Data Encryption Algorithm used for data channel packets when communicating with clients that do not support data encryption algorithm negotiation (e.g. Shared Key). This algorithm is automatically included in the Data Encryption Algorithms list.
<u>Auth digest algorithm</u>	SHA256 (256-bit)	The algorithm used to authenticate data channel packets, and control channel packets if a TLS Key is present. When an AEAD Encryption Algorithm mode is used, such as AES-GCM, this digest is used for the control channel only, not the data channel. The server and all clients must have the same setting. While SHA1 is the default for OpenVPN, this algorithm is insecure.
<u>Hardware Crypto</u>	No Hardware Crypto Acceleration	

Tunnel Settings

IPv4 Tunnel Network

10.8.0.0/24

This is the IPv4 virtual network or network type alias with a single entry used for private communications between this server and client hosts expressed using CIDR notation (e.g. 10.0.8.0/24). The first usable address in the network will be assigned to the server virtual interface. The remaining usable addresses will be assigned to connecting clients.

A tunnel network of /30 or smaller puts OpenVPN into a special peer-to-peer mode which cannot push settings to clients. This mode is not compatible with several options, including Exit Notify, and Inactive.

IPv6 Tunnel Network

This is the IPv6 virtual network or network type alias with a single entry used for private communications between this server and client hosts expressed using CIDR notation (e.g. fe80::/64). The ::1 address in the network will be assigned to the server virtual interface. The remaining addresses will be assigned to connecting clients.

Redirect IPv4 Gateway

☐ Force all client-generated IPv4 traffic through the tunnel.

Redirect IPv6 Gateway

☐ Force all client-generated IPv6 traffic through the tunnel.

IPv4 Local network(s)

192.168.1.0/24

IPv4 networks that will be accessible from the remote endpoint. Expressed as a comma-separated list of one or more CIDR ranges or host/network type aliases. This may be left blank if not adding a route to the local network through this tunnel on the remote machine. This is generally set to the LAN network.

IPv6 Local network(s)

IPv6 networks that will be accessible from the remote endpoint. Expressed as IP/PREFIX or host/network type aliases. This may be left blank if not adding a

English (United States)
US

Activate Windows
Go to Settings to activate Windows.
To switch input methods, press Windows key + space.

AuthoritiesCertificatesRevocation

Create / Edit CA

Descriptive name

myvpn-ca

The name of this entry as displayed in the GUI for reference.

This name can contain spaces but it cannot contain any of the following characters: ?, >, <, &, /, \, ", '

Method

Import an existing Certificate Authority

Trust Store

☐ Add this Certificate Authority to the Operating System Trust Store

When enabled, the contents of the CA will be added to the trust store so that they will be trusted by the operating system.

Randomize Serial

☐ Use random serial numbers when signing certificates

When enabled, if this CA is capable of signing certificates then serial numbers for certificates signed by this CA will be automatically randomized and checked for uniqueness instead of using the sequential value from Next Certificate Serial.

Existing Certificate Authority

Certificate data

-----BEGIN CERTIFICATE-----
MIIDWjCCAKKgAwIBAgIIU2cvhy/Un1EwDQYJKoZIhvcN

Microsoft Store

Activate Windows
Go to Settings to activate Windows.

[Edit an Existing Certificate](#)

Method Edit an existing certificate ▼

Descriptive name

This name can contain spaces but it cannot contain any of the following characters: ?, >, <, &, /, \, ", '.

Subject	CN=openvpn , C=IN
----------------	-------------------

[Edit Certificate](#)[Edit Certificate](#)

Certificate Type ☒ X.509 (PEM) ☐ PKCS #12 (PFX)

Certificate data

MRQwEgYDVQQDEwtprbnRl

```
MIIDvJCCAgagAwIBAgIBAJANBgkqhkiG9w0BAQsFADAj
MRQwEgYDVQQDEwtpbmRl
```

cm5hbc1jYTELMAKGA1UEBHMCSU4wHhcNMjYwNjA5MTMy
NzQ2WWhcNMzYwNjA2MTMy

Paste a certificate in X.509 PEM format here.

Private key data

```
-----BEGIN PRIVATE KEY-----
MIIEvAIBADANBgkqhkiG9w0BAQEFAASCBKYwggSiAgEA
```

AoIBAQCpRkatv50cYXW
obGo04Q0JqQE7NzpkJe7//rWTPJqRyxErpUsKDPeJjow
aRYqIj8IjLwnvp2kDodz

Paste a private key in X.509 PEM format here. This field may remain empty if the private key is stored on a PKCS#11 token.



[Users](#)
[Groups](#)
[Settings](#)
[Authentication Servers](#)

11. Results

User Properties	
Defined by	USER

Disabled ☐ This user cannot login

Username

Password

Full name

User's full name, for administrative information only

Expiration date

Leave blank if the account shouldn't expire, otherwise enter the expiration date as MM/DD/YYYY

Custom Settings ☐ Use individual customized GUI options and dashboard layout for this user.

Group membership admins

Not member of Microsoft Activate Windows

Not member of Member of Go to Settings to activate Windows

[move to member of list](#)
[move to Not member of list](#)

OpenVPN Connect



Securely Connected!

00:08:21



192.168.31.141 [pfSense-U...]
192.168.31.141

Disconnect



↓ 0 KB/s

↑ 0 KB/s

~8 sec ago

More Details

Outlook