



LOKNETE DR. BALASAHEB VIKHE PATIL
(PADMA BHUSHAN AWARDEE)
PRAVARA RURAL EDUCATION SOCIETY'S
**PRAVARA RURAL
ENGINEERING COLLEGE**
LONI
Tal. Rahata, Dist. Ahmednagar



TITLE PAGE

Name of Department : IT Subject : DBMS

Experiment No. 6

Roll No. 36

Name of Expt. <u>Create table with primary key & Foreign key constraints.</u>

Date of Performance of Experiment :- 13/3/23

Date of Completion of Experiment :- 23/3/23

Progressive Assessment Marks

Marks Obtained				Dated Sign Teacher
Attendance (3 Months)	Performance (4 Marks)	Writing & Submission (3 Marks)	Total (10 Marks)	
3	4	3	10	



* Practical No. 6 *

Title : Create table with primary Key and foreign Key Constraints.

Objectives :

Create table with primary Key and foreign Key constraints.

- Alter table with add & modify.
- Drop table.

Theory :

Keys are used to establish and identify relationships between tables.

Types of Keys :

1) Primary Key -

It is used to identify one and only one instance of an entity uniquely.

2) Candidate Key -

A candidate Key is an attribute or set of attributes that can uniquely identify a tuple. Except for the primary Key, the remaining attributes are considered a candidate Key.



3) Super Key -

It is an attribute set that can uniquely identify a tuple. A super Key is a superset of a candidate Key.

4) Foreign Key -

Foreign keys are the columns of the table used to point to the primary key of another table.

5) Alternate Key -

The total number of the alternate keys minus the primary key. It may or may not exist.

6) Composite Key -

Whenever a primary key consists of more than one attribute, it is known as Composite Key.

* DDL Queries :

* CREATE TABLE With Primary Key

If you want to create a table you should name the table and define its column and each column's data type.



Example: CREATE TABLE Students (Id INT NOTNULL, NAME Varchar (20), Age INT, Address CHAR (25), PRIMARY KEY (Id));

* DROP TABLE

A SQL Drop table statement is used to delete a table definition and all data from a table.

Syntax: DROP TABLE table_name;

* DELETE TABLE

The DELETE Statement is used to delete rows from a table. If you want to remove a specific row from a table you should use WHERE condition.

Syntax: DELETE FROM table_name [Where condition];

DELETE FROM table_name;

* RENAME TABLE

Any database user can easily change the name by using the RENAME TABLE.



Syntax: RENAME old-table-name To new-table-name ;

* TRUNCATE TABLE

A truncate SQL statement is used to remove all rows (complete data) from a table.

Syntax: TRUNCATE TABLE table-name ;

* COPY TABLE

The SELECT INTO statement in SQL copies the content from one existing table into the new table.

Syntax : SELECT * INTO New-table-name FROM Old-table-name ;

* ALTER TABLE

The ALTER TABLE in SQL allow to ADD , MODIFY and DELETE columns of an existing table.

its columns



1) ALTER TABLE ADD COLUMN

It is used to add the columns in the existing table.

Syntax : ALTER TABLE table_name ADD column_name column_definition ;

2) ALTER TABLE MODIFY COLUMN

The Modify keyword is used for changing the column definition of the existing table.

Syntax : ALTER TABLE table_name MODIFY column_name column_definition ;

3) ALTER TABLE DROP COLUMN

It is used to delete the columns from the existing table.

Syntax : ALTER TABLE table_name DROP column_name ;



* DML Queries :

- 1) Select Command
- 2) Insert Command
- 3) Update Command
- 4) Delete Command

1) Select DML Command -

It shows the records of the specified table.

Syntax : `Select * From table_name;`

2) Insert DML Command -

It allows user to insert data in database tables.

Syntax : `INSERT INTO table_name (column_name1, ..., column-N) VALUES (value_1, ..., Value-N);`

3) Update DML Command -

It allows users to update or modify the existing data in databases.

Syntax : `UPDATE table_name SET column_name = value WHERE column_name = value;`



4) Delete DML Command -

It allows users to remove single or multiple existing records from the database tables.

Syntax: DELETE FROM table_name WHERE condition;

* Conclusion -

We have successfully implemented all the queries on the table using primary & foreign key.

②

Enter password: *****

Welcome to the MySQL monitor. Commands end with ; or \g.

Your MySQL connection id is 8

Server version: 8.0.32 MySQL Community Server - GPL

Copyright (c) 2000, 2023, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> show databases;

Database
bank
bank_magnt_system
bank_magt
bank_management
bank_mgnt
cust
information_schema
it
mysql
performance_schema
student
students
sys

13 rows in set (0.09 sec)

mysql> use bank_magnt_system;

Database changed

mysql> select * from employee_table;

id	name	occupation	age	address	Salary
36	naziya	student	19	shrirampur	10000
37	naz	student	18	loni	2000
38	nazi	student	18	Mumbai	10000
39	zi	student	17	delhi	3000
40	ziya	student	16	solapur	5000

5 rows in set (0.03 sec)

mysql> CREATE TABLE Orders (

-> OrderID int NOT NULL,

-> OrderNumber int NOT NULL,

-> id int,

-> PRIMARY KEY (OrderID),

-> FOREIGN KEY (id) REFERENCES employee_table(id)

->);

Query OK, 0 rows affected (0.14 sec)

mysql> select * from employee_table;

id	name	occupation	age	address	Salary
36	naziya	student	19	shrirampur	10000
37	naz	student	18	loni	2000
38	nazi	student	18	Mumbai	10000
39	zi	student	17	delhi	3000
40	ziya	student	16	solapur	5000

5 rows in set (0.00 sec)

```
mysql> select *from orders;
Empty set (0.00 sec)
```

```
mysql> insert into orders values(11,303,36),(22,89,38);
Query OK, 2 rows affected (0.03 sec)
Records: 2 Duplicates: 0 Warnings: 0
```

```
mysql> select *from Orders;
```

OrderID	OrderNumber	id
11	303	36
22	89	38

2 rows in set (0.00 sec)

A