



LOKNETE DR. BALASAHEB VIKHE PATIL
(PADMA BHUSHAN AWARDEE)
PRAVARA RURAL EDUCATION SOCIETY'S
**PRAVARA RURAL
ENGINEERING COLLEGE**
LONI
Tal. Rahata, Dist. Ahmednagar



TITLE PAGE

Name of Department : IT Subject : DBMS

Experiment No. 8

Roll No. 36

Name of Expt. Execute DDL/DML statements which demonstrate the use of views.

Date of Performance of Experiment :- 13/4/23

Date of Completion of Experiment :- 3/5/23

Progressive Assessment Marks

Marks Obtained				Dated Sign Teacher
Attendance (3 Months)	Performance (4 Marks)	Writing & Submission (3 Marks)	Total (10 Marks)	
3	4	3	10	

COLUMNS FROM Table Name WHERE Condition;



* Practical No.8 *

Title : Execute DDL / DML Statements for Views.

Objectives :

Execute DDL / DML statements which demonstrate the use of views.

Theory :

Views in SQL are kind of virtual tables. A view also has rows and columns as they are in a real table in the database. We can create a view by selecting fields from one or more tables present in the database. A view can either have all the rows of a table or specific rows based on certain condition.

1) Creating View -

A view can be created using the Create View statement. We can create a view from a single table or multiple tables.

Syntax : CREATE VIEW view_name AS SELECT columns FROM table_name WHERE condition;

2) Updating a View -

- The SELECT statement which is used to create the view should not include GROUP BY clause or ORDER BY clause.
- The select statement should not have the DISTINCT keyword.
- The view should have all NOT NULL values.
- The view should not be created using nested queries or complex queries.
- The view should be created from a single table. If the view is created using multiple tables then we will not be allowed to update the view.

Syntax : CREATE or REPLACE VIEW view_name
AS SELECT column1, column2,
FROM table_name WHERE condition ;



3) Inserting a row in a View -

We can insert a row in a View in a same way as we do in a table. We can use the INSERT INTO Statement of SQL to insert a row in a View.

Syntax : INSERT INTO view_name (column1, column2, ---) VALUES (value1, ---, valueN);

4) Deleting a row from a View -

We can use the DELETE statement of SQL to delete rows from a view.

Syntax : DELETE FROM view_name WHERE condition ;


5) Deleting View -

A view can be deleted using the DROP View statement.

Syntax : DROP VIEW view_name ;



* Conclusion - We learned that DDL and DML commands with their syntax and executed it.



Syntax : INSERT INTO view_name (column, ..., VALUES (values, ...))

1) Deleting a row from a view -

We can use the DELETE statement of SQL to delete rows from a view.

Syntax : DELETE FROM view_name WHERE condition ;

2) Deleting View - A view can be deleted using the DROP VIEW statement.

Syntax : DROP VIEW view_name ;

Enter password: *****

Welcome to the MySQL monitor. Commands end with ; or \g.

Your MySQL connection id is 33

Server version: 8.0.32 MySQL Community Server - GPL

Copyright (c) 2000, 2023, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> create database students;

Query OK, 1 row affected (0.08 sec)

mysql> show databases;

Database
customers
employee
information_schema
management
medicine
mysql
performance_schema
student
students

9 rows in set (0.04 sec)

mysql> use students;

Database changed

mysql> create table stud(id int Primary key,Name varchar(20),Age int,Address varchar(30));

Query OK, 0 rows affected (0.07 sec)

mysql> insert into stud values(1,'Naziya',20,'Shrirampur'),(2,'Radhika',19,'Loni'),(3,'Raj',23,'Delhi');

Query OK, 3 rows affected (0.01 sec)

Records: 3 Duplicates: 0 Warnings: 0

mysql> select *from stud;

id	Name	Age	Address
1	Naziya	20	Shrirampur
2	Radhika	19	Loni
3	Raj	23	Delhi

3 rows in set (0.00 sec)

mysql> create view newview as select * from stud;

Query OK, 0 rows affected (0.00 sec)

mysql> select *from newview;

id	Name	Age	Address
1	Naziya	20	Shrirampur
2	Radhika	19	Loni
3	Raj	23	Delhi

3 rows in set (0.00 sec)

mysql> update newview set name = "Naz" where id =1;

Query OK, 1 row affected (0.00 sec)

Rows matched: 1 Changed: 1 Warnings: 0

mysql> select *from newview;

id	Name	Age	Address
1	Naz	20	Shrirampur
2	Radhika	19	Loni
3	Raj	23	Delhi

3 rows in set (0.00 sec)

mysql> insert into newview values(4,'Ram',24,'loni');

Query OK, 1 row affected (0.00 sec)

mysql> select *from newview;

id	Name	Age	Address
1	Naz	20	Shrirampur
2	Radhika	19	Loni
3	Raj	23	Delhi
4	Ram	24	loni

4 rows in set (0.00 sec)

mysql> delete from newview where name ='Raj';

Query OK, 1 row affected (0.00 sec)

mysql> select *from newview;

id	Name	Age	Address
1	Naz	20	Shrirampur
2	Radhika	19	Loni
4	Ram	24	loni

3 rows in set (0.00 sec)

```
mysql> drop view newview;  
Query OK, 0 rows affected (0.00 sec)
```

```
mysql> select *from newview;  
ERROR 1146 (42S02): Table 'students.newview' doesn't exist  
mysql>
```

