

Library DAO Tutorial

Step 9: Hibernate Version – Spring Configuration Changes for Hibernate

Copyright © 2016 The Learning House, Inc.

All rights reserved. No part of these materials may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of The Learning House. For permission requests, write to The Learning House, addressed "Attention: Permissions Coordinator," at the address below.

The Learning House

427 S 4th Street #300

Louisville KY 40202

Step 9: Hibernate Version – Spring Configuration Changes for Hibernate

Overview

Now we will add entries to the Spring configuration file so that we'll be able to use our new DAO.

Notes:

We add a bean definition for the Hibernate implementation of our DAO.

1. We add a bean definition for the Hibernate SessionFactory. We specify the following:
 - a. The data source to be used
 - b. The packages to scan for relational mapping annotations
 - c. The particular database dialect that Hibernate should use

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xmlns:context="http://www.springframework.org/schema/context"
       xmlns:tx="http://www.springframework.org/schema/tx"
       xmlns:aop="http://www.springframework.org/schema/aop"
       xsi:schemaLocation="http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans.xsd
http://www.springframework.org/schema/mvc
http://www.springframework.org/schema/mvc/spring-mvc.xsd
http://www.springframework.org/schema/tx
http://www.springframework.org/schema/tx/spring-tx-3.0.xsd
http://www.springframework.org/schema/context
http://www.springframework.org/schema/context/spring-context.xsd
http://www.springframework.org/schema/aop
http://www.springframework.org/schema/aop/spring-aop-3.2.xsd">

    <!-- Bean definitions go here -->
    <tx:annotation-driven/>

    <context:component-scan base-package="com.swcguild.library.dao" />

    <bean id="dataSource"
          class="org.apache.commons.dbcp.BasicDataSource">
        <property name="driverClassName" value="com.mysql.jdbc.Driver"/>
        <property name="url"
            value="jdbc:mysql://localhost:3306/library_test"/>
        <property name="username" value="root"/>
        <property name="password" value="root"/>
        <property name="initialSize" value="5"/>
        <property name="maxActive" value="10"/>
    </bean>
```

```

<bean id="transactionManager"
      class="org.springframework.jdbc.datasource.DataSourceTransactionManager">
    <property name="dataSource" ref="dataSource"/>
</bean>

<bean id="jdbcTemplate"
      class="org.springframework.jdbc.core.JdbcTemplate">
    <property name="dataSource" ref="dataSource"/>
</bean>

<bean id="libraryDao" class="com.swcguild.library.dao.LibraryDaoDbImpl">
    <property name="jdbcTemplate" ref="jdbcTemplate"/>
</bean>

<bean id="hibernateLibraryDao"
class="com.swcguild.library.dao.LibraryDaoHibernateImpl">
    <constructor-arg ref="sessionFactory"/>
</bean>

<!-- HIBERNATE CONFIGURATION -->
<bean id="sessionFactory"
class="org.springframework.orm.hibernate3.annotation.AnnotationSessionFactoryBean">
    <property name="dataSource" ref="dataSource" />
    <property name="packagesToScan"
        value="com.swcguild.library.model" />
    <property name="hibernateProperties">
        <props>
            <prop key="dialect">org.hibernate.dialect.MySQLDialect</prop>
        </props>
    </property>
</bean>
</beans>

```