

Library DAO Tutorial

Step 4: Creating the Database



SOFTWARE-GUILD

Copyright © 2016 The Learning House, Inc.

All rights reserved. No part of these materials may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of The Learning House. For permission requests, write to The Learning House, addressed "Attention: Permissions Coordinator," at the address below.

The Learning House


427 S 4th Street #300

Louisville KY 40202

Step 4: Creating the Database

Overview

In this step, we will create the database for our library. Our database will consist of four tables as in the following diagram:



Note the FK constraints in `books.publisher_id` back to `publishers.publisher_id`, `books_authors.book_id` back to `books.book_id`, and `books_authors.author_id` back to `authors.author_id`.

The `books.publisher_id` column and FK constraint represents the many-to-one relationship between Publishers and Books (publishers may publish many books but a book can have only one publisher). The `books_authors` table and related FK constraints represent the many-to-many relationship between Books and Authors (books can have many authors and authors can write many books).

SQL Script

Run the following SQL script to create your database:

```
-- phpMyAdmin SQL Dump
-- version 4.0.6deb1
-- http://www.phpmyadmin.net
--
-- Host: localhost
-- Generation Time: Jun 17, 2014 at 02:54 PM
-- Server version: 5.5.37-0ubuntu0.13.10.1
-- PHP Version: 5.5.3-1ubuntu2.3

SET SQL_MODE = "NO_AUTO_VALUE_ON_ZERO";
SET time_zone = "+00:00";

/*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */;
/*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS */;
/*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */;
/*!40101 SET NAMES utf8 */;

--
-- Database: `library`
--

--
-- Table structure for table `authors`
--

CREATE TABLE IF NOT EXISTS `authors` (
  `author_id` int(11) NOT NULL AUTO_INCREMENT,
  `first_name` varchar(20) NOT NULL,
  `last_name` varchar(20) NOT NULL,
  `street` varchar(20) NOT NULL,
  `city` varchar(20) NOT NULL,
  `state` varchar(20) NOT NULL,
  `zip` varchar(20) NOT NULL,
  `phone` varchar(20) NOT NULL,
  PRIMARY KEY (`author_id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1 AUTO_INCREMENT=1 ;

--
--
```

```
--
-- Table structure for table `books`
--

CREATE TABLE IF NOT EXISTS `books` (
  `book_id` int(11) NOT NULL AUTO_INCREMENT,
  `isbn` varchar(20) NOT NULL,
  `title` varchar(50) NOT NULL,
  `publisher_id` int(11) NOT NULL,
  `price` decimal(5,2) NOT NULL,
  `publish_date` datetime NOT NULL,
  PRIMARY KEY (`book_id`),
  KEY `publisher_id` (`publisher_id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1 AUTO_INCREMENT=1 ;

-----

--
-- Table structure for table `books_authors`
--

CREATE TABLE IF NOT EXISTS `books_authors` (
  `book_id` int(11) NOT NULL,
  `author_id` int(11) NOT NULL,
  KEY `book_id` (`book_id`),
  KEY `author_id` (`author_id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;

-----

--
-- Table structure for table `publishers`
--

CREATE TABLE IF NOT EXISTS `publishers` (
  `publisher_id` int(11) NOT NULL AUTO_INCREMENT,
  `name` varchar(20) NOT NULL,
  `street` varchar(20) NOT NULL,
  `city` varchar(20) NOT NULL,
  `state` varchar(20) NOT NULL,
  `zip` varchar(20) NOT NULL,
  `phone` varchar(20) NOT NULL,
  PRIMARY KEY (`publisher_id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1 AUTO_INCREMENT=1 ;
```

```
--
-- Constraints for dumped tables
--

--
-- Constraints for table `books`
--
ALTER TABLE `books`
  ADD CONSTRAINT `books_ibfk_1` FOREIGN KEY (`publisher_id`) REFERENCES `publishers`
  (`publisher_id`) ON DELETE NO ACTION;

--
-- Constraints for table `books_authors`
--
ALTER TABLE `books_authors`
  ADD CONSTRAINT `books_authors_ibfk_1` FOREIGN KEY (`book_id`) REFERENCES `books`
  (`book_id`) ON DELETE NO ACTION,
  ADD CONSTRAINT `books_authors_ibfk_2` FOREIGN KEY (`author_id`) REFERENCES `authors`
  (`author_id`) ON DELETE NO ACTION;

/*!40101 SET CHARACTER_SET_CLIENT=@OLD_CHARACTER_SET_CLIENT */;
/*!40101 SET CHARACTER_SET_RESULTS=@OLD_CHARACTER_SET_RESULTS */;
/*!40101 SET COLLATION_CONNECTION=@OLD_COLLATION_CONNECTION */;
```

Wrap-up

In this step, we did the following:

1. Created the database.
2. Reviewed the many-to-one relationship between Publishers and Books.
3. Reviewed the many-to-many relationship between Books and Authors.

In the next step, we will implement the JdbcTemplate version of our DAO.