



RESPONSIBILITIES

POSITION TITLE	ROLE	DESCRIPTION OF TASK
Safety Team	Develop and amend this document	Review and amend this document
Landscapers INC employees and contractors	Adherence	All employees and contractors engaged in work shall adhere to the guidelines in this procedure
Human Resources	Monitoring	Monitor and report on employee excessive hours
Departmental managers	Ensure compliance	Ensure compliance to procedure requirements

Do not operate any machinery without complete and clear instructions from your supervisor. It is his/her responsibility to make certain that each employee knows and understands the proper operation of the machine as well as any potential hazards involved. If you have any questions or concerns about the hazards or operation of any machine, do not run it before your supervisor has answered your questions.

Since machine-related accidents are usually profoundly serious, any written rules or supervisor's directions, Which are not explicitly followed, will result in strong disciplinary actions.

- No machine should be oiled, cleaned, or adjusted while it is in operation, unless specific provisions have been made for this purpose.
- Safety devices should not be by-passed, blocked, or tied down.
- Guards are placed at all hazardous points on the machine. They must be in place when the machinery is in operation. When this is not the case, a supervisor signed *Danger Tag* with printed operating instructions must be posted on the unguarded area *and* on the safety switch. The department head and safety officer must be duly informed.
- If, of necessity, a guard must be removed and the machine power operated, keep a safe distance. Never attempt a repair or adjustment in an area that cannot be reached safely.
- Do not make any alterations on your own. Tell your supervisor if you feel a guard needs changing.
- You may make only those operating adjustments stated in the machine operation instructions.

- When you leave your machine. No machine should be left running unattended unless specifically designed for that purpose.
- *Wait for the machine to stop!* Do not try to slow down or brake a moving machine by hand or with a makeshift device. If there is a problem, notify your supervisor. He/she will inform the proper authorities.
- Before clearing a jam is sure to turn the safety switch OFF unless there are other written procedures from the Safety Department.
- Make sure everyone is clear of the machine before you start it.
- Adjusting tools or keys should not be left in places where they can fall, slide, or be thrown into the machine when it is started.
- Only use those machines and equipment for which you have been trained and authorized.
- Do not wear jewelry, gloves, neckties, long sleeves, or loose clothing around machines. Hair should not be loose or straggly. Revolving shafts can catch onto these. Extreme caution is always necessary around running machinery.
- Machines should always be clean and free of rags, tools, or other devices.
- Use the proper brush, hook, or tool to remove residue such as chips or shavings. Never use your hands or an air hose.
- Do not use pins, projecting set screws, etc. on rotating parts unless properly guarded.
- Report all hazards to your supervisor.