

```
1: $Id: 2014q4-soln1,v 1.3 2014-10-29 13:36:09-07 - - $
2: Answers to 2014q4-test1, page 1
3:
4:
5: Question 1. [3]
6:
7: C++      |Bjarne Stroustrup's most noted contribution to language design
8: COBOL    |Business data processing language, designers included Grace
9: Algol 60 |Designed in Europe to express algorithms in a structured way.
10: C        |First version of Unix was 9000 lines of this language
11: Lisp     |List processing language typically used in artificial
12: FORTRAN  |Numeric and scientific computation language developed at IBM.
13: Simula 67|Simulation language that influenced the design of C++.
14: Pascal   |Small language for structured programming designed by Niklaus
15: Java     |Sun Microsystems claimed this language is ``write once, run
16:
17:
18: Question 2. [3]
19:
20: while (<>) {
21:     @nums = split m/ /;
22:     $total[$_] += $nums[$_] for 0..3;
23: }
24: print " @total\n";
25:
26:
27: Question 3. [4]
28:
29: Object subclass: Complex [
30:     |real imag|
31:     real [ ^ real ]
32:     imag [ ^ imag ]
33:     real: r [ real := r. imag := 0. ]
34:     imag: i [ real := 0. imag := i. ]
35:     real: r imag: i [ real := r. imag := i. ]
36:     + other [
37:         |r|
38:         r := Complex new.
39:         r real: self real + other real imag: self imag + other imag.
40:         ^ r
41:     ]
42: ]
43:
```

```
44:
45: Answers to 2014q4-test1, page 2
46:
47:
48: Question 4(a). [1]
49:
50: sub fac{
51:     my ($n) = @_;
52:     my $s = 1;
53:     $s *= $_ for 1..$n;
54:     return $s;
55: }
56:
57:
58: Question 4(b). [2]
59:
60: Number extend [
61:     fac [
62:         |s|
63:         s := 1.
64:         1 to: self do: [:i | s := s * i].
65:         ^ s
66:     ]
67: ]
68:
69:
70: Question 5. [2]
71:
72: Parametric (template, generic):
73:     template <typename T> class stack {...}
74:     class stack<T> {...}
75: Inclusion (inheritance):
76:     class bar {...}
77:     class foo extends bar {...}
78:
79:
80: Question 6. [2]
81:
82: Coercion (conversion):
83:     int a; double b; a = b;
84: Overloading:
85:     void foo (double);
86:     void foo (stringnt);
87:
88:
89: Question 7. [3]
90:
91: while ($line = <>) {
92:     ++$count{$_} for split m/\W+/, $line;
93: }
94:
95: push @array, sprintf "%10d %s\n", $count{$_}, $_ for keys %count;
96: @array = sort { $b cmp $a } @array;
97: print $array[$_] for 0..9;
98:
```

99:
100: **Answers to 2014q4-test1, page 3**
101:
102: 1. (D) ? :
103:
104: 2. (A) \$!
105:
106: 3. (A) $((a-b)*c)+d$
107:
108: 4. (C) [4+9] value
109:
110: 5. (B) M is possible, but not D.
111:
112: 6. (C) When the program is linked.
113:
114: 7. (C) map
115:
116: 8. (A) $\$p \rightarrow \{\$k\}$
117:
118: 9. (D) sum value: 3 value: 4
119:
120: 10. (B) 0.0/0.0
121:
122: 11. (C) The stack frame of the function in which this function is
123:
124: 12. (A) goto
125: