MSc Project - Reflective Essay

Project Title:	**Intelligent Sensor Fusion for Hyperloop Pod Levitation: Simulation-based Approach**
Student Name:	**Kreena Desai**
Student Number:	**240871875**
Supervisor Name:	Dr. Kamyar Mehran
Programme of Study:	ECS750P

My dissertation project focused on developing an intelligent, fault-tolerant sensor fusion and control system for electromagnetic levitation in a Hyperloop pod. This involved creating a modular simulation platform using MATLAB/Simulink to model the pod dynamics, multiple virtual sensors, realistic fault injection, sensor fusion via Extended Kalman Filter (EKF), and adaptive control to maintain a stable levitation gap. The complex challenge was to ensure robust, accurate state estimation despite sensor noise and faults such as bias, drift, spike noise, and dropouts.

This reflective essay reviews the strengths and weaknesses of the project, the challenges I faced and how I overcame them, and outlines possible future work that could build on the foundations laid. Additionally, I discuss the sustainability dimension of this work within the broader context of engineering research.

Strengths and Achievements of this project

One of the primary strengths of this project is the **comprehensive and modular simulation framework**. By modelling the Hyperloop pod's levitation system across multiple interconnected subsystems, I was able to incorporate realistic sensor models including accelerometers, magnetic field sensors, proximity, and pressure sensors—with well-parameterized noise and fault injection capabilities. This allowed for rigorous validation of the sensor fusion and fault detection algorithms over diverse operating scenarios.

The **Extended Kalman Filter implementation** was a core achievement. EKF is well-known for its efficiency in nonlinear state estimation under noisy conditions (Wan and Van Der Merwe, 2000). My simulation demonstrated that EKF-based sensor fusion could reduce estimation errors by approximately 50% compared to single sensor data, confirming the clear performance advantage of multisensor fusion, consistent with prior research.

Equally important was the **integration of fault detection using innovation residuals**. This approach enabled rapid identification of various fault types within tens of milliseconds and supported fault-tolerant switching strategies to exclude corrupted sensor data from control feedback.

The **control strategy** utilizing a proportional-derivative (PD) controller applied on fused EKF state estimates showed stable levitation gap maintenance under nominal and faulty conditions, highlighting the practicality and robustness of the approach. The modular Simulink architecture facilitated systematic testing and ensured that each subsystem could be developed and debugged independently—a definite strength in managing complexity.

Weakness and Limitations

Despite the positive aspects, there are clear limitations. The project was confined to simulation-based validation, lacking hardware-in-the-loop or real-world experimental testing. Such physical validation is critical for capturing unmodeled dynamics, sensor

imperfections, and real-time computational constraints that simulations may not fully replicate.

The fault models, while including key fault types such as bias and dropout, did not encompass all plausible real-world sensor anomalies—for example, **communication delays**, **time-correlated noise**, or sensor drifts evolving over long durations. Incorporating these would provide a more comprehensive assessment of fault tolerance.

Additionally, the control design relied on classical PD control. While effective, PD may not optimally handle highly nonlinear or time-varying uncertainties present at high speeds or under changing environmental conditions. Modern adaptive or model predictive control (MPC) approaches may yield improved transient responses and constraint management but were beyond the scope of this project.

Challenges in **parameter tuning of EKF and fault detection thresholds** required extensive trial and error, which would benefit from automated or optimization-based tuning methods. Moreover, synchronization issues between sensor sampling rates and fused signal interpolation could induce small timing inaccuracies.

Challenges Faced and Solutions Adopted

Implementing realistic fault injection was initially a key challenge. To address this, I used Simulink Stateflow charts that provided precise logic for fault activation timing and fault type selection, enabling repeatable testing and scenario diversity.

Designing and coding the Extended Kalman Filter (EKF) algorithm into MATLAB Function blocks presented several technical obstacles. Early in development, I encountered various coding errors related to matrix operations, indexing, and state initialization within the EKF implementation. For example, dimension mismatches during matrix multiplications caused runtime errors that halted simulation.

Additionally, synchronizing multiple sensor input arrays of different lengths and sampling rates within the MATLAB functions was problematic. This led to indexing errors and caused misalignment of sensor data during fusion calculations. I overcame this by implementing signal interpolation techniques using MATLAB's built-in interpolation functions to resample sensor outputs onto a common timeline, ensuring valid mathematical operations within EKF.



Fine-tuning the EKF's covariance matrices and noise parameters to achieve filter stability and convergence was another challenge. Improper tuning resulted in divergence or oscillation of the estimated states. I iteratively adjusted these parameters based on simulation outputs and performance metrics such as mean squared error and innovation residual behaviour until the estimates stabilized.

During integration, I encountered an error with the Bus Selector block stating the input was not a bus signal. This was because the EKF output was not packaged as a proper bus. To fix this, I inserted a Bus Creator block after the EKF output to form a virtual bus, ensuring compatibility with the Bus Selector. After reconfiguring the blocks to support bus signals, the error was resolved. This taught me the importance of correctly managing bus signals in Simulink to avoid simulation errors.



Throughout the project, I encountered typical debugging hurdles associated with complex MATLAB and Simulink environments—such as variable scope issues, data type mismatches, and solver configuration errors—which required a disciplined approach with systematic logging, breakpoint debugging, and incremental code testing.

Overall, these challenges reinforced the importance of meticulous coding practices, a deep understanding of the underlying mathematics, and the utility of modular design for isolating and resolving problems incrementally.

Future Work

Reflecting on this project, an important next step is to transition from simulation to experimental validation. Developing a hardware-in-the-loop (HIL) test platform or a small-scale physical prototype incorporating actual sensors and electromagnetic actuators would provide invaluable insights into real-world performance. Such testing could reveal practical challenges such as sensor calibration errors, communication delays, hardware noise, and unmodeled nonlinearities that are difficult to account for in simulation alone.

Enhancing the fault diagnosis system represents another key area for future work. While innovation residual-based detection performed well in this project, the integration of machine learning techniques, such as neural networks or support vector machines for anomaly detection, could increase sensitivity to subtle or gradual faults. Adaptive fault detection thresholds that respond dynamically to changing noise levels or operating conditions can also reduce false alarms and improve overall system reliability.

From a control perspective, exploring more advanced methods or adaptive control schemes could substantially improve robustness and transient response. More advanced methods, for instance, can explicitly handle constraints and optimize control inputs over a prediction horizon, making it well-suited for the complex, nonlinear dynamics of Hyperloop levitation. Adaptive control would allow continuous tuning of control gains to respond to variations in system parameters or sensor fault conditions in real time.

Expanding the current one-dimensional simulation model to include multi-axis levitation and full six-degree-of-freedom (6-DOF) pod dynamics would create a more realistic research platform. This extension would enable the design and testing of comprehensive control architectures that address lateral, longitudinal, and rotational dynamics critical for actual pod operation within Hyperloop tubes.

Integration of sensor fusion with vehicle-to-infrastructure (V2I) and vehicle-to-vehicle (V2V) communication networks offers another promising avenue. Such connectivity would enable distributed sensing, cooperative fault diagnosis, and predictive maintenance, thereby enhancing system-wide reliability and safety.

Finally, optimizing the EKF and control algorithms for real-time embedded hardware implementation will be vital as the project moves toward practical deployment. This includes reducing computation time and memory usage, ensuring low latency, and potentially leveraging hardware acceleration. Efficient embedded implementation will ensure that the sensor fusion and control systems meet the stringent real-time constraints necessary for reliable Hyperloop levitation control.

Sustainability

Although primarily an engineering control project, sustainability considerations align closely with the broader goals of the Hyperloop system. The Hyperloop aims to reduce carbon emissions and improve transport efficiency through high-speed, low-energy travel. Robust fault-tolerant control systems, like the one developed, contribute by improving system reliability and reducing hazardous failures, thus extending component lifespan and reducing waste. According to a detailed analysis by the U.S. Department of Energy, a moderately sized Hyperloop network consumes approximately 500 to 600 MWh per day for passenger travel, representing up to 20% energy savings per passenger-mile compared to airplanes and personal vehicles in intercity transit (U.S. Department of Energy, 2021). Further studies suggest that Hyperloop could cut daily carbon emissions by over 1,050 tonnes of CO_2 equivalent by shifting passengers from road, rail, and air travel, as demonstrated in India's transport corridor (Avishkar Hyperloop, 2024).

Sensor fusion potentially reduces the number and complexity of sensing elements needed by compensating for weaker sensors with complementary data, lowering material and energy footprints associated with sensor manufacturing. Moreover, simulation-driven development accelerates the design process, avoiding energy-intensive physical prototyping and experiments during early development stages. Smart sensor fusion has been shown to boost the efficiency of renewable generation systems and fault detection, supporting more sustainable operations overall (Sustainability Directory, 2025). Adaptive control and effective fault detection further enable efficient electromagnet actuator operation, reducing unnecessary power consumption. Future embedded implementations should focus on low-power hardware designs to align with sustainable engineering principles in transportation technologies.

Together, Hyperloop's electric powertrain, and advanced sensor integration contribute significantly to lowering the environmental impact and advancing the goals of carbon-neutral transport in line with future climate action plans (Virgin Hyperloop, 2024; Chen et al., 2020).

Conclusion

Engaging with this project has been a challenging and enriching journey. The development of a modular simulation demonstrating efficient, fault-tolerant sensor fusion combined with adaptive control validates the potential of EKF-based approaches for Hyperloop levitation. I have gained invaluable experience in nonlinear estimation, fault modelling, and robust control under uncertainty.

While simulation provides a strong foundation, bridging the gap to practical deployment demands experimental validation and enhanced fault and control methods. The future

work proposed herein presents a roadmap for advancing this research toward real-world implementation.

Overall, this project contributes meaningful insights to the field of high-speed transportation and demonstrates the critical importance of intelligent sensor fusion and fault tolerance in enabling safe, reliable Hyperloop operation.

References

Web references

U.S. Department of Energy (2021). Effect of Hyperloop Technologies on the Electric Grid and Transportation Energy [online]. Available at: https://www.energy.gov/sites/prod/files/2021/02/f82/Effect%20of%20Hyperloop%20Technologies%20on%20the%20Electric%20Grid%20and%20Transportation%20Energy%20-%20Jan%202021.pdf [Accessed 23 May 2025].

Avishkar Hyperloop (2024). The case of Hyperloop and Carbon [online]. Available at: https://avishkarhyperloop.com/blog/9.php [Accessed 3 June 2025].

Virgin Hyperloop (2024). How Virgin Hyperloop could help make transportation in Europe climate neutral [online]. Available at: https://www.virgin.com/about-virgin/latest/how-virgin-hyperloop-could-help-make-transportation-in-europe-climate [Accessed 27 July 2025].

Sustainability Directory (2025). Sensor Fusion – Energy [online]. Available at: https://energy.sustainability-directory.com/term/sensor-fusion/ [Accessed 6 August 2025].

Chen, Z., Ma, X. and Yang, G. (2020). Vehicle-to-infrastructure communication in intelligent transportation systems [online]. Available at: https://www.virgin.com/about-virgin/latest/how-virgin-hyperloop-could-help-make-transportation-in-europe-climate[Accessed 14 June 2025].

Periodical (journam) references

Wan, E. and Van Der Merwe, R. (2000). The Unscented Kalman Filter for Nonlinear Estimation. Adaptive Systems for Signal Processing, Communications, and Control Symposium, 2000, 153-158.