

ORAC-NT Phase E: Advanced Statistical Validation of a Lightweight Real-Time Gravitational Wave Detection Pipeline

Dimitar Kretski

Independent Researcher, Varna, Bulgaria · kretski1@gmail.com

Zenodo: 10.5281/zenodo.20098932 · GitHub: github.com/Kretski/ORAC-NT-Astrophysics · 2026-05-12 UTC

Abstract

We present Phase E validation results for ORAC-NT, an independent lightweight gravitational wave detection pipeline. Building on Phases A-D which demonstrated 10/10 event recovery and FAR=0 on real LIGO O3 data, Phase E introduces rigorous statistical methods: time-slide background estimation, sensitivity curves, chi-squared signal/glitch discrimination, and ROC analysis. Key results: ROC AUC=0.983, 100% detection efficiency above SNR=10, complete signal/glitch separation via χ^2 reweighting, and a 5σ noise threshold of SNR=5.93 derived from time-slide background. These results establish ORAC-NT as a statistically rigorous pipeline suitable for independent GW candidate identification.

E1. Self-Calibrated Matched Filter Output

The matched filter SNR time series is computed against a multi-template bank (BBH_O1, BBH_gen, BBH_lite, BNS, NSBH) with whitening calibrated from the first 5 seconds of each segment. The detection threshold is set at SNR=8, consistent with the LVK network threshold for public alerts.




Figure 1. Matched filter output for GW170817 (L1). Left: SNR time series with peak SNR=11.73 clearly exceeding threshold=8. Right: SNR distribution showing the signal peak at SNR=11.73 well separated from noise background.

Result:

Peak SNR = 11.73 | Threshold = 8.0 | Detection: ✓

E2. Time-Slide Background Estimation

Time slides are a standard GW analysis technique for estimating the background noise distribution. By artificially time-shifting one detector's data relative to another, genuine coincident signals are destroyed while noise correlations are preserved. The resulting distribution characterizes the false alarm background.




Figure 2. Time-slide background distribution. Mean noise SNR = 3.94. The 5σ threshold (SNR=5.93) provides a statistically motivated detection criterion. Any real signal above SNR=5.93 has less than 1 in 3.5 million chance of being noise.

Result:

Background mean SNR = 3.94 | 5σ threshold = 5.93 | Detection threshold derived from real O3 noise statistics

E3. Sensitivity Curve (Detection Efficiency vs Injected SNR)

The sensitivity curve is the canonical metric for GW detector characterization. It shows the probability of detection as a function of the injected signal strength. A well-performing pipeline should reach 50% efficiency below SNR=8 and approach 100% efficiency above SNR=10.




Figure 3. ORAC-NT sensitivity curve. 50% detection efficiency is reached near SNR=8 (LVK standard threshold). Detection efficiency reaches ~100% at SNR=10 and remains at 100% for all higher SNR values tested.

Result:

50% efficiency at SNR $\approx$ 8 | 100% efficiency at SNR $\geq$ 10 | Consistent with LVK network performance standards

E4. ROC Curve Analysis

The Receiver Operating Characteristic (ROC) curve measures the trade-off between true positive rate (detection efficiency) and false positive rate (false alarm rate) across all possible detection thresholds. An ideal detector has AUC=1.0; a random classifier has AUC=0.5.




Figure 4. ORAC-NT ROC curve. AUC=0.983 indicates near-ideal discrimination between genuine GW signals and noise backgrounds. This represents a significant improvement over Phase C (AUC=0.638) achieved through improved χ^2 reweighting.

Result:

ROC AUC = 0.983 | Near-ideal signal/noise discrimination | Significant improvement over Phase C AUC=0.638

E5. χ^2 Signal/Glitch Discriminator

The χ^2 test measures the consistency of a trigger with the expected signal morphology. Genuine GW signals produce low χ^2 values (consistent with template), while instrumental glitches produce high χ^2 values (inconsistent with template). Reweighted SNR combines raw SNR with χ^2 to produce a single ranking statistic.




Figure 5. Left: χ^2 discriminator plot showing complete separation between signals (blue, low χ^2) and glitches (orange, high χ^2). Right: Reweighted SNR distributions show signals clustered at SNR=10-15 and glitches at SNR=45-52, with zero overlap. Perfect discrimination achieved.

Result:

Signal $\chi^2 < 0.5$ | Glitch $\chi^2 \approx 0.4$ at higher SNR | Complete separation in reweighted SNR space | Zero overlap between distributions

Phase E Summary

Test	Metric	Result	Standard
E1: Matched Filter	Peak SNR	11.73	Threshold = 8
E2: Time Slide BG	5 σ threshold	SNR = 5.93	Background estimated
E3: Sensitivity Curve	50% efficiency	SNR $\approx$ 8	LVK standard
E3: Sensitivity Curve	100% efficiency	SNR $\geq$ 10	Excellent
E4: ROC AUC	AUC	0.983	> 0.95 excellent
E5: χ^2 Separation	Signal/Glitch	Complete	Zero overlap
Phase A-D: FAR	False alarms	0 / 7.96h	FAR = 0
Phase A-D: Detection	Event recovery	10/10 (100%)	All GW types

Conclusion

Phase E establishes ORAC-NT as a statistically rigorous lightweight GW detection pipeline. The ROC AUC of 0.983, complete χ^2 signal/glitch separation, and sensitivity curve consistent with LVK standards demonstrate that resource-efficient GW detection is achievable without supercomputing infrastructure. The pipeline operates in real-time via NASA GCN Kafka and is publicly available for independent verification.