

Terry – AI Agent Vector Database Training Data (Qdrant)

This document is used to train an AI Agent (Terry) to infer user intent using a vector database (Qdrant). Each training sentence is embedded and stored as a vector. The payload metadata determines which tool and functionality the agent is allowed to execute.

Qdrant Payload Schema

Each vector point MUST include the following payload fields:

Field	Description
text	User utterance to embed
intent_id	Unique machine-readable intent identifier
intent_name	Human-readable intent name
tool	Tool the agent must use
functionality	Allowed operation
confidence_required	Minimum similarity score to execute

Training Data (Embed the 'text' field)

Text (Embed)	Intent ID	Tool	Functionality
Check if nginx is running	web_server_check	Docker_tool	NGINX + Website check
Is the website up	web_server_check	Docker_tool	NGINX + Website check
Check all machines	machine_status	Machine_status	Ping VMs
Are any hosts down	machine_status	Machine_status	Ping VMs
List files on sftp	sftp_list	Sftp_status	SFTP list
Upload file to sftp	sftp_upload	Sftp_status	SFTP upload
Download file from sftp	sftp_download	Sftp_status	SFTP download
Show local files	local_file_list	Sftp_status	Local ls
Check samba server	samba_list	samba_server_status	Samba list
Upload to samba share	samba_upload	samba_server_status	Samba upload
Is ntp synced	ntp_status	Ntp_sync_check	NTP tracking
Show ntp clients	ntp_clients	Ntp_sync_check	NTP clients

Runtime Inference Logic

1. Embed user message.
2. Query Qdrant (top_k = 1).
3. Compare similarity score with confidence_required.
4. If score is sufficient, route to tool defined in payload.

5. Else respond: I don't know.