

# Patient Community system - example Privacy analysis

## Contents

<b>1</b>	<b>Understanding the architecture</b>	<b>2</b>
<b>2</b>	<b>Privacy analysis</b>	<b>2</b>
2.1	Data Flow Diagram . . . . .	2
2.2	Mapping of threats to DFD . . . . .	2
2.3	Threat elicitation . . . . .	4
2.3.1	Assumptions . . . . .	4
2.3.2	Threats . . . . .	5
	T01 - Profiling PHR data (linking) . . . . .	6
	T02 - Linking PHR data to user data . . . . .	6
	T03 - Identifying a patient from his PHR data . . . . .	7
	T04 - Information disclosure of patient community data . . . . .	7
	T05 - Spoofing a user of the social network system by falsifying credentials . . . . .	8
	T06 - Spoofing a user of the social network system by eavesdropping communication . . . . .	9
	T07 - Spoofing a user of the social network system because of weak credential storage . . . . .	10
	T08 - Disclosure of the transmitted log-in credentials . . . . .	10
	T09 - Disclosure of the transmitted session token . . . . .	11
	T10 - Disclosure of transmitted medical/personal information . . . . .	11
	T11 - Linkability of symptoms sent to external disease service . . . . .	12
	T12 - Identifiability of data sent to external disease service . . . . .	13
	T13 - Disclosure of internal transmitted medical/personal information . . . . .	13
	T14 - Information disclosure internal process . . . . .	14
	T15 - Side channel information disclosure internal process . . . . .	14
	T16 - Non-compliance of employees . . . . .	15
	T17 - Missing user consents . . . . .	16
	T18 - Non-compliance management . . . . .	16
	T19 - User unawareness . . . . .	17
	T20 - content inaccuracy . . . . .	17
2.4	Prioritization of threats . . . . .	19
2.4.1	High priority . . . . .	19
2.4.2	Medium priority . . . . .	19
2.4.3	Low priority . . . . .	20



Table 1

	Threat target	L	I	N	D	D	U	N
Data Store	PHR data (5.1)	×	×	×	×	×		×
	user data (5.2)	×	×	×	×	×		×
Data Flow	patient - portal flow (1 – 5.3)	×	×	×	×	×		×
	portal - patient flow (5.3 – 1)	×	×	×	×	×		×
	researcher - portal flow (2 – 5.4)	×	×	×	×	×		×
	portal - researcher flow (5.4 – 2)	×	×	×	×	×		×
	nurse - portal flow (3 – 5.5)	×	×	×	×	×		×
	portal - nurse flow (5.5 – 3)	×	×	×	×	×		×
	diseases service - browse diseases flow (4 – 5.6)	×	×	×	×	×		×
	browse diseases- diseases service flow (5.6 – 4)	×	×	×	×	×		×
	patient portal - browse diseases flow (5.3 – 5.6)	×	×	×	×	×		×
	browse diseases data - patient portal flow (5.6 – 5.3)	×	×	×	×	×		×
	patient portal - manage PHR flow (5.3 – 5.7)	×	×	×	×	×		×
	manage PHR - patient portal flow (5.7 – 5.3)	×	×	×	×	×		×
	patient portal - consult group PHR flow (5.3 – 5.8)	×	×	×	×	×		×
	consult group PHR data - patient portal flow (5.8 – 5.3)	×	×	×	×	×		×
	researcher portal - PHR data flow (5.4 – 5.1)	×	×	×	×	×		×
	PHR data - researcher portal flow (5.1 – 5.4)	×	×	×	×	×		×
	nurse portal - user data flow (5.5 – 5.2)	×	×	×	×	×		×
	user data - nurse portal flow (5.2 – 5.5)	×	×	×	×	×		×
	manage PHR - PHR data flow (5.7 – 5.1)	×	×	×	×	×		×
	PHR data - manage PHR flow (5.7 – 5.1)	×	×	×	×	×		×
	consult group PHR - PHR data flow (5.8 – 5.1)	×	×	×	×	×		×
	PHR data - consult group PHR flow (5.1 – 5.8)	×	×	×	×	×		×
	consult group PHR - user data flow (5.8 – 5.2)	×	×	×	×	×		×
	user data - consult group PHR flow (5.2 – 5.8)	×	×	×	×	×		×
	patient - authN flow (1 – 5.9)	×	×	×	×	×		×
	authN - patient flow (5.9 – 1)	×	×	×	×	×		×
	researcher - authN flow (2 – 5.9)	×	×	×	×	×		×
	authN - researcher flow (5.9 – 2)	×	×	×	×	×		×
	nurse - authN flow (3 – 5.9)	×	×	×	×	×		×
	authN - nurse flow (5.9 – 3)	×	×	×	×	×		×
	user data - authN flow (5.2 – 5.9)	×	×	×	×	×		×
	authN - user data flow (5.9 – 5.2)	×	×	×	×	×		×
	patient portal - authN flow (5.3 – 5.9)	×	×	×	×	×		×
	authN - patient portal flow (5.9 – 5.3)	×	×	×	×	×		×
	researcher portal - authN flow (5.4 – 5.9)	×	×	×	×	×		×
	authN - researcher portal flow (5.9 – 5.4)	×	×	×	×	×		×
	nurse portal - authN flow (5.5 – 5.9)	×	×	×	×	×		×
	authN - nurse portal flow (5.9 – 5.5)	×	×	×	×	×		×
Process	patient portal (5.3)	×	×	×	×	×		×
	researcher portal (5.4)	×	×	×	×	×		×
	nurse portal (5.5)	×	×	×	×	×		×
	browse diseases (5.6)	×	×	×	×	×		×
	manage PHR (5.7)	×	×	×	×	×		×
	consult group PHR (5.8)	×	×	×	×	×		×
	authN (5.9)	×	×	×	×	×		×
Entity	patient (1)	×	×				×	
	researcher (2)	×	×				×	
	nurse (3)	×	×				×	
	diseases service (4)	×	×				×	

## 2.3 Threat elicitation

### 2.3.1 Assumptions

1. all internal processes are only susceptible to insider threats, as we consider the back-end sufficiently protected against outsider threats. We will therefore combine the process threats and examine only one, as the threats apply to all of them
2. all data flows between internal processes and between internal processes and internal data stores are only susceptible to insider threats, as we consider the back-end sufficiently protected against outsider threats. We will therefore combine the data flow threats and examine only one, as the threats apply to all of them
3. data flows between an entity and a process are not considered trusted (as it involves transactions of an external entity to and from a trusted process over an insecure communication line)
4. data stores are not considered confidential, as no access control system is present
5. No non-repudiation threats exist in the system, as the data flows, processes and data stores do not require plausible deniability
6. detectability is not considered a threat for this specific system. The privacy concerns of this system are all focused on the data itself, not on the detectability of it
7. non-compliance is an important threat, however, it is not specific to one part of the system, but poses to the system as a whole. We will therefore not make a distinction between the different DFD elements for this threat.
8. Identifiability of entities (researchers, nurses, patients or the external service) is not considered a threat, as all entities should have their own unique (long-term) identifier and there is no need to hide the entity's identity. Knowing that an entity is using the community service is not considered an issue.
9. Identifiability of the data flow only poses a threat to one specific data flow:  $5.6 \rightarrow 4$  (browse diseases to external disease services), as the external service should not be able to identify the patient that is using this disease browsing service.
10. Linkability of the data flow to the external disease service ( $5.6 \rightarrow 4$ ) is the only linkability threat to data flows in the patient community system. Although less likely, when the patient identifiers are replaced by pseudonyms, linking the different symptoms (of different searches) together can still result in an identifiability threat
11. Linkability of entities (sensors, cardiologists, nurses, or patients) is not considered a threat, as all entities should have their own unique (long-term) identifier and there is no need to hide the entity's identity. Knowing that an entity is using the community service is not considered an issue.
12. The information the external disease service passes back the the browse disease process does not contain any personal information and should thus not be protected against information disclosure threats
13. The external disease service is not authenticated (as shown in the architecture/DFD) to the back-end system
14. Linkability and identifiability do not pose a threat to the data flows between entities (patient, nurse, and researcher) and (portal) processes because of assumptions 8 and 11
15. Linkability and identifiability do not apply to internal data flows as knowing that 2 requests belong to the same user, or knowing who made "a request" does not violate the patient's privacy. The patient's privacy is only violated when the content of the communication is revealed (information disclosure threat)

16. Linkability and identifiability do not apply to internal processes as knowing that 2 actions belong to the same user does not violate the patient's privacy. The patient's privacy is only violated when the content of the action is revealed (information disclosure threat)
17. Identifiability and linkability are applicable to both data stores, and will therefore be examined in a combined fashion
18. Only spoofing of users (patients, nurses, and researchers) of the portals are considered a privacy threat. Spoofing the external disease service cannot result in information disclosure as the external disease service has no access to the community data.
19. Content unawareness only applies to the patient, as the researcher does not add any information, a nurse only registers patients, and the external disease service does not directly input any data
20. We assume that the data stores are sufficiently protected and that side-channel attacks, extra-monitor and bad storage management are not possible
21. Side channel attacks on data flows are not considered as they are highly-unlikely to occur because they take a lot of analysis and the extracted information is not in correspondence of the effort
22. Internal processes are not susceptible to corruption as we assume processes are implemented correctly and input is sufficiently validated, and memory access is dealt with as well
23. The authentication process is assumed to be well implemented and secure

### **2.3.2 Threats**

## **T01 - Profiling PHR data (linking)**

**Summary:** A researcher or other insider with malicious intent links PHR data or user data

**Primary mis-actor:** unskilled insider (authenticated user, e.g. researcher)

**Basic path:**

- bf1. The misactor performs a set of targeted queries on the PHR data or user data store and retrieves very detailed results
- bf2. The misactor links the results of the queries together (e.g. based on medication which is usually combined, medical conditions which occur together, or pseudo-identifiers like street and age)

**Consequence:** By combining the query results, the misactor has access to more information about the patient than anticipated

**Reference to threat tree node(s):** L<sub>ds2</sub>, L<sub>e2</sub>

**Parent threat tree(s):** L<sub>ds</sub>, L<sub>ds</sub>

**DFD element(s):** 5.1 PHR data, 5.2 user data

**Remarks:**

- r1. This threat can be used as precondition for the identifiability threat at the data store (T03 - Identifying a patient from his PHR data)
- r2. This threat was inspired by L<sub>ds2</sub> and L<sub>e2</sub>, however none of L<sub>e2</sub>'s leaf nodes matched
- r3. The (weak) access requirement (L<sub>ds1</sub>) is fulfilled because the misactor is an “insider” who has access to the database
- r4. Although this threat mainly describes the PHR data case, it also applies to the user data store (assumption 4)

## **T02 - Linking PHR data to user data**

**Summary:** The administrator or other insider with access to both the PHR data store and user data store is able to link the data from both databases (and sell this information to advertisers, insurance companies, etc.)

**Primary mis-actor:** unskilled insider with access to both data stores

**Basic path:**

- bf1. The misactor retrieves information from both the PHR data store and the user data store
- bf2. The misactor links both sets of data (e.g. based on a shared foreign key)

**Consequence:** The combined set of data contains (possibly sensitive) personal identifiable information and especially poses a privacy threat when the misactor sells the information (e.g. to a company selling medication, to the patient's insurance company, etc.)

**Reference to threat tree node(s):** L<sub>ds2</sub>, L<sub>e6</sub>

**Parent threat tree(s):** L\_ds, I\_ds

**DFD element(s):** 5.1 PHR data, 5.2 user data

**Remarks:**

- r1. The L\_ds1 requirement of (weak) access is fulfilled, as this threat only involves insiders who have access to the data stores
- r2. The linkability of entity leaf node L\_e6, indicating linkability based on the user's temporary ID inspired to this data store linkability threat
- r3.

**T03 - Identifying a patient from his PHR data**

**Summary:** A researcher with malicious intent identifies a patient in a set of PHR (or user) data

**Primary mis-actor:** unskilled insider

**Basic path:**

- bf1. The misactor performs a set of targeted queries on the PHR data or user data store and retrieves very detailed results
- bf2. The misactor can extract the identity of the patient from each individual query result because of weak anonymization or he first links several results to each other (T01 - Profiling PHR data (linking), T02 - Linking PHR data to user data) which provides him with identifiable information

**Consequence:** The misactor gains access to the patient's identity although this should have remained secret

**Reference to threat tree node(s):** I\_ds2

**Parent threat tree(s):** I\_ds

**DFD element(s):** 5.1 PHR data, 5.2 user data

**Remarks:**

- r1. This threat was inspired by I\_ds2, however none of the leaf nodes from the entity identifiable tree seemed to match
- r2. Threats T01 - Profiling PHR data (linking) and T02 - Linking PHR data to user data are part of the preconditions of this threat
- r3. The (weak) access requirement (I\_ds1) is fulfilled because the misactor is an "insider" who has access to the database
- r4. Although this threat mainly describes the PHR data case, it also applies to the user data store (assumption 4)

**T04 - Information disclosure of patient community data**

**Summary:** An authenticated user can access personal information of all patients

**Primary mis-actor:** Unskilled insider/ skilled outsider

**Basic path:**

- bf1. The misactor authenticates himself (by using his own valid credentials or by spoofing a user (threats T06 - Spoofing a user of the social network system by eavesdropping communication, T05 - Spoofing a user of the social network system by falsifying credentials, T07 - Spoofing a user of the social network system because of weak credential storage))
- bf2. The misactor gains access to the PHR data and/or user data

**Consequence:** Confidential patient data (5.1) or user registration data (5.2) are exposed to unauthorized users or outsiders

**Reference to threat tree node(s):** ID\_ds7, ID\_ds2

**Parent threat tree(s):** ID\_ds

**DFD element(s):** 5.1 PHR data, 5.2 user data

**Remarks:**

- r1. This threat is applicable to both data stores, as they are both designed in the same way and use the same authentication process (5.9)
- r2. Spoofing a user (T06 - Spoofing a user of the social network system by eavesdropping communication, T05 - Spoofing a user of the social network system by falsifying credentials, T07 - Spoofing a user of the social network system because of weak credential storage) is considered a precondition of this threat
- r3. Assumption 4 states that no access control system is present
- r4. We assume that the data store itself is sufficiently protected which eliminates unencrypted data, side channel attacks (ID\_ds4), extra-monitor access (ID\_ds3) and bad storage management (ID\_ds5) (assumption 20)

#### **T05 - Spoofing a user of the social network system by falsifying credentials**

**Summary:** The misactor obtains user credentials allowing him to log in and access the system

**Primary mis-actor:** skilled outsider

**Basic path:**

- bf1. The misactor gains access to the credentials of a user (by stealing, guessing, phishing, etc.) (S\_8, S\_12, S\_13)
- bf2. The misactor uses the authentic credentials to log in to the system
- bf3. The misactor receives all privileges of the spoofed employee

**Consequence:** Confidential data (patient health information, log-in credentials, etc.) are exposed to outsiders (see threat T04 - Information disclosure of patient community data)

**Reference to threat tree node(s):** S\_8, S\_12, S\_13

**Parent threat tree(s):** ID\_ds, S



**DFD element(s):** 1 patient, 2 researcher, 3 nurse

**Remarks:**

- r1. An authentication system is present in the architecture, which rules out threat S\_4
- r2. The authentication process is considered secure (assumption 23) thus the tampering threat (leaf of S\_3) does not hold, and it does not support null credentials (S\_10) or equivalence (S\_09), downgrade authentication (S\_11) or weak change management (S\_09). Also no key distribution storage is present (S\_14)
- r3. Spoofing due to weak server-side storage is described by T07 - Spoofing a user of the social network system because of weak credential storage
- r4. Spoofing due weak transit is described by T06 - Spoofing a user of the social network system by eavesdropping communication
- r5. Spoofing only applies to patients, nurses, and researchers (assumption 18)

**T06 - Spoofing a user of the social network system by eavesdropping communication**

**Summary:** The misactor obtains user credentials allowing him to log in and access the system

**Primary mis-actor:** skilled outsider

**Basic path:**

- bf1. The misactor gains access to the credentials of a user by eavesdropping the credential communication (threats T08 - Disclosure of the transmitted log-in credentials and T09 - Disclosure of the transmitted session token) (S\_6, S\_7)
- bf2. The misactor uses the authentic credentials to log in to the system
- bf3. The misactor receives all privileges of the spoofed employee

**Consequence:** Confidential data (patient health information, log-in credentials, etc.) are exposed to outsiders (see threat T04 - Information disclosure of patient community data)

**Reference to threat tree node(s):** S\_6, S\_7

**Parent threat tree(s):** L\_ds, S

**DFD element(s):** 1 patient, 2 researcher, 3 nurse

**Remarks:**

- r1. An authentication system is present in the architecture, which rules out threat S\_4
- r2. The authentication process is considered secure (assumption 23) thus the tampering threat (leaf of S\_3) does not hold, and it does not support null credentials (S\_10) or equivalence (S\_09), downgrade authentication (S\_11) or weak change management (S\_09). Also no key distribution storage is present (S\_14)
- r3. Gaining access to the credentials in transit is described by threats T08 - Disclosure of the transmitted log-in credentials and T09 - Disclosure of the transmitted session token
- r4. Spoofing due to falsifying credentials is described in T05 - Spoofing a user of the social network system by falsifying credentials

- r5. Spoofing due to weak credential storage is described in T07 - Spoofing a user of the social network system because of weak credential storage
- r6. Spoofing only applies to patients, nurses, and researchers (assumption 18)

#### **T07 - Spoofing a user of the social network system because of weak credential storage**

**Summary:** The misactor obtains user credentials allowing him to log in and access the system

**Primary mis-actor:** skilled outsider

**Basic path:**

- bf1. The misactor gains access to the credentials of a user by weak credential storage at the server side (threat T04 - Information disclosure of patient community data) (S\_15)
- bf2. The misactor uses the authentic credentials to log in to the system
- bf3. The misactor receives all privileges of the spoofed employee

**Consequence:** Confidential data (patient health information, log-in credentials, etc.) are exposed to outsiders (see threat T04 - Information disclosure of patient community data)

**Reference to threat tree node(s):** S\_8, S\_12, S\_13

**Parent threat tree(s):** ID\_ds, S

**DFD element(s):** 1 patient, 2 researcher, 3 nurse

**Remarks:**

- r1. An authentication system is present in the architecture, which rules out threat S\_4
- r2. The authentication process is considered secure (assumption 23) thus the tampering threat (leaf of S\_3) does not hold, and it does not support null credentials (S\_10) or equivalence (S\_09), downgrade authentication (S\_11) or weak change management (S\_09). Also no key distribution storage is present (S\_14)
- r3. Spoofing due to falsifying credentials is described in T05 - Spoofing a user of the social network system by falsifying credentials
- r4. Spoofing due to communication eavesdropping is described in T06 - Spoofing a user of the social network system by eavesdropping communication
- r5. Spoofing only applies to patients, nurses, and researchers (assumption 18)

#### **T08 - Disclosure of the transmitted log-in credentials**

**Summary:** The misactor gains access to the data flow that contains the credentials used for log-in

**Primary mis-actor:** Skilled outsider

**Basic path:**

- bf1. The misactor gains access to the data flow between the user and the authentication process
- bf2. The misactor intercepts the credentials (username, password) of the user

**Consequence:** The misactor now has access to the user's log-in information and can from now on spoof the user

**Reference to threat tree node(s):** ID\_df4, ID\_df7

**Parent threat tree(s):** ID\_df, S, ID\_ds

**DFD element(s):** patient-authN (1-5.9), nurse-authN (2-5.9), researcher-authN (3-5.9)

**Remarks:**

- r1. This threat is possible as the data flow between the entities and the system is considered insecure (assumption 3)
- r2. Side channel attacks are not considered (assumption 21)

#### **T09 - Disclosure of the transmitted session token**

**Summary:** The misactor gains access to the data flow that contains the session token (which authenticates the user during the entire session)

**Primary mis-actor:** Skilled outsider

**Basic path:**

- bf1. The misactor gains access to the data flow between the authentication process and the user, or between the user and the portal
- bf2. The misactor intercepts the session token of the user

**Consequence:** The misactor can use the session token to spoof the user during the current session

**Reference to threat tree node(s):** ID\_df4, ID\_df7

**Parent threat tree(s):** ID\_df, S, ID\_ds

**DFD element(s):** patient-portal (1-5.3), nurse-portal (2-5.3), researcher-portal (3-5.3), authN-patient (5.9-1), authN-nurse (5.9-2), authN-researcher(5.9-3)

**Remarks:**

- r1. This threat is possible as the data flow between the entities and the system is considered insecure (assumption 3)
- r2. Side channel attacks are not considered (assumption 21)

#### **T10 - Disclosure of transmitted medical/personal information**

**Summary:** The misactor gains access to the transmitted patient information

**Primary mis-actor:** Skilled outsider

**Basic path:**

- bf1. The misactor gains access to the data flow between the user and the portal
- bf2. The misactor intercepts the transmitted personal information

**Consequence:** The misactor has access to sensitive health or personal information

**Reference to threat tree node(s):** ID\_df4, ID\_df7

**Parent threat tree(s):** ID\_df, S, ID\_ds

**DFD element(s):** patient-portal(1-5.3), nurse-portal(3-5.5), portal-patient(5.3-1), portal-nurse(5.5-3), researcher-portal(2-5.4), portal-researcher (5.4-2), browse diseases-disease service (5.6-4)

**Remarks:**

- r1. This threat is possible as the data flow between the entities and the system is considered insecure (assumption 3)
- r2. We do not consider the response of the external disease service as it does not contain personal information (assumption 12)
- r3. Side channel attacks are not considered (assumption 21)

**T11 - Linkability of symptoms sent to external disease service**

**Summary:** The misactor links several requests to the same user and creates a profile of this user

**Primary mis-actor:** unskilled insider (external disease service) /skilled outsider

**Basic path:**

- bf1. The patient searches diseases by providing his symptoms to the patient portal, which forwards the request (including the patient's pseudonym) to the external disease service
- bf2. The misactor intercepts the dataflow (threat T10 - Disclosure of transmitted medical/personal information or is (or has access to) the external disease service
- bf3. The misactor can link several requests to the same patient

**Consequence:** The misactor can build a profile of the patient

**Reference to threat tree node(s):** L\_df1, L\_df8

**Parent threat tree(s):** L\_df

**DFD element(s):** data flow from browse service to external disease service (5.6 → 4)

**Remarks:**

- r1. L\_df1 requires an unprotected data flow, which is currently present (assumption 3) and misactor is receiver, thus assumption always applies
- r2. The different requests are linked, based on the transmitted (temporary/internal) user ID (L\_df8)
- r3. The right branch of the tree (insecure anonymity system (L\_df4)) and the other leaf nodes of the non-anonymous communication branch (L\_df3) are not considered, as it is not the sender (browse service) whose identity should be protected, but the patient, who is not directly part of the data flow

**T12 - Identifiability of data sent to external disease service**

**Summary:** The misactor extracts the patient's identity from the request and links it to the symptoms

**Primary mis-actor:** unskilled insider/skilled outsider

**Basic path:**

- bf1. The patient searches diseases by providing his symptoms to the patient portal, which forwards the request (include the patient's identifiable information (e.g. SSN, address, etc.) to the external disease service
- bf2. The misactor intercepts the dataflow or is (or has access to) the external disease service

**Consequence:** The misactor knows which patient has which symptoms

**Reference to threat tree node(s):** L\_df1, L\_df8

**Parent threat tree(s):** L\_df

**DFD element(s):** data flow from browse service to external disease service (5.6  $\rightarrow$  4)

**Remarks:**

- r1. L\_df1 requires an unprotected data flow, which is currently present (assumption 3) and misactor is receiver, thus assumption always applies
- r2. The different requests are traced back based on the transmitted (temporary/internal) user ID (L\_df8)
- r3. The right branch of the tree (insecure anonymity system (L\_df4)) and the other leaf nodes of the non-anonymous communication branch (L\_df3) are not considered, as it is not the sender (browse service) whose identity should be protected, but the patient, who is not directly part of the data flow

**T13 - Disclosure of internal transmitted medical/personal information**

**Summary:** The misactor gains access to the transmitted patient information

**Primary mis-actor:** Skilled insider (e.g. admin)

**Basic path:**

- bf1. The misactor gains access to the data flow between the user and the authentication process
- bf2. The misactor intercepts the transmitted personal information

**Consequence:** The misactor has access to sensitive health or personal information

**Reference to threat tree node(s):** ID\_df4, ID\_df7

**Parent threat tree(s):** ID\_df, S, ID\_ds

**DFD element(s):** patient-portal(1-5.3), nurse-portal(2-5.3), portal-patient(5.3-1), nurse-patient(2-5.3)

**Remarks:**

- r1. This threat is possible as the data flow between the entities and the system is considered insecure (assumption 3)
- r2. Side channel attacks are not considered (assumption 21)

**T14 - Information disclosure internal process**

**Summary:** The misactor gains access to one of the internal processes

**Primary mis-actor:** authorized insider

**Basic path:**

- bf1. The misactor has the required privileges to access to processes
- bf2. The misactor uses his privileges to access information outside the scope of his job

**Consequence:** The misactor has access to (possibly sensitive) personal identifiable information

**Reference to threat tree node(s):** ID\_p

**Parent threat tree(s):** ID\_p

**DFD element(s):** patient portal (5.3), researcher portal (5.4), nurse portal (5.5), browse diseases (5.6), manage PHR (5.7), consult group PHR (5.8), authN (5.9)

**Remarks:**

- r1. This threat is inspired by “spoofing an entity” leaf threat, however, when an insider has too much privileges, this threat applies as well. Spoofing entities with access to internal processes is not considered, as we assume the system is physically protected (assumption 1)
- r2. We assume processes are not corruptable (assumption 22)
- r3. The side channel attack is described in T15 - Side channel information disclosure internal process

**T15 - Side channel information disclosure internal process**

**Summary:** The misactor gains access to one of the internal processes

**Primary mis-actor:** skilled insider

**Basic path:**

bf1. The misactor performs a side channel attack on one of the internal processes

bf2. The misactor obtains process information

**Consequence:** The misactor has access to (possibly sensitive) personal identifiable information

**Reference to threat tree node(s):** ID\_p2

**Parent threat tree(s):** ID\_p

**DFD element(s):** patient portal (5.3), researcher portal (5.4), nurse portal (5.5), browse diseases (5.6), manage PHR (5.7), consult group PHR (5.8), authN (5.9)

**Remarks:**

r1. The alternative spoofing attack is described in T14 - Information disclosure internal process

r2. We assume processes are not corruptable (assumption 22)

#### **T16 - Non-compliance of employees**

**Summary:** The community service does not process patient data in compliance with legislations or policies

**Primary mis-actor:** insider (employee: admin, nurse, etc.)

**Basic path:**

bf1. The misactor fails to comply with the community's policy or legislation (e.g. the patient's data is revealed to third parties)

**Consequence:** The patient's personal information is shared without his knowledge. When detected, the community service can get fined, and its trustworthy reputation is ruined

**Reference to threat tree node(s):** PN\_2

**Parent threat tree(s):** PN

**DFD element(s):** all (except entities)

**Remarks:**

r1. This threat applies to the entire system, as no individual DFD element is specifically targetted

r2. A similar threat which is posed by the developer is described in T18 - Non-compliance management

r3. A specific non-compliance threat concerning consents is described in T17 - Missing user consents

### **T17 - Missing user consents**

**Summary:** The system did not ask the patient's permission to share part of his (pseudonymized) medical information with his group members

**Primary mis-actor:** Management

**Basic path:**

bf1. The management fails to require patient consents to be included in the user flow

bf2. The user is unable to state his preferences concerning personal data sharing

**Consequence:** The user's medical information (although pseudonymized), will be shared with the patient's group against his will

**Reference to threat tree node(s):** PN\_3

**Parent threat tree(s):** PN

**DFD element(s):** entire (back-end) system (excluding entities)

**Remarks:**

r1. This threat applies to the entire system (assumption 7)

r2. Two general threats which correspond to general non-compliance are described in T16 - Non-compliance of employees and T18 - Non-compliance management

### **T18 - Non-compliance management**

**Summary:** The management fails to request a design and implementation of the system in compliance with legislation

**Primary mis-actor:** Management

**Basic path:**

bf1. The misactor fails to require a system that is legally compliant (either he is unaware of the legislation or he consciously decides to ignore it)

bf2. The patient data is not processed or collected in accordance to (privacy) legislation

**Consequence:** The patient's personal information is shared without his knowledge. When detected, the community service can get fined, and its trustworthy reputation is ruined

**Reference to threat tree node(s):** PN\_2

**Parent threat tree(s):** PN

**DFD element(s):** all (except entities)



**Remarks:**

- r1. This threat applies to the entire system, as no individual DFD element is specifically targetted
- r2. A similar threat which is posed by the employees when the system is up-and-running is described in T16 - Non-compliance of employees
- r3. A specific non-compliance threat concerning consents is described in T17 - Missing user consents

**T19 - User unawareness**

**Summary:** The user is unaware of the consequences of sharing information (e.g. by sharing too much information even anonymized data can reveal the user's identity)

**Primary mis-actor:** Management

**Basic path:**

- bf1. The management fails to add as requirement the need of notifications and warnings when the patients intends to upload sensitive and/or identifiable content (e.g. picture of his broken arm which also shows his face)
- bf2. The user adds information to the system which can easily identify him (e.g. a picture of himself) as he is unaware of the consequences
- bf3. Group members retrieve information and can still identify the "pseudonymized" user

**Consequence:** When group members retrieve information, the identifiable information is returned. The user's privacy is thus violated as he assumes that his information stays confidential and his identity will not be revealed.

**Reference to threat tree node(s):** U\_1

**Parent threat tree(s):** U

**DFD element(s):** 1 patient

**Remarks:**

- r1. This threat only applies to the patient (assumption 19)
- r2. The threat concerning inaccurate user information is described in T20 - content inaccuracy

**T20 - content inaccuracy**

**Summary:** The user failed to update his medical information or administrative information

**Primary mis-actor:** Management

**Basic path:**

- bf1. The management fails to indicate the need of a notification that warns the user of the importance of up-to-date and accurate information
- bf2. The user provides inaccurate or incomplete medical information or fails to update old information

**Consequence:** The user himself or users from his group consult the user's inaccurate medical information and deduce the wrong conclusion (e.g. user claims he got better by taking medication X, while he actually took medication Y)

**Reference to threat tree node(s):** U\_3, U\_4

**Parent threat tree(s):** U

**DFD element(s):** 1. patient

**Remarks:**

- r1. This threat only applies to the patient (assumption 19)
- r2. The threat concerning users providing too much information is described in T19 - User unawareness

## 2.4 Prioritization of threats

This section provides an list of the threats (ID + title) of the previous section. The order is based on the threat's risk (likelihood \* impact). You should make a distinction between high, medium, and low risk and, if possible, within each category also order the threats according to their risk. Also, you should briefly explain why you ordered the threats in this particular order.

### 2.4.1 High priority

- T04 - Information disclosure of patient community data
- T03 - Identifying a patient from his PHR data
- T08 - Disclosure of the transmitted log-in credentials
- T09 - Disclosure of the transmitted session token
- T10 - Disclosure of transmitted medical/personal information
- T05 - Spoofing a user of the social network system by falsifying credentials
- T07 - Spoofing a user of the social network system because of weak credential storage
- T06 - Spoofing a user of the social network system by eavesdropping communication

Information disclosure of data (both medication data and patient data) is the most important threat as it violates the patient's privacy the most (the patient uses this system under the assumption that his information is kept confidential).

Also identifiability of stored PHR data has high priority as it should be assured that only the patient himself can access his own identifiable information and group members should not be able to identify the patient from his shared, de-identified medical data.

Information disclosure of transmitted data also poses a high risk, but less than information disclosure of the data store, as the data flow only reveals part of the information.

Finally, spoofing is considered high-priority. Even though spoofing is security threat, it can result in information disclosure of stored information, which has the highest risk.

### 2.4.2 Medium priority

- T12 - Identifiability of data sent to external disease service
- T11 - Linkability of symptoms sent to external disease service
- T01 - Profiling PHR data (linking)
- T02 - Linking PHR data to user data
- T18 - Non-compliance management
- T17 - Missing user consents
- T19 - User unawareness

Linkability and identifiability of the symptoms sent to the external disease service can violate the patient's privacy as they can reveal a certain disease. However, the threats are only considered medium risk as there is still some plausible deniability (as the patient might have been looking up a disease for a friend or relative).

Linking PHR data (to other PHR data or th user data) only poses a real threat when the linking actual leads to identification. Therefore, linkability on its own is only considered medium risk.

Non-compliance of the system in general, and missing consents and user unawareness specifically, will result in a violation of the patients' privacy. However, the management are considered knowledgeable and at least aware of the consequences of ignoring legislation. Also, even though officially a system is non-compliant, it is still possible that the general legislation concepts are present.

### 2.4.3 Low priority

- T16 - Non-compliance of employees
- T20 - content inaccuracy
- T14 - Information disclosure internal process
- T13 - Disclosure of internal transmitted medical/personal information
- T15 - Side channel information disclosure internal process

Information inaccuracy is considered low risk, as inaccurate data can indeed lead to false conclusions, the patient community system is mainly focused on peer-information and in practice, no important decisions will be made based on these data.

The internal process and data flow threats are considered low priority as there is a trust relation with the employees. Most likely there is also a non-disclosure agreement in their contract with associated consequences (fine, fired, etc.) Non-compliance of employees is considered low risk for the same reason as the internal processes and data flows. Given the trust relationship between the employees and the company, it is less likely that they will violate the rules.