



香港中文大學(深圳)
The Chinese University of Hong Kong, Shenzhen



Ack: Prof. Jignesh Patel @ CMU
Prof. Andy Pavlo @CMU

CSC3170

9: Index Concurrency Control

Chenhao Ma

School of Data Science

The Chinese University of Hong Kong, Shenzhen

Observation

- We (mostly) assumed all the data structures that we have discussed so far are single-threaded.
- But a DBMS needs to allow **multiple threads** to safely access data structures to take advantage of additional CPU cores and hide disk I/O stalls.

Observation

- We (mostly) assumed all the data structures that we have discussed so far are single-threaded.
- But a DBMS needs to allow **multiple threads** to safely access data structures to take advantage of additional CPU cores and hide disk I/O stalls.



They Don't Do This!

VOLTDB



redis



H-Store

Concurrency Control

- A **concurrency control** protocol is the method that the DBMS uses to ensure “correct” results for concurrent operations on a shared object.
- A protocol’s correctness criteria can vary:
 - **Logical Correctness:** Can a thread see the data that it is supposed to see?
 - **Physical Correctness:** Is the internal representation of the object sound?

Concurrency Control

- A **concurrency control** protocol is the method that the DBMS uses to ensure “correct” results for concurrent operations on a shared object.
- A protocol’s correctness criteria can vary:
 - **Logical Correctness:** Can a thread see the data that it is supposed to see?
 - **Physical Correctness:** Is the internal representation of the object sound?

This Lecture

- Latches Overview
- Hash Table Latching
- B+Tree Latching
- Leaf Node Scans

Latches

Locks vs. Latches

- **Locks (Transactions)**

- Protect the database's logical contents from other transactions.
- Held for transaction's duration.
- Need to be able to rollback changes.

- **Latches (Workers)**

- Protect the critical sections of the DBMS's internal data structure from other workers (e.g., threads).
- Held for operation duration.
- Do not need to be able to rollback changes.

Locks vs. Latches

	<i>Locks</i>	<i>Latches</i>
Separate...	Transactions	Workers (threads, processes)
Protect...	Database Contents	In-Memory Data Structures
During...	Entire Transactions	Critical Sections
Modes...	Shared, Exclusive, Update, Intention	Read, Write
Deadlock	Detection & Resolution	Avoidance
...by...	Waits-for, Timeout, Aborts	Coding Discipline
Kept in...	Lock Manager	Protected Data Structure

Source: [Goetz Graefe](#)

Locks vs. Latches

<i>Locks</i>		<i>Latches</i>
Separate...	Transactions	Workers (threads, processes)
Protect...	Database Contents	In-Memory Data Structures
During...	Entire Transactions	Critical Sections
Modes...	Shared, Exclusive, Update, Intention	Read, Write
Deadlock	Detection & Resolution	Avoidance
...by...	Waits-for, Timeout, Aborts	Coding Discipline
Kept in...	Lock Manager	Protected Data Structure

Source: [Goetz Graefe](#)

Locks vs. Latches

Future
Lecture



Locks

Separate...	Transactions
Protect...	Database Contents
During...	Entire Transactions
Modes...	Shared, Exclusive, Update, Intention
Deadlock	Detection & Resolution
...by...	Waits-for, Timeout, Aborts
Kept in...	Lock Manager

Latches

Workers (threads, processes)
In-Memory Data Structures
Critical Sections
Read, Write
Avoidance
Coding Discipline
Protected Data Structure

Source: [Goetz Graefe](#)

Latch Modes

- **Read Mode**

- Multiple threads can read the same object at the same time.
- A thread can acquire the read latch if another thread has it in read mode.

- **Write Mode**

- Only one thread can access the object.
- A thread cannot acquire a write latch if another thread has it in any mode.

Latch Modes

- **Read Mode**

- Multiple threads can read the same object at the same time.
- A thread can acquire the read latch if another thread has it in read mode.

- **Write Mode**

- Only one thread can access the object.
- A thread cannot acquire a write latch if another thread has it in any mode.

Compatibility Matrix

	Read	Write
Read	✓	X
Write	X	X

Latch Implementation Goals

- Small memory footprint.
- Fast execution path when no contention.
- Deschedule thread when it has been waiting for too long to avoid burning cycles.
- Each latch should not have to implement their own queue to track waiting threads.

Source: [Filip Pizlo](#)

Latch Implementations

- Test-and-Set Spinlock
- Blocking OS Mutex
- Reader-Writer Locks
- Advanced approaches:
 - Adaptive Spinlock ([Apple ParkingLot](#))
 - Queue-based Spinlock ([MCS Locks](#))

Latch Implementations

- **Approach #1: Test-and-Set Spin Latch (TAS)**
 - Very efficient (single instruction to latch/unlatch)
 - Non-scalable, not cache friendly, not OS friendly.
 - Example: `std::atomic<T>`

Latch Implementations

- **Approach #1: Test-and-Set Spin Latch (TAS)**
 - Very efficient (single instruction to latch/unlatch)
 - Non-scalable, not cache friendly, not OS friendly.
 - Example: `std::atomic<T>`

```
std::atomic_flag latch;  
:  
while (latch.test_and_set(...)) {  
    // Retry? Yield? Abort?  
}
```

Latch Implementations

- **Approach #1: Test-and-Set Spin Latch (TAS)**
 - Very efficient (single instruction to latch/unlatch)
 - Non-scalable, not cache friendly, not OS friendly.
 - Example: `std::atomic<T>`

`std::atomic<bool>`


```
std::atomic_flag latch;  
:  
while (latch.test_and_set(...)) {  
    // Retry? Yield? Abort?  
}
```

Latch Implementations

- **Approach #1: Test-and-Set Spin Latch (TAS)**
 - Very efficient (single instruction to latch/unlatch)
 - Non-scalable, not cache friendly, not OS friendly.
 - Example: `std::atomic<T>`

`std::atomic<bool>`

```
std::atomic_flag latch;  
:  
while (latch.test_and_set(...)) {  
    // Retry? Yield? Abort?  
}
```




Latch Implementations

- **Approach #1: Test-and-Set Spin Latch (TAS)**
 - Very efficient (single instruction to latch/unlatch)
 - Non-scalable, not cache friendly, not OS friendly.
 - Example: `std::atomic<T>`

`std::atomic<bool>`

```
std::atomic_flag latch;  
:  
while (latch.test_and_set(...)) {  
    // Retry? Yield? Abort?  
}
```



Latch Implementations

- **Approach #2: Blocking OS Mutex**
 - Simple to use
 - Non-scalable (about 25ns per lock/unlock invocation)
 - Example: `std::mutex`

Latch Implementations

- **Approach #2: Blocking OS Mutex**
 - Simple to use
 - Non-scalable (about 25ns per lock/unlock invocation)
 - Example: `std::mutex`

```
std::mutex m;  
:  
m.lock();  
// Do something special...  
m.unlock();
```

Latch Implementations

- **Approach #2: Blocking OS Mutex**
 - Simple to use
 - Non-scalable (about 25ns per lock/unlock invocation)
 - Example: `std::mutex` → `pthread_mutex`

```
std::mutex m;  
:  
m.lock();  
// Do something special...  
m.unlock();
```

Latch Implementations

- **Approach #2: Blocking OS Mutex**
 - Simple to use
 - Non-scalable (about 25ns per lock/unlock invocation)
 - Example: `std::mutex` → `pthread_mutex` → `futex`

```
std::mutex m;  
:  
m.lock();  
// Do something special...  
m.unlock();
```


Latch Implementations

- **Approach #2: Blocking OS Mutex**
 - Simple to use
 - Non-scalable (about 25ns per lock/unlock invocation)
 - Example: `std::mutex` → `pthread_mutex` → `futex`

```
std::mutex m;  
:  
m.lock();  
// Do something special...  
m.unlock();
```


 *OS Latch* *Userspace Latch*

Latch Implementations

- **Approach #2: Blocking OS Mutex**
 - Simple to use
 - Non-scalable (about 25ns per lock/unlock invocation)
 - Example: `std::mutex` → `pthread_mutex` → `futex`

```
std::mutex m;  
:  
m.lock();  
// Do something special...  
m.unlock();
```


 *OS Latch*
 *Userspace Latch*



Latch Implementations

- **Approach #2: Blocking OS Mutex**
 - Simple to use
 - Non-scalable (about 25ns per lock/unlock invocation)
 - Example: `std::mutex` → `pthread_mutex` → `futex`


```
std::mutex m;  
:  
m.lock();  
// Do something special...  
m.unlock();
```



Latch Implementations

- **Approach #2: Blocking OS Mutex**
 - Simple to use
 - Non-scalable (about 25ns per lock/unlock invocation)
 - Example: `std::mutex` → `pthread_mutex` → `futex`


```
std::mutex m;  
:  
m.lock();  
// Do something special...  
m.unlock();
```



Latch Implementations

- **Approach #2: Blocking OS Mutex**
 - Simple to use
 - Non-scalable (about 25ns per lock/unlock invocation)
 - Example: `std::mutex` \longrightarrow `pthread_mutex` \longrightarrow `futex`

```
std::mutex m;  
:  
m.lock();  
// Do something special...  
m.unlock();
```



Latch Implementations

- **Approach #3: Reader-Writer Latches**
 - Allows for concurrent readers. Must manage read/write queues to avoid starvation.
 - Can be implemented on top of spinlocks.
 - Example: `std::shared_mutex`

Latch Implementations


- **Approach #3: Reader-Writer Latches**
 - Allows for concurrent readers. Must manage read/write queues to avoid starvation.
 - Can be implemented on top of spinlocks.
 - Example: `std::shared_mutex` → `pthread_rwlock`

Latch Implementations

- **Approach #3: Reader-Writer Latches**

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock`


Latch



Latch Implementations

- **Approach #3: Reader-Writer Latches**


- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock`



Latch Implementations

- **Approach #3: Reader-Writer Latches**


- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock`



Latch Implementations

- **Approach #3: Reader-Writer Latches**


- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock`



Latch Implementations

- **Approach #3: Reader-Writer Latches**


- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock`



Latch Implementations

- **Approach #3: Reader-Writer Latches**


- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock`



Latch Implementations

- **Approach #3: Reader-Writer Latches**


- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock`



Latch Implementations

- **Approach #3: Reader-Writer Latches**


- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock`



Latch Implementations

- **Approach #3: Reader-Writer Latches**


- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock`



Latch Implementations

- **Approach #3: Reader-Writer Latches**

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock`



Compare-and-Swap

- Atomic instruction that compares contents of a memory location **M** to a given value **V**
 - If values are equal, installs new given value **V'** in **M**
 - Otherwise, operation fails


M

20

```
__sync_bool_compare_and_swap(&M, 20, 30)
```


Compare-and-Swap

- Atomic instruction that compares contents of a memory location **M** to a given value **V**
 - If values are equal, installs new given value **V'** in **M**
 - Otherwise, operation fails



Compare-and-Swap

- Atomic instruction that compares contents of a memory location **M** to a given value **V**
 - If values are equal, installs new given value **V'** in **M**
 - Otherwise, operation fails



Hash Table Latching


Hash Table Latching

- Easy to support concurrent access due to the limited ways threads access the data structure.
 - All threads move in the same direction and only access a single page/slot at a time.
 - Deadlocks are not possible.
- To resize the table, take a global write latch on the entire table (e.g., in the header page).

Hash Table Latching


- **Approach #1: Page/Block-level Latches**
 - Each page/block has its own reader-writer latch that protects its entire contents.
 - Threads acquire either a read or write latch before they access a page/block.
- **Approach #2: Slot Latches**
 - Each slot has its own latch.
 - Can use a single-mode latch to reduce meta-data and computational overhead.

Hash Table - Page/Block Latches




Hash Table - Page/Block Latches


T_1 : Find D
hash(D)



Hash Table - Page/Block Latches




Hash Table - Page/Block Latches




Hash Table - Page/Block Latches

T_1 : Find D
hash(D)



Hash Table - Page/Block Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

Hash Table - Page/Block Latches


T_1 : Find D
hash(D)




T_2 : Insert E
● *hash(E)*

Hash Table - Page/Block Latches

T_1 : Find D
hash(D)




T_2 : Insert E
hash(E)




Hash Table - Page/Block Latches


T_1 : Find D
hash(D)




T_2 : Insert E
hash(E)




Hash Table - Page/Block Latches



Hash Table - Page/Block Latches




Hash Table - Page/Block Latches




Hash Table - Page/Block Latches

T_1 : Find D
 $hash(D)$




T_2 : Insert E
 $hash(E)$




Hash Table - Page/Block Latches

T_1 : Find D
hash(D)




T_2 : Insert E
hash(E)



Hash Table - Page/Block Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

Hash Table - Page/Block Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

Hash Table - Page/Block Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

Hash Table - Page/Block Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

Hash Table - Page/Block Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

Hash Table - Page/Block Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

Hash Table – Slot Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)


Hash Table – Slot Latches

T_1 : Find D
 $hash(D)$




T_2 : Insert E
 $hash(E)$

Hash Table – Slot Latches



Hash Table – Slot Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

Hash Table – Slot Latches


T_1 : Find D
 $hash(D)$



T_2 : Insert E
 $hash(E)$

Hash Table – Slot Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)


Hash Table – Slot Latches

T_1 : Find D
hash(D)




T_2 : Insert E
hash(E)

Hash Table – Slot Latches



Hash Table – Slot Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

Hash Table – Slot Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

Hash Table – Slot Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

Hash Table – Slot Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

Hash Table – Slot Latches


T_1 : Find D
hash(D)



T_2 : Insert E
hash(E)

Hash Table – Slot Latches

T_1 : Find D
hash(D)




T_2 : Insert E
hash(E)

B+Tree Concurrency Control


B+Tree Concurrency Control

- We want to allow multiple threads to read and update a B+Tree at the same time.
- We need to protect against two types of problems:
 - Threads trying to modify the contents of a node at the same time.
 - One thread traversing the tree while another thread splits/merges nodes.


B+Tree Multi-Threaded Example




B+Tree Multi-Threaded Example




B+Tree Multi-Threaded Example




B+Tree Multi-Threaded Example




B+Tree Multi-Threaded Example




B+Tree Multi-Threaded Example




B+Tree Multi-Threaded Example




B+Tree Multi-Threaded Example




B+Tree Multi-Threaded Example




B+Tree Multi-Threaded Example




B+Tree Multi-Threaded Example




B+Tree Multi-Threaded Example




B+Tree Multi-Threaded Example



B+Tree Multi-Threaded Example



B+Tree Multi-Threaded Example




Latch Crabbling/Coupling

- Protocol to allow multiple threads to access/modify B+Tree at the same time.
 - Get latch for parent
 - Get latch for child
 - Release latch for parent if “safe”
- A **safe node** is one that will not split or merge when updated.
 - Not full (on insertion)
 - More than half-full (on deletion)


Latch Crabbling/Coupling

- **Find:** Start at root and traverse down the tree:
 - Acquire **R** latch on child,
 - Then unlatch parent.
 - Repeat until we reach the leaf node.
- **Insert/Delete:** Start at root and go down, obtaining **W** latches as needed. Once child is latched, check if it is safe:
 - If child is safe, release all latches on ancestors


Example #1 – Find 38




Example #1 – Find 38




Example #1 – Find 38




Example #1 – Find 38




Example #1 – Find 38




Example #1 – Find 38




Example #1 – Find 38




Example #1 – Delete 38




Example #1 – Delete 38




Example #1 – Delete 38




Example #1 – Delete 38




Example #1 – Delete 38




Example #1 – Delete 38




Example #1 – Delete 38




Example #1 – Delete 38




Example #1 – Delete 38




Example #1 – Delete 38




Example #1 – Insert 45




Example #1 – Insert 45




Example #1 – Insert 45




Example #1 – Insert 45




Example #1 – Insert 45




Example #1 – Insert 45




Example #1 – Insert 45




Example #1 – Insert 45




Example #1 – Insert 25




Example #1 – Insert 25




Example #1 – Insert 25




Example #1 – Insert 25




Example #1 – Insert 25




Example #1 – Insert 25




Example #1 – Insert 25



Example #1 – Insert 25



Example #1 – Insert 25






Observation

- What was the first step that all the update examples did on the B+Tree?


Observation

- What was the first step that all the update examples did on the B+Tree?



Observation


- What was the first step that all the update examples did on the B+Tree?



- Taking a write latch on the root every time becomes a bottleneck with higher concurrency.

Better Latching Algorithm


- Most modifications to a B+Tree will not require a split or merge.
- Instead of assuming that there will be a split/merge, optimistically traverse the tree using read latches.
- If you guess wrong, repeat traversal with the pessimistic algorithm.




Better Latching Algorithm

- **Search:** Same as before.
- **Insert/Delete:**
 - Set latches as if for search, get to leaf, and set **W** latch on leaf.
 - If leaf is not safe, release all latches, and restart thread using previous insert/delete protocol with write latches.
- This approach optimistically assumes that only leaf node will be modified; if not, **R** latches set on the first pass to leaf are wasteful.


Example #2 – Delete 38




Example #2 – Delete 38




Example #2 – Delete 38




Example #2 – Delete 38




Example #2 – Delete 38




Example #2 – Delete 38



Example #2 – Insert 25




Example #2 – Insert 25



Observation


- The threads in all the examples so far have acquired latches in a “top-down” manner.
 - A thread can only acquire a latch from a node that is below its current node.
 - If the desired latch is unavailable, the thread must wait until it becomes available.
- But what if threads want to move from one leaf node to another leaf node?

Leaf Node Scan Example #1




Leaf Node Scan Example #1

T_1 : Find Keys < 4




Leaf Node Scan Example #1




Leaf Node Scan Example #1

T_1 : Find Keys < 4




Leaf Node Scan Example #1

T_1 : Find Keys < 4




Leaf Node Scan Example #1

T_1 : Find Keys < 4




Leaf Node Scan Example #1

T_1 : Find Keys < 4




Leaf Node Scan Example #2



T_1 : Find Keys < 4

T_2 : Find Keys > 1


Leaf Node Scan Example #2




T_1 : Find Keys < 4

T_2 : Find Keys > 1


Leaf Node Scan Example #2



Leaf Node Scan Example #2




Leaf Node Scan Example #2




Leaf Node Scan Example #2

T_1 : Find Keys < 4


T_2 : Find Keys > 1




Leaf Node Scan Example #2




Leaf Node Scan Example #2




Leaf Node Scan Example #2



Leaf Node Scan Example #3




Leaf Node Scan Example #3



T_1 : Delete 4

T_2 : Find Keys > 1


Leaf Node Scan Example #3



T_1 : Delete 4

T_2 : Find Keys > 1


Leaf Node Scan Example #3




T_1 : Delete 4

T_2 : Find Keys > 1


Leaf Node Scan Example #3




Leaf Node Scan Example #3




Leaf Node Scan Example #3




Leaf Node Scan Example #3




Leaf Node Scan Example #3




Leaf Node Scan Example #3



Leaf Node Scan Example #3



Leaf Node Scan Example #3



Leaf Node Scans

- Latches do not support deadlock detection or avoidance. The only way we can deal with this problem is through coding discipline.
- The leaf node sibling latch acquisition protocol must support a “no-wait” mode.
- The DBMS’s data structures must cope with failed latch acquisitions.

Conclusion

- Making a data structure thread-safe is notoriously difficult in practice.
- We focused on B+Trees, but the same high-level techniques are applicable to other data structures.

Next Lecture

- We are finally going to discuss how to execute some queries...