



香港中文大學(深圳)  
The Chinese University of Hong Kong, Shenzhen



# CSC3170

## Tutorial 2

School of Data Science

The Chinese University of Hong Kong, Shenzhen

# Outline

- Views
  - Nested Views
- Authorization
  - Roles

# Views

- Motivation: Sometimes, it is not desirable for all users to see the entire relation.
  - Example: a certain staff working at cuhksz can view the basic information of instructors, but not their salary.

Actual Relation

id	name	department	title	salary	address
----	------	------------	-------	--------	---------

Visible Relation

id	name	department	title
----	------	------------	-------

- View: provides a mechanism to hide certain data from certain users

# Views

- Definition:

**create view v as** <query expression>

where <query expression> is any legal SQL expression.

Actual Relation

id	name	department	title	salary	address
----	------	------------	-------	--------	---------

Visible Relation

id	name	department	title
----	------	------------	-------

- A view of instructors:

**create view** faculty **as**

**select** id, name, department, title  
**from** instructor

- Find all instructors in SDS:

**select** name

**from** faculty

**where** department = 'SDS'

# Views

- Practice: create a view of department salary totals (department, total\_salary)

instructor

id	name	department	title	salary	address
----	------	------------	-------	--------	---------

# Views

- Practice: create a view of department salary totals (department, total\_salary)

instructor

id	name	department	title	salary	address
----	------	------------	-------	--------	---------

```
create view dept_salary_totals as  
  select department, sum(salary) as total_salary  
  from instructor  
  group by department
```

# Nested Views

- We can define a view  $v2$  based on another view  $v1$ .

customers 

customer_id	customer_name	city
-------------	---------------	------

orders 

order_id	customer_id	product_id	quantity	date
----------	-------------	------------	----------	------

products 

product_id	product_name	price
------------	--------------	-------

- Step 1: we need a view that shows the order details for each customer.

**create view** customerOrderDetailsView **as**

**select** c.customer\_id, c.customer\_name, o.order\_id, o.product\_id, o.quantity

**from** customers c

**join** orders o **on** c.customer\_id = o.customer\_id;

# Nested Views

- We can define a view *v2* based on another view *v1*.

customerOrderDetailsView

customer_id	customer_name	order_id	product_id	quantity
-------------	---------------	----------	------------	----------

products	product_id	product_name	price
----------	------------	--------------	-------

- Step 2: we need a view that shows the total amount of each customer's order.

**create view** customerOrderSummaryView **as**

**select** cod.customer\_id, cod.customer\_name, cod.order\_id, p.product\_name,  
cod.quantity, (cod.quantity \* p.price) **as** total\_amount

**from** customerOrderDetailsView cod

**join** products p **on** cod.product\_id = p.product\_id;



# Nested Views

- Advantages of nested views:

- Simplification of Complex Queries

What will happen if we directly create the second view (customerOrderSummaryView) ?

**create view** customerOrderSummaryView **as**

**select** cod.customer\_id, cod.customer\_name, cod.order\_id, p.product\_name,  
cod.quantity, (cod.quantity \* p.price) **as** total\_amount

**from** (**select** cod.customer\_id, cod.customer\_name, cod.order\_id, p.product\_name,  
cod.quantity, (cod.quantity \* p.price) **as** total\_amount

**from** customerOrderDetailsView cod

**join** products p **on** cod.product\_id = p.product\_id) cod

**join** products p **on** cod.product\_id = p.product\_id;

# Nested Views

- Advantages of nested views:
  - Simplification of Complex Queries
  - Data Security (Permission Management)
  - Dynamic (Always returns real-time result)
  - Readability

# Authorization

- We may assign a user several forms of authorization (privilege):
  - Read (select), Insert (insert), Update (update), Delete (delete), All Privileges (all)
- Example: a certain staff working at cuhksz can view the basic information of instructors, but not their salary.

faculty

id	name	department	title
----	------	------------	-------

- Confer Authorization: **grant** <privilege list> **on** <relation / view> **to** <user list>  
**grant** select **on** faculty **to** staffA: staffA can run “select” statement on faculty
- Revoke Authorization: **revoke** <privilege list> **on** <relation / view> **to** <user list>

# Roles

- Problem: we may need to assign a group of user a certain privilege.
  - Example: 50 staffs in HR department can access *faculty*  
**grant select on faculty to** staff1, staff2, ..., staff50  
what if we want to revoke the privilege?
- A role is a way to distinguish among various users as far as what these users can access/update in the database.
- Create a role: **create role** <name>
- Assign a user to a role: **grant** <role> **to** <users>  
**grant select on faculty to** hr\_department

# Reminder

1. Due date of As1 is 9.28 23:59.
2. The website cannot be accessed outside the school. Please connect to the campus network to open the website.  
[https://oj.cuhk.edu.cn/d/csc3170\\_2025\\_fall/](https://oj.cuhk.edu.cn/d/csc3170_2025_fall/)
3. After you login the OJ, it will automatically go to the main site, so you need manually copy the whole link again.
4. When you submit your solution (Q4 – Q23), you just need to write the SQL query (that is, **do not add the table creation and record insertion code** anymore)

# Q&A

Thanks to the previous CSC3170 teaching team from which part of the content was sourced.