

MAT 3007 Optimization Final Review

Yuang Chen

School of Data Scienc
The Chinese University of Hong Kong, Shenzhen

July 21, 2025

Final Exam Logistics

- Time and Date: 1:30 - 4:30 pm, July 24 (Thursday)
- Shaw F301 (different from your midterm, seat assignment will be posted soon.)
- Closed-book, closed-notes, no internet, no calculators, no electronics
- Two cheat sheets (double-sided) are allowed.
- 7 problems, 100 points total

- Problem 1 IP Modeling (15 pts)
- Problem 2 Branch-and-Bound Algorithm (10 pts)
- Problem 3 Optimality Conditions (15 pts)
- Problem 4 Convexity (15 pts)
- Problem 5 KKT Conditions (15 pts)
- Problem 6 Algorithms (15 pts)
- Problem 7 Short Answers (15 pts)

Problem 1 Modeling (15 points)

If $f(x_1, x_2, \dots, x_n) > a$, then $g(x_1, x_2, \dots, x_n) \geq b$.

$$\begin{cases} f(x_1, x_2, \dots, x_n) \leq a + My \\ g(x_1, x_2, \dots, x_n) \geq b - M(1 - y) \\ y \in \{0, 1\} \end{cases}$$

Either $f(x_1, x_2, \dots, x_n) \leq a$ or $g(x_1, x_2, \dots, x_n) \leq b$

$$\begin{cases} f(x_1, x_2, \dots, x_n) \leq a + My \\ g(x_1, x_2, \dots, x_n) \leq b + M(1 - y) \\ y \in \{0, 1\} \end{cases}$$

Problem 1 Modeling (15 pts)

- (a) x_i for $i = 1, 2, 3$ are continuous nonnegative variables. Write a set of constraints to model the requirement that:

$$|2x_1 - x_2 - x_3| \geq 2$$

by introducing an additional binary variable.

- (b) x_1 and x_2 are integer variables. Write a set of constraints to model the requirement that: either $x_1 + x_2 \leq 10$ or $2x_1 - x_2 \geq 5$ but not both by introducing an additional binary variable.
- (c) If at least 3 of 4 events are selected from events A, B, C, D, then no more than 2 of 3 events can be selected from events E, F, G.

Problem 2 Branch-and-Bound Algorithm (10 pts)

Consider the following knapsack problem:

$$\begin{aligned} &\text{maximize} && 13x_1 + 7x_2 + 9x_3 + 3x_4 \\ &\text{subject to} && 5x_1 + 3x_2 + 4x_3 + 2x_4 \leq 10 \\ &&& x_1, x_2, x_3, x_4 \in \{0, 1\}. \end{aligned}$$

Use the branch-and-bound method to solve it (draw the branch-and-bound tree and mark the results on each node).

Problem 3 Optimality Conditions (15 pts)

Consider the function $f_\alpha : \mathbb{R}^2 \rightarrow \mathbb{R}$,

$$f_\alpha(x) := \alpha x_1^2 + x_2^2 - 2x_1x_2 - 2x_2,$$

where $\alpha \in \mathbb{R}$ is a scalar.

- (a) Find the stationary points (in case they exist) of f_α for each value of α .
- (b) For each stationary point x^* in part (a), determine whether x^* is a local maximizer or a local minimizer or a saddle point of f_α .
- (c) For which values of α can f_α have a global minimizer?

Problem 4 Convexity (15 pts)

- Verify whether the following set is convex or not:

$$X = \{x \in \mathbb{R} : \alpha \leq \sqrt{x} \leq \beta\}, \quad \alpha \in \mathbb{R}, \quad \beta \geq 0, \quad \alpha \leq \beta.$$

- Verify $f(x) := \frac{1}{2}\|Ax - b\|_2^2 + \mu\|Lx\|_\infty$ is a convex function or not, where $\|\cdot\|_\infty$ denotes the maximum norm.
- Verify $f(x) := \frac{1}{2}\|Ax - b\|_2^2 + \mu\|Lx\|_\infty + \lambda\|Qx\|_0$ is a convex function or not, where $\|\cdot\|_\infty$ denotes the maximum norm, $\|x\|_0$ counts the number of non-zero elements in x .
- Verify $f(x_1, x_2) = -\ln x_1 - \ln x_2$ is convex or not on the interval $\{(x_1, x_2) : x_1 \geq 0, x_2 \geq 0\}$.

Problem 5 KKT Conditions (15 pts)

Consider the problem

$$\begin{aligned} \min_{x \in \mathbb{R}^2} \quad & 4x_1^2 + x_2^2 - x_1 - 2x_2 \\ \text{s.t.} \quad & 2x_1 + x_2 \leq 1, \quad x_1^2 \leq 1. \end{aligned}$$

- (a) Show the above problem is a convex optimization problem.
- (b) Show that Slater's condition is satisfied for the above problem.
- (c) Derive the KKT conditions for the above problem and find all KKT points.
- (d) Does this problem have a unique global solution? Briefly explain your answer!

Problem 6 Algorithm (15 pts)

Let us consider the following least-squares optimization problem:

$$\min_{x \in \mathbb{R}^n} f(x) := \|Ax - b\|^2, \quad (1)$$

where $A \in \mathbb{R}^{m \times n}$ and $b \in \mathbb{R}^m$ are given.

- (a) Suppose that $A^\top A \in \mathbb{R}^{n \times n}$ has full rank and we apply Newton's method for solving problem (1). We start from some $x^0 \in \mathbb{R}^n$. Compute the first iterate x^1 using Newton's method. What property does x^1 have?
- (b) Suppose that $m \geq 2$. In this case, the mapping f in (1) can be written as $f(x) = \sum_{i=1}^m f_i(x)$ with $f_i(x) = (a_i^\top x - b_i)^2$, where $a_i^\top \in \mathbb{R}^{1 \times n}$ is the i -th row of A and b_i is the i -th element of b . Assume that $x^k = 0 \in \mathbb{R}^n$ at the k -th iteration. Is $-\nabla f_i(x^k)$ always a descent direction of f at x^k ? If yes, justify your answer. If no, provide a suitable counterexample.

Problem 6 Algorithm (15 pts)

(c) Let A and b be given via

$$A = \begin{bmatrix} 1 & 0 \\ 0 & \frac{1}{2} \end{bmatrix}, \quad b = \begin{bmatrix} 1 \\ 2 \end{bmatrix}.$$

Suppose that we apply the gradient descent method for solving problem (4) for this specific choice of A and b . We use backtracking line search with parameters $\sigma, \gamma \in (0, 1)$ for choosing the step size α_k . Assume that $x^k = (0, 0)^\top$ at the k -th iteration. What is the range of γ so that $\alpha_k = 1$ will be chosen by the line search procedure?

Remark: Backtracking line search procedure is to determine the step size α_k as the largest element in $\{1, \sigma^2, \sigma^3, \dots\}$ such that

$$f(x^k + \alpha_k d^k) - f(x^k) \leq \gamma \alpha_k \nabla f(x^k)^\top d^k.$$

Problem 7 Short Answer Questions (15 pts)

- Three question (5 pts each). Two of them will be something we discussed in class.
- What are the update equations in each iteration for gradient descent and Newton's method for a maximization problem?
- Is Lagrangian dual problem always a convex optimization problem?
- Given the class's notations, if x^* , λ^* , and μ^* are optimal solutions to the primal and dual problems and satisfy the KKT conditions, does this imply that the primal problem must be a convex optimization problem?

- Thank you for taking the optimization class with me this semester!
- People often say CUHK-Shenzhen is an "OR university" because we have many outstanding professors conducting cutting-edge research in operations research.
- CUHK-Shenzhen offers many advanced optimization courses through the School of Data Science. Optimization also plays a key role in fields such as machine learning, statistics, computer algorithms, automatic control, signal processing, energy systems, financial engineering, and more.
- Good luck with your future studies at CUHK-Shenzhen! I am the director of the DSBDT program in the School of Data Science. If you have any questions about the major, I'm always happy to help.