

SKILL 2 OSSP

KRISH SUREJA

1. NANO SIMPLECOMMANDLOOP.C

```
#include <stdio.h>
#include <unistd.h>
#include <string.h>

int main()
{
    char command[100];

    while(1)
    {
        printf("2520030181_SHELLFORGE$");

        fgets(command, sizeof(command), stdin);

        command[strcspn(command, "\n")] = '\0';

        if(strcmp(command, "exit") == 0)
            break;

        printf("you entered %s \n", command);
    }

    return 0;
}
```

OUTPUT :

```
nano 01phat.c
nano simplecommandloop.c
gcc simplecommands.c -o commands
gcc simplecommandslloop.c -o commands
gcc simplecommandloop.c -o command
nano simplecommandloop.c
ls
gcc simplecommandloop.c -o simple
nano simplecommandloop.c
gcc simplecommandloop.c -o simple
nano simplecommandloop.c
gcc simplecommandloop.c -o simple
```

2. ORPHAN.C

GNU nano 8.7.1

```
#include <stdio.h>
#include <unistd.h>

int main()
{
    pid_t pid = fork();

    if (pid > 0)
    {
        printf("Parent Process Exiting\n");
        return 0;
    }
    else
    {
        sleep(5);
        printf("Child PID = %d\n", getpid());
        printf("New Parent PID = %d\n", getppid());
    }

    return 0;
}
```