

SQL to MongoDB Mapping

SQL	MongoDB
CREATE TABLE lju (id MEDIUMINT NOT NULL AUTO_INCREMENT, user_id Varchar(20),age Number, status char(1), PRIMARY KEY (id))	db.createCollection ("lju") creates collection no need to define schema
ALTER TABLE lju ADD join_date DATETIME	db.lju.updateMany({ }, { \$set: { join_date: new Date() } }) Note: new Date().toLocaleDateString()-The toLocaleDateString() method returns the date (not the time) of a date object as a string, using locale conventions.
ALTER TABLE lju DROP COLUMN join_date	db.lju.updateMany({ }, { \$unset: { "join_date": "" } })
DROP TABLE lju	db.lju.drop()
INSERT INTO lju (name, age, status) VALUES ("Test", 45, "A")	db.lju.insertOne({ name: "Test", age: 18, status: "A" })
SELECT *FROM lju	db.lju.find()
SELECT id, name FROM lju	db.lju.find({ }, { name:1 })
SELECT name, status FROM lju	db.lju.find({ }, { name:1,status:1,_id: 0 })
SELECT * FROM lju WHERE status ="A"	db.lju.find({ status: "A" })

SQL to MongoDB Mapping

SELECT name FROM lju WHERE status = "A"	db.lju.find({ status: "A" }, { name: 1, _id: 0 })
SELECT * FROM lju WHERE status != "A"	db.lju.find({ status: { \$ne: "A" } })
SELECT * FROM lju WHERE status = "A" AND age = 50	db.lju.find({status:"A",age:50}) or db.lju.find({ \$and: [{ status: "A" }, { age: 50 }] })
SELECT * FROM lju WHERE status = "A" OR age = 30	db.lju.find({ \$or: [{ status: "A" }, { age: 30 }] })
SELECT * FROM lju WHERE age > 25	db.lju.find({ age: { \$gt: 25 } })
SELECT * FROM lju WHERE age <= 25	db.lju.find({ age: { \$lte: 25 } })
SELECT * FROM lju WHERE age > 25 AND age <= 50	db.lju.find({ age: { \$gt: 25, \$lte: 50 } })
SELECT * FROM lju WHERE name like "%abc%"	db.lju.find({ name: { \$regex: /abc/ } }) or db.lju.find({ name: { \$regex: /abc/ } })
SELECT * FROM lju WHERE name like "abc%"	db.lju.find({ name: /^bc/ }) or db.lju.find({ name: { \$regex: /^abc/ } })
SELECT * from lju where name="abc" and age=20	db.lju.find({name:"abc",age:20})
SELECT * FROM lju WHERE status = "A" ORDER BY age ASC	db.lju.find({ status: "A" }).sort({ age: 1 })
SELECT * FROM lju WHERE status = "A" ORDER BY age DESC	db.lju.find({ status: "A" }). sort({ age: -1 })

SQL to MongoDB Mapping

SELECT COUNT(*) FROM lju	db.lju. count() or db. lju. find(). count()
SELECT COUNT(*) FROM lju WHERE age > 30	db.lju.count({ age: { \$gt: 30 } }) or db.lju.find({ age: { \$gt: 30 } }).count()
SELECT * FROM lju LIMIT 1	db.lju.findOne()or db.lju.find().limit(1)
SELECT * FROM lju LIMIT 2 OFFSET 3;	db.lju.find().limit(2).skip(3)
EXPLAIN SELECT * FROM lju WHERE status = "A"	db.lju. find({ status: "A" }).explain()
UPDATE lju SET status = "C" WHERE age > 25	db.lju.updateMany({ age: { \$gt: 25 } }, { \$set: { status: "C" } })
UPDATE lju SET age = age + 3 WHERE status = "A"	db.lju.updateMany({ status: "A" } , { \$inc: { age: 3 } }
DELETE FROM lju WHERE status = "D"	db.lju.deleteMany({ status: "D" })
DELETE FROM lju	db.lju.deleteMany({ })
SELECT * FROM lju WHERE name NOT IN ('aaa','abc','bbb');	db.lju.find({ name: { \$nin: ['aaa','abc','bbb'] } })
SELECT name FROM lju WHERE age IN (20,23,33);	db.lju.find({ age: { \$in: [20, 23, 33] } ,{name:1,_id:0})