

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
Chapter-7									
243	7	Correct the following code : function App() { const abc="Hello"; return (<div className="App"> <h1 style={{backgroundColor:"red"}}> Friends {2+2} </h1> <Example frame=abc age="30"/> </div>); } export default App;	<pre>{} missing at : <Example frame={abc} age="30"/></pre>	1		Quotes missing at : <Example "frame"= abc "age"="30"/>	\$ missing at : <h1 style={{backgroundColor:"red"}}> Friends \${2+2} </h1>	Quotes missing at : <h1 style={{"backgroundColor":"red"}}> Friends {2+2} </h1>	<pre>{} missing at : <Example frame={abc} age="30"/></pre>
244	7	What output will be generated by following program. Example.js import React from 'react' const Example = (Props)=>{ return({Props.Name} : {Prop.Price}) } export default Example; App.js import Example from "./Example"; function App() { return (<Example Name="Mobile" Price="20000" />);}export default App;	It will give an error regarding prop	1		Mobile : 20000	Mobile 20000	It will give an error regarding prop	Nothing will be printed.
245		Which command is used to create a React app using Vite?	npm create vite@latest myApp	1		npx create-react-app myApp	npm init react-app	npm create vite@latest myApp	vite create react
246		One key advantage of Vite over traditional bundlers is:	Faster development server startup	1		Slower startup time	Faster development server startup	Built only for backend projects	No support for modern frameworks
247		What is Vite mainly used for?	Frontend build tool and development server	1		Database management	Frontend build tool and development server	used for operating system features	none of these
248	7	What will be the output of following program? import React from 'react'; function App() { const handleClick = () => { alert ("Welcome to LJU"); } return (<center> <button onClick={handleClick}>Click me</button> </center>) }; } export default App;	It will show an alert box once page will be loaded for first time, and it will perform nothing while clicking on button	1	LJU-2023	By clicking on click me button it will show an alert box	It will show an alert box once page will be loaded for first time, and it will perform nothing while clicking on button	It will perform nothing	It will show an error.
249	7	What will be the correct syntax to perform any fuction on double click in REACT?	<pre><button onDoubleClick = {doubleClickHandler}>Double Click here</button></pre>	1		<pre><button oubleClick = {doubleClickHandler()}>Double Click here</button></pre>	<pre><button ondoubleClick = {doubleClickHandler}>Double Click here</button></pre>	<pre><button onDoubleClick = {{doubleClickHandler}}>Double Click here</button></pre>	<pre><button onDoubleClick = {doubleClickHandler}>Double Click here</button></pre>
250	7	Which of the following port is the default where react server runs?	3000	0.5		8080	3000	3030	3080
251	7	What are arbitrary inputs of components in react also known as?	Props	0.5		elements	Props	Ref	Keys
252	7	Select correct syntax to render output with "LJU" heading and textfield.	<pre><div></div> <h1>LJU</h1> <input type="text" className="demo"/> </></pre>	1		<pre><div></div> <h1>LJU</h1> <input type="text" className="demo"/> <div></div></pre>	<pre><div></div> <h1>LJU</h1> <input type="text" className="demo"/> </></pre>	<pre><div></div> <h1>LJU</h1> <input type="text" className="demo"> </></pre>	<pre><h1>LJU</h1> <input type="text" className="demo"/></pre>
253	7	What will be the output of the following program? const x = 9; let text = "Welcome"; x = 10; if (x <= 10) { text = "Welcome To LJU"; } return ({text})	Error will be generated	1		Welcome To LJU	Error will be generated	Welcome	x=10

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
254	7	Correct syntax to write Arrow function Msg = ____ "Hi, there!";	() =>	0.5		> () =	() =>	() =	> () =>
255	1	Identify error/output in following code of App.js file. const arr=[10,20,30,40,50]; let sum=0; return({ arr.map(v) => { sum=sum+v; return sum = {sum} } });	Sum is printed correctly for each iteration in <h1> tag	1	LJU-2023	error, since sum=sum+v statement must be specified using JSX	Sum is printed correctly for each iteration in <h1> tag	error, since let sum=0 statement is specified at wrong place	sum is printed as "NaN" for each iteration in<h1> tag
256	7	Which is the correct syntax to get output of expression between HTML tags	const a=1; const b=1; return({a+b})	1		const a=1; const b=1; return({{a+b}})	const a=1; const b=1; return({a+b})	const a=1; const b=1; return({{(a+b)}})	const a=1; const b=1; return([a+b])
257	7	What will be the output of the following program? App.js import Example from './Example'; function App() { const Info = { name: "ABC" }; return (<div><h1>What is your name?</h1><Example name={ Info }></div> </div>); } export default App; ----- Example.js import React from 'react' function Example(props) { return(<h2>My name is { props.name.name }!</h2> </div>); }; export default Example;	What is your name? My name is ABC!	1		What is your name?	What is your name? My name is ABC!	My name is ABC!	Error will be generated
258	7	What will be the output of below program? App.js import {BrowserRouter,Route,Routes} from "react-router-dom"; import contact from './Contact' function App() { return (<div> <Navbar> <BrowserRouter> <Routes> <Route exact path="/Contact" element={}<contact > } /> </Routes> </BrowserRouter> </div> </div>); } export default App	SyntaxError	1		It will give an error as <BrowserRouter> tag is used in place of <Router> tag.	SyntaxError	It will run properly	It will not throw an error but wont display anything.
259	7	How many numbers of elements a valid react component can return?	1	0.5		Multiple	1	Not more than two	Null
260	7	What is the declarative way to render a dynamic list of components based on values in an array?	Using the Array.map() method	0.5		Using the reduce array method	Using the <Each /> component	Using the Array.map() method	With a for/while loop
261	7	In which of the following directory React.js components can be saved?	Inside the src folder	0.5		Inside the vendor folder	Inside the src folder	Inside the public folder	Inside the node modules
262	7	What will be the output of the following code? App.js import Example from './Example'; function App() { return (<div className="App"> <Example frame="A" + " B" + " C"/> </div> </div>); } export default App; ----- Example.js import React from 'react' const Example = (props) => { return (<div> <h1>Friends:{props.frame}</h1> </div> </div>); } export default Example	Error will be generated	1		Error will be generated	Friends : A B C	Friends:ABC	Friends:A+B+C

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
263	7	What will be the output of following code? App.js import Example from './Example'; function App() { const abc="LJU"; return (<div className="App"> <Example frame={abc} age="30"/> </div>);}export default App; Example.js import React from 'react' const Example = (p) => { return (<div> <h1>{p.frame}</h1> <h1 style={{backgroundColor:"blue"}}>age</h1> </div>);}export default Example	LJU age	1	LJU Display "age" with blue background color	LJU Display "30" with blue background	LJU 30	LJU age	
264	7	How to write comments in JSX?	{/* */}	0.5	{/* */}	{*/ /*}	{/* */}	{/* */}	
265	7	What will be the output of following code. New.js import React from 'react'; import img1 from './P.jpg'; import img2 from './R.jpg'; const New = () => { const images=[{ id:1,pic:img1 }, {id:1,pic:img2}]; return ({images.map((val) => { return () }}));}export default New App.js import New from './New'; function App() { return (<New />);}export default App;	2 Images will be displayed vertically on browser.	1	It will display 2 images side by side on browser	It will only display first image on browser	2 Images will be displayed vertically on browser.	It will only display last image on browser.	
266	7	Consider following code for App.js file. Identify error/output. function App(){ return(This is Demo1 This id Demo2); }export default App;	Error as JSX fragment tag must required	1	This is Demo1 This is Demo2	This is Demo1	This id Demo2	Error as JSX fragment tag must required	
267	7	Consider following code in App.js file and Example.js file. Identify error/output import Example from './Example'; function App() {const obj= { type:"car",models:["i10","i20","Grandi10"] } } const string=JSON.stringify(obj); return(<Example name={obj}/>); export default App; Example.js const Example = (props)=>{ return({props.name.type}) }export default Example	"car" is printed successfully by referring props.name.type	1	"car" is printed successfully by referring props.name.type	Error as props.name.type is invalid use of props to refer type	Error since type must be fetched by passing "string" rather than "obj"	Error as JSON object can not be passed to other component i.e. "Example"	
268	7	What will following code do? const arr=['A','B','C','a','b'] const newArr=arr.filter((value)=> { if(value===value.toUpperCase()) return false; else return true; })	Returns array having only small letters	1	Returns array having only capital letters	Returns empty array	Returns array having only small letters	Error as not proper use of ' toUpperCase()	

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
269	7	Fill the blanks in following code to generate proper output. New.js import React from 'react'; import img1 from './P.jpg'; import img2 from './R.jpg'; const New = () => { const images=[{ id:1,pic:img1 },{id:2,pic:img2}]; return ({_____map(val) => { return ()} }) }; export default New;	images_src={val.pic}	1		images, src={{{val.pic}}}	img_src={val}	images,src={-val.pic}	img.src=""val.pic"
270	7	What will be the output of the following code : const arr=["a","java","Full Stack","567","Python"]; return (map function { arr.map(value)>> {return array values= {value.toUpperCase()} }}))	map function array values= A array values= JAVA array values= FULL STACK array values= 567 array values= PYTHON	1		map function array values= A array values= JAVA array values= FULL STACK array values= 567 array values= PYTHON	A JAVA FULL STACK 567 PYTHON	Error:567 can't be added in list	Error:all inputs should be of type in array
271	7	Identify correct statement to apply CSS on a paragraph. The CSS is given as below. const css= { color:"cyan", textAlign:"center", backgroundColor:"red" }	<p style={css}>This is my data</p>	0.5		<p style={{css}}>This is my data</p>	This is my data	<p style={css}>This is my data</p>	<p style=[css]>This is my data</p>
272	7	Identify error/output for following code. const arr=[10,2,30,3,50]; const newArr=arr.filter(v=>=> { if(v%10===0) { return false; } else { return true; } }) let arr1=newArr.join(",") function Form1() { return ({arr1}) }	2,3	0.5		10,30,50	10	10,2,30,3,50	2,3
273	7	Identify correct code to change CSS,attributes of a paragraph & text on double click.	function changeCssAttr(e) { e.target.innerHTML="Thanks buddy"; e.target.style.fontFamily="times new roman"; e.target.align="center"; } return (<p onDoubleClick={changeCssAttr}>This is my para</p> </>)	1		function changeCssAttr(e) { e.target.value="Thanks buddy"; e.target.style.fontFamily="times new roman"; e.target.align="center"; } return (<p onDoubleClick={changeCssAttr}>This is my para</p> </>)	function changeCssAttr(e) { e.target.value="Thanks buddy"; e.target.style.font-family="times new roman"; e.target.align="center"; } return (<p onDoubleClick={changeCssAttr}>This is my para</p> </>)	function changeCssAttr(e) { e.target.innerHTML="Thanks buddy"; e.target.style.font-family="times new roman"; e.target.align="center"; } return (<p onDoubleClick={changeCssAttr}>This is my para</p> </>)	function changeCssAttr(e) { e.target.innerHTML="Thanks buddy"; e.target.style.fontFamily="times new roman"; e.target.align="center"; } return (<p onDoubleClick={changeCssAttr}>This is my para</p> </>)
274	7	What will be the output of below program? App.js import {Router,Route,Routes,Link} from "react"; import CA from './CA' function App() { return (<Router> <Routes> <Route path="/"CA" element={ <CA/> }/> </Routes> </Router>) }export default App	Cause of error is Router/Route/Routes/Link is imported from react	1	LJU 2023	It will give an error as <BrowserRouter> tag is not used	Reached at the end- no executable code	It will run properly	Cause of error is Router/Route/Routes/Link is imported from react
275	7	In ReactJS, to filter an array of objects named "dataArray" based on a specific condition, which of the following options shows the correct syntax?	dataArray.filter(item => item.id === 1)	1	LJU 2023	dataArray.filter(item => item.id === 1)	this.filterData(dataArr, item => item.id === 1)	filterData(dataArr, item => item.id === 1)	this.state.dataArr.filter(item => item.id === 1)

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)	
--	--

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
276	7	In a React application, a parent component ParentComponent is passing a prop called username to its child component ChildComponent. Which of the following options correctly accesses and displays the username prop in the ChildComponent?	{props.username}	1	LJU 2023	{this.props.uname}	{props.username}	{username}	{props}
277	7	Which of the following represents the correct syntax for rendering a React component named "Button" with JSX in ReactJS?	<Button></Button>	0.5	LJU 2023	<Button></Button>	render(Button)	React.render(Button)	React.createElement(Button)
278	7	Complete the array method that will allow you to run a function on each item in the array and return a new array. const myList = myArray._____((item) => {item})	map	0.5		execute	apply	map	iterate
279	7	What is the correct syntax to write an expression in JSX?	{ expression }	0.5		{{ expression }}	<{ expression }>	{ expression }	# { expression }
280	7	Which of the following options correctly represents JSX syntax in a React functional component?	Hello, World!	0.5		Hello, World!	React.createElement("div", "Hello, World!")	("div", "Hello, World!")	div: "Hello, World!"
281	7	Which of the following is used to access a function display() from h1 element in JSX?	{display()}	0.5		{{display}}	{'display'}	{display()}	{display()}
282	7	Which event handler in React is used to handle a form submission in a functional component?	onSubmit	0.5		onFormSubmit	onSubmitForm	onSubmit	handleFormSubmit
283	7	Identify error/output in following code of App.js file. const arr=["apple", "banana", "kiwi", "orange"]; const result = arr.filter((fruit) => { if(fruit.length > 5) { return true;} else { return false; } }); var arr1=result.join(",") return ({arr1})	Output:banana,orange	1		Output: apple,kiwi	Error: The filter function should have a closing parenthesis.	Output:banana,orange	Error: JSX elements should be returned within a single parent element.
284	7	Which syntax is commonly used for defining a route in React using react-router-dom?	<Route path="/about" element= {<About />} />	1		<Route path="/about" element=About />	<Route url="/about" element={About} />	<Route path="/about" element= {<About />} />	<Route path="/about"><About /></Route>
285	7	Give the correct output. import React from 'react'; const App = () => { const name = "John"; const age = 30; return (<h1>Hello, {name}</h1> <p>You are {age} years old.</p> - age > 18 ? - You are an adult : - You are a minor } </div>); }; export default App;	Hello, John! and "You are 30 years old." with an unordered list item "You are an adult"	1		Hello, John! and "You are 30 years old." with an unordered list item "You are an adult"	Hello, John! and "You are 30 years old." with an unordered list item "You are a minor"	An error will occur due to incorrect syntax in the JSX	Nothing will be displayed on the screen
286	7	Consider following code in App.js file and Program.js file. Identify error/output. App.js const obj1= {Name:"Hiyan",Age:32,Branch:["CSE","CE","IT"]} const str = JSON.stringify(obj1); return(<Program Name={obj1} />); Program.js const Program=(props)=>{ return({props.Name.Branch[0]});	CSE will be printed on browser in <h1> tag	1	LJU-2023	CSE will be printed on browser in <h1> tag	Prints entire JSON object including all members	Error: Value not initialized	CE will be printed on browser in <h1> tag
287	7	Identify error/output in following code of App.js file. function App() { const a="Hello"; const b=8; return (<div className="App"> <h1 style={{backgroundColor:"green"}}> The addition is: {a+2+b} </h1> </div>); } export default App;	Output:"The addition is: Hello28" with green background color in <h1> tag	1	LJU-2023	Output:"The addition is: Hello10" with green background color in <h1> tag.	Output:"The addition is: Hello28" with green background color in <h1> tag	Output:"The addition is: 28Hello" with green background color in <h1> tag	Error: "value not initialized"

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
288	7	What will be the output of following code? function map1() { let arr = [2, 4, 6, 3, 7, 5] const val = arr.sort(); return (Output: { arr.map((value)=>{ const val = value + 3 + "2" return ({val}) })})}export default map1	Output: 52 62 72 82 92 102	1	102 92 82 72 62 52	7 9 11 8 12 10	Output: 52 62 72 82 92 102	232 432 632 332 732 532	
289	7	Random numbers stored as an array named "arr", how can you use the 'filter' method to get only even numbers in output?	arr.filter(num => num % 2 === 0)	1		arr.filter(num => num % 2 === 0)	arr.filter(num => num % 2 !== 0)	arr.filter(num => num.isEven())	arr.filter(num => num % 2 === 1)
290	7	Identify Correct CSS syntax in below code for mystyle to get proper output. function App(){ const mystyle= ?? return (<div> <h1 style={mystyle}>Demo1</h1> </div>)} export default App;	{fontSize:"40px", color:"green", textTransform:"uppercase"}	1	font-Size:"40px", color:"green", text-Transform:"uppercase"	{font-Size:"40px", color:"green", text-Transform:"uppercase"}	{fontSize:"40px", color:"green", textTransform:"uppercase"}	fontSize:"40px", color:"green", textTransform:"uppercase"	
291	7	Which of the following is not an incorrect statement/s regarding react. 1.React components are composed to create a user interface with only webpack. 2.All React components must act like recursive functions with respect to their props. 3.map() function is a callback function that is called once for each element in the array. 4.First file loaded by the browser in a basic React project is index.js 5.React's virtual DOM is A library that handles asynchronous operations in React applications.	Only 3	1	1,2,3	3,5	3,4,5	Only 3	
292	7	What do you call the message wrapped in curly braces below? let message = "Welcome to LJU"; const element = {message} ;	a JS expression	0.5		a JS function	a JS expression	a JS event	a JS property
293	7	What will be the output of the following JSX code? <button onClick={() => alert("Button clicked!")}>Click me</button>	A button with the text "Click me" that triggers an alert when clicked.	1		A warning about the missing onClick handler.	A syntax error due to the arrow function syntax.	A button with the text "Click me" that triggers an alert when clicked.	A button is not clickable.
294	7	What will be the output of the following code: import React from 'react'; export function App() { const arr = [10, 20, 30, 40, 50]; return (< {arr.map((v, index) => { let s = index * 5; return <h3 key={index}>s = {s}</h3>; })} </>;)} }	s = 0 s = 5 s = 10 s = 15 s = 20	1	s = 0 s = 1 s = 2 s = 3 s = 4	s = 0 s = 5 s = 10 s = 15 s = 20	s = 10 s = 20 s = 30 s = 40 s = 50	s = 50 s = 100 s = 150 s = 200 s = 250	
295	7	In a React form, which event is typically used to handle changes in an input field?	onChange	1		onChange	onSubmit	onClick	onInputhere
296	7	Build basic react app that display "Hello World" in browser.		3					
297	7	Create an ReactJS app which shows the how to pass and read data using props		3					
298	7	Write a React code to print car's brand name and its model name which are passed as props using JSON.		4					
299	7	Write react js script to display alert box with text "Welcome to LJ.U" by clicking on button.		3					

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
300	7	Write react js script to display values in console while changing it in text box.		4					
301	7	Write react js script to display alert box with text "welcome to lju" only on double click button		3					
302	7	Create react app to perform tasks as asked. First create files as asked below in routing folder 1. Home.js - for the home page content 2. Shop.js - for the shop page content 3. Contact.js - for the contact page content 4. Nopage.js - for the page other than mentioned links Create Main.js file which contains Links for Home, Shop and Product page. Also, add functionality of page routing. Finally call Main.js in App.js.		4					
303	7	Create React app to pass student name, roll number, t1 marks and t2 marks of 2 students to component and read the information and display in table format. Use Props.		5					
304	7	Create react app and use routing functionality of react to perform the tasks as asked. Create one file named Main.js which contains links for home and about page and routing functionality. In Home.js file add one image and heading(h1) "LJ University" In About.js file add branch list (CSE,IT,CE).		5					
305	7	Write a ReactJS code in which we have apply filter to skip digits which are less than "10" from the array and display all remaining digits of the array [3,5,11,4,17,8,21,2,26,13,8]. Pass values as props.		4					
306	7	Create React app to pass color(red), background color(yellow), font size(25px) and font style(italic) as properties to component and apply css to "Lj Students" text written in p tag. use Props		4					
307	7	Write react js script to perform the tasks as asked below. Add an array of objects which contains name and age of people. Apply filter to find people with age less than 40. And display name of all people using map function. Use props.		4	LJU-2023				
308	7	Write react js script to perform the tasks as asked below. Add an array of objects which contains name and branch(CSE,IT,CE) of students. Apply filter to find students who are from CSE branch. And display name of all students of CSE branch using map function.		5					
309	7	Create react app and use routing functionality of react to perform the tasks as asked. Create one file named Main.js which contains links for React Js, Node Js and Express Js and routing functionality. Create components for each links and add heading "React JS","Node JS" and "Express JS" in component files Ex1.js, Ex2.js and EX3.js respectively.		4					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
310	7	Create a React app to perform tasks as asked using functional component: 1)Create a React Router that includes three routes: Home, Food Items, and Contact and implement navigation between these routes. 2)Create a route that displays a Home page, Food Items details page and Contact details page. 3) When a user clicks on Home page it should navigate to the home page and display "Welcome to LJU" in bold in the h1 heading. When a user clicks on a Food Items page, it should navigate to the Food Items Detail page and display three products; information with name, price and description using props. And when the user clicks on Contact page it should navigate to contact details page and display contact information with blue color font.		5	LJU-2025				
311	7	Create react app to pass product image, name and price as properties from one component to another component. Add an array of objects with pic, name and price properties of 2 products. Display Image name and price of the products in browser using map method.		4					
312	7	Create react app using function component to pass background color(green), font size(50px) font style(italic),text transform(uppercase) as properties to Example.js component and apply css to "This is an React Application" text written in h1 tag in Example2.js component. Use props.		3					
313	7	Create react app using function component to perform tasks as asked. First create files as asked below in folder named " component" 1. Login.js - for the login page content 2. Product.js - for the Product page content 3. Contact.js - for the contact page content 4. About.js - for the about page content Create Home.js file which contains Links for Login,Product,Contact and About page. Also, add functionality of page routing. Finally call Home.js in App.js. Write code for All necessary files.		4					
314	7	Write a react.js file to pass an integer value to a component, which is defined as a property in app.js file. Fetch that value in component and print its table on console. Write all necessary files i.e. App.js and Component.js. Perform task by function component.		5					
315	7	Write React JS script to display three products. Products having title, product image, price and description. All three products should be horizontally adjacent to each other. Note: using props show all products and use Functional component for complete this script.		3					
316	7	Write react js script to perform the tasks as asked below using functional component: 1)Add an array of objects which contains name and age of people. 2)Apply filter to find people with age less than 40. And display name of all people using map function. Use props.		3					
317	7	Create a React app to perform tasks as asked using functional component: 1)Create a react Router that includes three routes: Home, Product, and Contact and implement navigation between these routes. 2)Create a route that displays a Home page, Product details page and Contact details page. 3) When a user clicks on Home page it should navigate to home page and display "Welcome to LJU" in bold in h1 heading. When a user clicks on a Product page, it should navigate to the product detail page and display three products information with price and description using props. And when user clicks on Contact page it should navigate to contact details page and display contact information with blue color font.		4	LJU-2023				

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
318	7	Write a program to create function based ReactJS app having an array of 6 people having mentioned age [70,83,38,65,49,94] and display list of people whose age is greater than 60 using filter method. Also display total count of people whose age is greater than 60 on the same page. Use props.		4					
319	7	Create a React function component named File1 that receives two props, productName and price. The component should display the product name and price. Additionally, add a button labeled "Add to cart" to the component. When the button is clicked onClick event triggered and an alert should be displayed with the message "Your Product is Added to cart!".		5					
320	7	Write react js script to perform the task as below using function component: •Create array of objects which have id, name & city of person. •Display id & name of persons having city name "Ahmedabad" . Use props. No need to write App.js file.		3					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD									
Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)									
Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.									
Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
Chapter-8									
321	8	Identify correct sequence to code API using Axios.	ios.get("url").then(response).catch(err	0.5		axios.get("url").catch(error).then(res ponse)	axios.get("url").then(response).catch(error)	axios.catch(error).then(response).get ("url")	axios.get("url").then(request).catch(e rror)
322	8	What is the use of useContext Hook ?	Used to create global variables	0.5		Used to create global variables	Used to transfer values as a argument to another components	To create a constant variable	To use createContext hook
323	8	What will be the error in the following program : import React, { useState } from 'react' const Hook3 = () => { const [firstName, setFirstName]=useState(""); function handleChange(){ setFirstName(e.target.value); } return (<input name="firstName" value={firstName} onChange={handleChange}/> {firstName}) } export default Hook3	e is not defined	1		Unexpected use of Input type	handleChange is undefined	e is not defined	firstname is undefined
324	8	We can not export more than one context from a module.(True/False)	False	0.5		TRUE	FALSE		
325	8	Identify the correct result of following code snippet const [cb,setCb] = useState(""); const handleChange=(e)=>{setCb(e.target.value);} const handleChange1=(e)=>{setCb(e.target.value);} return(<input type="radio" value="Male" onChange="{handleChange} name="gender" />Male <input type="radio" value="Female" onChange="{handleChange1} name="gender" />Female {cb});	Both "Male" and "Female" will be printed by selecting respective radio buttons	1		Error, since onChange event can't be applied on radio button	Error, since we have to take two separate useStates to store 2 radio button values	radio buttons are shown correctly, but events are not performed on both radio buttons, no error is shown	Both "Male" and "Female" will be printed by selecting respective radio buttons
326	8	_____ hook is used to maintain a state and its updating function with its definition.	useState	0.5		useState	useEffect	useForm	useReducer
327	8	Which of the following options correctly represents the syntax for using useReducer in ReactJS?	const [state, dispatch] = useReducer(reducerFunction, initialState);	0.5		const [state, dispatch] = useReducer(reducerFunction, initialState);	const {state, dispatch} = useReducer(reducerFunction, initialState);	const [dispatch, state] = useReducer(initialState, reducerFunction);	const {dispatch, state} = useReducer(initialState, reducerFunction);
328	8	The useContext hook in React is primarily used to:	Share state and data between components without prop drilling.	0.5		Manage and update the state of a component using a reducer function.	Fetch data from an API and handle asynchronous operations.	Create a new context for managing global state.	Declare state variables in functional components.
329	8	What does the useState hook in React return?	An array with two elements: the current state value and a function to update the state.	0.5		An object with properties state and setState.	An array with two elements: the current state value and a function to update the state.	A single value representing the current state.	An object with a get method to access the state and a set method to update the state.
330	8	How do you initialize a state variable named count with an initial value of 0 using the useState hook in a React component	const [count, setCount] = useState(0);	1		const [count, setCount] = useState(0);	const [count, setCount] = useState(\$count:0);	const {count, setCount} = useState(count: 0);	const [count, setCount] = useState(count: 0);
331	8	Consider you have a context named ThemeContext that provides a theme value. How would you consume this context value using the useContext hook inside a functional component	const theme = useContext(ThemeContext);	1		const { ThemeContext } = useContext();	const { theme } = {useContext(ThemeContext)};	const theme = useContext(ThemeContext);	const { [theme]} = ThemeContext;
332	8	What will be the output? import React, { useReducer } from 'react' const Hook = () => { const [sum,dispatch]=useReducer((state,action)=>{ return state+action; }, 20); return ({sum} <button onClick={()=>dispatch(5)}>Add</button>) } export default Hook	It displays number 20 and increase the number by 5 each time when DoubleClick on button	1		It displays number 20 and increase the number by 5 only once	It displays number 5 and increase the number by 20 only once	It displays number 20 and increase the number by 5 each time when button clicked	It displays number 5 and increase the number by 20 each time when button clicked
333	1	how do you use the useContext hook to access the context value?	const contextValue = useContext(myContext);	0.5		const contextValue = useContext(myContext);	const contextValue = useValue(myContext);	const contextValue = this.useContext(myContext);	const contextValue = this.useValue(myContext);
334	8	How do you handle errors in Axios?	By using the .catch() method on the promise returned by Axios	0.5		By using the .error() method on the response object	By using a try-catch block	Axios automatically handles errors and throws exceptions	By using the .catch() method on the promise returned by Axios
335	8	How do you invoke setTxt only when component mounts, using hooks? function MyComponent(props) { const [txt, setTxt] = useState(false); return Done: {txt} ; }	useEffect(() => { setTxt(true); }, []);	1		useEffect(() => { setTxt(true); });	useEffect(() => { setTxt(true); }, [setTxt]);	useEffect(() => { setTxt(true); }, [txt, setTxt]);	useEffect(() => { setTxt(true); }, []);

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
336	8	What will be the output? import React, { useState, useEffect } from 'react'; const Ex = () => { const [seconds, setSeconds] = useState(0); useEffect(() => { setInterval(() => { setSeconds(prevSeconds => prevSeconds + 1); }, 1000); },[]) return (Seconds: {seconds}) } export default Ex	It renders the component every 2 seconds	1	LJU-2023	It updates the scroll position whenever the component renders	It increments the seconds state every second	It handles clicks on a button to increment seconds	It renders the component every 2 seconds
337	8	What will be the output of below code? import { useState } from 'react'; function Example () { const [buttonText,setbuttonText]=useState("Hide"); const [text,setText]=useState("Hello"); function clickButton() { if(buttonText === 'Hide') { setbuttonText("Show") setText("") } else { setbuttonText("Hide") setText("Hello") } } return (<button onClick={clickButton}>Hide/show</button>) }	Initially the button text "Hide/show" and the text "Hello" will be displayed in the browser. Clicking that button will not change button text just the text will be hidden.	1	LJU-2023	Initially the button text "Hide" and the text "Hello" will be hidden in the browser. Clicking that button will change button text to "Show" and the text will be displayed.	Initially the button text "Show" and the text "Hello" will be hidden in the browser. Clicking that button will change button text to "Hide" and the text will be displayed	Initially the button text "Hide" and the text "Hello" will be hidden in the browser. Clicking that button will not change button text and the text will be displayed.	Initially the button text "Hide" and the text "Hello" will be displayed in the browser. Clicking that button will change button text to "Show" and the text will be hidden.
338	8	Find the correct syntax for Axios?	function fetchactivity(){ axios .get(siteURL) .then((data) => console.log(data.data)) .catch((error)=>console.log(error)) }	1		function fetchactivity(){ axios .get(siteURL) .then((data) => console.log(data.data)) .catch((error)=>console.log(error)) }	function fetchactivity(){ axios .get(siteURL) .then(data => console.log(data.data)) axios .catch(error=>console.log(error)) }	function fetchactivity(){ axios .get(siteURL) .then((data) => console.log(data.data)) .catch((error)=>console.log(error)) }	function fetchactivity(){ axios .get(siteURL) .then({data} => console.log(data.data)) axios.catch({error}=>console.log(error)) }
339	8	What will happen when the button is clicked? const [count,setCount] = useState(0); <button onClick={()=>setCount(count+1)}>Click</button> {count}	It increments the count value by 1 on each click	1		It decrements the count value	It increments the count value by 1 on each click	It resets the count to 0	It shows an error
340	8	How do you correctly initialize a state variable 'name' with value 'John' using useState?	const [name, setName] = useState('John');	1		const name = useState('John');	const [name, setName] = useState('John');	const {name, setName} = useState('John');	useState name = 'John';
341	8	What will be displayed initially? const [text,setText] = useState('Hello'); {text}	Hello	1		undefined	null	Hello	Nothing will be displayed
342	8	If the initial state is false: const [show,setShow] = useState(false); What is correct way to toggle it?	setShow(!show);	1		setShow(show++);	setShow(!show);	show = true;	setShow = true;
343	8	You created useContext in Parent component and wrapped <Child/> inside <UserContext.Provider value='abc'>. How will Child component access this value?	const user = useContext(UserContext);	1		const user = useContext(UserContext);	const user = useContext();	const user = this.useContext(UserContext);	useContext = useContext;
344	8	In a Theme application, ThemeContext provides value 'dark'. If value changes to 'light', what happens to components using useContext(ThemeContext)?	They automatically re-render with new theme value	1		They automatically re-render with new theme value	They need manual refresh	Application crashes	Nothing changes
345	8	You want to pass 'blue' color from Parent to deeply nested Child without passing props manually at each level. Which is correct approach?	Create Context in Parent and consume it using useContext in Child	1		Use useState in Child only	Create Context in Parent and consume it using useContext in Child	Use useEffect to send props	Store value in local variable
346	8	Consider: const value = useContext(MyContext); If MyContext has no Provider above this component, what will value be?	The default value passed while creating MyContext	1		undefined always	The default value passed while creating MyContext	Application error immediately	Null pointer exception

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
347	8	You want to increase count by 1 using useReducer. Which dispatch call is correct if reducer handles action type 'increment'?	dispatch({type:'increment'});	1		dispatch({type:'increment'});	dispatch('increment');	setCount(count+1);	useReducer('increment');
348	8	Initial state is 0. Reducer returns state + action.payload. What will dispatch({payload:5}) do?	Increase state by 5	1		Reset state to 5	Increase state by 5	Multiply state by 5	Throw error always
349	8	When is useReducer preferred over useState in practical applications?	When state logic is complex with multiple actions	1		When state logic is complex with multiple actions	When only one variable is used	When API call is required	When styling components
350	8	What does useReducer return?	Current state and dispatch function	1		Only dispatch function	Only state value	Current state and dispatch function	Reducer function itself
351	8	If reducer does not match any action type, what should it return to avoid errors?	Return current state	1		Return null	Return current state	Return undefined	Return new object always
352	8	How do you run useEffect only once when component mounts?	useEffect(()=> {}, []);	1		useEffect(()=> {});	useEffect(()=> {}, [state]);	useEffect(()=> {}, []);	useEffect(state);
353	8	You want to fetch API data when component loads. Where should API call be written?	Inside useEffect with empty dependency array	1		Inside useState	Inside useEffect with empty dependency array	Inside return statement	Inside reducer
354	8	If dependency array contains [count], when will useEffect execute?	Whenever count value changes	1		Only once	Whenever count value changes	On every render regardless	Never executes
355	8	If no dependency array is provided in useEffect, what happens?	It runs after every render	1		It runs only once	It runs after every render	It never runs	It throws error
356	8	Write a program to build React app to perform the tasks as asked below using useState hook. •Add three buttons "Change Text", "Change Color", "Hide/Show". •Add heading "LJ University" in red color(initial) and also add "React Js Hooks" text in h2 tag. •By clicking on "Change text" button text should be changed to "Welcome students" and vice versa. •By clicking on "Change Color" button change color of text to "blue" and vice versa. This color change should be performed while double clicking on the button. •Initially button text should be "Hide". While clicking on it the button text should be changed to "Show" and text "React Js Hooks" will not be shown.		5					
357	8	Write a program to build React app having a button which changes image by clicking it. (Add two images)		3					
358	8	Write a program to build React app having 2 input text fields (First name and last name) and display the entered value on the same page.		3					
359	8	Write a program to build React app for task todo list. •Add 1 input field and button and by clicking on button display entered task on the same page. •Also, add delete button with each added task to delete the task.		5					
360	8	Write a program to build React app having text and button to show and hide the text.		3					
361	8	Write a program to build React app having 2 input number fields (Number 1 and Number 2) and display the entered value on the same page. And then click on add button to calculate the addition of two numbers. Display the addition in h2 tag.		3					

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
362	8	Write a program to build React app to perform the tasks as asked below. •Add a button "Change Text". •Add "Hello" text in h2 tag. •By clicking on "Change text" button text should be changed to "How are you?" and vice versa.		4					
363	8	Write a program to build React app having a button which increase count by 1 while clicking it. (useState)		3					
364	8	Create a program to build React app having buttons to increment and decrement the number by clicking that respective button. Also, increment of the number should be performed only if number is less than 10 and decrement of the number should be performed if number is greater than 0.		4					
365	8	Write a ReactJS script to create a digital clock running continuously. (useEffect)		3					
366	8	Write a reactJS program to perform the tasks as asked below. •Create one main file (parent file) name Comp.js and other 3 component files Comp1.js, Comp2.js, Comp3.js. •Pass Number1 and Number 2 from Comp.js file to Comp3.js file. Calculate multiplication of the numbers using useContext.		4					
367	8	Write a reactJS program to perform the tasks as asked below. 1) Create one main file (parent file)Main.js and other 2 component files Comp1.js, Comp2.js. Pass username from Main.js file to Comp2.js file. Display this user name in browser in Blue color. (useContext)		3					
368	8	Create a Sign-up form using React asking for username, age, email, password, and confirm password. When the user clicks on the 'submit' button, it will display an alert box with a username, age, and email details entered by the user.		4					
369	8	Create a React Form for email and password validation.		2					
370	8	Create a React Form for select any of pizza size using radio button.		3					
371	8	Create React Js app to perform the tasks as asked below. -Add buttons "increment" and "decrement" -By clicking on increment button the value should be incremented by 1 and by clicking on decrement button value should be decremented by 1. -Use useReducer hook to perform the above tasks.		3					
372	8	Create React Js app to perform the tasks as asked below. -Add button "Click" -By clicking on button the value should be incremented by 5. Initial value is 20. -Use useReducer hook to perform the above tasks.		3					
373	8	Create a react app to generate random joke using AXIOS to make API request.		4					
374	8	Create react app to create exam form. Fields are as under. Name -text, Email -email Password -password, Gender-radio, Exam date-datepicker, Exam center-dropdown) Use useState hook to save the state of the form. Also, add validation for the email and password fields. Display submitted values.		4	LJU-2023 LJU-2025				

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
375	8	Create a react app using function component to display image of flower using AXIOS to make API request. Use API Url (https://flower.ceo/api/image/random). Key name in API which store image is "sample".		3					
376	8	Create a Student Data Entry Form using React. Fields are Student Name (input Field), Gender (Radio Button values are Boy, Girl), Subjects (Dropdown values are English, Gujarati), Comments (textarea). When the user Click on the Submit button , it will display an alert and use useState hook.		4					
377	8	Build a survey form with radio buttons, and dropdowns. display selected results on the alert box on user responses using React JS Hooks.(App.js file not required).		5					
378	8	Create a React app with two components using functional component: Parent and Child. Use useContext to pass two colors from the Parent component to the Child component. The Child component should display the received color as its background(red) and other color(green) on its font to display "Welcome to LJU".		4	LJU-2023				
379	8	Create a React app with three components: parent component P.js and two child components C1.js, C2.js. Use useContext hook to pass two colors from the Parent component P.js to the Child component C2.js. (Yellow color as font color and Blue color as background color) In Child component C1.js import child component C2.js. In C2.js display "Full stack Development" text in h1 heading with above mentioned background color and font color using context.		5					
380	8	Create a ReactJS program using function component having two input fields for num1 and num2 and two buttons for addition and subtraction of the two numbers. Display the respective outputs on same page using useState hook. Also display alert box as an effect on every time the addition button is clicked using useEffect hook.		5					
381	8	Create react app which to perform following task using function component: •Create one main file name F1.js & other 2 component files F2.js & F3.js. •Main file contains form with following fields: oFirst Name (Input type text) oLast Name (Input type text) oMessage (Textarea) oCity (Dropdown) oGender (Radio Button) •Pass values of all fields from F1.js file to F3.js file. And display all submitted values in alert box using useContext & useState hook. No need to write App.js file.		5					
382		Create a React app with three components: parent component P.js and two child components C1.js, C2.js. Use useContext hook to pass fontStyle and fontSize from the Parent component P.js to the Child component C2.js. In Child component C1.js import child component C2.js. In C2.js display "Full stack Development" text in h1 heading with above mentioned fontStyle and fontSize using context.							
383	8	Create a React app: • Add two buttons "Dark Mode" and "Light Mode" • Initially background should be white and text black • On clicking "Dark Mode" change background to black and text to white • On clicking "Light Mode" revert back		5					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
384	8	Create a React app: • Add one textarea • Display live character count below it • If characters exceed 100, text color becomes red		5					
385	8	Create a React app: • Add Start and Stop buttons • When Start is clicked, counter increments every second • When Stop is clicked, counter stops • Use useEffect with cleanup		5					
386	8	Create a React app: • Display product quantity • Add buttons "Add Item" and "Remove Item" • Quantity should never go below 0 • Use useReducer to manage state		5					
387	8	Create a React app: • Parent component stores language value ("English" or "Hindi") • Pass language using useContext • Child component displays "Welcome" in selected language • Add button in parent to toggle language		5					
388	8	Create a React app that: • Add an input field to enter city name • On clicking "Get Weather", fetch weather data using Axios • Display temperature, humidity, and weather description • If city is invalid, display error message • Show loading message while fetching data		5					