ASSIGNMENT - 3

Q1. Create a new directory named permission_practice in your home directory.

wCommand & Output:

```
jiyansh2006@LENOVO:/mnt/d/jiy$ mkdir ~/permissions_practice
jiyansh2006@LENOVO:/mnt/d/jiy$ ls -l
total 0
```

Q2. Change your current directory to permission_practice.

Command & Output:

```
jiyansh2006@LENOVO:/mnt/d/jiy$ cd ~/permissions_practice
```

Q3. Create an empty file named my_file.txt using the touch command.

Command & Output:

```
jiyansh2006@LENOVO:~/permissions_practice$ touch myfile.txt
```

Q4. Display the permissions of my_file.txt using ls -l. Command s

Output:

```
jiyansh2006@LENOVO:~/permissions_practice$ ls -l
total 0
-rw-r--r-- 1 jiyansh2006 jiyansh2006 0 Sep 14 13:17 myfile.txt
```

Q5. Make my_file.txt executable only by its owner. Verify the change. Command s

Output:

```
jiyansh2006@LENOVO:~/permissions_practice$ chmod u+x myfile.txt
jiyansh2006@LENOVO:~/permissions_practice$ ls -l
total 0
-rwxr--r-- 1 jiyansh2006 jiyansh2006 0 Sep 14 13:17 myfile.txt
```

Q6. Prevent users in the group from modifying my_file.txt. Verify the change. Command s

Output:

```
jiyansh2006@LENOVO:~/permissions_practice$ chmod g-w myfile.txt
jiyansh2006@LENOVO:~/permissions_practice$ ls -l
total 0
-rwxr--r-- 1 jiyansh2006 jiyansh2006 0 Sep 14 13:17 myfile.txt
```

Q7. Ensure that other users can only read (view) my_file.txt, not write or execute it. Verify the change.

Command s Output:

```
jiyansh2006@LENOVO:~/permissions_practice$ chmod o=r myfile.txt
jiyansh2006@LENOVO:~/permissions_practice$ ls -l
total 0
-rwxr--r-- 1 jiyansh2006 jiyansh2006 0 Sep 14 13:17 myfile.txt
```

Q8. Create another empty file called report.txt. Command s

Output:

```
jiyansh2006@LENOVO:~/permissions_practice$ touch report.txt
```

QG. Set the permissions of report.txt such that:

(i) Owner has read, write, and execute permissions.

(ii) Group has read and execute permissions.

(iii) Others have only read permission.

Command s Output:

```
jiyansh2006@LENOVO:~/permissions_practice$ chmod 754 report.txt
jiyansh2006@LENOVO:~/permissions_practice$ ls -l report.txt
-rwxr-xr-- 1 jiyansh2006 jiyansh2006 0 Sep 14 13:20 report.txt
```

Q10. Create a new user named guestuser (Requires sudo or root access). Command s

Output:

```
jiyansh2006@LENOVO:~/permissions_practice$ sudo useradd -m guestuser
[sudo] password for jiyansh2006:
```

Q11. Change ownership of report.txt to guestuser. Command s

Output:

```
jiyansh2006@LENOVO:~/permissions_practice$ sudo chown guestuser report.txt
jiyansh2006@LENOVO:~/permissions_practice$ ls -l report.txt
-rwxr-xr-- 1 guestuser jiyansh2006 0 Sep 14 13:20 report.txt
```

Q12. Navigate back to your home directory: Command s

Output:

```
jiyansh2006@LENOVO:~/permissions_practice$ cd ~
```

Q13. Remove the working directory and its contents.

Command s Output:

```
jiyansh2006@LENOVO:~$ rm -rf permissions_practice
jiyansh2006@LENOVO:~$ sudo userdel -r guestuser
userdel: guestuser mail spool (/var/mail/guestuser) not found
```