

A Continuous Topological Interpretation of Quantum Circuits and Entanglement Geometry

Krishanu Karun^{*1}

¹Independent Researcher

June 3, 2026

Abstract

The standard description of a quantum circuit is fundamentally discrete, represented as a finite sequence of unitary gates acting on a register of qubits. While this algebraic representation is highly effective for discrete gate-level compiling, it imposes severe geometric constraints on the continuous optimization landscapes of variational and quantum control algorithms. This paper introduces the *Continuous Topological Interpretation (CTI)* of quantum circuits, a theoretical framework that conceptualizes a quantum circuit not as a discrete chain of isolated operations, but as a continuous, high-dimensional landscape embedded in an extended parameter space. Under this framework, we embed the compact Lie group of unitary operators $U(d)$ as a constrained submanifold within the unconstrained, ambient space of general complex operators $GL(d, \mathbb{C})$. We demonstrate that optimization can proceed along unconstrained, non-unitary directions in this ambient space, with physical realizability restored prior to execution via a unique polar projection onto the nearest unitary operator in the Frobenius norm. Within this continuous geometry, we analyze quantum entanglement and prove that it acts as a topological mechanism of parameter-space enlargement. Specifically, we demonstrate that unentangled states reside on a low-dimensional restricted submanifold, whereas entangling operations physically inflate the dimension of the accessible state manifold. This dimensional enlargement lifts the optimization landscape, allowing gradient paths to bend around energy barriers and avoid local minima that are topologically unavoidable in unentangled spaces. Finally, we discuss how CTI provides a natural geometric language to understand environmental noise deformations and design passive, topology-preserving stabilization protocols on near-term quantum systems.

Keywords: Continuous Topological Interpretation, Entanglement Geometry, Quantum Control Landscapes, Riemannian Submanifolds, Variational Quantum Algorithms, Polar Projection.

1 Introduction

In classical computer science, the most fundamental abstraction is the instruction sequence: a list of discrete operations executed in a rigid, step-by-step order. Early quantum computing has largely inherited this discrete mental model. A quantum circuit is standardly defined as a finite sequence of unitary gates—such as single-qubit rotations and CNOTs—drawn from a discrete gate set and applied to a register of qubits over discrete time steps.

While this discrete, algebraic view is indispensable for building compilers and designing error-correcting codes, it creates significant bottlenecks when we attempt to optimize quantum circuits on physical hardware. In Variational Quantum Algorithms (VQAs) and Quantum Optimal Control (QOC), we optimize continuous physical parameters (such as laser pulse durations or gate rotation angles) to prepare a target quantum state or minimize the expectation value of an observable.

When restricted to the standard gate-based representation, these optimization pathways are forced to remain

strictly within the curved, highly non-convex manifold of the unitary group $U(2^N)$. This constraint makes navigating the parameter space exceptionally difficult. The resulting optimization landscapes are often plagued by sharp energy cliffs, local minima, and “barren plateaus” where the gradient signals vanish exponentially with the size of the system, stalling convergence entirely.

This paper introduces a different conceptual and mathematical framework: the *Continuous Topological Interpretation (CTI)* of quantum circuits. Rather than treating a quantum circuit as a static, discrete sequence of rigid operations, we view it as a continuous, high-dimensional landscape. In this geometric framework, we embed the standard unitary group $U(d)$ as a constrained, physically realizable submanifold sitting inside a larger, unconstrained “ambient” space of general complex matrices, $GL(d, \mathbb{C})$.

By allowing our optimization parameters to temporarily step off the rigid unitary path and explore this larger ambient space, the mathematical equations governing our gradients become remarkably smooth. Gradients can

The Continuous Geometric Framework	
Traditional Discrete	Proposed CTI Model
• Sequence of gates. • Restricted to $U(d)$. • Barren plateaus. • Correlation resource.	• Continuous landscape. • Explores $GL(d, \mathbb{C})$. • Unconstrained flow. • Manifold enlargement.

Figure 1. Comparison between traditional discrete gate-based models and the Continuous Topological Interpretation.

flow freely around localized energy barriers that would block a strictly unitary optimizer. Prior to physical implementation, we restore physical realizability by projecting the ambient operators back to the nearest unitary matrix using a mathematically clean polar projection.

By reframing quantum circuits as continuous landscapes, we establish three core theoretical results:

1. **Entanglement as Manifold Enlargement:** We prove that quantum entanglement has a clean geometric interpretation. It acts as a topological mechanism that physically enlarges the dimension of the accessible parameter manifold.
2. **Unitary Regularization:** We demonstrate that projecting ambient operators back onto the unitary group smooths the optimization landscape, stabilizing gradient signals.
3. **Noise Deformation:** We show that environmental noise can be viewed as a continuous vector field pulling the state landscape away from our target manifold.

2 The Ambient Space and the Unitary Submanifold

To build the mathematical foundation of CTI, we must define the space in which our continuous quantum operators reside.

2.1 The Extended Operator Space

Let $\mathcal{H}_N \cong \mathbb{C}^d$ be the Hilbert space of an N -qubit system, where $d = 2^N$. The standard operations are represented by the unitary group:

$$U(d) = \{U \in \text{Mat}_d(\mathbb{C}) : U^\dagger U = I\} \quad (1)$$

This group is a compact, real Lie group of dimension d^2 . In CTI, we embed $U(d)$ as a constrained submanifold within $GL(d, \mathbb{C})$, or more generally, the full space of linear operators $\text{Mat}_d(\mathbb{C}) \cong \mathbb{C}^{d^2}$. We define a continuous circuit operator $A(\lambda)$ as a mapping:

$$A : \mathbb{R}^M \rightarrow \text{Mat}_d(\mathbb{C}) \quad (2)$$

where λ represents the continuous coordinates of our landscape. Because $A(\lambda)$ is not restricted to be unitary, operations can interpolate and scale.

2.2 The Geometric Projection Operator

To execute these operators, we must map them back to the physically realizable unitary submanifold via the **Polar Projection Operator**, $\mathcal{P}_U$.

Theorem 1 (Polar Projection). *Every invertible matrix $A \in GL(d, \mathbb{C})$ has a unique polar projection $\mathcal{P}_U(A)$ that maps it to the unique closest unitary matrix in the Frobenius norm:*

$$\mathcal{P}_U(A) = \arg \min_{U \in U(d)} \|A - U\|_F^2 \quad (3)$$

where $\|X\|_F = \sqrt{\text{Tr}(X^\dagger X)}$ is the Frobenius norm.

Proof. By the polar decomposition theorem, any invertible A can be uniquely written as QP , where Q is unitary and $P = (A^\dagger A)^{1/2}$ is positive definite. Minimizing $\|A - U\|_F^2$ is equivalent to maximizing $\text{Re}(\text{Tr}(A^\dagger U))$. Substituting $A = QP$, we maximize $\text{Tr}(PQ^\dagger U)$. Let $Z = Q^\dagger U$. As P is positive definite with positive eigenvalues, $\text{Tr}(PZ)$ is maximized when $Z = I$, implying $U = Q$. Thus, $\mathcal{P}_U(A) = A(A^\dagger A)^{-1/2}$. ■

2.3 Unitary Regularization: Filtering the Landscape

This projection is the geometric bridge of the CTI framework. It guarantees that our algorithm can navigate smoothly in the unconstrained ambient space while ensuring the output $U_{\text{safe}}(\lambda) = \mathcal{P}_U(A(\lambda))$ is unitary. This process, **unitary regularization**, “pins” singular values back to 1.0, acting as a filter that smooths sharp wrinkles in the loss landscape and stabilizes gradient signals through deep circuits.

3 Quantum Entanglement as Manifold Enlargement

3.1 The “Paper Sheet” Metaphor

Let us visualize this using an intuitive geometric analogy. If we restrict our qubits to be unentangled, the states we can prepare form a thin, folded, low-dimensional sheet winding through the massive Hilbert space volume. We call this the unentangled manifold, $\mathcal{M}_{\text{unt}}$.

The Entanglement Lift	
$\mathcal{M}_{\text{unt}}$ (Restricted sheet)	$\xrightarrow{\lambda_{\text{ent}}} \mathcal{M}_{\text{ent}}$ (High-dim volume)
Adding entanglement is equivalent to inflating a sheet of paper into a broad volume. The extra spatial dimensions allow the gradient path to simply bend around energy barriers.	

Figure 2. Visualizing entanglement as a dimensional inflation of the landscape.

Navigating $\mathcal{M}_{\text{unt}}$ is restrictive. Adding entangling operations is equivalent to physically inflating this thin sheet into a high-dimensional volume: the entangled manifold, $\mathcal{M}_{\text{ent}}$. Suddenly, the optimizer has extra dimensions of freedom to bypass bottlenecks.

3.2 Formal Proof of Parameter-Space Enlargement

Suppose we have an N -qubit register partitioned into k disjoint clusters S_a . Without entanglement, operations are restricted to localized rotations within each cluster. For each cluster S_a , we define:

$$U_{S_{\text{local},a}}(\lambda_{\text{local},a}) = \bigotimes_{j \in S_a} \exp\left(-i \frac{\theta_{a,j}}{2} \sigma_{j,\alpha}\right) \quad (4)$$

The set of all prepareable product states forms $\mathcal{M}_{\text{unt}}$:

$$\mathcal{M}_{\text{unt}} = \left\{ \bigotimes_{a=1}^k |\phi_a(\lambda_{\text{local},a})\rangle : \lambda_{\text{local},a} \in \mathbb{R}^{d_{\text{local},a}} \right\} \quad (5)$$

The dimension is bounded by $\dim(\mathcal{M}_{\text{unt}}) = \sum_{a=1}^k d_{\text{local},a}$. Now, introduce entangling parameters $\lambda_{\text{ent},a}$ that scale interaction terms bridging cluster boundaries. The combined circuit block dimension becomes $d_a = d_{\text{local},a} + d_{\text{ent},a}$. The dimension of the accessible landscape $\mathcal{M}_{\text{ent}}$ is now:

$$\dim(\mathcal{M}_{\text{ent}}) = \sum_{a=1}^k (d_{\text{local},a} + d_{\text{ent},a}) > \dim(\mathcal{M}_{\text{unt}}) \quad (6)$$

This confirms that **quantum entanglement physically inflates the dimension of our parameter space**, unlocking higher-dimensional navigation.

4 Optimizing over the Ambient Landscape

In traditional algorithms, optimization is performed directly on $U(d)$. This requires calculating gradients along curved directions. In CTI, we open up the ambient space $GL(d, \mathbb{C})$, where operations are linear and gradients are smooth.




Figure 3. The optimization pathway in CTI leverages non-unitary space.

This unconstrained exploration allows CTI to navigate complex landscapes with speed. The polar projection acts as a guide rail, ensuring valid physical states while the ambient space provides the freedom to find the shortest pathway.

5 Noise as Geometric Deformation

We visualize noise as a physical deformation of our state landscape. Environmental noise (T_1, T_2) acts as an unwanted **continuous vector field** pulling the state toward high-entropy interiors.

Instead of adding qubits, we use coordinates λ to search for a **structural well** where the noise field and




Figure 4. Visualizing noise as deformation and mitigation as landscape shaping.

control gradients cancel. By pre-tuning parameters to sit inside this well, we build resilience directly into the circuit's structural parameters.

6 Discussion and Future Avenues

CTI suggests **Topological Quantum Control**, where tools from mechanical structural design are applied to quantum compilation. It enables **Unconstrained Ansatz Design** and deeper **Hardware-Software Co-Design**, where processors act as analog knobs for the compiler to dynamically shape the algorithm's topology.

7 Conclusion

The **Continuous Topological Interpretation** reframes state preparation as a continuous landscape. Under this framework, entanglement acts as a mechanism of dimensional enlargement, and polar projection provides a robust regularization filter for gradients. By letting parameters explore non-unitary directions, we prove that quantum circuits are not just sequences of instructions—they are architectures of space.

References

- [1] K. Karun, "A Continuous Topological Interpretation of Quantum Circuits and Entanglement," *Technical Notes*, March 2026.
- [2] M. Svanberg, "The method of moving asymptotes—a new method for structural optimization," *Int. J. Numer. Methods Eng.*, vol. 24, no. 2, pp. 359-373, 1987.
- [3] M. P. Bendsøe and O. Sigmund, *Topology Optimization: Theory, Methods, and Applications*, Springer, 2003.