

Tech Stack

Layer	Technology	Notes
Frontend	Next.js 14.2.5, React 18	Pages router; plain CSS modules, no UI library
Backend	Node.js, Express 4	JSON API, CORS enabled
Database	PostgreSQL	Hosted on Supabase; accessed with plain SQL
DB driver	pg 8	Connection pool in <code>server/src/db/pool.js</code>
Hashing	Node built-in <code>crypto</code>	SHA-256, hex digest
Config	dotenv	<code>.env</code> files, git-ignored
Dev tooling	nodemon	Auto-restart for the API
Version control	Git / GitHub	PR-based, <code>feature/<role></code> branches

Dependencies

Server: `express`, `cors`, `dotenv`, `pg`; dev: `nodemon` **Client:** `next`, `react`, `react-dom` **Fonts:** Bricolage Grotesque and IBM Plex Mono via Google Fonts

Environment variables

Variable	Where	Purpose
<code>DATABASE_URL</code>	server	PostgreSQL connection string
<code>PORT</code>	server	API port (default 4000)
<code>NEXT_PUBLIC_API_BASE</code>	client	API base URL (default <code>http://localhost:4000</code>)

Scripts

Location	Command	Does
server	<code>npm run dev</code>	Start API with nodemon
server	<code>npm start</code>	Start API
server	<code>npm run migrate</code>	Run <code>schema.sql</code> through <code>psql</code>
client	<code>npm run dev</code>	Next.js dev server (port 3000)
client	<code>npm run build</code> / <code>npm start</code>	Production build and serve

Deliberate non-choices

- **No blockchain:** no Solidity, wallets, or gas. The hash chain is plain PostgreSQL, sized for a one-day hackathon.
- **No auth library:** demo login only (see limitations in the README).