



**Mithibai College of Arts,
Chauhan Institute of Science &
Amrutben Jivanlal College of Commerce and Economics
(AUTONOMOUS)**

Affiliated to University of Mumbai

NAAC Reaccredited 'A' Grade, CGPA : 3.57 (February 2016)

Granted under RUSA for Enhancing Quality & Excellence in select Autonomous Colleges
GRANTED UNDER FIST-DST & STAR COLLEGE SCHEME OF DBT, GOVERNMENT OF INDIA
BEST COLLEGE (2016-17), University of Mumbai



Practical-1 Static code analysis using open source tool Flaw-finder

Date: -12/07/2024

Submission Date: - 19/07/2024

Write-up: -

- Static code Analysis & Benefits
- Vulnerability
- Flaw-finder

Implement static code analysis using open source tool Flaw-finder for the following:

- Buffer overflow
- String problem
- Race conditions, etc.

Code /Steps:

1. Download Flaw-finder
2. Set up the path where the Flaw-finder
3. Get the test file for the practical
4. Now open the terminal
5. Then check is the flaw-finder is available or not
6. Then run the command flaw-finder command
 - Flawfinder test.c

Output:

```
C:\Windows\System32\cmd.exe
Microsoft Windows [Version 10.0.22000.1042]
(c) Microsoft Corporation. All rights reserved.

C:\Users\Admin\Desktop\Dhawal\cyber\flawfinder-2.0.19\test>flawfinder test.c
Flawfinder version 2.0.19, (C) 2001-2019 David A. Wheeler.
Number of rules (primarily dangerous function names) in C/C++ ruleset: 222
Examining test.c

FINAL RESULTS:

test.c:32: [5] (buffer) gets:
  Does not check for buffer overflows (CWE-120, CWE-20). Use fgets() instead.
test.c:60: [5] (buffer) strncpy:
  Easily used incorrectly (e.g., incorrectly computing the correct maximum
  size to add) [MS-banned] (CWE-120). Consider strcat_s, strlcat, snprintf,
  or automatically resizing strings. Risk is high; the length parameter
  appears to be a constant, instead of computing the number of characters
  left.
test.c:61: [5] (buffer) _tcnscat:
  Easily used incorrectly (e.g., incorrectly computing the correct maximum
  size to add) [MS-banned] (CWE-120). Consider strcat_s, strlcat, or
  automatically resizing strings. Risk is high; the length parameter appears
  to be a constant, instead of computing the number of characters left.
test.c:64: [5] (buffer) MultiByteToWideChar:
  Requires maximum length in CHARACTERS, not bytes (CWE-120). Risk is high,
  it appears that the size is given as bytes, but the function requires size
  as characters.
test.c:66: [5] (buffer) MultiByteToWideChar:
  Requires maximum length in CHARACTERS, not bytes (CWE-120). Risk is high,
  it appears that the size is given as bytes, but the function requires size
  as characters.
test.c:77: [5] (misc) SetSecurityDescriptorDacl:
  Never create NULL ACLs; an attacker can set it to Everyone (Deny All
  Access), which would even forbid administrator access (CWE-732).
test.c:77: [5] (misc) SetSecurityDescriptorDacl:
  Never create NULL ACLs; an attacker can set it to Everyone (Deny All
  Access), which would even forbid administrator access (CWE-732).
test.c:17: [4] (buffer) strcpy:
  Does not check for buffer overflows when copying to destination [MS-banned]
  (CWE-120). Consider using snprintf, strcpy_s, or strncpy (warning: strcpy
  easily misused).
test.c:20: [4] (buffer) sprintf:
  Does not check for buffer overflows (CWE-120). Use sprintf_s, snprintf, or
  vsnprintf.
test.c:21: [4] (buffer) sprintf:
  Does not check for buffer overflows (CWE-120). Use sprintf_s, snprintf, or
  vsnprintf.
test.c:22: [4] (format) sprintf:
  Potential format string problem (CWE-134). Make format string constant.
test.c:23: [4] (format) printf:
  If format strings can be influenced by an attacker, they can be exploited
  (CWE-134). Use a constant for the format specification.
test.c:25: [4] (buffer) scanf:
  The scanf() family's %s operation, without a limit specification, permits
  buffer overflows (CWE-120, CWE-20). Specify a limit to %s, or use a
  different input function.
test.c:27: [4] (buffer) scanf:
  The scanf() family's %s operation, without a limit specification, permits
  buffer overflows (CWE-120, CWE-20). Specify a limit to %s, or use a
  different input function.
test.c:38: [4] (format) syslog:
  If syslog's format strings can be influenced by an attacker, they can be
  exploited (CWE-134). Use a constant format string for syslog.
```


C:\Windows\System32\cmd.exe

```
test.c:38: [4] (format) syslog:
  If syslog's format strings can be influenced by an attacker, they can be
  exploited (CWE-134). Use a constant format string for syslog.
test.c:49: [4] (buffer) _mbscopy:
  Does not check for buffer overflows when copying to destination [MS-banned]
  (CWE-120). Consider using a function version that stops copying at the end
  of the buffer.
test.c:56: [4] (buffer) lstrcat:
  Does not check for buffer overflows when concatenating to destination
  [MS-banned] (CWE-120).
test.c:79: [3] (shell) CreateProcess:
  This causes a new process to execute and is difficult to use safely
  (CWE-78). Specify the application path in the first argument, NOT as part
  of the second, or embedded spaces could allow an attacker to force a
  different program to run.
test.c:79: [3] (shell) CreateProcess:
  This causes a new process to execute and is difficult to use safely
  (CWE-78). Specify the application path in the first argument, NOT as part
  of the second, or embedded spaces could allow an attacker to force a
  different program to run.
test.c:81: [3] (misc) LoadLibraryEx:
  Ensure that the full path to the library is specified, or current directory
  may be used (CWE-829, CWE-20). Use a flag like LOAD_LIBRARY_SEARCH_SYSTEM32
  or LOAD_LIBRARY_SEARCH_APPLICATION_DIR to search only desired folders.
test.c:99: [3] (buffer) getopt_long:
  Some older implementations do not protect against internal buffer overflows
  (CWE-120, CWE-20). Check implementation on installation, or limit the size
  of all string inputs.
test.c:16: [2] (buffer) strcpy:
  Does not check for buffer overflows when copying to destination [MS-banned]
  (CWE-120). Consider using snprintf, strncpy, or strlcpy (warning: strncpy
  easily misused). Risk is low because the source is a constant string.
test.c:19: [2] (buffer) sprintf:
  Does not check for buffer overflows (CWE-120). Use sprintf_s, snprintf, or
  vsnprintf. Risk is low because the source has a constant maximum length.
test.c:45: [2] (buffer) char:
  Statically-sized arrays can be improperly restricted, leading to potential
  overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use
  functions that limit length, or ensure that the size is larger than the
  maximum possible length.
test.c:46: [2] (buffer) char:
  Statically-sized arrays can be improperly restricted, leading to potential
  overflows or other issues (CWE-119!/CWE-120). Perform bounds checking, use
  functions that limit length, or ensure that the size is larger than the
  maximum possible length.
test.c:50: [2] (buffer) memcpy:
  Does not check for buffer overflows when copying to destination (CWE-120).
  Make sure destination can always hold the source data.
test.c:53: [2] (buffer) memcpy:
  Does not check for buffer overflows when copying to destination (CWE-120).
  Make sure destination can always hold the source data.
test.c:54: [2] (buffer) memcpy:
  Does not check for buffer overflows when copying to destination (CWE-120).
  Make sure destination can always hold the source data.
test.c:55: [2] (buffer) CopyMemory:
  Does not check for buffer overflows when copying to destination (CWE-120).
  Make sure destination can always hold the source data.
test.c:105: [2] (misc) fopen:
  Check when opening files - can an attacker redirect it (via symlinks),
  force the opening of special file type (e.g., device files), move things
  around to create a race condition, control its ancestors, or change its
  contents? (CWE-362).
test.c:15: [1] (buffer) strcpy:
```

C:\Windows\System32\cmd.exe

```
test.c:15: [1] (buffer) strcpy:
  Does not check for buffer overflows when copying to destination [MS-banned]
  (CWE-120). Consider using snprintf, strcpy_s, or strncpy (warning: strncpy
  easily misused). Risk is low because the source is a constant character.
test.c:18: [1] (buffer) sprintf:
  Does not check for buffer overflows (CWE-120). Use sprintf_s, snprintf, or
  vsnprintf. Risk is low because the source is a constant character.
test.c:26: [1] (buffer) scanf:
  It's unclear if the %s limit in the format string is small enough
  (CWE-120). Check that the limit is sufficiently small, or use a different
  input function.
test.c:57: [1] (buffer) strncpy:
  Easily used incorrectly; doesn't always \0-terminate or check for invalid
  pointers [MS-banned] (CWE-120).
test.c:58: [1] (buffer) _tcscpy:
  Easily used incorrectly; doesn't always \0-terminate or check for invalid
  pointers [MS-banned] (CWE-120).
test.c:59: [1] (buffer) strncat:
  Easily used incorrectly (e.g., incorrectly computing the correct maximum
  size to add) [MS-banned] (CWE-120). Consider strcat_s, strlcat, snprintf,
  or automatically resizing strings.
test.c:62: [1] (buffer) strlen:
  Does not handle strings that are not \0-terminated; if given one it may
  perform an over-read (it could cause a crash if unprotected) (CWE-126).
test.c:68: [1] (buffer) MultiByteToWideChar:
  Requires maximum length in CHARACTERS, not bytes (CWE-120). Risk is very
  low, the length appears to be in characters not bytes.
test.c:70: [1] (buffer) MultiByteToWideChar:
  Requires maximum length in CHARACTERS, not bytes (CWE-120). Risk is very
  low, the length appears to be in characters not bytes.
```

ANALYSIS SUMMARY:

```
Hits = 39
Lines analyzed = 125 in approximately 0.07 seconds (1901 lines/second)
Physical Source Lines of Code (SLOC) = 86
Hits@level = [0] 16 [1] 9 [2] 9 [3] 4 [4] 10 [5] 7
Hits@level+ = [0+] 55 [1+] 39 [2+] 30 [3+] 21 [4+] 17 [5+] 7
Hits/KSLOC@level+ = [0+] 639.535 [1+] 453.488 [2+] 348.837 [3+] 244.186 [4+] 197.674 [5+] 81.3953
Suppressed hits = 2 (use --neverignore to show them)
Minimum risk level = 1
```

Not every hit is necessarily a security vulnerability.
You can inhibit a report by adding a comment in this form:
// flawfinder: ignore
Make **sure** it's a false positive!
You can use the option --neverignore to show these.

There may be other security vulnerabilities; review your code!
See 'Secure Programming HOWTO'
(<https://dwheeler.com/secure-programs>) for more information.

C:\Users\Admin\Desktop\Dhawal\cyber\flawfinder-2.0.19\test>