

Week:06-01-One Dimensional Arrays

Roll No:241501091

Name:Krishna Akhileshwaran AV

Q1)Problem Statement:

Given an array A of sorted integers and another non-negative integer k, find if there exists 2 indices i and j such that $A[j] - A[i] = k$, $i \neq j$.

Input Format:

1. First line is number of test cases T. Following T lines contain:
2. N, followed by N integers of the array
3. The non-negative integer k

Output format:

Print 1 if such a pair exists and 0 if it doesn't.

Sample Input:

```
1
3 1 3 5
4
```

Sample Output:

```
1
```

GE23131-Programming Using C-2024

Quiz navigation

1

2

3

Show one page at a time

Finish review

Status	Finished
Started	Tuesday, 14 January 2025, 12:09 AM
Completed	Tuesday, 14 January 2025, 12:41 AM
Duration	32 mins 24 secs

Question 1

Correct

Marked out of 3.00

Flag question

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[i] - A[j] = k$, $i \neq j$.

Input Format

1. First line is number of test cases T. Following T lines contain:
2. N, followed by N integers of the array
3. The non-negative integer k

```

1 #include<stdio.h>
2 int main(){
3     int T;
4     scanf("%d",&T);
5     while(T-->0)
6     {
7         int N;
8         scanf("%d",&N);
9         int A[N];
10        for(int i =0;i<N;i++)
11        {
12            scanf("%d",&A[i]);
13        }
14        int K;
15        scanf("%d",&K);
16        int found =0;
17        for(int i =0;i<N;i++)
18        {
19            for(int j=i+1;j<N;j++)
20            {
21                if(A[i]-A[j]==K || A[j]-A[i]==K)
22                {
23                    found = 1;
24                    break;
25                }
26            }if(found)break;
27        }printf("%d\n",found);
28    }
29 }
30
31

```

Output:

	Input	Expected	Got	
✓	1 3 1 3 5 4	1	1	✓
✓	1 3 1 3 5 99	0	0	✓

Passed all tests! ✓

Q2)Problem Statement:

Sam loves chocolates and starts buying them on the 1st day of the year. Each day of the year, (x) , is numbered from 1 to (Y) . On days when (x) is odd, Sam will buy (x) chocolates; on days when (x) is even, Sam will not purchase any chocolates. Complete the code in the editor so that for each day (N_i) (where $(1 \leq x \leq N \leq Y)$) in array arr, the number of chocolates Sam purchased (during days 1 through (N_i)) is printed on a new line. This is a function-only challenge, so input is handled for you by the locked stub code in the editor.

Input Format:

The program takes an array of integers as a parameter.

The locked code in the editor handles reading the following input from stdin, assembling it into an array of integers (arr), and calling calculate(arr).

The first line of input contains an integer, T (the number of test cases). Each line of the T subsequent lines describes the i^{th} test case as an integer, N_i (the number of days).

Constraints:

- $1 \leq x \leq 10^5$
- $1 \leq x \leq 2 \times 10^6$
- $1 \leq x \leq Y$

Output Format:

For each test case, T_i in arr, your calculate method should print the total number of chocolates Sam purchased by day N_i on a new line.

Sample Input 0:

```
3
1
2
3
```

Sample Output 0

```
1
1
4
```

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int T,N,total_chocolates,i;
5     scanf("%d",&T);
6     for(int j =0;j<T;j++)
7     {
8         scanf("%d",&N);
9         total_chocolates=0;
10        for(i=1;i<=N;i++)
11        {
12            if(i%2==1)
13            {
14                total_chocolates+=i;
15            }
16        }printf("%d\n",total_chocolates);
17    }
18 }
```

Output:

	Input	Expected	Got	
✓	3	1	1	✓
	1	1	1	
	2	4	4	
	3			
✓	18	1396	1396	✓
	71	2588	2588	
	100	1849	1849	
	88	729	729	
	54	489	489	
	48	25	25	
	9	1521	1521	
	77	35	35	
	9	49	49	
	13	2481	2481	
	98			
Passed all tests! ✓				

Q3)Problem Statement:

The number of goals achieved by two football teams in matches in a league is given in the form of two lists. Consider:

Football team A has played three matches and has scored {1, 2, 3} goals in each match respectively. Football team B has played two matches and has scored {2, 4} goals in each match respectively. Your task is to compute, for each match of team B, the total number of matches of team A where team A has scored less than or equal to the number of goals scored by team B in that match.

In the above case:

For 2 goals scored by team B in its first match, team A has 2 matches with scores 1 and 2.

For 4 goals scored by team B in its second match, team A has 3 matches with scores 1, 2, and 3.

Hence, the answer: {2, 3}.

Complete the code in the editor below. The program must return an array of m positive integers, one for each maxes[i], representing the total number of elements nums[j] satisfying $\text{nums}[j] \leq \text{maxes}[i]$ where $0 \leq j < n$ and $0 \leq i < m$, in the given order.

It has the following:

nums[nums[0],...,nums[n-1]]: first array of positive integers

maxes[maxes[0],...,maxes[m-1]]: second array of positive integers

Constraints:

$2 \leq n, m \leq 105$, $1 \leq \text{nums}[j] \leq 109$, $0 \leq j < n$, $1 \leq \text{maxes}[i] \leq 109$, $0 \leq i < m$

Input Format For Custom Testing

Input from stdin will be processed as follows and passed to the function:

The first line contains an integer n, the number of elements in nums.

The next n lines each contain an integer describing nums[j] where $0 \leq j < n$.

The next line contains an integer m, the number of elements in maxes.

The next m lines each contain an integer describing maxes[i] where $0 \leq i < m$.

Sample Input

```
4
1
2
3
4
2
4
```

5 Sample Output

2

4

Question 3
Correct
Marked out of
7.00
Flag
question

The number of goals achieved by two football teams in matches in a league is given in the form of two lists. Consider:

- Football team A, has played three matches, and has scored { 1, 2, 3 } goals in each match respectively.
- Football team B, has played two matches, and has scored { 2, 4 } goals in each match respectively.
- Your task is to compute, for each match of team B, the total number of matches of team A, where team A has scored less than or equal to the number of goals scored by team B in that match.
- In the above case:
 - For 2 goals scored by team B in its first match, team A has 2 matches with scores 1 and 2.
 - For 4 goals scored by team B in its second match, team A has 3 matches with scores 1, 2 and 3.

Hence, the answer: {2, 3}.

Complete the code in the editor below. The program must return an array of m positive integers, one for each maxes[i] representing the total number of elements nums[j] satisfying $\text{nums}[j] \leq \text{maxes}[i]$ where $0 \leq j < n$ and $0 \leq i < m$, in the given order.

It has the following:

nums[nums[0]...nums[n-1]]: first array of positive integers
maxes[maxes[0]...maxes[m-1]]: second array of positive integers

Constraints

- $2 \leq n, m \leq 100$
- $1 \leq \text{nums}[i] \leq 100$, where $0 \leq i < n$.
- $1 \leq \text{maxes}[i] \leq 100$, where $0 \leq i < m$.

Input Format For Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer n, the number of elements in nums.
The next n lines each contain an integer describing nums[i] where $0 \leq i < n$.
The next line contains an integer m, the number of elements in maxes.
The next m lines each contain an integer describing maxes[i] where $0 \leq i < m$.

Sample Case 0

Sample Input 0

```
4
1
4
2
4
2
3
5
```

Sample Output 0

```
2
```

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,m,i,j,count;
5     scanf("%d",&n);
6     int num[n];
7     for(i=0;i<n;i++)
8     {
9         scanf("%d",&num[i]);
10    }
11    scanf("%d",&m);
12    int maxes[m];
13    for(i =0;i<m;i++)
14    {
15        scanf("%d",&maxes[i]);
16    }
17    for(i =0;i<m;i++)
18    {
19        count=0;
20        for(j=0;j<n;j++)
21        {
22            if(num[j]<=maxes[i])
23            {
24                count++;
25            }
26        }printf("%d\n",count);
27    }
28 }
```

Output:

	Input	Expected	Got	
✓	4	2	2	✓
	1	4	4	
	4			
	2			
	4			
	2			
	3			
	5			
✓	5	1	1	✓
	2	0	0	
	10	3	3	
	5	4	4	
	4			
	8			
	4			
	3			
	1			
	7			
	8			

Passed all tests! ✓

