

DECOUPLING IDENTITY CONFOUNDERS FOR ENHANCED FER (DICE-FER)

“Decoupling Identity to recognise facial expression using mutual information”

Project members:

Aashika (230024)

Akshat (230100)

Krishna (230621)

Ritika (230862)

What it does ?

As FER suggests , it recognises facial expressions like happy, sad, anxious, etc.

Images



Facial Expression

Shocked

Happy

Why Facial Expression Recognition (FER) Is Hard?

1. **Inter-class variation is small**
2. **Intra-class variation is big** (young vs. old, different ethnicities, facial impairments)
3. **Identity and Expression entanglement problem :**
People's unique facial features (called identity features)—like nose shape or jawline—get mixed up with the expression features (smile, frown), which confuses the model.



Challenges in Existing FER Methods

1. Dependence on Auxiliary Labels & Synthetic Data

Models often rely on facial landmarks, Action Units, or GAN-generated faces, which are costly, noisy, or unrealistic, limiting real-world applicability.

2. High Computational Cost of GANs

GAN-based data augmentation or expression synthesis is resource-intensive, unstable to train, and impractical for real-time or low-power environments.

3. Incomplete Disentanglement of Identity and Expression

Expression features often get mixed with identity cues, leading to poor generalization to unseen subjects and biased predictions.

How can we overcome this?

DICE - FER

It skips creating photos and teaches the model using mathematics based Mutual Information Detection to separate emotions from identities—no fake images needed.

Benefits:

- No identity labels required
- No need for computation intensive GANs
- Fully disentangles expression and identity

Decoupling Expression from Identity

- Facial expression recognition is often affected by identity-related factors (e.g., face shape, age), which overlap with expression features.
- DICE-FER tackles this by explicitly separating expression and identity features from facial images.
- It uses paired images with the same expression to learn :
 - A shared expression representation (common across the pair).
 - An exclusive identity representation (unique to each individual).
- This separation ensures expression recognition relies only on emotional cues—not static identity traits.
- Crucially, the method requires no identity labels or neutral reference images, making it scalable and label-efficient.

Mutual Information Framework

- DICE-FER uses a mutual information-based framework inspired by InfoMax and MINE
- It maximizes mutual information (MI) between:
 1. The input image and its expression representation (global + local MI)
 2. This is done in a cross-referenced way, by swapping expression features between image pairs.
- It minimizes MI between expression and identity representations using an adversarial loss, promoting disentanglement.
- The overall framework involves :
 - Stage 1: Maximize expression MI + enforce consistency between expression features.
 - Stage 2: Maximize identity MI + adversarially minimize MI between identity and expression
- This enables robust, identity-invariant expression learning without synthetic images or auxiliary annotations

Theoretical MI:

$$I(M, Z) = \int \int p(m, z) \log \left(\frac{p(m, z)}{p(m)p(z)} \right) dm dz$$

- M = image (or image patch)
- Z = an embedding
- $p(m, z)$: The probability of seeing the pair (M, Z) together (i.e., the chance that $E(M) = Z$).
- $p(m)$: The probability of seeing image M , regardless of what feature Z it produces.
- $p(z)$: The probability of feature z showing up, no matter which image it came from.

The MI formula compares the actual joint distribution: $p(m, z)$
vs. what we'd get if m and z were independent: $p(m)p(z)$.

If they're very different, knowing m tells you a lot about z (and vice versa) $\Rightarrow$ **High mutual information**

If they're the same, m and z are unrelated $\Rightarrow$ **Zero mutual information**

MINE Approximation:

True distribution $p(m, z)$, $p(m)$ and $p(z)$ are not calculatable during training

$$\hat{I}_{\theta}(M, Z) = \mathbb{E}_{p(m, z)} [T_{\theta}(m, z)] - \log \mathbb{E}_{p(m)p(z)} [e^{T_{\theta}(m, z)}]$$

- $\mathbb{E}_{p(m, z)} [T_{\theta}(m, z)]$ = Average score on real pairs (i.e., image & its own features)
- $\mathbb{E}_{p(m)p(z)} [e^{T_{\theta}(m, z)}]$ = Average score on randomly mixed pairs (image & unrelated features)
- $T_{\theta}()$ = statistics network; trained to maximize the above difference

By training T_{θ} to maximize the difference, we reinforce it to give high value when there is more similarity and vice-versa, i.e. training to detect MI.

Global and Local Components of MINE

- *Global MI*: Measures information between the entire image and the full embedding vector


$$\hat{I}_{\theta, \text{global}}(M, Z) = \hat{I}_{\theta}(M, Z) \quad (3)$$


- *Local MI*: Measures information between image patches and the embedding, capturing fine-grained spatial relationships

$$\hat{I}_{\theta, \text{local}}(M, Z) = \sum_{i=1}^{N_{\text{patches}}} I(P^{(i)}(M), Z) \quad (4)$$

- $P^{(i)}(M)$ represents the i^{th} patch of M


Patch 1, Patch 2, Patch 3





Abstract representation of model

High Dimension Input → Lower Dimension Embeddings → Classification




Model Training

1) FER model training:

- **Stage 1: Expression Encoder** → Maximize expression MI + enforce consistency between expression features.
- **Stage 2: Identity Encoder** → Maximize identity MI + adversely minimize MI between identity and expression

2) Classification model training

FER Model Training




Model learns to extract features in such a way that :

- if image X and Y has same expression then extracted expression feature of X and Y are very similar so that irrespective of person model can give expression.
- Extracted identity and extracted expression have least overlap i.e. identity X only extract unique features of image X such as eyes separation, bone structure etc.
- Extracted identities of X and Y have also least possible overlap incase of different persons X and Y as we expect model to capture unique features.


Then our expression representation extractor is ready to do its job!

FER Stage 1: Expression Encoder Training

M



Expression Encoder CNN




0.6	0.3	0.1	-----
-----	-----	-----	-------

0.8	0.5	0.3	-----
-----	-----	-----	-------

N






$$\mathcal{L}_{\text{expMI}} = \frac{1}{B} \sum_{i=1}^B \left[\mu_{\text{exp}} \left(\hat{I}(M_i, E_{N_i}) + \hat{I}(N_i, E_{M_i}) \right) + \nu_{\text{exp}} \left(\hat{I}(\text{patches}(M_i), E_{N_i}) + \hat{I}(\text{patches}(N_i), E_{M_i}) \right) \right]$$


$$\mathcal{L}_1 = \frac{1}{B} \sum_{i=1}^B |E_{M_i} - E_{N_i}|_1 = \frac{1}{B} \sum_{i=1}^B \sum_{j=1}^{512} |E_{M_i}^j - E_{N_i}^j|$$

where $\mu_{\text{exp}}, \nu_{\text{exp}}$ are weighting hyperparameters.



$$\mathcal{L}_{\text{exp}} = \mathcal{L}_{\text{expMI}} - \delta \cdot \mathcal{L}_1$$

Stage 2: Extracting Identity Embedding



Then we Maximize


$$T_x = [E_x, Id_x], T_y = [E_y, Id_y]$$
$$\mathcal{L}_{idMI} = \frac{1}{B} \sum_{i=1}^B \left[\mu_{id} \hat{I}(M_i, T_{M_i}) + \nu_{id} \hat{I}(\text{patches}(M_i), T_{M_i}) \right]$$

Further to decouple it from expression , what we can do is minimize mutual information between I_dX and E_x where X belongs to W .

But there comes an issue, minimizing our current mutual score expression by Belghasi will lead to divergence due to $-\log x$ function.

Thus for minimizing Donsker divergence we use adversarial framework.

We train another model called the Discriminator to compete with the Identity Encoder.



$$\mathcal{L}_{\text{adv}} = \frac{1}{B} \sum_{i=1}^B [\log D(E_{M_i}, I_{M_i}) + \log(1 - D(E_{M_i}, I_{N_i}))]$$

Combined Loss for Stage 2

$$\mathcal{L}_{\text{id}} = \mathcal{L}_{\text{idMI}} - \zeta \cdot \mathcal{L}_{\text{adv}}$$

- ζ : Controls how hard we try to keep identity and expression separate
- $\mathcal{L}_{\text{idMI}}$: Makes sure identity features are meaningful
- $\mathcal{L}_{\text{adv}}$: Makes sure identity doesn't mix with emotion

Data Out: Final identity loss $\mathcal{L}_{\text{id}} \in \mathbb{R}$ for the entire batch

Combined FER Model Training


Total Loss is Computed over the 2 stages for the forward pass, by simple addition.

$$\mathcal{L}_{\text{total}} = \mathcal{L}_{\text{exp}} + \mathcal{L}_{\text{id}}$$


Weight Optimization: The model maximizes $\mathcal{L}_{\text{total}}$ with respect to encoder parameters using Adam optimizer with learning rate 10^{-4} . Gradients are computed from the batch-averaged loss, providing stable training signals.

Feature Extraction & Classification

Feature Extraction




Classification



D. Final Classification

After training the disentanglement model, only the expression encoder E_{exp} is retained. A simple classifier (fully connected layer + softmax) is trained on expression embeddings and their labels corresponding.

Experiment



What is the need of experiments ?

We want to prove that DICE-FER works better than other methods at:

1. Separating identity and expression (no mixing!).
2. Recognizing facial expressions accurately (even with different faces).
3. Working in real-world conditions (not just perfect lab photos).

Preprocessing Steps

Before feeding images into the model, they are cleaned and aligned:

1. Face detection & alignment using MTCNN to remove background noise

2. Whitening to reduce image redundancy

3. Resize to $112 \times 112 \times 1$ to make all images consistent

4. Data augmentation to avoid overfitting:

Rotations ($\pm 15^\circ$, $\pm 10^\circ$, $\pm 5^\circ$, 0°)

Horizontal flipping

Total of 14 augmentations

This helps deal with limited expression data.

Also, image pairs with the same expression are created for training.

Implementation Details

1. Model Architecture:

- Expression Encoder: Extracts emotion-relevant features
- Identity Encoder: Trained to extract identity features
- Discriminator: Trained adversarially to detect entanglement between expression and identity.
- Statistics Network: Compute global and local information estimates.

2. Training : Batch size = 32(balance of speed and accuracy)

Epochs:

- Stage 1: (Expression Encoder): 15 epochs
- Stage 2: (Identity Encoder + Adversarial): 30 epochs
- Classifier fine-tuning: 10 epochs

Quantitative Disentanglement Evaluation

GOAL: Check how well identity and expression have been separated

For this purpose , we will use MIG (Mutual Information Gap)

$$\mathbf{MIG} = I(\mathbf{E}_m, \mathbf{E}_n) - I(\mathbf{E}_m, \mathbf{I}_m)$$

What does high MIG indicates?

1. Expression features are similar when emotion is the same
2. Expression features are independent from identity features



Qualitative Validation: Image Retrieval

Expression-based retrieval: same expression, different IDs

Identity-based retrieval: same ID, different expressions


Expression-based retrieval:

same expression, different IDs



Identity-based retrieval:

same ID, different expressions





Thank you