



Gradient Boosting From Scratch – Regression

⚡ Application: Energy Consumption Forecasting

Problem Statement

Electric power companies must accurately **forecast daily energy consumption** to ensure:

- grid stability
- optimal power generation
- reduced operational cost

Energy consumption depends on multiple interacting, non-linear factors such as:

- Ambient temperature
- Humidity levels
- Number of occupants
- Duration of daylight

Objective

Build a **Gradient Boosting Regressor from scratch** that:

- Predicts daily energy consumption (kWh)
- Minimizes **Mean Squared Error (MSE)**
- Learns incrementally by correcting residual errors

Input Features

Feature	Description
temperature	Average daily temperature (°C)
humidity	Average humidity (%)
occupancy	Number of people
daylight	Hours of daylight



Output

- Continuous numeric value representing **energy consumption (kWh)**



Common Utilities

```
In [1]: import numpy as np
```



Dataset Generation

```
In [2]: np.random.seed(1)
n = 350

temperature = np.random.uniform(5, 40, n)
humidity = np.random.uniform(20, 90, n)
occupancy = np.random.randint(1, 6, n)
daylight = np.random.uniform(8, 14, n)

energy = (
    50
    + 1.8 * temperature
    + 0.6 * humidity
    + 12 * occupancy
    - 3 * daylight
    + np.random.normal(0, 10, n)
)

X = np.column_stack((temperature, humidity, occupancy, daylight))
y = energy
```

```
In [3]: idx = np.random.permutation(n)
train, test = idx[:280], idx[280:]
X_train, X_test = X[train], X[test]
y_train, y_test = y[train], y[test]
```



Weak Learner: Regression Tree

```
In [4]: class Node:
    def __init__(self, f=None, t=None, l=None, r=None, v=None):
        self.f, self.t, self.l, self.r, self.v = f, t, l, r, v
```

```
In [5]: class RegressionTree:
    def __init__(self, max_depth=2):
        self.max_depth = max_depth

    def fit(self, X, y):
```

```

self.nf = X.shape[1]
self.root = self._grow(X, y, 0)

def _grow(self, X, y, d):
    if d >= self.max_depth or len(y) < 2:
        return Node(v=np.mean(y))

    bf, bt, bl = None, None, float("inf")
    for f in range(self.nf):
        for t in np.unique(X[:, f]):
            l = y[X[:, f] <= t]
            r = y[X[:, f] > t]
            if len(l) == 0 or len(r) == 0:
                continue
            loss = len(l)*np.var(l) + len(r)*np.var(r)
            if loss < bl:
                bf, bt, bl = f, t, loss

    if bf is None:
        return Node(v=np.mean(y))

    m = X[:, bf] <= bt
    return Node(bf, bt,
                self._grow(X[m], y[m], d+1),
                self._grow(X[~m], y[~m], d+1))

def _pred(self, x, n):
    if n.v is not None:
        return n.v
    return self._pred(x, n.l if x[n.f] <= n.t else n.r)

def predict(self, X):
    return np.array([self._pred(x, self.root) for x in X])

```



Gradient Boosting Regressor (From Scratch)

```

In [6]: class GradientBoostingRegressorScratch:
    def __init__(self, n_estimators=120, lr=0.1, depth=2):
        self.n_estimators, self.lr, self.depth = n_estimators, lr, depth
        self.trees = []

    def fit(self, X, y):
        self.init = np.mean(y)
        pred = np.full(len(y), self.init)

        for _ in range(self.n_estimators):
            residuals = y - pred
            t = RegressionTree(self.depth)
            t.fit(X, residuals)
            pred += self.lr * t.predict(X)
            self.trees.append(t)

```

```
def predict(self, X):
    pred = np.full(len(X), self.init)
    for t in self.trees:
        pred += self.lr * t.predict(X)
    return pred
```

```
In [7]: model = GradientBoostingRegressorScratch()
        model.fit(X_train, y_train)

        pred = model.predict(X_test)
        rmse = np.sqrt(np.mean((pred - y_test)**2))
        print("RMSE:", rmse)
```

RMSE: 12.62789164348103



Asset-Based Test Cases

These tests validate the **internal correctness** of the Gradient Boosting Regression pipeline.

```
In [8]: # Asset 1: Initial prediction equals mean
        assert np.isclose(model.init, np.mean(y_train))
        print("✅ Initial prediction test passed")
```

✅ Initial prediction test passed

```
In [9]: # Asset 2: Residuals decrease after boosting
        baseline_pred = np.full(len(y_train), np.mean(y_train))
        baseline_rmse = np.sqrt(np.mean((baseline_pred - y_train)**2))

        boosted_rmse = np.sqrt(np.mean((model.predict(X_train) - y_train)**2))

        assert boosted_rmse < baseline_rmse
        print("✅ Residual reduction test passed")
```

✅ Residual reduction test passed

```
In [10]: # Asset 3: Weak learner prediction shape
        tree = RegressionTree()
        tree.fit(X_train, y_train)
        preds = tree.predict(X_test)
        assert preds.shape[0] == X_test.shape[0]
        print("✅ Weak learner shape test passed")
```

✅ Weak learner shape test passed

```
In [11]: # Asset 4: Ensemble size check
        assert len(model.trees) == model.n_estimators
        print("✅ Ensemble size test passed")
```

✅ Ensemble size test passed

```
In [12]: # Asset 5: Prediction continuity (no NaNs)
```

```
assert not np.isnan(pred).any()  
print("✅ Prediction continuity test passed")
```

✅ Prediction continuity test passed

✅ Conclusion

This notebook demonstrated:

- Gradient Boosting **Regression** from scratch
- Residual-based learning with squared loss
- Asset-based testing for internal validation