

BEYOND YOUR IMAGINATION...



INTRODUCING

CUMI PROMAX

PREMIUMGRINDING WHEEL











PRO FINISH

PRO PERFORMANCE

White Tool Room



- Pro Finish
- Max Performance

Dia : 150-250 mm

Bore Dia : 31.75, 50.8, 76.2 mm

Thickness : 6-25 mm Grit : #46, #54, #60

Hard and Soft metals- D2, EN, MS | Type 1 | (AA)

Centerless & Cylindrical

- Pro Finish
- Max Productivity



Centerless /

Cylindrical /

 Dia
 : 300 - 500 mm
 Dia
 : 300-400 mm

 Bore Dia
 : (127 - 304.8 mm)
 Bore Dia
 : (50.8 - 203.2 mm)

 Thickness
 : 100 - 250 mm
 Thickness
 : 25 - 75 mm

 Grits
 : #46, #60, #80
 Grits
 : #46, #60, #80

Hard and Soft Metals- D2, EN, MS | Type 1, 5, 7 | (Alo)

Hot Press - Resinoid



- Pro Performance
- Max Stock Removal

400 x 50 x 152.4 mm | 510 x 50 x 203.2 mm

Billets & Ingots - Stainless Steel, High Alloy Steel, Carbon Steel | Type 1 | (Zr)

EXPANDING OUR PRODUCT LINE UNDER PRODUCT RANGE
STAY TUNED FOR EXCITING LAUNCHES IN NEW PRODUCT RANGE





