

EXPERIMENT – 5

AIM: To create and manipulate SQL views for department salary summary and employee hierarchy, test the updatability of views, and implement a recursive CTE to display employee reporting chains.

SOURCE CODE:

USING EXPERIMENT – 3 DATABASE


SQL QUERIES:

DEPARTMENT SALARY SUMMARY VIEW

```
CREATE VIEW Department_Salary_Summary AS
SELECT
    d.dept_id,
    d.dept_name,
    COUNT(e.emp_id) AS total_employees,
    SUM(e.salary) AS total_salary,
    AVG(e.salary) AS average_salary,
    MAX(e.salary) AS highest_salary,
    MIN(e.salary) AS lowest_salary
FROM Department d
LEFT JOIN Employee e
    ON d.dept_id = e.dept_id
GROUP BY d.dept_id, d.dept_name;

SELECT *
FROM Department_Salary_Summary;
```

OUTPUT:




The screenshot shows a MySQL IDE interface with a table named 'Department_Salary_Summary'. The table has 7 columns: dept_id, dept_name, total_employees, total_salary, average_salary, highest_salary, and lowest_salary. The data is as follows:

dept_id	dept_name	total_employees	total_salary	average_salary	highest_salary	lowest_salary
1	IT	6	456000.00	76000.000000	95000.00	64000.00
2	HR	6	373000.00	62166.666667	71000.00	55000.00
3	Finance	6	504000.00	84000.000000	92000.00	73000.00
4	Marketing	6	437000.00	72833.333333	81000.00	66000.00
5	Research	6	544000.00	90666.666667	98000.00	79000.00

QUERY THE VIEW

```
--Find departments with an average salary greater than ₹75,000
SELECT
    dept_name,
    average_salary
FROM Department_Salary_Summary
WHERE average_salary > 75000;
```

OUTPUT:



The screenshot shows the MySQL Workbench interface. On the left is the 'EXPLORER' pane with a search bar and a list of tables: 'demo', 'department', 'employee', 'employee_project', and 'project'. The 'demo' table is selected. The main area displays 'Query 1' with the following SQL code:

```
1 SELECT
2     dept_name,
3     average_salary
4 FROM Department_Salary_Summary
5 WHERE average_salary > 75000;
6
```

Below the query, the results are shown in a table with two columns: 'dept_name' and 'average_salary'.

dept_name	average_salary
IT	76000.000000
Finance	84000.000000
Research	90666.666667

EMPLOYEE HIERARCHY

```
ALTER TABLE Employee
ADD manager_id INT NULL;
```

```
ALTER TABLE Employee
ADD CONSTRAINT fk_employee_manager
FOREIGN KEY (manager_id)
REFERENCES Employee(emp_id);
```

INSERT EMPLOYEE HIERARCHY

```
-- Update Manager IDs
```

```
UPDATE Employee SET manager_id = NULL WHERE emp_id IN
(105, 112, 114, 122, 125);
```

```
-- IT
```

```
UPDATE Employee
SET manager_id = 105
WHERE emp_id IN (103, 104);
```

```
UPDATE Employee
SET manager_id = 103
WHERE emp_id IN (101, 102);
```

```
UPDATE Employee
SET manager_id = 104
```

```

WHERE emp_id = 106;

-- HR

UPDATE Employee
SET manager_id = 105
WHERE emp_id IN (103, 104);

UPDATE Employee
SET manager_id = 103
WHERE emp_id IN (101, 102);

UPDATE Employee
SET manager_id = 104
WHERE emp_id = 106;

-- Finance

UPDATE Employee
SET manager_id = 112
WHERE emp_id IN (107, 108);

UPDATE Employee
SET manager_id = 107
WHERE emp_id = 109;

UPDATE Employee
SET manager_id = 108
WHERE emp_id IN (110, 111);

-- Marketing

UPDATE Employee
SET manager_id = 112
WHERE emp_id IN (107, 108);

UPDATE Employee
SET manager_id = 107
WHERE emp_id = 109;

UPDATE Employee
SET manager_id = 108
WHERE emp_id IN (110, 111);

-- Research

UPDATE Employee
SET manager_id = 125
WHERE emp_id IN (126, 127, 128);

UPDATE Employee
SET manager_id = 126

```


```
WHERE emp_id = 129;
```

```
UPDATE Employee  
SET manager_id = 128  
WHERE emp_id = 130;
```

EMPLOYEE HIERARCHY VIEW

```
CREATE VIEW Employee_Hierarchy AS  
SELECT  
    e.emp_id,  
    e.emp_name AS employee_name,  
    e.manager_id,  
    m.emp_name AS manager_name,  
    e.salary,  
    e.dept_id  
FROM Employee e  
LEFT JOIN Employee m  
    ON e.manager_id = m.emp_id;  
  
SELECT *  
FROM Employee_Hierarchy;
```

OUTPUT:



emp_id	employee_name	manager_id	manager_name	salary	dept_id
101	Aarav Sharma	103	Rohan Verma	75000.00	1
102	Ananya Singh	103	Rohan Verma	68000.00	1
103	Rohan Verma	105	Karan Mehta	82000.00	1
104	Priya Gupta	105	Karan Mehta	72000.00	1
105	Karan Mehta	null	null	95000.00	1
106	Sneha Kapoor	104	Priya Gupta	64000.00	1
107	Rahul Kumar	112	Riya Agarwal	55000.00	2
108	Neha Sharma	112	Riya Agarwal	62000.00	2
109	Amit Jain	107	Rahul Kumar	58000.00	2
110	Pooja Verma	108	Neha Sharma	67000.00	2
111	Vikas Singh	108	Neha Sharma	60000.00	2
112	Riya Agarwal	null	null	71000.00	2
113	Arjun Patel	null	null	88000.00	3
114	Meera Shah	null	null	92000.00	3

TEST UPDATABILITY OF A SINGLE VIEW

```
CREATE VIEW Employee_Basic AS
SELECT
    emp_id,
    emp_name,
    salary,
    dept_id
FROM Employee;
```

```
SELECT *
FROM Employee_Basic
WHERE emp_id = 101;
```

OUTPUT:



The screenshot shows the MySQL IDE interface. The 'EXPLORER' panel on the left lists tables: demo, department, employee, employee_project, and project. The 'Query 1' editor contains the following SQL code:

```
7 FROM Employee;
8
9 SELECT *
10 FROM Employee_Basic
11 WHERE emp_id = 101;
12
```

The result set is displayed in a table with the following data:


emp_id	emp_name	salary	dept_id
101	Aarav Sharma	75000.00	1

UPDATE THROUGH THE VIEW

```
UPDATE Employee_Basic
SET salary = 78000
WHERE emp_id = 101;
```

```
SELECT *
FROM Employee
WHERE emp_id = 101;
```

OUTPUT:



The screenshot shows the MySQL IDE interface. The 'Query 1' editor contains the following SQL code:

```
3 WHERE emp_id = 101;
4
5 SELECT *
6 FROM Employee
7 WHERE emp_id = 101;
8
```

The result set is displayed in a table with the following data:

emp_id	emp_name	gender	salary	hire_date	dept_id	manager_id
101	Aarav Sharma	M	78000.00	2021-01-15T00:00:00.000Z	1	103

TEST NON-UPDATABILITY OF DEPARTMENT SALARY VIEW

```
UPDATE Department_Salary_Summary
SET average_salary = 80000
WHERE dept_id = 1;
```

OUTPUT:



RECURSIVE CTE

```
WITH RECURSIVE EmployeeChain AS
(
    -- Anchor member
    SELECT
        emp_id,
        emp_name,
        manager_id,
        0 AS level,
        CAST(emp_name AS CHAR(500)) AS reporting_chain
    FROM Employee
    WHERE manager_id IS NULL


    UNION ALL

    -- Recursive member
    SELECT
        e.emp_id,
        e.emp_name,
        e.manager_id,
        ec.level + 1,
        CONCAT(ec.reporting_chain, ' -> ', e.emp_name)
    FROM Employee e
    INNER JOIN EmployeeChain ec
        ON e.manager_id = ec.emp_id
)

SELECT
    emp_id,
    emp_name,
    manager_id,
    level,
    reporting_chain
```

```
FROM EmployeeChain
ORDER BY reporting_chain;
```

OUTPUT:



emp_id	emp_name	manager_id	level	reporting_chain
119	Aditya Joshi	null	0	Aditya Joshi
113	Arjun Patel	null	0	Arjun Patel
125	Dev Malhotra	null	0	Dev Malhotra
126	Aditi Mishra	125	1	Dev Malhotra -> Aditi Mishra
129	Yash Thakur	126	2	Dev Malhotra -> Aditi Mishra -> Yash Thakur
128	Shreya Das	125	1	Dev Malhotra -> Shreya Das
130	Diya Kapoor	128	2	Dev Malhotra -> Shreya Das -> Diya Kapoor
127	Varun Nair	125	1	Dev Malhotra -> Varun Nair
122	Isha Malhotra	null	0	Isha Malhotra
105	Karan Mehta	null	0	Karan Mehta
104	Priya Gupta	105	1	Karan Mehta -> Priya Gupta
106	Sneha Kapoor	104	2	Karan Mehta -> Priya Gupta -> Sneha Kapoor
103	Rohan Verma	105	1	Karan Mehta -> Rohan Verma
101	Aarav Sharma	103	2	Karan Mehta -> Rohan Verma -> Aarav Sharma

RECURSIVE CTE FOR ONE EMPLOYEE

```
WITH RECURSIVE ReportingChain AS
(
    SELECT
        emp_id,
        emp_name,
        manager_id,
        0 AS level
    FROM Employee
    WHERE emp_id = 101

    UNION ALL

    SELECT
        e.emp_id,
        e.emp_name,
        e.manager_id,
        rc.level + 1
    FROM Employee e
    JOIN ReportingChain rc
        ON e.manager_id = rc.emp_id
)


SELECT
    emp_id,
    emp_name,
```

```

        manager_id,
        level
FROM ReportingChain;

```

OUTPUT:



The screenshot shows a MySQL IDE window titled "MySQL - db_454577wwy". The left sidebar contains an "EXPLORER" panel with a search bar and a "TABLES" list including "demo", "department", "employee", "employee_project", and "project". The main editor displays a SQL query in "Query 1" with line numbers 23 to 28. The query is:


```

23 SELECT
24     emp_id,
25     emp_name,
26     manager_id,
27     level
28 FROM ReportingChain;
    
```

 Below the query editor, the results of the query are displayed in a table with four columns: "emp_id", "emp_name", "manager_id", and "level". The table contains three rows of data.

emp_id	emp_name	manager_id	level
101	Aarav Sharma	103	0
103	Rohan Verma	105	1
105	Karan Mehta	null	2