










Introduction to Python-II & Operators

Session Objectives:

-  Understand the basic syntax of Python.
-  Learn about variables and their usage.
-  Declare and assign values to variables.
-  Differentiate between variables, identifiers, and keywords.
-  Explore data types, check them, and perform type conversion.
-  Understand what operators are and why they are used.
-  Explore different types of operators in Python.
-  Learn about operator precedence and order of execution.
-  Understand constraints in programming.

```
# Indentation :  
z = 15  
if z > 10: # Comparision Operator [Boolean Result [True/False]]  
    print("Z is greater than 10.") # skiped if the above statement is false  
  
print("Outside the If Statement")
```

```
Z is greater than 10.  
Outside the If Statement
```

```
# Indentation :  
z = 15  
if z > 20: # Comparision Operator [Boolean Result [True/False]]  
    print("Z is greater than 20.") # skiped if the above statement is false  
  
print("Outside the If Statement")
```

```
Outside the If Statement
```

```
print(10>5) # Comparison Operators [True]
```

```
True
```

```
print(99>199) # False
```

```
False
```

Variables : What & How?

Variables act as a container used for storing data which helps with

Variables : What & How?

Variables acts as a container used for storing data, which help with:

- Store Data.
- Manipulating Values.
- Reusability.
- Improving the Readability:
 - `total_sum >> ts`
 - `compound_interest >> c_i`
 - `age >> a`
 - `finding_prod_sum >> finding_the_product_and_sum >> p_s`

```
# Declaring and assigning Variables
```

```
val = 99
user_name = 'UltimateForce'
print(val)
print(user_name)
```

```
99
UltimateForce
```

```
a,b,c = 10,20,30
print(a)
print(b)
print(c)
```

```
10
20
30
```

```
a,b,c = 10,20,30,40,50,60,70 # ValueError: too many values to unpack (expected 3)
print(a)
print(b)
print(c)
```

```
a,b,*c = 10,20,30,40,50,60,70
print(a)
print(type(a))
print(b)
print(type(b))
print(c) # [30,40,50,60,70] 5 elements in a list
print(type(c)) # 'List'
```

```
10
<class 'int'>
20
<class 'int'>
[30, 40, 50, 60, 70]
<class 'list'>
```

```
a,*b,*c = 10,20,30,40,50,60,70 # SyntaxError: multiple starred expressions in assignment
print(a)
print(type(a))
print(b)
print(type(b))
print(c) # [30,40,50,60,70] 5 elements in a list
print(type(c)) # 'List'
```

```
a,*b,c = 10,20,30,40,50,60,70
print(a)
print(type(a))
print(b) # [20,30,40,50,60]
print(type(b)) # 'List'
print(c)
print(type(c))
```

```
10
<class 'int'>
[20, 30, 40, 50, 60]
<class 'list'>
70
<class 'int'>
```

```
*a,b,c = 10,20,30,40,50,60,70
print(a) # [10,20,30,40,50]
print(type(a)) # 'List'
print(b)
print(type(b))
print(c)
print(type(c))
```

```
[10, 20, 30, 40, 50]
<class 'list'>
60
<class 'int'>
70
<class 'int'>
```

```
*a,b,c = 10,20,30
print(a) # 10
print(type(a)) # 'List'
print(b)
print(type(b))
print(c)
print(type(c))
```

```
[10]
<class 'list'>
20
<class 'int'>
30
<class 'int'>
```

```
*a,b,c = 10,20,'a','b','c','d',30,50
print(a) # [10,20,'a','b','c','d']
print(type(a)) # 'List'
print(b)
print(type(b))
print(c)
print(type(c))
```

```
[10, 20, 'a', 'b', 'c', 'd']
<class 'list'>
30
<class 'int'>
50
<class 'int'>
```

```
p=q=r=s = 'Hello World'
print(p)
print(q)
print(r)
print(s)
```



```
Hello World
Hello World
Hello World
Hello World
```


Rules for Naming a 'Variables' :


- Can include letters, digits and underscore.
- Must start with a letter or underscore.
- case-sensitive:
 - val != Val
 - num != NuM
 - digit != Digit
- Can't use Python Keyword.
 - for, input, print, if, else, def, tuple, list, dict, true, false, while
- Can't have space or special Characters (except _)
- Variable names Can't start with Number.


```
my_first_variable = 'Python Learning'
print(my_first_variable)
```


```
Python Learning
```



Is it a valid Variable Name or Not :  

_var : 

22_user : 


word count : 

counter_var : 

boolean : 

loop123 : 

def :  [Keyword]

user-name : 

String -> Escape Characters ('\')

```
print('Hi, I\'m good, What about you?') # '\'
```

```
print("Hi, I'm good, What about you?")
```

Hi, I'm good, What about you?

Hi, I'm good, What about you?

```
print("an \"apple\" a day keeps the doctor away")
```

an "apple" a day keeps the doctor away

```
print('an "apple" a day keeps the doctor away')
```

an "apple" a day keeps the doctor away

```
print("an 'apple' a day keeps the doctor away")
```

an 'apple' a day keeps the doctor away

Multiline Strings [""" """] <pre> tag in html

```
print("""
        Ina meena Dika,           Daai,           Daamo nika
        Maaka naaka naaka, chika           pika rika
        Ina meena           dika dika de           daai daamo nika
        Maaka naaka           maaka naaka           chika pika rola rika
""")
```

Ina meena Dika, Daai, Daamo nika

Maaka naaka naaka, chika pika rika

Ina meena dika dika de daai daamo nika

Maaka naaka maaka naaka chika pika rola rika

```
# Escape Characters "\n"[Next Line] & '\t' [tab space]
print("Hey: What is your name:\t 'Annu Mishra'")
print("Hello \nWorld")
print("x", end = " ")
print("y", end = " ")
print("z", end = "\n")
print("Welcome Back!")
```

```
Hey: What is your name:  'Annu Mishra'
Hello
World
x y z
Welcome Back!
```

```
# type -> conversion()
x = 10.0
print(type(x))
```

```
<class 'float'>
```

```
num1 = int(x)
print(num1)
```

```
10
```

```
num1 = 99.99
print(int(num1))
```

```
99
```

```
x = 55
y = str(x)
print(y) # '55'
print(type(y)) # 'str'
```

```
55
<class 'str'>
```

```
_bool = True
int_bool = int(_bool)
print(int_bool) # 1
print(type(_bool)) # 'bool'
print(type(int_bool)) # 'int'
```

```
1
<class 'bool'>
<class 'int'>
```

```
_bool = False
int_bool = int(_bool)
print(int_bool) # 0
print(type(_bool)) # 'bool'
print(type(int_bool)) # 'int'
```


```
0
<class 'bool'>
<class 'int'>
```

What are Operators?

Operators are tools in programming used to perform actions like arithmetic, comparisons, assignments, logical evaluations, etc.

Types of Operators in Python:

1. Arithmetic Operators
2. Comparison Operators
3. Logical Operators
4. Bitwise Operators
5. Assignment Operators
6. Membership Operators
7. Identity Operators



What are Operators?

Operators are tools in programming used to perform actions like arithmetic, comparisons, assignments, logical evaluations, etc.

Types of Operators in Python:

1. Arithmetic Operators
2. Comparison Operators
3. Logical Operators
4. Bitwise Operators
5. Assignment Operators
6. Membership Operators
7. Identity Operators

Arithmetic Operators :

- '+' Addition
- '-' Subtraction
- '*' Multiplication
- '/' Division
- '%' Modulus (Remainder)
- '**' Exponentiation (power)
- '//' Floor Division

Ceil -> Rounding Up - `ceil(9.71)` - 10

Floor -> Rounding Down - `floor(9.71)` - 9

```
x = 11
y = 7
z = 15
print(x+y) # 18
print(x-y) # 4
print(x*y) # 77
print(x/y) # 1.571
print(x%y) # 4
print(z%y) # 1
print(z%x) # 4
print(x**2) # 121
print(x//2) # 5
```

```
18
4
77
1.5714285714285714
4
1
4
121
5
```

```
x = '10' + 11 # TypeError: can only concatenate str (not "int") to str
print(x)
```

Comparison Operators :

- '==' Equal to
- '!=' Not Equal to
- '>' Greater Than
- '>=' Greater Than or Equal To
- '<' Less Than
- '<=' Less Than or Equal To

```

x = 11
y = 7
z = 15
print(x==y) # False
print(x!=y) # True
print(z!=y) # True
print(z!=15) # False
print(x>y) # True
print(x>=y) # True
print(z<=y) # False
print(z<x) # False
print(x!= 2) # True
print(x>=2) # True

```

```

False
True
True
False
True
True
False
False
True
True

```

Logical Operators:

Cond1	Cond2	Result
T	T	T
T	F	F
F	T	F
F	F	F

'and'

Both Condition needs to be True in order to make the Result True

Cond1	Cond2	Result
T	T	T
T	F	T
F	T	T
F	F	F

'or'

If any condition is True, your final result would be True

cond	Result
T	- F
F	- T

'not'

negate the condition using ~ not logic

Logical Operators :

- and : 'Returns True' if both the conditions are True
- or : 'Returns False' if both the conditions are False
- not : 'Returns the Opposite'
- 'not' > 'and' > 'or'

```
x = 11
y = 7
z = 15
print((x == y) and (z!=y) or (y>x)) # ((F) and (T) or (F)) # (F or F) # 'False'
print((x!=y) or (z!=y) or (y>x)) # (T or T or F) # 'True'
print((x>=y) and (z==y) and (z>x)) # (T and F and T) # 'False'
print(not(z!=15)) # not(False) # True
print(not((x<=y) and (z>=y) or (y!=x))) # not(F and T or T) , not(True) - 'False'
```

False
True
False
True
False

Bitwise Operators

Bitwise Operators :

- 'AND' : '&' -> 'Both bit with value 1 return 1 else 0'
- 'OR' : '|' -> 'Any bit with value 1 return 1 else 0'
- 'XOR' : '^' -> 'Alternative bits return 1 else same bits return 0'
- 'NOT' : '~' -> '2s Complement to check the sign and evaluate'
- 'Left Shift' : '<<' -> 'Shifts the bit to the left'
- 'Right Shift' : '>>' -> 'Shifts the bit to the right'

```
x = 10
y = 6
print(x&y) # 2
print(x|y) # 14
```

2
14

bit1	bit2	Result
1	1	1
1	0	0
0	1	0
0	0	0

'and &'

bit1	bit2	Result
1	1	1
1	0	1
0	1	1
0	0	0

'or |'

bit1	bit2	Result
1	1	0
1	0	1
0	1	1
0	0	0

'XOR ^'

10 decimal -> binary

2	10
2	5 - 0
2	2 - 1
2	1 - 0
	0 - 1

10 -> 1010

1010

$$\begin{aligned}
 & (1 \cdot 2^3 + 0 \cdot 2^2 + 1 \cdot 2^1 + 0 \cdot 2^0) \\
 & = (1 \cdot 8 + 0 \cdot 4 + 1 \cdot 2 + 0 \cdot 1) \\
 & = 8 + 2 = 10
 \end{aligned}$$

10 & 6

2	6
2	3 - 0
2	1 - 1
2	0 - 1

6 -> 0110

0110

$$\begin{aligned}
 & = (0 \cdot 8 + 1 \cdot 4 + 1 \cdot 2 + 0 \cdot 1) \\
 & = (0 + 4 + 2 + 0) = 6
 \end{aligned}$$

$$\begin{array}{r}
 1010 \\
 \& 0110 \\
 \hline
 0010
 \end{array}$$

$0+0+(1*2)+0 = 2$

$$\begin{array}{r}
 1010 \\
 | 0110 \\
 \hline
 1110
 \end{array}$$

$8+4+2+0=14$